



Monitoring IBM Db2

IBM: Db2 PowerPack version 107

Table of Contents

Introduction	3
What Does the IBM: Db2 PowerPack Monitor?	3
Installing the IBM: Db2 PowerPack	4
Configuring IBM Db2 Monitoring	5
Prerequisites for Monitoring IBM Db2	5
Prerequisites for Linux/Unix Users	6
Prerequisites for Windows Users	9
Creating Credentials for IBM Db2	10
Creating an SSH/Key Credential (Linux and Unix Users)	11
Creating an SSH/Key Credential (Linux and Unix Users) in the SL1 Classic User Interface	13
Creating a PowerShell Credential (Windows Users)	14
Creating a PowerShell Credential (Windows Users) in the SL1 Classic User Interface	15
Creating a SOAP/XML Credential (Linux and Unix Users)	16
Creating a SOAP/XML Credential (Linux and Unix Users) in the SL1 Classic User Interface	18
Creating a SOAP/XML Credential for an SSL Certificate (Linux and Unix Users)	20
Creating a SOAP/XML Credential for an SSL Certificate (Linux and Unix Users) in the SL1 Classic User Interface	23
Creating a SOAP/XML Credential (Windows Users)	24
Creating a SOAP/XML Credential (Windows Users) in the SL1 Classic User Interface	26
Creating a SOAP/XML Credential for an SSL Certificate (Windows Users)	27
Creating a SOAP/XML Credential for an SSL Certificate (Windows Users) in the SL1 Classic User Interface	30
Updating the Database Credential	32
Discovering IBM Db2 Component Devices	32
Discovering IBM Db2 Component Devices in the SL1 Classic User Interface	34
Verifying Discovery and Dynamic Application Alignment	34
Viewing IBM Db2 Component Devices	39
IBM Db2 Dashboards in the SL1 Classic User Interface	42
Device Dashboard	42
IBM Db2: Database	43
IBM: DB2 Tablespace	45

Chapter

1

Introduction

Overview

This manual describes how to monitor IBM Db2 databases in SL1 using the *IBM: Db2 PowerPack*.

Use the following menu options to navigate the SL1 user interface:

- To view a pop-out list of menu options, click the menu icon (☰).
- To view a page containing all of the menu options, click the Advanced menu icon (⋮).

The following sections provide an overview of IBM Db2 and the *IBM: Db2 PowerPack*:

This chapter covers the following topics:

What Does the IBM: Db2 PowerPack Monitor?	3
Installing the IBM: Db2 PowerPack	4

NOTE: ScienceLogic provides this documentation for the convenience of ScienceLogic customers. Some of the configuration information contained herein pertains to third-party vendor software that is subject to change without notice to ScienceLogic. ScienceLogic makes every attempt to maintain accurate technical information and cannot be held responsible for defects or changes in third-party vendor software. There is no written or implied guarantee that information contained herein will work for all third-party variants. See the End User License Agreement (EULA) for more information.

What Does the IBM: Db2 PowerPack Monitor?

To monitor IBM Db2 databases using SL1, you must install the *IBM: Db2 PowerPack*. This PowerPack enables you to discover, model, and collect data about IBM Db2 databases.

The *IBM: Db2* PowerPack includes:

- Example credentials you can use as templates to create credentials to discover and connect to the IBM Db2 databases and instances you want to monitor
- Dynamic Applications to discover, model, and monitor performance metrics and collect configuration data for IBM Db2 databases
- Event Policies and corresponding alerts that are triggered when IBM Db2 databases meet certain status criteria
- A Run Book Action and Run Book Automation policy for aligning Dynamic Applications
- A device dashboard to display summary information about Db2 instances

Installing the IBM: Db2 PowerPack

Before completing the steps in this manual, you must import and install the latest version of the *IBM: Db2* PowerPack.

TIP: By default, installing a new version of a PowerPack overwrites all content from a previous version of that PowerPack that has already been installed on the target system. You can use the **Enable Selective PowerPack Field Protection** setting in the **Behavior Settings** page (System > Settings > Behavior) to prevent new PowerPacks from overwriting local changes for some commonly customized fields. For more information, see [Global Settings](#).

IMPORTANT: The minimum required MySQL version is 5.6.0.

To download and install the PowerPack:



1. Search for and download the PowerPack from the **PowerPacks** page (Product Downloads > PowerPacks & SyncPacks) at the [ScienceLogic Support Site](#).
2. In SL1, go to the **PowerPacks** page (System > Manage > PowerPacks).
3. Click the **[Actions]** button and choose *Import PowerPack*. The **Import PowerPack** dialog box appears.
4. Click **[Browse]** and navigate to the PowerPack file from step 1.
5. Select the PowerPack file and click **[Import]**. The **PowerPack Installer** modal displays a list of the PowerPack contents.
6. Click **[Install]**. The PowerPack is added to the **PowerPacks** page.

NOTE: If you exit the **PowerPack Installer** modal without installing the imported PowerPack, the imported PowerPack will not appear in the **PowerPacks** page. However, the imported PowerPack will appear in the **Imported PowerPacks** modal. This page appears when you click the **[Actions]** menu and select *Install PowerPack*.

Configuring IBM Db2 Monitoring

Overview

Use the following menu options to navigate the SL1 user interface:

- To view a pop-out list of menu options, click the menu icon (.
- To view a page containing all of the menu options, click the Advanced menu icon ().

The following sections describe how to configure and discover IBM Db2 databases for monitoring by SL1 using the *IBM: Db2 PowerPack*:

This chapter covers the following topics:

<i>Prerequisites for Monitoring IBM Db2</i>	5
<i>Creating Credentials for IBM Db2</i>	10
<i>Discovering IBM Db2 Component Devices</i>	32
<i>Verifying Discovery and Dynamic Application Alignment</i>	34
<i>Viewing IBM Db2 Component Devices</i>	39

Prerequisites for Monitoring IBM Db2

To configure the SL1 system to monitor IBM Db2 databases using the *IBM: Db2 PowerPack*, you must first perform the following prerequisites, which are based on your operating system.

NOTE: After you have configured SL1 to monitor IBM Db2 databases and you have discovered an IBM Db2 server and all associated component devices, make sure that the ports for the IBM Db2 instance are open to the SL1 Data Collector.

Prerequisites for Linux/Unix Users

1. Create a shell session and SSH into the Db2 database you want to monitor.
2. Create a new group to monitor by entering the following command:

```
sudo groupadd <group_name>
```

3. Create a new user for the group you created by entering the following command:

```
sudo useradd -u <user_id> -g <group_name> -m -d /home/<user_name>  
<user_name>
```

4. Set a password for the user you created by entering the following command:

```
sudo passwd <user_name>
```

5. Log in with the instance admin user. For example: `su - db2inst1`

6. Run the following commands:

```
db2 update database manager configuration using SYSMON_GROUP <group_<br>name>
```

```
db2stop
```

```
db2start
```

7. Connect to your database with the following command:

```
db2 connect to <db_name>
```

8. Run the following command to grant the DATAACCESS privilege to the user:

```
db2 "grant DATAACCESS ON DATABASE TO USER <user_name>"
```

NOTE: If you do not want to grant DATAACCESS privilege to the user, ScienceLogic provides a Bash and SQL scripts in a .zip file in the PowerPack download folder that grants the user permissions required to monitor Db2 databases.

- The Bash script grants required permissions to monitor Linux Db2 databases. To use the Bash script in the Linux Db2 server:
 - Copy the Bash script named **grant_mon_per.sh** to the Linux Db2 server.
 - Give the execute permission to the script with: `chmod +x grant_mon_per.sh`
 - Log in with the instance administrator user, for example: `su -db2inst1`.
 - Run the script with the following command in the same directory where you copied the script above. Replace the required information before running the command:

```
./grant_mon_per.sh <DB_NAME> <DB_USER> <mon_user_name>
```

 - **DB_NAME:** Database name you want to grant permissions
 - **DB_USER:** The Db2 instance admin user. For example: `su - db2inst1`
 - **mon_user_name:** The new user name that you want to grant the permissions to.
 - Enter the database password of the instance admin user. The required permissions should be configured.

9. Verify permissions with the following commands:

```
db2 connect to <db_name> user <user_name> using <user_password>
```

```
db2 "select SUBSTR(AUTHORITY,1,30), D_USER, D_GROUP, D_PUBLIC, ROLE_
USER, ROLE_GROUP, ROLE_PUBLIC, D_ROLE from table (sysproc.auth_list_
authorities_for_authid(CURRENT_USER, 'U'))"
```

NOTE: Repeat steps 5 - 8 for each Db2 instance.

1	D_USER	D_GROUP	D_PUBLIC	ROLE_USER	ROLE_GROUP	ROLE_PUBLIC	D_ROLE
-----	-----	-----	-----	-----	-----	-----	-----
SYSADM	*	N	*	*	*	*	*
DBADM	N	N	N	N	N	N	*
CREATETAB	N	N	Y	N	N	N	*
BINDADD	N	N	Y	N	N	N	*
CONNECT	N	Y	Y	N	N	N	*
CREATE_NOT_FENCED_ROUTINE	N	N	N	N	N	N	*
SYSCTRL	*	N	*	*	*	*	*
SYSMINT	*	N	*	*	*	*	*
IMPLICIT_SCHEMA	N	N	Y	N	N	N	*
LOAD	N	N	N	N	N	N	*
CREATE_EXTERNAL_ROUTINE	N	N	N	N	N	N	*
QUIESCE_CONNECT	N	N	N	N	N	N	*
SECADM	N	N	N	N	N	N	*
SYSMON	*	Y	*	*	*	*	*
SQLADM	N	N	N	N	N	N	*
WLMADM	N	N	N	N	N	N	*
EXPLAIN	N	N	N	N	N	N	*
DATAACCESS	Y	N	N	N	N	N	*
ACCESSCTRL	N	N	N	N	N	N	*

NOTE: The user you create will likely need to use KornShell (for Unix systems) or Bash (for Linux systems).

If you are unsure of the shell directory, you can use the command `which ksh` to determine the KornShell directory, or `which bash` to determine the Bash directory.

After you have determined shell directory, run the following commands, replacing `<shell_directory>` with the KornShell or Bash directory:

```
sudo useradd -u <user_id> -g <group_name> -s <shell_directory> -m -d
/home/<user_name> <user_name>
```

You **should not** use Shell (sh) as the shell for the user. Using Shell for the user shell could result in shell-related errors appearing in the Device Log.

Prerequisites for Windows Users

NOTE: Before performing the steps for the Windows prerequisites, ensure that you have followed the steps in the *Configuring Windows Servers for Monitoring with PowerShell* section of the **Monitoring Windows Systems with PowerShell** manual.

Windows users will need to create a local user and group for the Db2 database. If you have already done so, proceed to [adding the group to the instance database manager](#).

To create the user and group:

1. Click **[Start]** and select **Run**.
2. In the **Run** window, enter `lusrmgr.msc` and click **[OK]**.
3. In the **Local Users and Groups** pane, select the **Users** folder.
4. Click the **Action** menu and select *New User...* Enter the new user's information in the **New User** window and click **[Create]**.
5. In the **Local Users and Groups** pane, select the **Groups** folder.
6. Click the **Action** menu and select *New Group...* Enter the new group's information in the **New Group** window and click **[Create]**.
7. To add the new user to the group, double-click on the group name.
8. Click the **[Add...]** button under the **Members** window and enter the username. Click **[OK]**.

NOTE: You may need to add the user to the Administrators group in order to use PowerShell remoting if you don't have a PowerShell group/policy in place for non-administrative users.

Next, you will need to add the group you created to the instance database manager:

1. Log in to the Db2 database as the instance admin user.
2. Open the Db2 admin shell.
3. Run the following commands:

```
db2 update database manager configuration using SYSMON_GROUP <group_name>
```

```
db2stop
```

```
db2start
```

Next, you will grant the DATAACCESS privilege to the new user:

1. Log in to the Db2 database as the instance admin user.
2. Open the Db2 admin shell.
3. Run the following commands:

```
db2 connect to <database>
```

```
db2 "grant DATAACCESS on database to user <user_name>"
```

NOTE: If you do not want to grant DATAACCESS privilege to the user, ScienceLogic provides a Bash and SQL scripts in a .zip file in the PowerPack download folder that grants the user permissions required to monitor Db2 databases.

- The SQL script grants required permissions to monitor Windows Db2 databases. To use the SQL script in the Windows Db2 server:
 - Log in to the Windows Db2 database as the instance admin user.
 - Copy the SQL script named **grant_mon_per.sql** to the Windows Db2 server.
 - With a text editor, open the SQL script and replace `<mon_user_name>` with the user name that you want to grant the permissions to.
 - Save your changes and close the script window.
 - Open the "DB2 Command window" and at the Db2 command line, navigate to the directory where you copied the SQL script above.
 - Connect your database with the following command:

```
db2 connect to <db_name>
```
 - Run the query with the following command:

```
db2 -vtf grant_mon_per.sql
```
 - The required permissions should be configured.

NOTE: You will need to grant this access to each database.

NOTE: Perform the steps to add the group to the instance database manager and to grant the DATAACCESS privilege for each Db2 instance that you will monitor.

Creating Credentials for IBM Db2

To monitor Db2 databases using SL1, you must create two credentials. These credentials enable SL1 to collect data from your Db2 databases. The types of credentials that are required for monitoring depend on the type of database being monitored:

- Linux and Unix users must use an [SSH/Key credential](#) and a [SOAP/XML credential](#)
- Windows users must use a [PowerShell credential](#) and a [SOAP/XML credential](#)

In addition, if the password has changed for the account with access to the Db2 database, you will need to update the corresponding [Database credential](#).

NOTE: SL1 will use SSH or PowerShell at the beginning, and then the client provided by IBM. SL1 uses the instance database manager user to connect to the Db2 database.

Creating an SSH/Key Credential (Linux and Unix Users)

Linux and Unix users must create an SSH/Key credential.

NOTE: If you are using an SL1 system prior to version 11.1.0, the new user interface does not include the **Duplicate** option for sample credential(s). ScienceLogic recommends that you use [the classic user interface and the Save As button](#) to create new credentials from sample credentials. This will prevent you from overwriting the sample credential(s).

To create an SSH/Key credential:

1. Go to the **Credentials** page (Manage > Credentials).
2. Locate the **DB2 SSH Example** credential, click its **[Actions]** icon (⋮) and select **Duplicate**. A copy of the credential, called **DB2 SSH Example copy** appears.
3. Click the **[Actions]** icon (⋮) for the **DB2 SSH Example copy** credential and select **Edit**. The **Edit Credential** page appears. Update the following fields:

4. Supply values in the following fields:

- **Name.** Type a new name for the credential.
- **All Organizations.** Toggle on (blue) to align the credential to all organizations, or toggle off (gray) and then select one or more specific organizations from the **What organization manages this service?** drop-down field to align the credential with those specific organizations.
- **Timeout(ms).** Keep the default setting.
- **Hostname/IP.** Type the IP address or hostname of the Db2 database you want to monitor.
- **Port.** Keep the default setting.
- **Username.** Type the username for a user with access to the Db2 database.
- **Password.** Type the password for the account with access to the Db2 database.
- **Private Key (PEM Format).** Optional. Use if required for SSH authentication.

NOTE: The private key can have a maximum of 64 characters per line. Therefore, you cannot use keys in the OpenSSH format, because that format uses 70 characters per line. When you attempt to save the credential, SL1 will validate that the private key entered is in the correct format. You will be able to save the credential only if the private key is correctly formatted.

NOTE: If you are using a PEM key in the SSH/Key credential, then in your SOAP/XML credential you must fill in the **HTTP Auth User** and **HTTP Auth Password** fields with credentials for the same user.

5. Click the [Save & Close] button.

NOTE: The credential ID will appear in the **Credentials** page (Manage > Credentials) after it has been saved. Take note of the ID as you will need it when creating the SOAP/XML credential. If you cannot see the *ID* column in the **Credentials** page, click the gear icon (⚙️) in the upper-left corner of the page and select *Id* to view the column.

Creating an SSH/Key Credential (Linux and Unix Users) in the SL1 Classic User Interface

Linux and Unix users must create an SSH/Key credential.

To create an SSH/Key credential:

1. Go to the **Credential Management** page (System > Manage > Credentials).
2. Click the wrench icon (🔧) for the "DB2 SSH Example" credential. The **Credential Editor** modal page appears.
3. Supply values in the following fields:
 - **Credential Name.** Type a new name for the credential.
 - **Hostname/IP.** Type the IP address or hostname of the Db2 database you want to monitor.
 - **Port.** Keep the default setting.
 - **Timeout(ms).** Keep the default setting.
 - **Username.** Type the username for a user with access to the Db2 database.
 - **Password.** Type the password for the account with access to the Db2 database.
 - **Private Key (PEM Format).** Optional. Use if required for SSH authentication.

NOTE: The private key can have a maximum of 64 characters per line. Therefore, you cannot use keys in the OpenSSH format, because that format uses 70 characters per line. When you attempt to save the credential, SL1 will validate that the private key entered is in the correct format. You will be able to save the credential only if the private key is correctly formatted.

NOTE: If you are using a PEM key in the SSH/Key credential, then in your SOAP/XML credential you must fill in the **HTTP Auth User** and **HTTP Auth Password** fields with credentials for the same user.

4. Click the **[Save As]** button.
5. When the confirmation message appears, click **[OK]**.

NOTE: The credential ID will appear at the top of the window after it has been saved. Take note of the ID as you will need it when creating the SOAP/XML credential.

Creating a PowerShell Credential (Windows Users)

Windows users must create a PowerShell credential.

NOTE: If you are using an SL1 system prior to version 11.1.0, the new user interface does not include the **Duplicate** option for sample credential(s). ScienceLogic recommends that you use [the classic user interface and the Save As button](#) to create new credentials from sample credentials. This will prevent you from overwriting the sample credential(s).

To create a PowerShell credential:

1. Go to the **Credentials** page (Manage > Credentials).
2. Locate the **DB2 PowerShell Example** credential, click its **[Actions]** icon (⋮) and select **Duplicate**. A copy of the credential, called **DB2 PowerShell Example copy** appears.
3. Click the **[Actions]** icon (⋮) for the **DB2 PowerShell Example copy** credential and select **Edit**. The **Edit Credential** page appears. Update the following fields:

The screenshot shows the 'Edit Credential' interface. The main form contains the following fields and sections:

- Name:** DB2 Powershell Example copy
- Timeout (ms):** 1000
- All Organizations:** A toggle switch and a dropdown menu labeled 'Select the organizations the credential belongs to *'.
- Account Type:** Active Directory (with an 'Encrypted' toggle switch).
- Username:** USER_NAME_GOES_HERE
- Password:** Masked with asterisks.
- Hostname/IP:** %D
- Port:** 5985
- PowerShell Proxy Hostname/IP:** A section with two fields: 'Actual Directory Host/IP' (AD_HOSTNAME_GOES_HERE) and 'Actual Directory Domain' (DOMAIN_GOES_HERE).
- Buttons:** 'Save & Test' (blue) and 'Save & Close' (light blue).

To the right, the **Credential Tester** panel includes:

- Select Credential Test:** A dropdown menu.
- Select Collector:** A dropdown menu.
- IP or Hostname to test *:** A text input field.
- Test Credential:** A button.

4. Supply values in the following fields:


- **Name.** Type a new name for the credential. Can be any combination of alphanumeric characters.
- **All Organizations.** Toggle on (blue) to align the credential to all organizations, or toggle off (gray) and then select one or more specific organizations from the **What organization manages this service?** drop-down field to align the credential with those specific organizations.
- **Timeout (ms).** Type the time, in milliseconds, after which SL1 will stop trying to collect data from the authenticating server. For collection to be successful, SL1 must connect to the authenticating server, execute the PowerShell command, and receive a response within the amount of time specified in this field.
- **Account Type.** Select the type of authentication for the username and password in this credential. Choices are:
 - *Active Directory.* On the device, Active Directory will authenticate the username and password in this credential.
 - *Local.* Local security on the device will authenticate the username and password in this credential.
- **Encrypted.** Enable if you want SL1 to communicate with the device using an encrypted connection. If enabled, SL1 will communicate with the Windows server using a local user account with authentication of type "Basic Auth". You must then use HTTPS and can use a Microsoft Certificate or a self-signed certificate.
- **Username.** Type the username for a user with access to the Db2 database to be monitored.
- **Password.** Type the password for the user account with access to the Db2 database to be monitored.
- **Hostname/IP.** Type the IP address of the Db2 database from which you want to retrieve data, or enter the variable **%D**.
- **Port.** Leave as default value.
- **PowerShell Proxy Hostname/IP.** Leave this field blank.
- **Active Directory Host/IP.** Type the AD hostname or IP here if you selected *Active Directory* under **Account Type**.
- **Active Directory Domain.** Type the AD domain if you selected *Active Directory* under **Account Type**.

5. Click the **[Save & Close]** button.

Creating a PowerShell Credential (Windows Users) in the SL1 Classic User Interface

Windows users must create a PowerShell credential.

To create a PowerShell credential:

1. Go to the **Credential Management** page (System > Manage > Credentials).
2. Click the wrench icon () for the "DB2 Powershell Example" credential. The **Credential Editor** modal page appears.
3. Supply values in the following fields:

- **Profile Name.** Type a new name for the credential. Can be any combination of alphanumeric characters.
- **Account Type.** Select the type of authentication for the username and password in this credential. Choices are:
 - *Active Directory.* On the device, Active Directory will authenticate the username and password in this credential.
 - *Local.* Local security on the device will authenticate the username and password in this credential.
- **Hostname/IP.** Type the IP address of the Db2 database from which you want to retrieve data, or enter the variable **%D**.
- **Timeout (ms).** Type the time, in milliseconds, after which SL1 will stop trying to collect data from the authenticating server. For collection to be successful, SL1 must connect to the authenticating server, execute the PowerShell command, and receive a response within the amount of time specified in this field.
- **Username.** Type the username for a user with access to the Db2 database to be monitored.
- **Password.** Type the password for the user account with access to the Db2 database to be monitored.
- **Encrypted.** Select whether SL1 will communicate with the device using an encrypted connection. Choices are:
 - *yes.* When communicating with the Windows server, SL1 will use a local user account with authentication of type "Basic Auth". You must then use HTTPS and can use a Microsoft Certificate or a self-signed certificate.
 - *no.* When communicating with the Windows server, SL1 will not encrypt the connection.
- **Port.** Leave as default value.
- **PowerShell Proxy Hostname/IP.** Leave this field blank.

4. Click the **[Save As]** button.

Creating a SOAP/XML Credential (Linux and Unix Users)

After configuring the SSH/Key credential, you must then create a SOAP/XML credential.

NOTE: If you are using an SL1 system prior to version 11.1.0, the new user interface does not include the **Duplicate** option for sample credential(s). ScienceLogic recommends that you use [the classic user interface and the Save As button](#) to create new credentials from sample credentials. This will prevent you from overwriting the sample credential(s).

To create the SOAP/XML credential:

1. Go to the **Credentials** page (Manage > Credentials).
2. Locate the **DB2 Soap with SSH Example** credential, click its **[Actions]** icon (☰) and select **Duplicate**. A copy of the credential, called **DB2 Soap with SSH Example copy** appears.
3. Click the **[Actions]** icon (☰) for the **DB2 Soap with SSH Example copy** credential and select **Edit**. The **Edit Credential** page appears. Update the following fields:

The screenshot shows the 'Edit Credential' interface. The main form has the following fields and values:

- Name:** DB2 Soap with SSH Example copy
- All Organizations:** A toggle is turned on (blue), and a dropdown menu is open showing 'Select the organizations the credential belongs to'.
- Timeout (ms):** 2000
- Content Encoding:** text/xml
- Method:** POST
- HTTP Version:** http/1.1
- URL:** http://%D
- HTTP Auth User:** [DATABASE_USER]
- HTTP Auth Password:** [REDACTED]
- Proxy Hostname/IP:** optional
- Proxy Port:** 0
- Proxy User:** optional
- Proxy Password:** [REDACTED]
- Embedded Password [%P]:** [REDACTED]
- Embed Value [%1]:** [REDACTED]
- Embed Value [%2]:** [REDACTED]
- Embed Value [%3]:** [REDACTED]
- Embed Value [%4]:** [REDACTED]

On the right side, there is a 'Credential Tester' panel with the following fields:

- Select Credential Test:** [REDACTED]
- Select Collector:** [REDACTED]
- IP or Hostname to test:** [REDACTED]
- Test Credential:** [Button]

At the bottom right of the main form, there is a 'Save & Close' button.

4. Update the values in the following fields:
 - **Name.** Type a new name for the credential.
 - **All Organizations.** Toggle on (blue) to align the credential to all organizations, or toggle off (gray) and then select one or more specific organizations from the **What organization manages this service?** drop-down field to align the credential with those specific organizations.
 - **URL.** Leave the default value of https://%D.
 - **HTTP Auth User.** If you used a PEM key in the SSH/Key credential, type the username for the same user. Otherwise, if you are inserting the database username and password in the SSH/Key credential, leave this field blank.
 - **HTTP Auth Password.** If you used a PEM key in the SSH/Key credential, type the password for the same user. Otherwise, if you are inserting the database username and password in the SSH/Key credential, leave this field blank.

NOTE: If the **HTTP Auth User** and **HTTP Auth Password** fields are blank, then the Dynamic Applications in the **IBM: Db2 PowerPack** will use the credentials provided in the SSH/Key credential.

- **HTTP Headers.** Add the following headers by clicking + **Add a header**:
 - `base_db2_path:<DB2 Installation Path>`. For example: `base_db2_path:/opt/ibm/db2/V11.5`
 - `instance:<Instance Name>:<Port>` For example: `instance:db2inst1:50000`
 - `instance:<Instance Name2>:<Port2>` For example: `instance:db2inst2:50000`
 - `ssh:<SSH Credential ID>`

NOTE: In versions of the PowerPack prior to version 103, headers required the "<DB_NAME>" value. This value is no longer needed and can be deleted after you upgrade the PowerPack.

NOTE: You can create a header for each Db2 instance you have.

NOTE: During the discovery process, these headers will either find an existing Database credential that matches the user, password, port, and default database, or it will create a new Database credential.


NOTE: By default, the SOAP/XML credential deletes any white space before and after the colon (:) in the credential headers. If you want to include paths with white spaces in the credential, surround the path with double quotes after the colon. For example: `<base_db2_path:"/opt/folder name/program files">`

5. Click the **[Save & Close]** button.

Creating a SOAP/XML Credential (Linux and Unix Users) in the SL1 Classic User Interface

After configuring the SSH/Key credential, you must then create a SOAP/XML credential.

To create the SOAP/XML credential:

1. Go to the **Credential Management** page (System > Manage > Credentials).
2. Click the wrench icon () for the "DB2 Soap with SSH Example" credential for Linux/Unix users. The **Credential Editor** modal page appears.
3. Update the values in the following fields:

Basic Settings

- **Profile Name.** Type a new name for the credential.

- **URL.** Leave the default value of `https://%D`.
- **HTTP Auth User.** If you used a PEM key in the SSH/Key credential, type the username for the same user. Otherwise, if you are inserting the database username and password in the SSH/Key credential, leave this field blank.
- **HTTP Auth Password.** If you used a PEM key in the SSH/Key credential, type the password for the same user. Otherwise, if you are inserting the database username and password in the SSH/Key credential, leave this field blank.

NOTE: If the **HTTP Auth User** and **HTTP Auth Password** fields are blank, then the Dynamic Applications in the **IBM: Db2 PowerPack** will use the credentials provided in the SSH/Key credential.

HTTP Headers

- **HTTP Headers.** Add the following headers by clicking **+ Add a header**:
 - `base_db2_path:<DB2 Installation Path>`. For example: `base_db2_path:/opt/ibm/db2/V11.5`
 - `instance:<Instance Name>:<Port>` For example: `instance:db2inst1:50000`
 - `instance:<Instance Name2>:<Port2>` For example: `instance:db2inst2:50000`
 - `ssh:<SSH Credential ID>`

NOTE: In versions of the PowerPack prior to version 103, headers required the "`<DB_NAME>`" value. This value is no longer needed and can be deleted after you upgrade the PowerPack.

NOTE: You can create a header for each Db2 instance you have.

NOTE: During the discovery process, these headers will either find an existing Database credential that matches the user, password, port, and default database, or it will create a new Database credential.

NOTE: By default, the SOAP/XML credential deletes any white space before and after the colon (:) in the credential headers. If you want to include paths with white spaces in the credential, surround the path with double quotes after the colon. For example: `<base_db2_path:"/opt/folder name/program files">`

4. Click the **[Save As]** button.

Creating a SOAP/XML Credential for an SSL Certificate (Linux and Unix Users)

After configuring the SSH key, you must create a SOAP/XML credential with an SSL certificate if your Db2 server contains an SSL connection.

NOTE: If you are using an SL1 system prior to version 11.1.0, the new user interface does not include the **Duplicate** option for sample credential(s). ScienceLogic recommends that you use [the classic user interface and the Save As button](#) to create new credentials from sample credentials. This will prevent you from overwriting the sample credential(s).

To create the SOAP/XML credential:

1. Go to the **Credentials** page (*Manage > Credentials*).
2. Locate the **DB2 Soap SSL with SSH Example** credential, click its **[Actions]** icon (**---**) and select **Duplicate**. A copy of the credential called **DB2 Soap SSL with SSH Example copy** appears.
3. Click the **[Actions]** icon (**---**) for the **DB2 Soap SSL with SSH Example copy** credential and select **Edit**. The **Edit Credentials** page appears.

The screenshot shows the 'Edit Credential' window with the following details:

- Name:** DB2 Soap SSL with SSH Example
- Organizations:** All Organizations (selected)
- Timeout (ms):** 2000
- Content Encoding:** text/xml
- Method:** POST
- HTTP Version:** http/1.1
- URL:** https://%D
- HTTP Auth User:** [DATABASE_USER]
- HTTP Auth Password:** [REDACTED]
- Proxy Hostname/IP:** optional
- Proxy User:** optional
- Embedded Password [%P]:** [REDACTED]
- Embed Value [%1-4]:** [REDACTED]
- HTTP Headers:**
 - instance:<Instance Name><Port>
 - ssh:<SSH Credential ID>
 - base_db2_path:<DB2 Installation Path>
- CURL Options:** Add CURL Option
 - SSLCERT <PATH TO CER FILE>

The **Credential Tester** panel on the right includes:

- Select Credential test
- Select Collector
- IP or Hostname to test*
- Test Credential button

4. Update the values in the following fields:

- **Name.** Type a new name for the credential.
- **All Organizations.** Toggle on (blue) to align the credential to all organizations, or toggle off (gray) and then select one or more specific organizations from the **What organization manages this service?** drop-down field to align the credentials with those specific organizations.
- **URL.** Leave the default value of `https://%D`.
- **HTTP Auth User.** If you used a PEM key in the SSH credential, type the username for the same user. Otherwise, if you are inserting the database username and password in the SSH credential, leave this field blank.
- **HTTP Auth Password.** If you used a PEM key in the SSH credential, type the password for the same user. Otherwise, if you are inserting the database username and password in the SSH credential, leave this field blank.

NOTE: If the **HTTP Auth User** and the **HTTP Auth Password** fields are blank, then the Dynamic Applications in the IBM: Db2 PowerPack will use the credentials provided in the SSH key.

- **HTTP Headers.** Add the following headers by clicking **+ Add a header:**

- `base_db2_path:<DB2 Installation Path>`.
For example: `base_db2_path:/opt/ibm/db2/v11.5`
- `instance:<Instance Name>:<SSL Port>`
For example: `instance:db2inst1:60000`
- `instance:<Instance Name2>:<SSL Port2>`
For example: `instance:db2inst2:60001`
- `ssh:<SSH Credential ID>`

TIP: In versions of the PowerPack prior to version 103, headers required the `<DB_NAME>` value. This value is no longer needed and can be deleted after you upgrade the PowerPack.

NOTE: You can create a header for each Db2 instance you have.

NOTE: During the discovery process, these headers will either find an existing Database credential that matches the user, password, port, and default database, or it will create a new Database credential.

IMPORTANT: By default, the SOAP/XML credential deletes any white space before and after the colon (:) in the credential headers. If you want to include paths with white spaces in the credential, surround the path with double quotes after the colon. For example: `<base_db2_path: "/opt/folder/name/program files">`

- **CURL options:** Edit the following field in this section:
 - SSLCERT. Type the certificate path for your SSL certificate.

NOTE: The certificate path should be a path of the "Collector Unit" where the SSL certificate is located. For example: `/tmp/certificate.cer`. The permissions for the SSL certificate file should be at least "read" and "write" for the owner, and "read" for the group and others. The permissions for the directory that contains the SSL certificate should be at least "read", "write", and "execute" for the owner, and "read" and "execute" for the group and others.

The screenshot shows the 'Edit Credential' interface. It contains several input fields and sections:


- Proxy User:** optional text input.
- Proxy Password:** password input field with masked characters.
- Embedded Password [%P]:** password input field with masked characters.
- Embed Value [%1-4]:** four text input fields for embedding values.
- HTTP Headers:** a list of headers with 'Add Header' button. Headers include:
 - instance:<Instance Name>:<Port>
 - ssh:<SSH Credential ID>
 - base_db2_path:<DB2 Installation Path>
- CURL Options:** A section highlighted with a red box, containing:
 - SSLCERT: <PATH TO CER FILE>
- Add CURL Option:** A dropdown menu to add more options.

5. Use default values for all other fields.
6. Click **[Save & Close]**.

Creating a SOAP/XML Credential for an SSL Certificate (Linux and Unix Users) in the SL1 Classic User Interface

After configuring the SSH key, you must create a SOAP/XML credential with an SSL certificate if your Db2 server contains an SSL connection.

To create the SOAP/XML credential:

1. Go to the **Credential Management** page (*System > Manage > Credentials*).
2. Click the wrench icon () for the "DB2 Soap SSL with SSH Example" credential for Linux/Unix users. The **Credentials Editor** modal appears.
3. Update the values in the following fields:

Basic Settings

- **Profile Name.** Type a new name for the credential.
- **URL.** Leave the default value of `https://%D`.
- **HTTP Auth User.** If you used a PEM key in the SSH credential, type the username for the same user. Otherwise, if you are inserting the database username and password in the SSH credential, leave this field blank.
- **HTTP Auth Password.** If you used a PEM key in the SSH credential, type the password for the same user. Otherwise, if you are inserting the database username and password in the SSH credential, leave this field blank.

NOTE: If the **HTTP Auth User** and the **HTTP Auth Password** fields are blank, then the Dynamic Applications in the IBM: Db2 PowerPack will use the credentials provided in the SSH key.

- **HTTP Headers.** Add the following headers by clicking **+Add a header**:
 - `base_db2_path:<DB2 Installation Path>`
For example: `base_db2_path:/opt/ibm/db2/v11.5`
 - `instance:<Instance Name>:<SSL Port>`
For example: `instance:db2inst1:60000`
 - `instance:<Instance Name2>:<SSL Port2>`
For example: `instance:db2inst2:60001`
 - `ssh:<SSH Credential ID>`

TIP: In versions of the PowerPack prior to version 103, headers required the `<DB_NAME>` value. This value is no longer needed and can be deleted after you upgrade the PowerPack.

NOTE: You can create a header for each Db2 instance you have.

NOTE: During the discovery process, these headers will either find an existing Database credential that matches the user, password, port, and default database, or it will create a new Database credential.

IMPORTANT: By default, the SOAP/XML credential deletes any white space before and after the colon (:) in the credential headers. If you want to include paths with white spaces in the credential, surround the path with double quotes after the colon. For example: `<base_db2_path: "/opt/folder/name/program files">`

- **CURL Options.**
 - SSLCERT. Type the certificate path for your SSL certificate.
- 4. Use default values for all other fields.
- 5. Click the **[Save As]** button.

Creating a SOAP/XML Credential (Windows Users)

After configuring the PowerShell credential, you must then create a SOAP/XML credential.

NOTE: If you are using an SL1 system prior to version 11.1.0, the new user interface does not include the **Duplicate** option for sample credential(s). ScienceLogic recommends that you use [the classic user interface and the Save As button](#) to create new credentials from sample credentials. This will prevent you from overwriting the sample credential(s).

To create the SOAP/XML credential:

1. Go to the **Credentials** page (Manage > Credentials).
2. Locate the **DB2 Soap with PowerShell Example** credential, click its **[Actions]** icon (⋮) and select **Duplicate**. A copy of the credential, called **DB2 Soap with PowerShell Example copy** appears.
3. Click the **[Actions]** icon (⋮) for the **DB2 Soap with PowerShell Example copy** credential and select **Edit**. The **Edit Credential** page appears. Update the following fields:

4. Update the values in the following fields:

- **Name.** Type a new name for the credential.
- **All Organizations.** Toggle on (blue) to align the credential to all organizations, or toggle off (gray) and then select one or more specific organizations from the **What organization manages this service?** drop-down field to align the credential with those specific organizations.
- **URL.** Leave the default value of `https://%D`.
- **HTTP Auth User.** If you are inserting the database username and password in the PowerShell credential, leave this field blank.
- **HTTP Auth Password.** If you are inserting the database username and password in the PowerShell credential, leave this field blank.
- **HTTP Headers.** Add the following headers by clicking **+ Add a header**:
 - `instance:<Instance Name>:<Port>` For example: `instance:db2inst1:50000`
 - `instance:<Instance Name2>:<Port2>` For example: `instance:db2inst2:50000`
 - `powershell:<PowerShell Credential ID>`

NOTE: You can create a header for each Db2 instance you have.

NOTE: During the discovery process, these headers will either find an existing Database credential that matches the user, password, port, and default database, or it will create a Database credential.


NOTE: By default, the SOAP/XML credential deletes any white space before and after the colon (:) in the credential headers. If you want to include paths with white spaces in the credential, surround the path with double quotes after the colon. For example: `<base_db2_path:"/opt/folder name/program files">`

5. Click the **[Save & Close]** button.

Creating a SOAP/XML Credential (Windows Users) in the SL1 Classic User Interface

After configuring the PowerShell credential, you must then create a SOAP/XML credential.

To create the SOAP/XML credential:

1. Go to the **Credential Management** page (System > Manage > Credentials).
2. Click the wrench icon () for the "DB2 Soap with PowerShell Example" credential for Windows users. The **Credential Editor** modal page appears.
3. Update the values in the following fields:

Basic Settings

- **Profile Name.** Type a new name for the credential.
- **URL.** Leave the default value of `https://%D`.
- **HTTP Auth User.** If you are inserting the database username and password in the PowerShell credential, leave this field blank.
- **HTTP Auth Password.** If you are inserting the database username and password in the PowerShell credential, leave this field blank.

HTTP Headers

- **HTTP Headers.** Add the following headers by clicking **+ Add a header**:
 - `instance:<Instance Name>:<Port>` For example: `instance:db2inst1:50000`
 - `instance:<Instance Name2>:<Port2>` For example: `instance:db2inst2:50000`
 - `powershell:<PowerShell Credential ID>`

NOTE: You can create a header for each Db2 instance you have.

NOTE: During the discovery process, these headers will either find an existing Database credential that matches the user, password, port, and default database, or it will create a Database credential.

NOTE: By default, the SOAP/XML credential deletes any white space before and after the colon (:) in the credential headers. If you want to include paths with white spaces in the credential, surround the path with double quotes after the colon. For example: `<base_db2_path:"/opt/folder name/program files">`

4. Click the **[Save As]** button.

Creating a SOAP/XML Credential for an SSL Certificate (Windows Users)

After configuring the PowerShell credential, you must create a SOAP/XML credential with an SSL certificate if your Db2 server contains an SSL connection.

NOTE: If you are using an SL1 system prior to version 11.1.0, the new user interface does not include the **Duplicate** option for sample credential(s). ScienceLogic recommends that you use [the classic user interface and the Save As button](#) to create new credentials from sample credentials. This will prevent you from overwriting the sample credential(s).

To create the SOAP/XML credential:

1. Go to the **Credentials** page (*Manage > Credentials*).
2. Locate the **DB2 Soap SSL with PowerShell Example** credential, click its **[Actions]** icon (⋮) and select **Duplicate**. A copy of the credential called **DB2 Soap SSL with PowerShell Example copy** appears.
3. Click the **[Actions]** icon (⋮) for the **DB2 Soap SSL with PowerShell Example copy** credential and select **Edit**. The **Edit Credentials** page appears.

The screenshot shows the 'Edit Credential' dialog box. The main form has the following fields and options:

- Name:** DB2 Soap SSL with Powershell Example
- All Organizations:** A toggle switch is currently turned on (blue).
- Timeout (ms):** 2000
- Content Encoding:** text/xml
- Method:** POST
- HTTP Version:** http/1.1
- URL:** https://%D
- HTTP Auth User:** [DATABASE_USER]
- HTTP Auth Password:** [REDACTED]
- Proxy Hostname/IP:** optional
- Proxy User:** optional
- Proxy Password:** [REDACTED]
- Embedded Password [%P]:** [REDACTED]
- Embed Value [%1]:** [REDACTED]
- Embed Value [%2]:** [REDACTED]
- Embed Value [%3]:** [REDACTED]
- Embed Value [%4]:** [REDACTED]
- HTTP Headers:**
 - instance:<Instance Name>:<Port> (with an 'X' to remove)
 - powershell:<PowerShell Credential ID> (with an 'X' to remove)
- CURL Options:**
 - SSLCERT: <PATH TO CER FILE> (with an 'X' to remove)

On the right side, there is a 'Credential Tester' panel with the following options:

- Select Credential test: [Dropdown]
- Select Collector: [Dropdown]
- IP or Hostname to test: [Text Field]
- Test Credential: [Button]

A 'Close' button is located at the bottom right of the dialog.

4. Update the values in the following fields:

- **Name.** Type a new name for the credential.
- **All Organizations.** Toggle on (blue) to align the credential to all organizations, or toggle off (gray) and then select one or more specific organizations from the *What organization manages this service?* drop-down field to align the credentials with those specific organizations.
- **URL.** Leave the default value of https://%D.
- **HTTP Auth User.** If you are inserting the database username and password in the PowerShell credential, leave this field blank.
- **HTTP Auth Password.** If you are inserting the database username and password in the PowerShell credential, leave this field blank.
- **HTTP Headers.** Add the following headers by clicking + **Add a header:**
 - `instance: <Instance Name>:<Port>`
For example: `instance:db2inst1:6000`
 - `instance:<Instance Name2>:<Port2>`
For example: `instance:db2inst2:6000`
 - `powershell:<PowerShell Credential ID>`

NOTE: You can create a header for each Db2 instance you have.

NOTE: During the discovery process, these headers will either find an existing Database credential that matches the user, password, port, and default database, or it will create a new Database credential.

IMPORTANT: By default, the SOAP/XML credential deletes any white space before and after the colon (:) in the credential headers. If you want to include paths with white spaces in the credential, surround the path with double quotes after the colon. For example: `<base_db2_path:"/opt/folder/name/program files">`

- **CURL options:** Edit the following field in this section:
 - SSLCERT. Type the certificate path for your SSL certificate.

NOTE: The certificate path should be a path of the "Collector Unit" where the SSL certificate is located. For example: `/tmp/certificate.cer`. The permissions for the SSL certificate file should be at least "read" and "write" for the owner, and "read" for the group and others. The permissions for the directory that contains the SSL certificate should be at least "read", "write", and "execute" for the owner, and "read" and "execute" for the group and others.

5. Use default values for all other fields.
6. Click **[Save & Close]**.

Creating a SOAP/XML Credential for an SSL Certificate (Windows Users) in the SL1 Classic User Interface

After configuring the PowerShell credential, you must create a SOAP/XML credential with an SSL certificate if your Db2 server contains an SSL connection.

To create the SOAP/XML credential:

1. Go to the **Credential Management** page (*System > Manage > Credentials*).
2. Click the wrench icon (🔧) for the "DB2 Soap SSL with PowerShell Example" credential for Windows users. The **Credentials Editor** modal appears.
3. Update the values in the following fields:

Basic Settings

- **Profile Name.** Type a new name for the credential.
- **All Organizations.** Toggle on (blue) to align the credential to all organizations, or toggle off (gray) and then select one or more specific organizations from the **What organization manages this service?** drop-down field to align the credentials with those specific organizations.
- **URL.** Leave the default value of https://%D.
- **HTTP Auth User.** If you are inserting the database username and password in the PowerShell credential, leave this field blank.
- **HTTP Auth Password.** If you are inserting the database username and password in the PowerShell credential, leave this field blank.
- **HTTP Headers.** Add the following headers by clicking **+Add a header:**
 - `instance:<Instance Name>:<SSL Port>`
For example: `instance:db2inst1:60000`
 - `instance:<Instance Name2>:<SSL Port2>`
For example: `instance:db2inst2:60001`
 - `powershell:<PowerShell Credential ID>`

NOTE: You can create a header for each Db2 instance you have.

NOTE: During the discovery process, these headers will either find an existing Database credential that matches the user, password, port, and default database, or it will create a new Database credential.

IMPORTANT: By default, the SOAP/XML credential deletes any white space before and after the colon (:) in the credential headers. If you want to include paths with white spaces in the credential, surround the path with double quotes after the colon. For example: `<base_db2_path:"/opt/folder/name/program files">`

- **CURL Options.**
 - **SSLCERT.** Type the certificate path for your SSL certificate.

NOTE: The certificate path should be a path of the "Collector Unit" where the SSL certificate is located. For example: `/tmp/certificate.cer`. The permissions for the SSL certificate file should be at least "read" and "write" for the owner, and "read" for the group and others. The permissions for the directory that contains the SSL certificate should be at least "read", "write", and "execute" for the owner, and "read" and "execute" for the group and others.

4. Use default values for all other fields.
5. Click the **[Save As]** button.

Updating the Database Credential

If the password has changed for the account with access to the Db2 database, you must also update the corresponding Database credential in SL1. Otherwise, you can skip this section.


To update the Database credential:

1. Go to the **Credentials** page (Manage > Credentials).
2. Search for and locate the credential that includes the name and port of the database with the updated password, then click the credential's Actions icon (⋮) and select *Edit/Test*.
3. In the **Edit Credential** page that appears, type the new password in the **Password** field.
4. Click **[Save & Close]**.

Discovering IBM Db2 Component Devices

To discover an IBM Db2 database:


1. On the **Devices** page (📄) or the **Discovery Sessions** page (Devices > Discovery Sessions), click the **[Add Devices]** button. The **Select** page appears:



2. Click the **[Unguided Network Discovery]** button. Additional information about the requirements for discovery appears in the **General Information** pane to the right.
3. Click **[Select]**. The **Add Devices** page appears.
4. Complete the following fields:


- **Name.** Type a unique name for this discovery session. This name is displayed in the list of discovery sessions on the **[Discovery Sessions]** tab.
- **Description.** Optional. Type a short description of the discovery session. You can use the text in this description to search for the discovery session on the **[Discovery Sessions]** tab.
- **Select the organization to add discovered devices to.** Select the name of the organization to which you want to add the discovered devices

5. Click **[Next]**. The **Credentials** page of the **Add Devices** wizard appears:




6. On the **Credentials** page, locate and select the SOAP/XML **credential** you created for the Db2 database.

7. Click **[Next]**. The **Discovery Session Details** page of the **Add Devices** wizard appears:



8. Complete the following fields:



- **List of IPs/Hostnames.** Type the IP address of Type the IP address for the Db2 database.
- **Which collector will monitor these devices?** Required. Select an existing collector to monitor the discovered devices.
- **Run after save.** Select this option to run this discovery session as soon as you save the session.

In the **Advanced options** section, click the down arrow icon () to complete the following fields:

- **Discover Non-SNMP.** Enable this setting.
 - **Model Devices.** Enable this setting.
9. Click **[Save and Run]** if you enabled the **Run after save** setting, or **[Save and Close]** to save the discovery session. The **Discovery Sessions** page (Devices > Discovery Sessions) displays the new discovery session.
 10. If you selected the **Run after save** option on this page, the discovery session runs, and the **Discovery Logs** page displays any relevant log messages. If the discovery session locates and adds any devices, the **Discovery Logs** page includes a link to the **Device Investigator** page for the discovered device.

Discovering IBM Db2 Component Devices in the SL1 Classic User Interface

To discover an IBM Db2 database:

1. Go to the **Discovery Control Panel** page (System > Manage > Classic Discovery).
2. In the **Discovery Control Panel**, click the **[Create]** button. The **Discovery Session Editor** page appears.
3. In the **Discovery Session Editor** page, complete the following fields:
 - **Name.** Type a name for the discovery session.
 - **IP Address/Hostname Discovery List.** Type the IP address for the Db2 database.
 - **Other Credentials.** Select the SOAP/XML credential you created for the Db2 database.
 - **Discover Non-SNMP.** Select this checkbox.
 - **Model Devices.** Select this checkbox.
4. Optionally, you can enter values in the other fields on this page. For more information about the other fields on this page, see the **Discovery & Credentials** manual.
5. Click the **[Save]** button to save the discovery session and then close the **Discovery Session Editor** window.
6. The discovery session you created appears at the top of the **Discovery Control Panel** page. Click its lightning-bolt icon () to run the discovery session.
7. The **Discovery Session** window appears. When the cluster root device(s) are discovered, click the device icon () to view the **Device Properties** page for each device.

Verifying Discovery and Dynamic Application Alignment

To verify that SL1 has automatically aligned the correct Dynamic Applications during discovery:

1. After the discovery session has completed, go to the **Devices** page—or the **Device Manager** (Registry > Devices > Device Manager) page in the SL1 classic user interface—and find the device(s) you discovered. When you have located the device, click on its name or click on its edit icon (🔧) if you are in the SL1 classic user interface.
2. Click the **[Collections]** tab.
3. All applicable Dynamic Applications for the Db2 devices are automatically aligned during discovery.

NOTE: It can take several minutes after the discovery session has completed for Dynamic Applications to appear in the **Dynamic Application Collections** page.

To verify alignment of the IBM Db2 Dynamic Applications:


1. After discovery has completed, go to the **Discovery Logs** page (Devices > Discovery Sessions > click the Actions button ⋮ for that session > click Show Logs) and click on the IP address of the device. If you are in the SL1 classic user interface, click the device icon for the IBM Db2 device (🖨️). From the **Device Investigator** page for the IBM Db2 device, or the **Device Properties** page if you are in the SL1 classic user interface, click the **[Collections]** tab. The **Dynamic Application Collections** page appears.

NOTE: It can take several minutes after the discovery session has completed for Dynamic Applications to appear in the **Dynamic Application Collections** page.

2. All applicable Dynamic Applications are automatically aligned to the root device and component devices during discovery:


You should see the following Dynamic Application aligned to the root device:

- IBM DB2: Server Discovery




You should see the following Dynamic Application aligned to the Db2 server:

- IBM DB2: Instance Discovery



You should see the following Dynamic Application aligned to the Db2 instance:


- IBM DB2: Database Discovery
- IBM DB2: Diagnostics Log Configuration



You should see some or all of the following Dynamic Applications aligned to the Db2 database:

- IBM DB2: Authorizations Configuration
- IBM DB2: Buffer Pools Performance


- IBM DB2: Database Status
- IBM DB2: Indexes Configuration
- IBM DB2: Product Configuration
- IBM DB2: Subclass Performance
- IBM DB2: Summary Performance
- IBM DB2: System Utilization Performance
- IBM DB2: Tables Performance
- IBM DB2: Tablespace Discovery
- IBM DB2: Workload Performance
- IBM DB2: Installed Products Configuration



You should see the following Dynamic Applications aligned to the Db2 tablespace:

- IBM DB2: Tablespace Capacity Performance
- IBM DB2: Tablespace Configuration
- IBM DB2: Tablespace Container Configuration

- IBM DB2: Tablespace Container Performance
- IBM DB2: Tablespace Performance




NOTE: The *IBM Db2 PowerPack* uses *db2ilist* to discover all Db2 instances, but the Dynamic Applications will be aligned to only the instances specified in the SOAP/XML credential headers.

Viewing IBM Db2 Component Devices

In addition to the **Device Manager** page (Registry > Devices > Device Manager), you can view the IBM Db2 server and all associated component devices in the following places in the user interface:


- The **Device Investigator** Map page (click **Map** in the **Device Investigator** page) displays a map of a particular device and all of the devices with which it has parent-child relationships. Double-clicking any of the listed devices reloads the page to make the selected device the primary device:



- The **Device Components** page (Devices > Device Components) displays a list of all root devices and component devices discovered by SL1 in an indented view, so you can easily view the hierarchy and relationships between child devices, parent devices, and root devices. To view the component devices associated with an IBM Db2 server, find the IBM Db2 device and click its plus icon (+):

Device Name	IP Address	Device Category	Device Class Sub-class	DID	Organization	Current State	Collection Group	Collection State
1 + 10.2.21.176	10.2.21.176	Unknown	Ping Generic Linux	951	System	Healthy	OCG	User-Disabled
2 - 10.2.21.67	10.2.21.67	Pingable	Ping ICMP	947	System	Healthy	OCG	User-Disabled
1 - IBM Db2 Server	--	Software	IBM DB2 Server	948	System	Healthy	DCG	User-Disabled
1 dbinst1	--	Software	IBM DB2 Instance	949	System	Healthy	DCG	User-Disabled/Unavailable
2 dbinst2	--	Software	IBM DB2 Instance	950	System	Healthy	DCG	User-Disabled/Unavailable

- The **Component Map** page (Classic Maps > Device Maps > Components) allows you to view devices by root node and view the relationships between root nodes, parent components, and child components in a map. This makes it easy to visualize and manage root nodes and their components. SL1 automatically updates the **Component Map** as new component devices are discovered. The platform also updates each map with the latest status and event information. To view the map for an IBM Db2 server, go to the **Component Map** page and select the map from the list in the left NavBar. To learn more about the **Component Map** page, see the **Maps** manual.



Chapter

3

IBM Db2 Dashboards in the SL1 Classic User Interface

Overview

The following section describes the device dashboards that are included in the *IBM: Db2* PowerPack:


This chapter covers the following topics:

<i>Device Dashboard</i>	42
-------------------------------	----

Device Dashboard

The *IBM: Db2* PowerPack includes device dashboards that provide summary information for Db2 databases and tablespaces.

IBM Db2: Database



The IBM Db2: Database device dashboard displays the following information:

- Six gauges that display the following metrics:
 - I/O Wait Time
 - Compile Wait Time
 - Req. Wait Time
 - Net. Wait Time
 - Act. Wait Time
 - Lock Wait Time

- A line graph that displays the following information:
 - Average Request CPU Time (s)
 - Total Application Requests Completed (Count)
 - Total Activities Completed (Count)

- Total Application Commits (Count)
- Total Application Rollbacks (Count)
- A line graph that displays the following information on sections:
 - Sections Sort Time (%)
 - Sections Process Time (%)
 - Transactions End Process Time (%)
- A line graph that displays the following information on locks:
 - Average Lock Timeouts Per Activities (Count)
 - Average Deadlocks per Activities (Count)
 - Average Lock Waits Per Activities (Count)
- A line graph that displays the following information on wait times:
 - Network Wait Time (%)
 - Caching Wait Time (%)
 - I/O Wait Time (%)
 - Requests Wait Time (%)

IBM: DB2 Tablespace



The IBM DB2: Tablespace device dashboard displays the following information:

- Three gauges that display the following metrics:
 - Hit Ratio
 - Size Utilization
 - Pages Utilization
- A line graph that displays the following information:
 - Total Pages (Count)
 - Usable Size (KB)
 - Total Size (KB)
 - Used Size (KB)
 - Free Size (KB)
- A line graph that displays the following information:

- Direct Reads (Count)
- Direct Writes (Count)
- Logical Reads (Count)
- A line graph that displays the following information:
 - Direct Write Time (ms)
 - Direct Read Time (ms)
 - Pool Write Time (ms)
 - Pool Read Time (ms)

© 2003 - 2024, ScienceLogic, Inc.

All rights reserved.

LIMITATION OF LIABILITY AND GENERAL DISCLAIMER

ALL INFORMATION AVAILABLE IN THIS GUIDE IS PROVIDED "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED. SCIENCELOGIC™ AND ITS SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT.

Although ScienceLogic™ has attempted to provide accurate information on this Site, information on this Site may contain inadvertent technical inaccuracies or typographical errors, and ScienceLogic™ assumes no responsibility for the accuracy of the information. Information may be changed or updated without notice. ScienceLogic™ may also make improvements and / or changes in the products or services described in this Site at any time without notice.

Copyrights and Trademarks

ScienceLogic, the ScienceLogic logo, and EM7 are trademarks of ScienceLogic, Inc. in the United States, other countries, or both.

Below is a list of trademarks and service marks that should be credited to ScienceLogic, Inc. The ® and ™ symbols reflect the trademark registration status in the U.S. Patent and Trademark Office and may not be appropriate for materials to be distributed outside the United States.

- ScienceLogic™
- EM7™ and em7™
- Simplify IT™
- Dynamic Application™
- Relational Infrastructure Management™

The absence of a product or service name, slogan or logo from this list does not constitute a waiver of ScienceLogic's trademark or other intellectual property rights concerning that name, slogan, or logo.

Please note that laws concerning use of trademarks or product names vary by country. Always consult a local attorney for additional guidance.

Other

If any provision of this agreement shall be unlawful, void, or for any reason unenforceable, then that provision shall be deemed severable from this agreement and shall not affect the validity and enforceability of any remaining provisions. This is the entire agreement between the parties relating to the matters contained herein.

In the U.S. and other jurisdictions, trademark owners have a duty to police the use of their marks. Therefore, if you become aware of any improper use of ScienceLogic Trademarks, including infringement or counterfeiting by third parties, report them to Science Logic's legal department immediately. Report as much detail as possible about the misuse, including the name of the party, contact information, and copies or photographs of the potential misuse to: legal@sciencelogic.com. For more information, see <https://sciencelogic.com/company/legal>.

ScienceLogic

800-SCI-LOGIC (1-800-724-5644)

International: +1-703-354-1010