



Managing PowerPacks

Skylar One version 12.5.21

Table of Contents

Introduction to Managing PowerPacks	4
What is a PowerPack?	4
Who Should Read this Manual?	5
Installing a PowerPack	6
How Skylar One Updates Default PowerPacks	7
Importing and Installing a PowerPack	8
Importing a PowerPack	9
Installing a Single PowerPack	10
Installing Multiple PowerPacks	12
Checking the Status of Installed Content	13
Viewing the List of PowerPacks	15
Viewing Documentation for a PowerPack	16
Viewing a Document from the .em7pp File	16
Downloading a Document	16
System Settings that Affect PowerPacks	16
PowerPack Signing and Signature Verification	18
Managing Trusted GPG Public Keys	18
Requiring Signed PowerPacks	18
Signature Validation During PowerPack Installation	19
Installing Out-of-Band PowerPacks in FedRAMP Environments	19
Creating a PowerPack	20
Caveats	21
Creating a PowerPack	22
Creating a Container for a PowerPack	22
Adding Content to a PowerPack	24
Adding Documentation to a PowerPack	27
Adding a Documentation File to a PowerPack	27
Changing Visibility	28
Deleting a Document	28
Including Details on a PowerPack's Features, Benefits, and Technical Information	28
Features/Benefits	28

Technical Notes	29
Adding Intellectual Property Protection to Content in a PowerPack	29
Determining the PowerPack's Execution Environments	30
Building the PowerPack and Generating a License Key	31
Building a PowerPack	31
Generating an Embedded License Key During the Initial Build	31
Generating an Unembedded License During the Initial Build	36
Export Rules, Import Rules, and Substitutions	40
Dynamic Applications	40
Event Policies	40
Device Templates	41
Device Groups	41
Dashboards	41
Run Book Actions	42
Run Book Policies	43
Credentials	44
Credential Tests	44
Ticket Templates	44
IT Service Policies	45
Exporting a PowerPack	46
Generating an Embedded License Key After the Initial Build	46
Generating an Unembedded License Key After the Initial Build	47
Editing a PowerPack	48
Caveats	48
Privileges for Editing a PowerPack	49
Editing a PowerPack	57
Editing Dynamic Applications in a PowerPack	58
Generating a New License Key for the PowerPack	59
Assigning a New License Key to an Already-Installed PowerPack	59
Deleting One or More PowerPacks	60
Removing Content from a PowerPack	60

Chapter

1

Introduction to Managing PowerPacks

Overview

This manual describes how to manage and use PowerPacks in Skylar One.

This chapter covers the following topics:

<i>What is a PowerPack?</i>	4
<i>Who Should Read this Manual?</i>	5

What is a PowerPack?

A **PowerPack** is an exportable and importable package of one or more Dynamic Applications, device classes, device templates, event policies, custom reports, dashboard widgets, dashboards, run book policies, run book actions, ticket templates, credentials, themes, device categories, and/or business service policies.

You can use PowerPacks to share customized content among Skylar One systems and to download customized content from ScienceLogic.

You can create a PowerPack on a Skylar One system to export one or more Dynamic Applications, device classes, device templates, event policies, custom reports, dashboard widgets, dashboards, run book policies, run book actions, ticket templates, credentials, themes, device categories, and/or business service policies. You can then import that PowerPack on another Skylar One system to install these items on that system.

PowerPacks include automatically generated version numbers and license keys to provide version control and to protect the content of each PowerPack. When exporting a PowerPack you can generate a license that prevents users from editing content included in the PowerPack.

You can also apply Intellectual Property Protection (IPP) to the Dynamic Applications and event policies you include in a PowerPack. IPP prevents other users from viewing information required only for editing purposes, and from editing the Dynamic Application or event policy. When IPP is applied, the Dynamic Application or event policy can be ***edited only on the author system*** (Skylar One system where the Dynamic Application or event policy was created) and only by users with the appropriate Access Keys.

This manual will describe how to:

- Install a PowerPack
- Get information about a PowerPack
- Edit a PowerPack
- Create a PowerPack
- Delete a PowerPack

Who Should Read this Manual?

This manual is intended for administrators and developers who create, install, and manage Dynamic Applications, event policies, device classes, device templates, custom reports, custom dashboard widgets, dashboards, run book policies, run book actions, ticket templates, credentials, themes, and/or business service policies.

Chapter

2

Installing a PowerPack

Overview

This chapter describes how to install a PowerPack in your Skylar One system. There are two general steps to install a PowerPack:

- **Importing** a PowerPack loads the PowerPack file into Skylar One and allows you to see information about the PowerPack and how the contents of the PowerPack will be installed.
- **Installing** a PowerPack writes the contents of the PowerPack to your Skylar One system.

These steps can be performed to install new PowerPacks (a PowerPack that has not previously been installed in Skylar One) and to update PowerPacks that are already installed in your Skylar One system.

This chapter covers the following topics:

<i>How Skylar One Updates Default PowerPacks</i>	7
<i>Importing and Installing a PowerPack</i>	8
<i>Viewing the List of PowerPacks</i>	15
<i>Viewing Documentation for a PowerPack</i>	16
<i>System Settings that Affect PowerPacks</i>	16
<i>PowerPack Signing and Signature Verification</i>	18

NOTE: If ScienceLogic includes a new PowerPack in the standard software package, the PowerPack will be automatically installed the next time you apply an update to your Skylar One system. The release notes for every release indicate which PowerPacks will be automatically installed.

How Skylar One Updates Default PowerPacks

ScienceLogic includes multiple PowerPacks in the default installation of Skylar One. When you apply an update to your system, new versions of the default PowerPacks will be automatically imported in to your system. If a PowerPack is included in an update and is not currently installed on your system, Skylar One will automatically install the PowerPack. If a PowerPack is included in an update and is currently installed on your system, Skylar One will automatically import (but not install) the PowerPack.

If PowerPacks have been imported into your system but have not been installed, the **Update** column appears in the **PowerPack Manager** page (System > Manage > PowerPacks). For each PowerPack that has been imported to your system but has not been installed, the lightning bolt icon (⚡) appears in the **Update** field on the **PowerPack Manager** page.

NOTE: If a PowerPack updates one or more device classes, device categories, or Dynamic Applications, Skylar One will not overwrite the alignment between device dashboards and any updated device classes, device categories, or Dynamic Applications.

To install the new version of a single PowerPack:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. In the **PowerPack Manager** page, click the lightning bolt icon (⚡) for the PowerPack you want to install.
3. The **PowerPack Installer** modal page will display the contents of the PowerPack. The **PowerPack Installer** modal page will indicate how Skylar One will update each item in the PowerPack. If the actions that Skylar One will perform are acceptable, click the **[Install]** button.
4. If you have made any local changes to the Dynamic Applications or Event Policies in the PowerPack and that content will be overwritten with this update, Skylar One will display the following message before updating the PowerPack:

WARNING: Local PowerPack changes detected. Proceeding with installation will overwrite these changes.

Click the **[OK]** button to overwrite the local changes. Click the **[Cancel]** button to quit the update.

5. If you completed the update, , updated information about the PowerPack will appear in the **PowerPack Manager** page. All the items in the PowerPack will be automatically installed in your Skylar One system.

NOTE: The *Enable Selective PowerPack Field Protection* field in the **Behavior Settings** page affects how updates behave. If the *Enable Selective PowerPack Field Protection* checkbox is selected, certain fields in Event Policies, Dynamic Applications, and Device Classes will **not** be updated.

To install the updates for multiple PowerPacks:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. In the **PowerPack Manager** page, select the checkbox for each PowerPack you want to install.
3. In the **Select Action** drop-down field (in the lower right), choose *Update PowerPack(s)*.
4. Skylar One will display the following message before updating the PowerPack(s):

Update the selected PowerPacks?

NOTE: Any customizations to items contained in updated PowerPacks will be overwritten by the version contained within the more recently imported PowerPack file.

Click the **[OK]** button to continue the installation. Click the **[Cancel]** button to quit the update.

5. Click the **[Go]** button. If you completed the update, updated information about the PowerPack will appear in the **PowerPack Manager** page. All the items in the PowerPack will be automatically installed in your Skylar One system.

NOTE: You can install multiple PowerPacks with the **Select Action** drop-down list only if each selected PowerPack includes an embedded Installation Key. PowerPacks that do not include embedded Installation Keys will fail to install.

NOTE: The *Enable Selective PowerPack Field Protection* field in the **Behavior Settings** page affects how updates behave. If the *Enable Selective PowerPack Field Protection* checkbox is selected, certain fields in Event Policies, Dynamic Applications, and Device Classes will **not** be updated.

Importing and Installing a PowerPack

Before installing a PowerPack, you must first import it. After a PowerPack has been imported, you can immediately install it or install it at a later time.

NOTE: The following sections describe how to import and install PowerPacks using the user interface. In addition to the user interface, PowerPacks can also be imported or installed via the ScienceLogic API. PowerPacks imported or installed via the user interface will appear in the ScienceLogic API and vice versa. For information about importing or installing PowerPacks via the ScienceLogic API, see the manual *Using the ScienceLogic API*.

NOTE: Skylar One supports digital signature verification for PowerPacks. Depending on system settings and stack type, PowerPacks may be required to be signed by a trusted GPG public key before they can be imported or installed. Signature validation is performed automatically during the PowerPack import and installation process. For more information about managing trusted public keys, enforcing signed PowerPacks, and how signature verification affects PowerPack installation behavior, see [PowerPack Signing and Signature Verification](#).

Importing a PowerPack

You can import a PowerPack from the **PowerPack Manager** page. To import a PowerPack to be installed at a later time:

1. Search for and download the PowerPack from the **PowerPacks** page at the [ScienceLogic Support Center](#) (Skylar One > PowerPacks, login required).
2. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).

NOTE: To install a PowerPack, you might have to enter the license key for the PowerPack. You can get this license key from the PowerPack's author or the PowerPack administrator for your system. You cannot install a PowerPack that requires a license key without the license key.

3. In the **PowerPack Manager** page, click the **[Actions]** button. Click *Import PowerPack*.
4. The **Import PowerPack** dialog box appears.
 - Use the **[Browse]** button to navigate to the PowerPack file.
 - *If the PowerPack includes an embedded license key*, do not enter a value in the **License** field.
 - *If the PowerPack does not include an embedded license key*, enter the license key in the **License** field.
5. When the **PowerPack Installer** modal page appears, you can do one of the following:
 - Immediately install the PowerPack.
 - Exit the page without installing the PowerPack. If you do so, Skylar One will store the PowerPack for later installation.

NOTE: If you exit the **PowerPack Installer** modal page without installing the imported PowerPack, the imported PowerPack will not appear in the **PowerPack Manager** page. However, the imported PowerPack will appear in the **Imported PowerPacks** modal page. This page appears when you click the **[Actions]** menu and choose **Install PowerPack**.

CAUTION: If you have modified one or more content items in a PowerPack that you are updating and want to preserve your changes, you must remove those content items from the PowerPack in your system before installing the new version of the PowerPack. If the **Package Content** pane indicates that Skylar One will *update* a content item that you have edited, any changes you have made will be overwritten when you install the PowerPack. If you do not want your changes to be overwritten, click the **[Close / Esc]** button, remove the content item from the PowerPack, then follow the steps listed in the [Installing a PowerPack](#) section to install the PowerPack. For instructions on how to remove a content item from a PowerPack, see the [Editing a PowerPack](#) section.

Installing a Single PowerPack

To install a new or updated PowerPack that is not included in the default installation of Skylar One, you must first [import the PowerPack](#). You can then immediately install the PowerPack or install it at a later time.

To install a PowerPack that has previously been imported to your Skylar One system, perform the following steps:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. If you have not already done so, [import the PowerPack](#).
3. In the **PowerPack Manager** page, click the **[Actions]** menu and click **Install PowerPack**.
4. The **Imported PowerPacks** modal page appears, displaying a list of PowerPacks that have already been imported. The list displays:
 - **PowerPack Name**. Name of the PowerPack.
 - **Flag**. Indicates if the PowerPack is a beta release.
 - **Version**. Version of the PowerPack. This number is user-defined and manually incremented by the PowerPack author.
 - **Revision**. The revision number for the PowerPack.
 - **GUID**. Unique identifier for the PowerPack. This number is unique across all ScienceLogic appliances.
 - **Last Edited**. Date and time the PowerPack was last imported or updated.
 - **Imported**. Date and time the PowerPack was imported.
 - **Lightning-bolt icon** (⚡). Click this icon to install a single PowerPack.

- **Checkbox** (☐). Click the checkbox and use the **Select Action** menu to install multiple PowerPacks simultaneously.
5. In the **Imported PowerPack** modal page, click the lightning-bolt icon (⚡) for the PowerPack that you want to install.
 6. After selecting a PowerPack, the **Install PowerPack** modal page appears. The page displays:
 - **PowerPack Name**. Name of the PowerPack.
 - **Version**. Version number for the PowerPack. You can enter any combination of characters in this field. You must manually update this field to change the version number.
 - **Package Information**. Displays information about the PowerPack, including:
 - *GUID*. Unique identifier for the PowerPack. This number is unique across all Skylar One appliances.
 - *Revision*. The revision number for the PowerPack.
 - *Exported From*. If possible, displays the name and build ID of the version where the PowerPack was exported.
 - *Created*. Date and time the PowerPack was created.
 - *Updated*. Date and time the PowerPack was last edited.
 - *Compiled*. Date and time the PowerPack was last built.
 - *EM7 Minimum Version*. The minimum Skylar One version required to use the PowerPack.
 - **Package Content**. This pane displays a list of content items contained in the PowerPack and the action that Skylar One will perform for each content item when the PowerPack is installed.
 - *Content Item Name*. Name of the content item.
 - *Version*. Version number of the content item.
 - *GUID*. Unique identifier for the content item. This number is unique across all Skylar One appliances in your system.
 - *Action*. When you install a PowerPack, Skylar One will perform one of the following actions for each content item included in the PowerPack:
 - **Install**. The content item is not currently installed on your Skylar One system. When you install the PowerPack, Skylar One will add the content item to your system.
 - **Update**. The PowerPack you are installing is currently installed in your Skylar One system, and the content item is currently installed on your Skylar One system and still included in the PowerPack you are installing. When you install the PowerPack, Skylar One will replace the currently installed version of the content item with the new version of the content item. Skylar One will preserve the relationship the content item has to other entities in your system. For example, if a Dynamic Application is updated during the installation of a PowerPack, the Dynamic Application will remain aligned to devices with the same credential alignments and device-specific threshold settings.

- **Ignore.** The content item is currently installed on your Skylar One system, but is not currently associated with the PowerPack you are installing in your Skylar One system. This typically occurs when a user has removed the content item from the PowerPack in your Skylar One system. When you install the PowerPack, Skylar One will not modify the currently installed version of the content item nor add the new version of the content item to your Skylar One system.
 - **Installation Key.** The Installation Key for the PowerPack.
 - If the actions that Skylar One will perform are acceptable, click the **[Install]** button to install the PowerPack.
 - The PowerPack will now appear in the **PowerPack Manager** page. All the items in the PowerPack will be automatically installed in your Skylar One system.
7. If the actions that Skylar One will perform are acceptable, click the **[Install]** button to install the PowerPack.
 8. The PowerPack will now appear in the **PowerPack Manager** page. All the items in the PowerPack will be automatically installed in your Skylar One system.

Installing Multiple PowerPacks

To install multiple PowerPacks that have previously been imported to your Skylar One system, perform the following steps:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. If you have not already done so, [import the PowerPack](#).
3. In the **PowerPack Manager** page, click the **[Actions]** menu and click *Install PowerPack*.
4. The **Imported PowerPacks** modal page appears, displaying a list of PowerPacks that have already been imported. The list displays:
 - **PowerPack Name.** Name of the PowerPack.
 - **Flag.** Indicates if the PowerPack is a beta release.
 - **Version.** Version of the PowerPack. This number is user-defined and manually incremented by the PowerPack author.
 - **Revision.** The revision number for the PowerPack.
 - **GUID.** Unique identifier for the PowerPack. This number is unique across all ScienceLogic appliances.
 - **Last Edited.** Date and time the PowerPack was last imported or updated.
 - **Imported.** Date and time the PowerPack was imported.
 - **Lightning-bolt icon** (⚡). Click this icon to install a single PowerPack.
 - **Checkbox** (☐). Click the checkbox and use the **Select Action** menu to install multiple PowerPacks simultaneously
5. In the **Imported PowerPacks** modal page, click the checkbox for each PowerPack that you want to install. To select all checkboxes for all PowerPacks, select the checkbox at the top of the page.
6. In the **Select Action** drop-down list, click *Install PowerPacks*.

7. Click the **[Go]** button.
8. The **PowerPack Installation** modal page appears and displays the status of the installation.
 - To view details about each installed PowerPack or to enter an **Installation Key**, click the lightning-bolt icon (⚡). The **Install PowerPack** modal page appears. You can exit this page without performing any actions, and the PowerPacks are still automatically installed on your system. For a description of the **Install PowerPack** modal page, see the section on [Installing a Single PowerPack](#).
 - If the installation is successful, the selected PowerPacks are installed on your system.
 - Each PowerPack will now appear in the **PowerPack Manager** page. All the items in each PowerPack will be automatically installed in your Skylar One system.

Checking the Status of Installed Content

To check on the status of the installed content after one or more PowerPacks are installed:

- To check the status of any installed Dynamic Applications, look for the Dynamic Applications in the **Dynamic Applications Manager** page (System > Manage > Applications).
- To check the status of any installed event policies, look for the event policies in the **Event Policies** page (Events > Event Policies, or Registry > Events > Event Manager in the classic user interface) (or the **Event Policy Manager** page (Registry > Events > Event Manager) in the classic Skylar One user interface).
- To check the status of any installed device categories, look for device categories in the **Device Category Editor** page (System > Customize > Device Categories).
- To view any installed device classes, look for the device classes in the **Device Class Editor** page (System > Customize > Device Classes).
- To check the status of any installed device templates, look for the device template in the **Configuration Templates** page (Devices > Templates, or Registry > Devices > Templates in the classic user interface).
- To check the status of any installed device groups, look for the device groups in the **Device Groups** page (Devices > Device Groups).
- To view any installed custom reports, look for the report in the **Run Quick Report** page (Reports > Run Report), in the Run Quick Report drop-down list.
- To check the status of any installed custom dashboard widgets, look for the widgets in the **Classic Dashboard Widgets** page (System > Customize > Classic Dashboard Widgets).
- To check the status of any installed device dashboards, look for device dashboards in the **Device Dashboards** page (System > Customize > Device Dashboards).
- To check the status of any installed Skylar One dashboards, look for dashboards in the **Dashboards** page (☰).
- To check the status of any installed custom run book policies, look for run book policies in the **Automation Policy Manager** page (Registry > Run Book > Automation).
- To check the status of any installed custom run book actions, look for run book actions in the **Action Policy Manager** page (Registry > Run Book > Actions).

- To check the status of any installed custom run book action types, look for run book action types in the **Action Type Manager** page (Registry > Run Book > Action Types).
- To view any installed custom ticket templates, look for ticket templates in the **Ticket Templates** page (Registry > Ticketing > Templates).
- To check the status of any installed credentials, look for credentials in the **Credential Management** page (System > Manage > Credentials).
- To check the status of any installed credential tests, look for credential tests in the **Credential Test Management** page (System > Customize > Credential Tests).
- To view any installed UI Themes, look for Themes in the **Theme Management** page (System > Customize > Themes).
- To check the status of any installed IT service policies, look for IT service policies in the **IT Service Manager** page (Registry > IT Services > IT Service Manager).
- To check the status of any installed collection labels, look for collection labels in the **Collection Labels** page (System > Manage > Collection Labels).
- To check the status of any installed log file monitoring policies, look for log file monitoring policies in the **Log File Monitoring Policies** page (System > Manage > Log File Monitoring Policies).
- To check the status of any installed credential fields, look for credentials in the **Credentials** page (Manage > Credentials).
- To check the status of any installed guided discovery workflows, look for guided discovery workflows in the first page of the device discovery process (Devices > Add Device).
- To check the status of any installed AP content objects, look for the content objects in the **Content Management** page (Manage > Content Management).

NOTE: If there are any credentials that had specific organization alignments in the installed PowerPack, you will need to go to the **Credential Management** page (System > Manage > Credentials) to align the credentials to their appropriate organizations. To learn more about aligning credentials to an organization, see the *Discovery and Credentials* manual.

NOTE: Skylar One will automatically disable the *Organization* field in all Device Templates in the installed PowerPack. To learn more about Device Templates, see the *Device Groups and Device Templates* manual.

CAUTION: When you delete a PowerPack, Skylar One automatically deletes the associated content and all data associated with it from the Skylar One system. For example, if a PowerPack includes a Dynamic Application, when you delete the PowerPack, the Dynamic Application is removed from Skylar One. If you go to the **Dynamic Applications Manager** page (System > Manage > Applications), that Dynamic Application will not appear. In addition, all data collected from all devices with that Dynamic Application will also be deleted. If you must delete a PowerPack but want to keep the installed content, you should first remove the content from the PowerPack. This is described in the section

Removing Content from a PowerPack. To remove content from a PowerPack, you must either have administrator/owner privileges for the PowerPack, or you must be the creator of the PowerPack. For details on privileges associated with PowerPacks, see the chapter on *Creating a PowerPack*.

Viewing the List of PowerPacks

The **PowerPack Manager** page (System > Manage > PowerPacks) displays the list of existing PowerPacks. The page includes all PowerPacks that you have imported, installed, or created via the user interface or the ScienceLogic API.

For each PowerPack, the **PowerPack Manager** page displays the following:

TIP: To sort the list, click on a column heading. The list will be sorted by the column value, in ascending order. To sort the list by descending order, click the column heading again. You can also filter the items on this inventory page by typing filter text or selecting filter options in one or more of the filters found above the columns on the page. For more information, see *Filtering Inventory Pages* in the *Introduction to Skylar One* manual.

- **PowerPack Name.** Name of the PowerPack.
- **Version.** Version of the PowerPack. This number is defined and manually incremented by the author of the PowerPack.
- **Update.** Indicates whether an updated version of the PowerPack has been loaded onto the system by a patch. Possible values are *Yes* or *No*. This column is displayed only if at least one updated PowerPack has been loaded onto the system and has not yet been installed.
- **Publisher.** User-defined value that specifies the author of a PowerPack. For example, PowerPacks from ScienceLogic will include the value "ScienceLogic" in this field.
- **Apps.** Number of Dynamic Applications in the PowerPack.
- **Events.** Number of event policies in the PowerPack.
- **Classes.** Number of device classes in the PowerPack.
- **Reports.** Number of custom reports in the PowerPack.
- **Widgets.** Number of dashboard widgets in the PowerPack.
- **Dashbds.** Number of dashboards in the PowerPack.
- **Actions.** Number of run book actions in the PowerPack.
- **Creds.** Number of credentials in the PowerPack.
- **Tckt Tpl.** Number of ticket templates in the PowerPack.
- **Dash Skylar One.** Number of Skylar One dashboards in the PowerPack.
- **Dev Tpl.** Number of device templates in the PowerPack.

- **ID.** Numeric ID for the PowerPack, generated by Skylar One.
- **Edited By.** User who created or last edited the PowerPack.
- **Last Edited.** Date and time the PowerPack was created or last edited.

Viewing Documentation for a PowerPack

The **PowerPack Documentation Files** page allows you to view and download a document in a PowerPack.

Viewing a Document from the .em7pp File

If a PowerPack includes a document with a **Visibility** of *Public*, you can view that document before you import or install the PowerPack.

To view a document before you import or install a PowerPack:

1. Make sure the PowerPack file (ending in .em7pp) is available from your local computer.
2. Use an "unzip" utility to open the PowerPack file.
3. In the Documents directory, you can view all documents with a **Visibility** of *Public*.

Downloading a Document

If you are the author of a PowerPack or if you have installed a PowerPack and have access to the **PowerPack Documentation Files** page, you can download all documents included in the PowerPack, regardless of the **Visibility** assigned to each document.

To download documents that are included in a PowerPack:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. Find the PowerPack that contains the documents you want to download. Click its wrench icon (.
3. In the PowerPack NavBar, go to **Manage PowerPack** and click **Documentation**. The **PowerPack Documentation Files** page appears.
4. In the **PowerPack Documentation Files** page, find the document you want to download. Click its save icon (.
5. You will be prompted to navigate to the path where you want to store the file.

System Settings that Affect PowerPacks

The following setting in the **Behavior Settings** page affects the behavior of the Skylar One system when you update or install PowerPacks.

To define or edit the setting that affects PowerPacks:

1. Go to the **Behavior Settings** page (System > Settings > Behavior).
2. In the **Behavior Settings** page, edit the following:
 - **Enable Selective PowerPack Field Protection.** This field is disabled by default. If you select this field, when you update a PowerPack, the *following fields will not be updated*:
 - Event Policy > **Operational State**
 - Event Policy > **Event Severity**
 - Event Policy > **Event Message**
 - Event Policy > **Occurrence Count**
 - Event Policy > **Occurrence Time**
 - Event Policy > **Expiry Delay**
 - Event Policy > **Detection Weight**
 - Event Policy > **External Event ID**
 - Event Policy > **External Category**
 - Event Policy > **Use multi-match**
 - Event Policy > **Use message-match**
 - Event Policy > **Topology Suppression**
 - Dynamic Application > Properties > **Operational State**
 - Dynamic Application > Properties > **Poll Frequency**
 - Dynamic Application > Properties > **Disable Data Rollup**
 - Dynamic Application > Collection > **Custom Attribute**
 - Dynamic Application > Collection > **Asset / Formlink**
 - Dynamic Application > Collection > **Change Alerting**
 - Dynamic Application > Collection > **Hide Object**
 - Dynamic Application > Collection > **Component Identifiers**
 - Dynamic Application > Presentation > **Active State**
 - Dynamic Application > Threshold > **Override Threshold Value**
 - Dynamic Application > Threshold > **Numeric Range: High**
 - Dynamic Application > Threshold > **Numeric Range: Low**
 - Dynamic Application > Threshold > **Threshold Value**
 - Device Class > **Device Dashboard**
3. Click the **[Save]** button to save your changes.

PowerPack Signing and Signature Verification

Skylar One includes a security framework for PowerPack management that supports digital signature verification during PowerPack import and installation. This framework helps ensure the authenticity and integrity of PowerPacks before they are deployed, which is especially important in high-security environments such as FedRAMP.

When this framework is enabled, Skylar One automatically validates PowerPack digital signatures against trusted GNU Privacy Guard (GPG) public keys during the import and installation process. Administrators manage trusted public keys and control whether unsigned PowerPacks can be installed, depending on the security requirements of the stack.

Managing Trusted GPG Public Keys

Skylar One uses trusted GPG public keys to verify PowerPack digital signatures. Administrators can manage these public keys through the classic Skylar One user interface.

You can manage public keys from the **Public Keys** page (System > Manage > Public Keys). From this page, administrators can:

- Import new GPG public keys for use in validating signed PowerPacks.
- View information about imported keys, including the key name, key type, and the user who imported the key.
- Delete user-provided public keys in bulk.

NOTE: Only user-provided public keys can be removed from the system. System-provided keys cannot be deleted.

NOTE: The Public Keys management page is available starting in AP2 Nougat or later.

Requiring Signed PowerPacks

Skylar One provides a system-wide security setting that enforces signature verification for PowerPacks. This setting is available on the **Security Settings** page (System > Settings > Security).

When the ***Require Signed PowerPacks*** setting is enabled:

- Only PowerPacks that are digitally signed with a trusted GPG public key can be imported and installed.
- Unsigned PowerPacks are blocked from installation.

The behavior of this setting depends on the stack type:

- On Federal Information Processing Standards (FIPS) stacks, the ***Require Signed PowerPacks*** setting is always enabled and cannot be changed.
- On non-FIPS stacks, the setting is enabled by default on new installations but can be disabled by an administrator if unsigned PowerPacks are allowed.

Signature Validation During PowerPack Installation

When importing a PowerPack, Skylar One automatically checks whether the PowerPack is digitally signed and whether the signature matches a trusted public key.

During installation, the **PowerPack Installer** modal displays a ***Signed*** column that indicates whether each PowerPack is digitally signed, with values of *True* or *False*.

- A signed PowerPack with a trusted public key can always be imported and installed.
- On non-FIPS stacks, an unsigned PowerPack can only be imported and installed if unsigned PowerPacks are allowed by system settings.

You can access the **PowerPack Installer** modal by going to the **PowerPack Manager** page (System > Manage > PowerPacks), clicking the **[Actions]** button, then selecting *Install PowerPack*. For more information, see the section on [Importing and Installing a PowerPack](#).

Installing Out-of-Band PowerPacks in FedRAMP Environments

In FedRAMP environments, Skylar One supports a formal process for installing out-of-band PowerPacks. Out-of-band PowerPacks are PowerPacks that are not included in the default Skylar One build. This process allows SRE teams to securely verify and deploy signed Skylar One using standardized procedures while maintaining compliance with FedRAMP security requirements.

Chapter

3

Creating a PowerPack

Overview

This chapter will describe how to create a PowerPack, add content to a PowerPack, how to add intellectual property protection to content in a PowerPack, generate a license key for a PowerPack, and how to export a PowerPack.

This chapter covers the following topics:

<i>Caveats</i>	21
<i>Creating a PowerPack</i>	22
<i>Creating a Container for a PowerPack</i>	22
<i>Adding Content to a PowerPack</i>	24
<i>Adding Documentation to a PowerPack</i>	27
<i>Including Details on a PowerPack's Features, Benefits, and Technical Information</i>	28
<i>Adding Intellectual Property Protection to Content in a PowerPack</i>	29
<i>Determining the PowerPack's Execution Environments</i>	30
<i>Building the PowerPack and Generating a License Key</i>	31
<i>Export Rules, Import Rules, and Substitutions</i>	40
<i>Exporting a PowerPack</i>	46
<i>Generating an Embedded License Key After the Initial Build</i>	46
<i>Generating an Unembedded License Key After the Initial Build</i>	47

Caveats

If you have content (Dynamic Applications, event policies, device classes, device templates, custom reports, custom dashboard widgets, dashboards, custom run book policies, custom run book actions, custom ticket templates, credentials, themes, device categories, device dashboards, collection labels, or business services) that you must install on another Skylar One system, you can create a PowerPack for that content. However, you must be aware of the following caveats:

- Content can be included in only a single PowerPack. For example, if you include the Dynamic Application "Cisco: Summary Statistics" in the PowerPack "networking_powerpack", you cannot include that Dynamic Application in another PowerPack.
- When you delete a PowerPack, Skylar One automatically deletes the associated content from the Skylar One system and all data associated with it. For example, if a PowerPack includes a Dynamic Application, when you delete the PowerPack, the Dynamic Application is removed from Skylar One. If you go to the **Dynamic Applications Manager** page (System > Manage > Applications), that Dynamic Application will not appear. In addition, all data collected from all devices with that Dynamic Application will also be deleted.
- If you must delete a PowerPack but want to keep the installed content, you should first remove the content from the PowerPack. This is described in the section [Removing Content from a PowerPack](#). To remove content from a PowerPack, you must either have administrator/owner privileges for the PowerPack or you must be the creator of the PowerPack. For details on privileges associated with PowerPacks, see the [section on privileges](#).
- If you want to include content in a second PowerPack, you must first remove the content from the first PowerPack. This is described in the section [Removing Content from a PowerPack](#). To remove content from a PowerPack, you must either have administrator/owner privileges for the PowerPack or you must be the creator of the PowerPack. For details on privileges associated with PowerPacks, see the [section on privileges](#).
- If you include organization-specific credentials in a PowerPack, the organization alignment for those credentials is not preserved by that organization when the PowerPack is installed in another Skylar One system. The credentials in a PowerPack will not be organization-specific in another Skylar One system.
- If a PowerPack specifies that a minimum version of Skylar One is required for installation, you will receive an error message if you are running an earlier version of Skylar One and attempt to install the PowerPack.

Creating a PowerPack

To create a PowerPack, you must perform the following steps:

- In the **PowerPack Properties** page, create a container for the PowerPack.
- In the **Embedded/Available** page, add content to the PowerPack.
- Optionally, add documentation to the PowerPack.
- In the **Compiled PowerPacks / Generate Installation Key** page, build the PowerPack, grant privileges, and generate a license key.

These steps are described in the following sections.

NOTE: The following sections describe how to create PowerPacks using the user interface. In addition to the user interface, PowerPacks can also be created via the ScienceLogic API. PowerPacks created via the user interface will appear in the ScienceLogic API and vice versa. For information about creating PowerPacks via the ScienceLogic API, see the **ScienceLogic API manual**

Creating a Container for a PowerPack

To create a PowerPack, you must first define the basic properties and create the container. To do this:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. In the **PowerPack Manager** page, click the **[Actions]** button. Click *Create New PowerPack*. The **PowerPack Properties** page appears.
3. In the **PowerPack Properties** page, supply values in each field.
 - **Name.** Name of the PowerPack.
 - **Version.** Version number for the PowerPack. You can enter any combination of characters in this field. You must manually update this field to change the version number.
 - **Publisher.** User-defined value that specifies the author of a PowerPack. For example, PowerPacks from ScienceLogic will include the value "ScienceLogic" in this field.

NOTE: The **Publisher** field can be edited only on the system where the PowerPack was created and only by accounts with the appropriate Access Keys.

- **License Key.** The license key for the PowerPack. This key identifies the PowerPack and the author to Skylar One and is updated each time you make a change to the PowerPack. The License Key confers owner privileges and allows you to import, edit properties and content, build, generate an install key, and export the PowerPack.

NOTE: Best practice is to safeguard the License Key for use only by the PowerPack creator and to generate Install Keys for other users of the PowerPack.

- **Creation.** Read-only field. Skylar One automatically supplies the date and time the PowerPack was created.
- **Modification.** Read-only field. Skylar One automatically supplies the date and time the PowerPack was last modified.
- **Revision.** Read-only field. Skylar One automatically supplies the number of revisions to the PowerPack.

NOTE: When you save the values in the **PowerPack Properties** page, Skylar One assigns the revision number "1" (one) to the PowerPack. When you add content and build the PowerPack (and optionally define privileges), Skylar One assigns the revision number "2" (two) to the PowerPack. A PowerPack that contains content will have a revision number of "2" (two) or greater.

- **ID.** Read-only field. Skylar One automatically supplies a numeric ID for the PowerPack. This numeric ID uniquely identifies the PowerPack on the current system.
- **Description.** Enter a detailed description of the PowerPack and its content.
- **Vendor(s) Supported.** Specify the vendor associated with the content in the PowerPack. For example, if a PowerPack includes the Dynamic Applications that monitor VMware devices, you could enter "VMware" in this field."
- **Model(s) Supported.** Specify the hardware or software model associated with the content in the PowerPack. For example, if a PowerPack includes Dynamic Applications that monitor Cisco Catalyst switches, you could specify "Catalyst 2950 and Catalyst 2960" in this field.
- **Version(s) Supported.** Specify the version of the hardware or software associated with the content in the PowerPack. For example, if a PowerPack includes Dynamic Applications that monitor Cisco CUCM, you could specify "Version 12 and Version 14" in this field.
- **Minimum EM7 Version.** Specify the earliest version of Skylar One required by the PowerPack. If users try to install the PowerPack on earlier versions of Skylar One, an error message will appear.
 - You can enter any combination of numbers and periods. For example, you could enter "12.3.0".

- If you leave this field blank, users can install the PowerPack on all versions of Skylar One.

CAUTION: This field determines which versions of Skylar One the PowerPack can be installed on, but not necessarily which versions of Skylar One the PowerPack is compatible with. For example, PowerPacks created in Skylar One 12.3.0 or later cannot be exported to 12.2.x or earlier Skylar One systems due to a technical limitation. When creating a PowerPack, you should ensure that it is compatible with the oldest version of Skylar One that you intend to install it on.

- **Enable Selective PowerPack Field Protection.** This field affects how updates behave for this PowerPack. If you select this option, certain fields in Event Policies, Dynamic Applications, and Device Classes will not be updated. Select this option for individual PowerPacks if you do not want to use the global "Enable Selective PowerPack Field Protection" setting on the **Behavior Settings** page (System > Settings > Behavior) for all PowerPacks. If you select this option, it overrides the global setting.
- **Release Notes and Change Log.** Include any detailed release notes or record of changes to the PowerPack. The editor allows you to format the text and include links and images in the text. You can also use a document template to apply a standard format to the text.

4. Click the **[Save]** button to save the PowerPack and any changes you have made.

Adding Content to a PowerPack

After you have saved the values in the **PowerPack Properties** page you can add content from the menu on the left. From this menu, you can start to add content to the PowerPack. To add content to the PowerPack, perform the following steps:

1. If you do not already have the PowerPack open, go to the **PowerPack Manager** page (System > Manage > PowerPacks). Find the PowerPack you want to add content to. Click its wrench icon (.
2. From the **PowerPack Properties** page, select the type of content you want to add in the Navbar on the left side of the page. You can select from the following options:

NOTE: The entries under the **Contents** link are dependent upon your Access Hooks. An entry appears only if you have been granted an Access Key that contains the Access Hook that allows you to view the content-type in Skylar One. For example, the **Dynamic Applications** entry will appear under the **Contents** link only if you have permission to view the list of Dynamic Applications in the **Dynamic Applications Manager** page (System > Manage > Applications) in Skylar One.

- **Dynamic Applications.** Displays the **Embedded/Available** page, where you can view a list of Dynamic Applications that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (). To remove, click the delete icon (.

- **Event Policies.** Displays the **Embedded/Available** page, where you can view a list of event policies that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).

NOTE: Event policies associated with Dynamic Application alerts do not appear in the **Available** pane, and cannot be explicitly added to a PowerPack. When a Dynamic Application is added to a PowerPack, any event policies associated with the Dynamic Application are automatically added to the PowerPack. Automatically added event policies will appear in the **Embedded** pane when Event Policies is selected in the NavBar.

NOTE: If an event policy is included in a PowerPack and has the **Use Modifier** checkbox selected, when the event policy is installed on another Skylar One system, the event policy will have the **Use Modifier** checkbox selected.

- **Device Categories.** Displays the **Embedded/Available** page, where you can view a list of device categories that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Device Classes.** Displays the **Embedded/Available** page, where you can view a list of device classes that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Device Templates.** Displays the **Embedded/Available** page, where you can view a list of device templates that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Device Groups.** Displays the **Embedded/Available** page, where you can view a list of dynamic device groups that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Reports.** Displays the **Embedded/Available** page, where you can view a list of reports that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Dashboard Widgets.** Displays the **Embedded/Available** page, where you can view a list of dashboard-widgets that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Dashboards.** Displays the **Embedded/Available** page, where you can view a list of dashboards and device dashboards that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Dashboards Skylar One.** Displays the **Embedded/Available** page, where you can view a list of Skylar One dashboards that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Run Book Policies.** Displays the **Embedded/Available** page, where you can view a list of Run Book Automation policies that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).

NOTE: If you include a Run Book Automation policy that executes one or more Run Book Action policies, you must also include those Run Book Action policies with the PowerPack.

- **Run Book Actions.** Displays the **Embedded/Available** page, where you can view a list of available run book actions that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Run Book Action Types.** Displays the **Embedded/Available** page, where you can view a list of available run book action types that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Ticket Templates.** Displays the **Embedded/Available** page, where you can view a list of Ticket Templates that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Credentials.** Displays the **Embedded/Available** page, where you can view a list of Credentials that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Credential Tests.** Displays the **Embedded/Available** page, where you can view a list of credential tests that can be removed from or added to a PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **UI Themes.** Displays the **Embedded/Available** page, where you can view a list of UI Themes that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **IT Services.** Displays the **Embedded/Available** page, where you can view a list of IT Service policies that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Log File Monitoring Policies.** Displays the **Embedded/Available** page, where you can view a list of log file monitoring policies that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Credential Fields.** Displays the **Embedded/Available** page, where you can view a list of credential fields that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **Guided Discovery Workflow.** Displays the **Embedded/Available** page, where you can view a list of guided workflows that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑).
- **AP Content Objects.** Displays the **Embedded/Available** page, where you can view a list of AP content objects that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the delete icon (🗑). AP Content Objects are features, icons, modules, and updates for the Skylar One user-interface.

NOTE: Content can be included in only one PowerPack. For example, a Dynamic Application cannot be included in three different PowerPacks. If you want to include content in a second PowerPack, you must first remove it from its original PowerPack.

3. The display in the **Embedded/Available** modal page depends on your selection from the NavBar pane:

- **To add content**, go to the **Available** pane at the bottom of the page. Find the content you want to include in the PowerPack. Click the lightning bolt icon (⚡) for that content. The content will be moved to the top pane.

NOTE: The **Available** pane contains only content that is not included in any other PowerPack. If content is included in another PowerPack, it will not appear in the **Available** pane.

NOTE: If you include a Dynamic Application that has aligned event policies (i.e., one or more events that are triggered with an alert from the Dynamic Application), Skylar One will automatically include the corresponding event policies in the PowerPack. **Note that you cannot manually add an event with the source of "dynamic";** Skylar One automatically includes these events when you add the aligned Dynamic Applications to the PowerPack.

NOTE: If you want to include an event that is aligned with an "auto-clear" event, Skylar One requires that you include both events in the PowerPack. Skylar One will not allow you to add such an event without also adding its aligned "auto-clear" event.

- **To remove content**, go to the **Embedded** pane at the top of the page. Find the content you want to remove from the PowerPack. Click the delete icon (🗑️) for that content. The content will be removed from the PowerPack and will now appear in the bottom pane.

Adding Documentation to a PowerPack

The **PowerPack Documentation Files** page allows you to include a document in a PowerPack, download a document from a PowerPack, and delete a document from a PowerPack.

Adding a Documentation File to a PowerPack

To add a documentation file to a PowerPack:

1. In the left pane, go to **Manage PowerPack** and click **Documentation**.
2. In the **PowerPack Documentation Files** page, click the [Upload] button.

3. In the **Document Import** modal page, navigate to the document you want to add to the PowerPack. Click the **[Import]** button to add the document to the PowerPack.
4. The document appears in the top pane of the **PowerPack Documentation Files** page.
5. The document will be saved with the PowerPack and its contents.

Changing Visibility

After you have added a documentation file to a PowerPack, you can set its **Visibility**.

To change the visibility, click on the lock icon (🔒) in the **Visibility** column. You can toggle between *Private* and *Public*.

- **Private.** Document can be viewed and accessed only from the **PowerPack Documentation Files** page. This means that users other than the author of the PowerPack must install the PowerPack to view the document.
- **Public.** Document is included in the export file for the PowerPack and can be accessed by opening the PowerPack file with a "zip" utility. Users do not need to install the PowerPack to view the document.

Deleting a Document

If you are the author of a PowerPack or if you have installed a PowerPack and have access to the **PowerPack Documentation Files** page, you can delete one or more documents from the PowerPack, regardless of the **Visibility** assigned to each document.

To delete a document from a PowerPack:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. Find the PowerPack that contains the document(s) you want to delete and click its wrench icon (🔧).
3. In the PowerPack, go to the NavBar, go to **Manage PowerPack** and click **Documentation**.
4. In the **PowerPack Documentation Files** page, find the document you want to delete. Click its delete icon (🗑).
5. The document will be deleted from the PowerPack.

Including Details on a PowerPack's Features, Benefits, and Technical Information

You can optionally add additional information about a PowerPack's content in the **Features/Benefits** page and the **Technical Notes** page.

Features/Benefits

The **Features/Benefits** page allows you to add details on the features and benefits of the PowerPack content.

The editor allows you to format the text and include links and images in the text.

You can also use a document template to apply a standard format to the text.

Technical Notes

The **Technical Notes** page allows you to add technical information about the PowerPack and its content.

The editor allows you to format the text and include links and images in the text.

You can also use a document template to apply a standard format to the text.

Adding Intellectual Property Protection to Content in a PowerPack

After adding content to a PowerPack, you can add **Intellectual Property Protection** to included Dynamic Applications and event policies. Intellectual Properties Protection, or IPP, prevents other users from editing or viewing information on Dynamic Applications on any Skylar One system except the original system where the Dynamic Application was created.

- **When you enable Intellectual Property Protection for a Dynamic Application**, users are prevented from viewing and editing advanced implementation details about the Dynamic Application on any Skylar One system, except the original system where the Dynamic Application was created. After installation on another Skylar One system (other than the author system), users cannot disable the Intellectual Property Protection feature and can view and edit only the **[Properties]**, **[Policies]**, and **[Subscribers]** tab of the Dynamic Application (within the PowerPack or in the **Dynamic Applications Manager** page). Even if the PowerPack is installed with the License Key or with an Install Key that grants Administrator/Owner privileges, users will not be able to access all tabs for the Dynamic Application. When Intellectual Property Protection is enabled, the following tabs will not be displayed for the Dynamic Application:
 - **[Collections]**
 - **[Presentation]**
 - **[Thresholds]**
 - **[Snippets]** (for Dynamic Applications of type "snippet")
 - **[Requests]** (for Dynamic Applications of type "SOAP", "XSLT", and "WMI")
 - **[Alerts]**

- **When you add Intellectual Property Protection to an event policy**, users are prevented from viewing and editing advanced implementation details about the event policy on any Skylar One system, except the original system where the event policy was created. After installation on another Skylar One system (other than the author system), users cannot disable the Intellectual Property Protection feature and can edit only the **[Policy]** and **[Suppressions]** tab of the event policy application (within the PowerPack or in the **Event Policy Manager** page). Even if the PowerPack is installed with the License Key or with an Install Key that grants Administrator/Owner privileges, users will not be able to access all of the tabs for the event policy. When Intellectual Property Protection is enabled, the following tab and information will not be displayed for the event policy:

- **[Advanced]**
- The **[Save As]** button will not appear on any tab.

To add Intellectual Property Protection to a Dynamic Application or an event policy:

1. If you do not already have the PowerPack open, go to the **PowerPack Manager** page (System > Manage > PowerPacks). Find the PowerPack you want to add content to. Click its wrench icon ()
2. From the **PowerPack Properties** page, select from the applicable options in the navigation panel to the left.
3. Select the entry for the content to which you want to add Intellectual Property Protection:
 - **Dynamic Applications.** Displays the **Embedded/Available** page for Dynamic Applications, where you can view a list of Dynamic Applications that are already in the PowerPack and a list of Dynamic Applications that can be added to the PowerPack.
 - **Event Policies.** Displays the **Embedded/Available** page for event policies, where you can view a list of event policies that are already in the PowerPack and a list of event policies that can be added to the PowerPack.
4. To view the **Embedded/Available** page for a type of content, go to the **Embedded** pane at the top of the page, find the content you want to protect, and click on the lock icon (). If the **IPP** column contains the value "enabled", the Dynamic Application or event policy is protected.

Determining the PowerPack's Execution Environments

When you build a PowerPack, it includes the execution environments that are aligned with the PowerPack's Dynamic Applications, Credential Tests, and Run Book Actions that execute snippets.

An **execution environment** is an on-demand Python environment that includes the supporting modules, code, scripts, directories, and files (packaged in one or more ScienceLogic Libraries) needed to run a snippet. An execution environment includes its own installation directories, doesn't share libraries with other environments, and allows granular control of dependencies and versions.

To determine which execution environments are included in a PowerPack:

1. Go to the **Dynamic Applications Manager** page (System > Manage > Applications).
2. In the **PowerPack** filter-while-you-type field, type the name of the PowerPack. This filters the list so only the Dynamic Applications from the specified PowerPack appear.
3. The **Environment** column displays the execution environment aligned with each Dynamic Application included in the PowerPack.

Building the PowerPack and Generating a License Key

After you have added content to a PowerPack you must build the PowerPack (to generate a single file that contains all the associated content), select the permissions to associate with a license key for the PowerPack, and generate a license key for the PowerPack.

A license key allows a user to install a PowerPack on a Skylar One system. A license key used to install a PowerPack also determines the actions that can be performed on the PowerPack and its contents. You can embed a license key in the PowerPack, so the user will not need to enter a license key upon importing the PowerPack. If you do not embed a license key, you will need to provide a license key to the user that must be entered when they import the PowerPack.

You are not limited to one license key per PowerPack. You can generate multiple license keys for a single PowerPack. You are not required to rebuild a PowerPack each time you generate a new license key.

- For example, during initial build of a PowerPack, you could generate and embed a license key with "Install & Use Only" privileges. You could then export the PowerPack and distribute the PowerPack to a customer. When the customer imports and installs the PowerPack, the customer does not have to enter a license key and will be given "Install & Use Only" privileges.
- For the same PowerPack, you could generate an administrator-level license key that you copy and paste in a file. You could then distribute the same PowerPack file you distribute to customers to a system administrator in your organization. The system administrator can then use the administrator-level license key from the text file instead of the embedded license key.

Note that the last generated license key is the one that will be displayed in the **Compiled PowerPacks / Generate Installation Key** modal page, either in the **Embedded License Key** column in the top pane or in the **Generated Install Key** field in the bottom pane.

Building a PowerPack

To build a PowerPack:

1. If you have not already, go to the **PowerPack Manager** page (System > Manage > PowerPacks) and either create a PowerPack or edit an existing PowerPack.
2. Expand the Manage PowerPack entry in the left NavBar and click **Build/Export**.
3. If this is a new PowerPack or if you have made a change to the PowerPack, you will see a link telling you to *Create a new build*.
4. To build the PowerPack, click on the link.

Generating an Embedded License Key During the Initial Build

1. During the initial build, after you select the *Create a new build* link in the **Compiled PowerPacks / Generate Installation Key** modal page, the **Configure Export File** modal page appears.
2. The **Configure Export File** modal page allows you to embed a license key within the PowerPack. When you embed the license key in the PowerPack, the user who imports and installs the PowerPack does not have to enter a license key.

- If you want to embed a license key in the PowerPack, enter a value in each field.
 - If you do not want to embed a license key in the PowerPack, exit the **Configure Export File** page. You must manually generate a license key in the bottom pane of the **Compiled PowerPacks / Generate Installation Key** modal page.
3. To embed a license key, enter the following in the **Configure Export File** modal page:
- **Embedded license key.** Displays a drop-down list of options that allow you to select whether to want to embed the license key in the PowerPack, and if so, how you would like the embedded key to function. Choices are:
 - *None.* The license key will not be embedded in the PowerPack. You must manually generate the license key and then copy and paste the license key in a text file. The user who imports and installs the PowerPack must enter the license key during installation.
 - *Install & Use Only.* The license key will be embedded. Users will be allowed to install this PowerPack on another Skylar One system (other than the author system). In the **PowerPack Properties** page for the PowerPack, users will be allowed to edit only the name and version number of the PowerPack. Users will not be allowed to edit any of the installed content, either from within the PowerPack or in Skylar One.
 - *Administrative (including export & license).* The license key will be embedded. After installation on another Skylar One system (other than the author system), users will be allowed to edit each of the installed items from this PowerPack. Users can edit the content from within the PowerPack and in Skylar One. Users will also be allowed to edit the properties of the PowerPack, delete content from the PowerPack, export the PowerPack, and generate a license key for the PowerPack.
 - *Manage Content Items of Selected Types.* The license key will be embedded. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed content type, from the associated page in the user interface. In the **PowerPack Properties** page for the PowerPack, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
 - **Available Types/Selected Types.** The entries in these fields become active if you clicked *Manage Content Items of Selected Types* in the **Embedded license key** field.
 - **To select a content option,** in the *Available Types* field, highlight the option and click the right arrow button. The option will now appear in the **Selected Types** pane and will be included in the license key. Repeat these steps for each content type you want to include in the license key.
 - **To remove a content option,** in the *Selected Types* field, highlight the option and click the left arrow button. The option will now appear in the **Available Types** pane and will not be included in the license key. Repeat these steps for each content type you want to removed from the license key.

The content types are:

- *Dynamic Applications.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed Dynamic Applications from the **Dynamic Applications Manager** page (System > Manage > Applications). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Event Policies.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed event policies from the **Event Policy Manager** page (Registry > Events > Event Manager). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

NOTE: If the PowerPack contains one or more Dynamic Applications or event policies that use Intellectual Property Protection, users will not be able to edit the Dynamic Applications or event policies when they are installed on another server, even if the PowerPack includes Administrator/Owner privileges.

- *Device Categories.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed device categories from the **Device Category Editor** page (System > Customize > Device Categories). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Device Classes.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed device classes from the **Device Class Editor** page (System > Customize > Device Classes). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Device Templates.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed device templates from the **Configuration Templates** page (Devices > Templates, or Registry > Devices > Templates in the classic user interface). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Device Groups.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed device groups from the **Device Groups** page (Devices > Device Groups). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

- *Reports.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed report from the **[Reports]** tab. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Dashboard Widgets.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed widget from the **Classic Dashboard Widgets** page (System > Customize > Classic Dashboard Widgets). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Dashboards.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed dashboards from the **Dashboards tab**. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Dashboards Skylar One.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed Skylar One dashboards from the **Dashboards** page (☰). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Run Book Policies.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed Run Book policies from the **Automation Policy Manager** page (Registry > Run Book > Automation). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Run Book Actions.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed Run Book actions from the **Action Policy Manager** page (Registry > Run Book > Actions). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Run Book Action Types.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed Run Book Action Types from the **Action Type Manager** page (Registry > Run Book > Action Types). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Ticket Templates.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed ticket templates from the **Ticket Templates** page (Registry > Ticketing > Templates). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

- *Credentials*. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed credentials from the **Credential Management** page (System > Manage > Credentials). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

NOTE: If you include organization-specific credentials in a PowerPack, the credentials cannot be preserved by that organization when the PowerPack is installed on another environment. The credentials in a PowerPack are the responsibility of the customer, and cannot be guaranteed to be organization-specific in another Skylar One system.

- *Credential Tests*. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed credential tests from the **Credential Test Management** page (System > Customize > Credential Tests). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *UI Themes*. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed themes from the **Theme Management** page (System > Customize > Themes). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *IT Services*. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed IT Service policies from the **IT Service Manager** page (Registry > IT Services > IT Service Manager). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Log File Monitoring Policies*. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed log file monitoring policies from the **Log File Monitoring Policies** page (System > Manage > Log File Monitoring Policies). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Credential Fields*. After installation on another Skylar One system (other than the author system), users will be allowed to utilize the content type. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Guided Discovery Workflow*. After installation on another Skylar One system (other than the author system), users will be allowed to utilize the content type. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

- *AP Content Objects*. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed AP Content Objects from the **Content Management** page (Manage > Content Management). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
4. Click the **[Build]** button, and then click the **[Save]** button to save the embedded license. Notice that the *Embedded License* field in the top pane of the **Compiled PowerPacks / Generate Installation Key** page now matches the newly generated license.

Generating an Unembedded License During the Initial Build

If you did not embed a license key during the initial build of a PowerPack, you must generate a separate license key to install the PowerPack on other Skylar One systems. After selecting *None* in the **Configure Export File** modal page, perform the following steps to generate an unembedded license key:

1. In the bottom pane of the **Compiled PowerPacks / Generate Installation Key** page, select the values in the following fields:
 - **License key type**. Defines how the generated license key will function. Choices are:
 - *Install & Use Only*. After installation on another Skylar One system (other than the author system), users will be allowed to edit only the name and version number of the PowerPack in the **PowerPack Properties** page. Users will not be allowed to edit any of the installed content, either from within the PowerPack or in Skylar One.
 - *Administrative (including export & license)*. After installation on another Skylar One system (other than the author system), users will be allowed to edit each of the installed items from this PowerPack. Users can edit the content from within the PowerPack and in Skylar One. Users will also be allowed to edit the properties of the PowerPack, delete content from the PowerPack, export the PowerPack, and generate a license key for the PowerPack.
 - *Manage Content Items of Selected Types*. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed content type, from the associated page in the Skylar One interface. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
 - **Available Types/Selected Types**. The entries in these fields become active if you selected *Manage Content Items of Selected Types* in the **License key type** field.
 - **To select a content option**, in the **Available Types** field, highlight the option and click the right arrow button. The option will now appear in the **Selected Types** pane and will be included in the license key. Repeat these steps for each content type you want to include in the license key.
 - **To remove a content option**, in the **Selected Types** field, highlight the option and click the left arrow button. The option will now appear in the **Available Types** pane and will not be included in the license key. Repeat these steps for each content type you want to remove from the license key.

The content types are:

- *Dynamic Applications.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed Dynamic Applications from the **Dynamic Applications Manager** page (System > Manage > Applications). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Event Policies.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed event policies from the **Event Policy Manager** page (Registry > Events > Event Manager). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

NOTE: If the PowerPack contains one or more Dynamic Applications or event policies that use Intellectual Property Protection, users will not be able to edit the Dynamic Applications or event policies when they are installed on another server, even if the PowerPack includes Administrator/Owner privileges.

- *Device Categories.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed device categories from the **Device Category Editor** page (System > Customize > Device Categories). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Device Classes.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed device classes from the **Device Class Editor** page (System > Customize > Device Classes). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Device Templates.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed device templates from the **Configuration Templates** page (Devices > Templates, or Registry > Devices > Templates in the classic user interface). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Device Groups.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed device groups from the **Device Groups** page (Devices > Device Groups). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

- *Reports.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed report from the **[Reports]** tab. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Dashboard Widgets.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed widget from the **Classic Dashboard Widgets** page (System > Customize > Classic Dashboard Widgets). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Dashboards.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed dashboards from the **Dashboards tab**. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Dashboards Skylar One.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed Skylar One dashboards from the **Dashboards** page (☰). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Run Book Policies.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed Run Book policies from the **Automation Policy Manager** page (Registry > Run Book > Automation). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Run Book Actions.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed Run Book actions from the **Action Policy Manager** page (Registry > Run Book > Actions). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Run Book Action Types.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed Run Book Action Types from the **Action Type Manager** page (Registry > Run Book > Action Types). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Ticket Templates.* After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed ticket templates from the **Ticket Templates** page (Registry > Ticketing > Templates). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

- *Credentials*. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed credentials from the **Credential Management** page (System > Manage > Credentials). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

NOTE: If you include organization-specific credentials in a PowerPack, the credentials cannot be preserved by that organization when the PowerPack is installed on another environment. The credentials in a PowerPack are the responsibility of the customer, and cannot be guaranteed to be organization-specific in another Skylar One system.

- *Credential Tests*. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed credential tests from the **Credential Test Management** page (System > Customize > Credential Tests). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *UI Themes*. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed themes from the **Theme Management** page (System > Customize > Themes). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *IT Services*. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed IT Service policies from the **IT Service Manager** page (Registry > IT Services > IT Service Manager). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Log File Monitoring Policies*. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed log file monitoring policies from the **Log File Monitoring Policies** page (System > Manage > Log File Monitoring Policies). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Credential Fields*. After installation on another Skylar One system (other than the author system), users will be allowed to utilize the content type. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Guided Discovery Workflow*. After installation on another Skylar One system (other than the author system), users will be allowed to utilize the content type. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

- *AP Content Objects*. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed AP Content Objects from the **Content Management** page (Manage > Content Management). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
2. Click the **Generate Key** button.
 3. When the new license key appears in the *Generated Install Key* field, copy the license key and paste it into a text file.

Export Rules, Import Rules, and Substitutions

Some of the content items that can be included in a PowerPack are dependent on, or reference, other entities in Skylar One. The following sections describes how Skylar One handles each dependency or reference during export and import. When you build a PowerPack, for each item you include in the PowerPack, you must ensure that you have also included any referenced or dependent items. Skylar One will display an error message and will not build the PowerPack if dependent items are not included.

Dynamic Applications

Dynamic Applications have the following dependencies:

- If you include a Dynamic Application that has the **Caching** field set to Consume cached results, you must also include the Dynamic Application that creates the cache. The Dynamic Application that creates the cache has the **Caching** field set to Cache results.
- If you include a Dynamic Application that has the **Component Mapping** field selected, you must also include the aligned Device Class of type Component.
- If you include a Dynamic Application that contains a *Presentation* formula or an *Alert* formula, you must ensure that the referenced Collection Objects are included in the same Dynamic Application.
- If you include a Dynamic Application that uses Collection Labels, Skylar One will automatically export those Collection Labels with the PowerPack. However, those Collection Labels will not appear in the **Embedded/Available** page for the PowerPack and can still be included in other PowerPacks. Collection Labels cannot be explicitly added to or removed from a PowerPack.
- If you include a Dynamic Application that is aligned with an execution environment, Skylar One will automatically export that execution environment and its associated ScienceLogic Libraries with the PowerPack.

Event Policies

If you include an *event policy* that is aligned with an *auto-clear* event, Skylar One requires that you include both events in the PowerPack. Skylar One will not allow you to add an event that can be auto-cleared without also adding its aligned *auto-clear* event.

Device Templates

If you include a Device Template that contains one or more Dynamic Applications or Log File Monitoring Policies, you must also include those Dynamic Applications and Log File Monitoring Policies with the PowerPack.

When a device template is included in a PowerPack, Skylar One automatically makes some changes to the device template to make it more portable:

- **Device Organization.** This field will not contain a value and will be deactivated.

Device Groups

When a device group is included in a PowerPack, Skylar One automatically makes some changes to the device group to make it more portable:

- **Active Selectors.** *Custom Attributes* have special behavior in PowerPacks.
 - If you included a Base Custom Attribute in this pane, the Base Custom Attribute will be exported with the PowerPack and will appear on the new system when imported.
 - If you included an Extended Custom Attribute in this pane, the Extended Custom Attribute will be exported with the PowerPack.
 - If the target system does not already include the Extended Custom Attribute, the Extended Custom Attribute will not appear in the **Active Selectors** pane.
 - If the target system does include the Extended Custom Attribute, the Extended Custom Attribute will appear in the **Active Selectors** pane.

Dashboards

If you include a Dashboard in a PowerPack but do not include one or more of the widgets that appear on the dashboard in the PowerPack:

- For the widgets that are not included in the PowerPack, Skylar One will automatically export those widgets with the PowerPack. However, those widgets will not appear in the **Embedded/Available** page for the PowerPack and can still be included in other PowerPacks.
- When the PowerPack is installed on a Skylar One system, Skylar One will install the widgets that were not included in the PowerPack only if those widgets are not already installed. If Skylar One discovers one or more of the widgets in the PowerPack already exists on the Skylar One system and those widgets were not installed by the current PowerPack, **Skylar One will not overwrite the existing widgets.**
- If a widget is installed on a Skylar One system by a PowerPack that does not explicitly include that widget and the PowerPack that does include that widget is installed at a later date, the widget definition that exists on the system will be associated with its PowerPack and will be updated by that PowerPack.

Run Book Actions

NOTE: You cannot include Run Book of type "Create a New Ticket" in a PowerPack.

When a Run Book Action Policy is included in a PowerPack, some system-specific values will be automatically substituted by Skylar One.

- For action policies of type ***Send an Email Notification:***
 - ***Organization.*** This field will contain the default value "System".
 - ***Available Emails.*** This list will be automatically updated with email addresses from the system where the PowerPack is installed.
 - ***Assigned Emails.*** By default, this list will be empty.
- For action policies of type ***Send an SNMP Trap:***
 - ***Organization.*** This field will contain the default value "System".
 - ***Trap Host.*** By default, this field will be empty.
 - ***Trap Credential.*** By default, no value will be selected in this field.
- For action policies of type ***Send an SNMP Set:***
 - ***Organization.*** This field will contain the default value "System".
 - ***SNMP Host.*** By default, this field will be empty.
 - ***SNMP Credential.*** By default, no value will be selected in this field.
- For action policies of type ***Run a Snippet:***
 - ***Organization.*** This field will contain the default value "System".
 - ***Snippet Credential.*** By default, no value will be selected in this field.
- For action policies of type ***Execute an SQL Query:***
 - ***Organization.*** This field will contain the default value "System".
 - ***Database Credential.*** By default, no value will be selected in this field.

Additionally, if you include a Run Book Action policy of type ***Run a Snippet*** that is aligned with an execution environment, Skylar One will automatically export that execution environment and its associated ScienceLogic Libraries with the PowerPack.

Run Book Policies

When a Run Book Automation Policy is included in a PowerPack, the following system-specific values will be automatically substituted by the platform:

- **Organization.** This field will contain the default value "System".
- **Aligned Devices.** Specific devices will be removed from this field. The policy will match all devices.

If you include an IT service policy that includes a metric that uses a Dynamic Application in a PowerPack, Skylar One will automatically include the Dynamic Application in the PowerPack. When the PowerPack is installed on a ScienceLogic system, Skylar One will install the Dynamic Application (with their aligned PowerPack GUIDs). However, if Skylar One discovers one or more of the Dynamic Applications in the PowerPack already exists on the system, **Skylar One will not overwrite the existing widgets.**

If you include a Run Book Automation policy that executes one or more Run Book Action policies, you must also include those Run Book Action policies in the PowerPack.

If you include a Run Book Automation policy that includes an Automation Schedule, Skylar One will automatically include the required Automation Schedule in the PowerPack.

Credentials

If you include credentials in a PowerPack, you must make sure that the credentials are portable and can be used on both the author's system and the system where the PowerPack will be installed.

To make credentials more portable:

- You can use **%D** in place of a specific IP address.
- You can use **%N** in place of a specific host name.

Credentials can be aligned with an organization. When you align a credential with an organization, only users who are members of that organization can view the name of the credential in Skylar One. Only users who are members of that organization can assign that credential in Skylar One. For details, see the guide for the **Credential Management** page.

- **When creating or editing a PowerPack**, the **Available** pane will display a list of credentials that are not yet included in any other PowerPack and further filters the list by including only those credentials that you have access to. Your organization membership(s) might affect the list of credentials you can see in the **Available** pane. For details, see the guide for the **Credential Management** page.
- **When creating or editing a PowerPack**, if you remove a credential from the PowerPack using the bomb icon, and you are not a member of the organization aligned with that credential, the credential will not appear in the **Available** pane.
- **When viewing the list of included credentials** in the PowerPack in the **Embedded** pane, all users who can access the PowerPack, regardless of their organization, can view the list of credentials. If a credential is aligned with one or more organization, the **Organization** column in the **Embedded** pane displays *limited*. If the credential is aligned with all organization, the **Organization** column in the **Embedded** pane displays *all orgs*.
- **When a user imports and installs a PowerPack** on a system other than the author system:
 - credentials aligned with **all orgs** are still aligned with all organizations on the new system.
 - credentials aligned with one or more organizations on the author system are aligned with **no organizations** on the new system. An administrator or user who is a member of all organizations must edit the installed credential and align it with one or more organizations. Until the credential is aligned with one, multiple, or all organizations, it is not visible to other users in Skylar One.

Credential Tests

If you include a Credential Test that is aligned with an execution environment, Skylar One will automatically export that execution environment and its associated ScienceLogic Libraries with the PowerPack.

Ticket Templates

When a Ticket Template is included in a PowerPack, some system-specific values will be automatically substituted by Skylar One.

For each ticket template in a PowerPack, Skylar One will automatically substitute the following values:

- **Organization.** This field will contain the default value "System".
- **Ticket Queue.** By default, no value will be selected in this field.
- **Assigned User.** By default, no value will be selected in this field.
- **Category.** By default, no value will be selected in this field.

IT Service Policies

When an IT service policy is included in a PowerPack, the following properties of the IT service policy are included:

- The settings defined in the **[Properties]** sub-tab in the **IT Service Editor**. However, the following system-specific values are substituted when the PowerPack is installed:
 - The **IT Service Owner** field is set to the user that installed the PowerPack.
 - The values that were selected in the **Permission Keys** field are removed.
- The dynamic device rules defined in the **[Model]** sub-tab in the **IT Service Editor**. Statically aligned devices, device groups, and service dependencies are not included.
- The device subsets defined in the **[Model]** sub-tab in the **IT Service Editor**. However, only dynamic device rules are included in those subsets. Statically aligned devices are not included.
- All settings defined in the **[Metrics]**, **[Collection]**, and **[Alerting]** sub-tabs in the **IT Service Editor**.

When a PowerPack that includes an IT service policy is installed on a Skylar One system, the following items are also installed by the PowerPack:

- All event policies associated with the IT service policy.
- All interface tags that are specified in a metric in the IT service policy.

If you include an IT service policy that includes a metric that uses a Dynamic Application in a PowerPack but do not include the Dynamic Application in the PowerPack:

- For the Dynamic Applications that are not included in the PowerPack, Skylar One will automatically export those Dynamic Applications with the PowerPack. However, those Dynamic Applications will not appear in the **Embedded/Available** page for the PowerPack and can still be included in other PowerPacks.
- When the PowerPack is installed on a Skylar One system, Skylar One will install the Dynamic Applications that were not included in the PowerPack only if those Dynamic Applications are not already installed. If Skylar One discovers one or more of the Dynamic Applications in the PowerPack already exists on the Skylar One system and those Dynamic Applications were not installed by the current PowerPack, **Skylar One will not overwrite the existing Dynamic Applications**.
- If a Dynamic Application is installed on a Skylar One system by a PowerPack that does not explicitly include that Dynamic Application and the PowerPack that does include that Dynamic Application is installed at a later date, the Dynamic Application definition that exists on the system will be associated with its PowerPack and will be updated by that PowerPack.

Exporting a PowerPack

If you want users to be able to install a PowerPack on another Skylar One system, you must export the PowerPack to a file. To do this:

1. If the **Editing PowerPack** page is not open, go to the **PowerPack Manager** page (System > Manage > PowerPacks). Find the PowerPack you want to export and click its save icon (🔒).
2. If the PowerPack is already open, click **Build and Export** from the Navbar to the left.
3. In the **Compiled PowerPacks / Generate Installation Key** page, go to the **Compiled PowerPacks** pane at the top of the page.
4. Find the revision of the PowerPack you want to export and click its save icon (🔒).
5. When prompted, save the PowerPack to a local file.
6. You can now distribute the file for installation on other Skylar One systems.
7. If the exported PowerPack does not include an embedded license key, you must send the license key to each user who will install and import the PowerPack.

Generating an Embedded License Key After the Initial Build

If you want to generate a new, embedded license key for the PowerPack after the initial build, perform the following:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. Find the PowerPack for which you want to generate a license key. Click its save icon (🔒).
3. The **Compiled PowerPacks / Generate Installation Key** modal page appears.
4. In the **Compiled PowerPacks** pane, find the Version and Revision of the PowerPack for which you want to generate a new, embedded license key. Click its wrench icon (🔧).
5. In the **Configure Export File** page, define the embedded license key. For details on each field, see the section [Generating an Embedded License Key During the Initial Build](#).
6. Click the **[Save]** button to save the embedded license. Notice that the **Embedded License** field in the top pane of the **Compiled PowerPacks / Generate Installation Key** page now matches the newly generated license.
7. After saving the license key, you can export the PowerPack. To do this, go to the **Compiled PowerPacks / Generate Installation Key** modal page. In the **Compiled PowerPacks** pane, find the Version and Revision of the PowerPack you want to export.
8. Click the save icon (🔒). The PowerPack will be exported to your local computer. You can then distribute the PowerPack to users.
9. When users import and install the PowerPack, they do not need to enter a license key.

Generating an Unembedded License Key After the Initial Build

If you want to generate a new license key, not embedded, for the PowerPack after the initial build, perform the following:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. Find the PowerPack for which you want to generate a license key. Click its save icon ().
3. The **Compiled PowerPacks / Generate Installation Key** modal page appears.
4. In the **Compiled PowerPacks** pane, find the Version and Revision of the PowerPack for which you want to generate a new license key. Click its **Generate License Key** icon (.
5. The selected Version and Revision of the PowerPack is loaded into the **Generate Installation/License Key** pane.
6. In the **Generate Installation/License Key** pane, define the privileges for the new license key and generate the new license key. For details on each field, see the section [Generating an Unembedded License During the Initial Build](#).
7. Copy the license key and paste it into a text file.
8. After saving the license key, you can export the PowerPack. To do this, go to the **Compiled PowerPacks / Generate Installation Key** modal page. In the **Compiled PowerPacks** pane, find the Version and Revision of the PowerPack you want to export.
9. Click the save icon (). The PowerPack will be exported to your local computer. You can then distribute the PowerPack to users.
10. You must send the license key to each user who will install and import the PowerPack.

Chapter

4

Editing a PowerPack

Overview

This chapter describes how to edit a PowerPack, assign a new license key to a PowerPack that has already been installed, how to delete a PowerPack, and how to remove content from a PowerPack.

This chapter covers the following topics:

<i>Caveats</i>	48
<i>Privileges for Editing a PowerPack</i>	49
<i>Editing a PowerPack</i>	57
<i>Generating a New License Key for the PowerPack</i>	59
<i>Assigning a New License Key to an Already-Installed PowerPack</i>	59
<i>Deleting One or More PowerPacks</i>	60
<i>Removing Content from a PowerPack</i>	60

Caveats

- Content can be included in only a single PowerPack. For example, if you include the Dynamic Application "Cisco: Summary Statistics" in the PowerPack "networking_powerpack", you cannot include that Dynamic Application in another PowerPack. If you want to include content in a second PowerPack, you must first remove the content from the first PowerPack. This is described in the section [Removing Content from a PowerPack](#).

- When you delete a PowerPack, Skylar One automatically deletes the associated content from the Skylar One system and all data associated with it. For example, if a PowerPack includes a Dynamic Application, when you delete the PowerPack, the Dynamic Application is removed from Skylar One. If you go to the **Dynamic Applications Manager** page (System > Manage > Applications), that Dynamic Application will not appear. In addition, all data collected from all devices with that Dynamic Application will also be deleted.
- Device Classes and Device Categories are an exception to bullet above. When a PowerPack includes Device Classes or Device Categories, those Device Classes and Device Categories are not removed from the Skylar One system when you delete the PowerPack.
- If you must delete a PowerPack but want to keep the installed content, you should first remove the content from the PowerPack. This is described in the section [Removing Content from a PowerPack](#). To remove content from a PowerPack, you must either have administrator/owner privileges for the PowerPack or you must be the creator of the PowerPack. For details on privileges associated with PowerPacks, see the [section on privileges](#) in this chapter.
- If you want to include content in a second PowerPack, you must first remove the content from the first PowerPack. This is described in the section [Removing Content from a PowerPack](#). To remove content from a PowerPack, you must either have administrator/owner privileges for the PowerPack or you must be the creator of the PowerPack. For details on privileges associated with PowerPack, see the [section on privileges](#) in this chapter.
- The privileges associated with a PowerPack's license key control the actions that users can perform after they install a PowerPack.
- Authors of PowerPacks are allowed to perform all editing actions on the PowerPack and its content. On the Skylar One system where the PowerPack was created, only authors can edit the **Publisher** field for a PowerPack.
- If content in PowerPacks uses Intellectual Property Protection, you will not be able to edit the content on any system other than the system where the content was authored. This is true regardless of the license key associated with the PowerPack.
- If you include organization-specific credentials in a PowerPack, the credentials cannot be preserved by that organization when the PowerPack is installed on another environment. The credentials in a PowerPack are the responsibility of the customer, and cannot be guaranteed to be organization-specific in another Skylar One system.

Privileges for Editing a PowerPack

On the system where the PowerPack is created, privileges are controlled by user-type (user or administrator) and access keys. Additionally, on the author system, the license key for a PowerPack endows author privileges.

On the system where the PowerPack is installed, privileges are controlled by the license key, and/or Intellectual Property Protection. When creating a PowerPack or a revision of a PowerPack, the author can assign privileges and capture those privileges in a license key. ***The following table describes privileges on the system where the PowerPack is installed.***

NOTE: If the PowerPack contains one or more Dynamic Applications or event policies that use Intellectual Property Protection, users will not be able to edit the Dynamic Applications or event policies when they are installed on another system, even if the PowerPack includes Administrator/Owner privileges.

Privilege	Actions
License Key from PowerPack Properties page	Provides author-level privileges for the author of the PowerPack on the author system. Authors can edit the content from within the PowerPack and in Skylar One. Authors are also allowed to edit the properties of the PowerPack, including the Publisher field, delete content from the PowerPack, export the PowerPack, and generate a license key for the PowerPack. For users of the PowerPack, the License Key is a field on the Properties page that displays the license key currently associated with the PowerPack.
License Key - Install and Use Only	Users will be allowed to install this PowerPack on another system (other than the author system). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. Users will not be allowed to edit any of the installed content, either from within the PowerPack manager or in their respective management pages.
Administrative (Including Export & License)	After installation on a system (other than the author system), users will be allowed to edit each of the installed items from this PowerPack. Users can edit the content from within the PowerPack and in Skylar One. Users will also be allowed to edit the properties of the PowerPack (but cannot edit the Publisher field), delete content from the PowerPack, export the PowerPack, and generate a license key for the PowerPack.

Privilege	Actions
License Key - Dynamic Applications	After installation on a system (other than the author system), users will be allowed to edit the installed Dynamic Applications from the Dynamic Applications Manager page (System > Manage > Applications). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Event Policies	After installation on a system (other than the author system), users will be allowed to edit the installed event policies from Event Policy Manager page (Registry > Events > Event Manager). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access any other pages for the PowerPack.
License Key - Device Categories	After installation on a system (other than the author system), users will be allowed to edit the installed device categories from the Device Category Editor page (System > Customize > Device Categories). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Device Classes	After installation on a system (other than the author system), users will be allowed to edit the installed device classes from the Device Class Editor page (System > Customize > Device Classes). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Device Templates	After installation on a system (other than the author system), users will be allowed to edit the installed device classes from Configuration Templates page (Devices > Templates, or Registry > Devices > Templates in the classic user interface). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.

Privilege	Actions
License Key - Device Groups	After installation on a system (other than the author system), users will be allowed to edit the installed device groups from the Device Groups page (Devices > Device Groups). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Reports	After installation on a system (other than the author system), users will be allowed to edit the installed report from the [Reports] tab. In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Dashboard Widgets	After installation on a system (other than the author system), users will be allowed to edit the installed dashboard-widget from the Classic Dashboard Widgets page (System > Customize > Classic Dashboard Widgets). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Dashboards	After installation on a system (other than the author system), users will be allowed to edit the installed dashboards from the Dashboards tab page. In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Skylar One Dashboards	After installation on a system (other than the author system), users will be allowed to edit the installed Skylar One dashboards from the Dashboards page (☰). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.

Privilege	Actions
License Key - Run Book Policies	After installation on a system (other than the author system), users will be allowed to edit the installed run book policies from the Automation Policy Manager page (Registry > Run Book > Automation). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Run Book Actions	After installation on a system (other than the author system), users will be allowed to edit the installed run book actions from the Action Policy Manager page (Registry > Run Book > Actions). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Ticket Templates	After installation on a system (other than the author system), users will be allowed to edit the installed ticket templates from the Ticket Templates page (Registry > Ticketing > Templates). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Credentials	After installation on a system (other than the author system), users will be allowed to edit the installed credentials from the Credential Management page (System > Manage > Credentials). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack. If the credential is organization-restricted on the author system, these restrictions won't apply on the target system.

Privilege	Actions
License Key - Credential Tests	After installation on a system (other than the author system), users will be allowed to edit the installed credential tests from the Credential Test Management page (System > Customize > Credential Tests). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - UI Themes	After installation on a system (other than the author system), users will be allowed to edit the installed themes from the Theme Management page (System > Customize > Themes). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - IT Services	After installation on a system (other than the author system), users will be allowed to edit the installed IT service policies from the IT Service Manager page (Registry > IT Services > IT Service Manager). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Log File Monitoring Policies	After installation on a system (other than the author system), users will be allowed to edit the installed log file monitoring policies from the Log File Monitoring Policies page (System > Manage > Log File Monitoring Policies). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Credential Fields	After installation on another Skylar One system (other than the author system), users will be allowed to utilize the content type. In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

Privilege	Actions
License Key - Guided Discovery Workflow	After installation on another Skylar One system (other than the author system), users will be allowed to utilize the content type. In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
License Key - AP Content Objects	After installation on a system (other than the author system), users will be allowed to edit the installed AP Content Objects from the Content Management page (Manage > Content Management). In the PowerPack Properties page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.

Privilege	Actions
Intellectual Property Protection - Dynamic Applications	Adding Intellectual Property Protection to a Dynamic Application prevents users from viewing information required only for editing purposes, and from editing the Dynamic Application on any system except the system where the Dynamic Application was created. After installation on a system (other than the author system), users cannot disable the Intellectual Property Protection feature and can view only the [Properties] and [Subscribers] tab of the Dynamic Application (within the PowerPack or in the Dynamic Applications Manager page). Even if the PowerPack is installed with a license key that grants Administrator/Owner privileges, users won't be able to access all tabs for the Dynamic Application. When Intellectual Property Protections is enabled, the tabs below will not be displayed for the Dynamic Application: ◦ Collections ◦ Presentation ◦ Thresholds ◦ Snippets (for Dynamic Applications of type "snippet") ◦ Requests (for Dynamic Applications of type "SOAP" and "XSLT") ◦ Alerts

Privilege	Actions
Intellectual Property Protection - Event Policies	Adding Intellectual Property Protection to an event policy prevents users from viewing information required only for editing purposes, and from editing the event policy on any system except the system where the event policy was created. After installation on a system (other than the author system), users cannot disable the Intellectual Property Protection feature and can view only the [Policy] and [Suppressions] tab of the event policy application (within the PowerPack or in the Event Policy Manager page). Even if the PowerPack is installed with a license key that grants Administrator/Owner privileges, users won't be able to access all tabs for the event policy. When Intellectual Property Protections is enabled, the tab below will not be displayed for the event policy: ◦ Advanced

Editing a PowerPack

If you have administrator rights for a PowerPack, you can edit an existing PowerPack.

If you have installed a PowerPack on a system other than the author system, your [editing privileges](#) are determined by the license key and/or intellectual property protection associated with the PowerPack.

To edit a PowerPack:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. Find the PowerPack you want to edit and click its wrench icon (.
3. You can edit one or more fields in the **PowerPack Properties** page. For details on the Navbar for a PowerPack and their fields, see the section on [Creating a PowerPack](#).

NOTE: If you edit a content item in the PowerPack (either from the **Embedded** pane in the **Embedded/Available** page or from a page in the user interface) **after** the PowerPack is installed or the last time the PowerPack was compiled (whichever is late), that content item will be highlighted in red and will have an updated date in the **Last Edited** column in the **Embedded/Available** page.

4. If you edited the PowerPack, you must rebuild the PowerPack and generate a new license key. For details, see the section [Building the PowerPack and Generating a License Key](#).
5. When you have finished building the PowerPack and generating the license key, you can export the updated PowerPack. For details, see the [Exporting a PowerPack](#) section.

NOTE: Any edits applied to the PowerPack before you create a new build will be highlighted in red in the **PowerPack** pages.

Editing Dynamic Applications in a PowerPack

You cannot use a PowerPack to globally delete an existing collection object. When you install a PowerPack on multiple systems, and you log in to one of those systems and delete a collection object from a Dynamic Application in that PowerPack, you must then log in to each system and manually delete that collection object from each system. Saving the edited PowerPack and re-installing it will not perform a deletion. This is a behavior built into the PowerPack to protect your data.

For example:

- Suppose you have a PowerPack named ***PowerPack_test***.
- Suppose PowerPack_test includes a Dynamic Application named ***DynApp_test***.
- Suppose you install ***PowerPack_test*** on two systems, ***EM7_sys1*** and ***EM7_sys2***.
- Suppose you:
 - Log in to ***EM7_sys1***.
 - Edit ***PowerPack_test***.
 - In ***PowerPack_test***, edit ***DynApp_test***.
 - In ***DynApp_test***, delete a collection object called ***my_object***.
 - Save ***PowerPack_test*** with a new version number.
 - Export the new version of ***PowerPack_test***.
- Suppose you log in to ***EM7_sys2*** and install the new version of ***PowerPack_test***.
- The updated PowerPack will not delete the existing collection object from ***EM7_sys2***.
- After installing ***PowerPack_test***, go to the Dynamic Applications Manager page (System > Manage > Applications). Open the Dynamic Application ***DynApp_test***. Notice that the Dynamic Application still contains the collection object ***my_object***.
- To remove the collection object, you must manually edit the Dynamic Application and delete the collection object. You cannot use an updated PowerPack to delete the collection object.

Generating a New License Key for the PowerPack

To learn how to generate a new license key for a PowerPack, see the sections on generating embedded and un-embedded license keys after the initial build in the section [Creating a PowerPack](#).

Assigning a New License Key to an Already-Installed PowerPack

Suppose you want to change the privileges associated with an already-installed PowerPack, but you don't want to force the end-user to re-install the PowerPack. To do this, you can generate a new, un-embedded license key for the already-installed revision of the PowerPack.

The user of the PowerPack can then paste the new license key into the *License Key* field in the **PowerPack Properties** page for the PowerPack. To assign a new license key to an already-installed PowerPack:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. Find the PowerPack you want to assign a new license key to. Click its wrench icon (.
3. In the **PowerPack Properties** page, click *Build / Export*.
4. In the **Compiled PowerPacks / Generate Installation Key** page, each revision of the PowerPack is displayed. To select the PowerPacks revision for which you want to generate an installation key, click its pencil icon (.
5. In the **License Key type** field, you can now select if you want to embed the license key in the PowerPack, and if so, how you would like the embedded key to function. Choices are:
 - *Install & Use Only*. After installation on another Skylar One system (other than the author system), users will be allowed to edit only the name and version number of the PowerPack in the **PowerPack Properties** page. Users will not be allowed to edit any of the installed content, either from within the PowerPack or in Skylar One.
 - *Administrative (including export & license)*. After installation on another Skylar One system (other than the author system), users will be allowed to edit each of the installed items from this PowerPack. Users can edit the content from within the PowerPack and in Skylar One. Users will also be allowed to edit the properties of the PowerPack, delete content from the PowerPack, export the PowerPack, and generate a license key for the PowerPack.
 - *Manage Content Items of Selected Types*. After installation on another Skylar One system (other than the author system), users will be allowed to edit the installed content type, from the associated page in the user interface. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
6. Click the **Generate Key** button. When the new license key appears in the *Generated Install Key* field, copy the license key and paste it into a text file.

Deleting One or More PowerPacks

If you have the appropriate Access Keys, you can delete one or more PowerPacks from the **PowerPack Manager** page.

CAUTION: When you delete a PowerPack, Skylar One automatically deletes most PowerPack content from the Skylar One system and all data collected by the PowerPack. For example, if a PowerPack includes a Dynamic Application, when you delete the PowerPack, the Dynamic Application is removed from Skylar One. If you go to the **Dynamic Applications Manager** page (System > Manage > Applications), that Dynamic Application will not appear. In addition, all data collected from all devices with that Dynamic Application will also be deleted. If you must delete a PowerPack but want to keep the installed content, you should first remove the content from the PowerPack. This is described in the section [Removing Content from a PowerPack](#). To remove content from a PowerPack, you must either have administrator/owner privileges for the PowerPack or you must be the creator of the PowerPack. For details on privileges associated with PowerPacks, see the section on [Creating a PowerPack](#).

NOTE: When a PowerPack includes Device Classes or Device Categories, those Device Classes and Device Categories are not removed from the Skylar One system when you delete the PowerPack. Device Classes and Device Categories are an exception to the **Caution** above.

To delete a PowerPack:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. Find the PowerPack you want to delete. Select its checkbox.
3. Click the checkbox for each PowerPack you want to delete.
4. In the **Select Action** drop-down field (in the lower right), choose *Delete PowerPack(s)*.
5. Click the **[Go]** button.
6. In the pop-up window that appears, click the **[OK]** button.
7. The selected PowerPacks will be deleted from Skylar One.

Removing Content from a PowerPack

If you have the license key with author's privileges for a PowerPack or if you have owner/administrator privileges with your license key, you can remove content from a PowerPack. There are two situations where you might want to remove content from a PowerPack.

- If you must delete a PowerPack but want to keep the installed content, you should first remove the content from the PowerPack.

- Each piece of content in Skylar One can be included in **only one** PowerPack. If you want to include content in a second PowerPack, you must first remove the content from the first PowerPack.
- You cannot use a PowerPack to delete existing collection objects from a Dynamic Application. For details, section on [Editing a Dynamic Application in a PowerPack](#).

To remove content from a PowerPack:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. Find the PowerPack you want to edit. Click its wrench icon (.
3. In the **PowerPack Properties** page, in the Navbar on the left side, select the option for the content you want to remove:

NOTE: The entries under the **Contents** link are dependent upon your Access Hooks. An entry appears only if you have been granted an Access Key that contains the Access Hook that allows you to view the content-type in Skylar One. For example, the **Dynamic Applications** entry will appear under the **Contents** link only if you have permission to view the list of Dynamic Applications in the **Dynamic Applications Manager** page (System > Manage > Applications) in Skylar One.

- **Dynamic Applications.** Select this option to remove one or more Dynamic Applications from the PowerPack.
- **Event Policies.** Select this option to remove one or more event policies from the PowerPack.
- **Device Categories.** Select this option to remove one or more device categories from the PowerPack.
- **Device Classes.** Select this option to remove one or more device classes from the PowerPack.
- **Device Templates.** Select this option to remove one or more device templates from the PowerPack.
- **Device Groups.** Select this option to remove one or more device groups from the PowerPack.
- **Reports.** Select this option to remove one or more custom reports from the PowerPack.
- **Dashboard Widgets.** Select this option to remove one or more custom dashboard-widgets from the PowerPack.
- **Dashboards.** Select this option to remove one or more dashboards or device dashboards from the PowerPack.
- **Dashboards Skylar One.** Select this option to remove one or more Skylar One dashboards from the PowerPack.
- **Run Book Policies.** Select this option to remove one or more custom run book policies from the PowerPack.
- **Run Book Actions.** Select this option to remove one or more custom run book actions from the PowerPack.
- **Run Book Action Types.** Select this option to remove one or more run book action types from the PowerPack.

- ***Ticket Templates***. Select this option to remove one or more custom ticket templates from the PowerPack.
 - ***Credentials***. Select this option to remove one or more credentials from the PowerPack. If you delete an Embedded credential that is aligned to an organization you are not a member of, that credential will no longer be available to you.
 - ***Credential Tests***. Select this option to remove one or more credential tests from the PowerPack.
 - ***UI Themes***. Select this option to remove one or more UI themes from the PowerPack.
 - ***IT Services***. Select this option to remove one or more IT Services from the PowerPack.
 - ***Log File Monitoring Policies***. Select this option to remove one or more log file monitoring policies from the PowerPack.
 - ***Credential Fields***. Select this option to remove one or more credential fields from the PowerPack.
 - ***Guided Discovery Workflow***. Select this option to remove one or more guided discovery workflows from the PowerPack.
 - ***AP Content Objects***. Select this option to remove one or more AP content objects from the PowerPack.
4. In the **Embedded/Available** page for the content, go to the **Embedded** pane at the top of the page.
 5. Find the content you want to remove from the PowerPack. Click the delete icon (🗑️) for that content. The content will be removed from the PowerPack and will now appear in the bottom pane.

© 2003 - 2026, ScienceLogic, Inc.

All rights reserved.

ScienceLogic™, the ScienceLogic logo, and ScienceLogic's product and service names are trademarks or service marks of ScienceLogic, Inc. and its affiliates. Use of ScienceLogic's trademarks or service marks without permission is prohibited.

ALL INFORMATION AVAILABLE IN THIS GUIDE IS PROVIDED "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED. SCIENCELOGIC™ AND ITS SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT.

Although ScienceLogic™ has attempted to provide accurate information herein, the information provided in this document may contain inadvertent technical inaccuracies or typographical errors, and ScienceLogic™ assumes no responsibility for the accuracy of the information. Information may be changed or updated without notice. ScienceLogic™ may also make improvements and / or changes in the products or services described herein at any time without notice.



800-SCI-LOGIC (1-800-724-5644)

International: +1-703-354-1010