



---

# PowerPacks

SL1 version 8.10.0

---

# Table of Contents

<b>Introduction</b> .....	<b>4</b>
What is a PowerPack? .....	4
Who Should Read this Manual? .....	6
<b>Installing a PowerPack</b> .....	<b>7</b>
How SL1 Updates Default PowerPacks .....	8
Importing and Installing a PowerPack .....	11
Importing a PowerPack .....	11
Installing a Single PowerPack .....	12
Installing Multiple PowerPacks .....	15
Checking the Status of Installed Content .....	17
Viewing the List of PowerPacks .....	19
Filtering the List of PowerPacks .....	20
Viewing Documentation for a PowerPack .....	22
Viewing a Document from the .em7pp File .....	23
Downloading a Document .....	23
System Settings that Affect PowerPacks .....	24
<b>Creating a PowerPack</b> .....	<b>26</b>
Caveats .....	27
Creating a PowerPack .....	28
Creating a Container for a PowerPack .....	28
Adding Content to a PowerPack .....	30
Adding Documentation to a PowerPack .....	35
Adding a Documentation File to a PowerPack .....	35
Changing Visibility .....	35
Deleting a Document .....	36
Including Details on a PowerPack's Features, Benefits, and Technical Information .....	37
Features/Benefits .....	37
Technical Notes .....	38
Adding Intellectual Property Protection to Content in a PowerPack .....	39
Determining the PowerPack's Execution Environments .....	40
Building the PowerPack and Generating a License Key .....	41
Building a PowerPack .....	41
Generating an Embedded License Key During the Initial Build .....	42
Generating an Unembedded License During the Initial Build .....	46
Export Rules, Import Rules, and Substitutions .....	50
Event Policies .....	50
Dynamic Applications .....	50
Dashboards .....	50
Run Book Actions .....	51
Run Book Policies .....	52
Credentials .....	53
Credential Tests .....	53
Ticket Templates .....	53
Device Templates .....	54
Device Groups .....	54
IT Service Policies .....	54
Exporting a PowerPack .....	55
Generating an Embedded License Key After the Initial Build .....	57
Generating an Unembedded License Key After the Initial Build .....	58
<b>Editing a PowerPack</b> .....	<b>60</b>

Caveats .....	61
Privileges for Editing a PowerPack .....	61
Editing a PowerPack .....	68
Editing Dynamic Applications in a PowerPack .....	70
Generating a New License Key for the PowerPack .....	70
Assigning a New License Key to an Already-Installed PowerPack .....	71
Deleting One or More PowerPacks .....	72
Removing Content from a PowerPack .....	73

---

# Chapter

# 1



## Introduction

---

### Overview

This manual describes how to use PowerPacks in SL1 .

Use the following menu options to navigate the SL1 user interface:

- To view a pop-out list of menu options, click the menu icon ().
- To view a page containing all of the menu options, click the Advanced menu icon ().

This chapter includes the following topics:

<a href="#">What is a PowerPack?</a> .....	4
<a href="#">Who Should Read this Manual?</a> .....	6

---

### What is a PowerPack?

A PowerPack is an exportable and importable package of one or more Dynamic Applications, device classes, device templates, event policies, custom reports, dashboard widgets, dashboards, run book policies, run book actions, ticket templates, credentials, proxy XML transformations, themes, device categories, device dashboards, and/or IT service policies.

You can use PowerPacks to share customized content among SL1 systems and to download customized content from ScienceLogic.

You can create a PowerPack on a SL1 system to export one or more Dynamic Applications, device classes, device templates, event policies, custom reports, dashboard widgets, dashboards, run book policies, run book actions, ticket templates, credentials, proxy XML transformations, themes, device categories, device dashboards, and/or IT service policies. You can then import that PowerPack on another SL1 system to install the Dynamic Applications, device classes, device templates, event policies, custom reports, dashboard widgets, dashboards, run book policies, run book actions, ticket templates, credentials, proxy XML Transformation, themes, device categories, device dashboards, and/or IT service policies.

PowerPacks include automatically generated version numbers and license keys to provide version control and to protect the content of each PowerPack. When exporting a PowerPack you can generate a license that prevents users from editing content included in the PowerPack.

You can also apply Intellectual Property Protection (IPP) to the Dynamic Applications and event policies you include in a PowerPack. IPP prevents other users from viewing information required only for editing purposes, and from editing the Dynamic Application or event policy. When IPP is applied, the Dynamic Application or event policy can be **edited only on the author system** (SL1 system where the Dynamic Application or event policy was created) and only by users with the appropriate Access Keys.

This manual will describe how to:

- Install a PowerPack
- Get information about a PowerPack
- Edit a PowerPack
- Create a PowerPack
- Delete a PowerPack

---

## Who Should Read this Manual?

This manual is intended for administrators and developers who create, install, and manage Dynamic Applications, event policies, device classes, device templates, custom reports, custom dashboard widgets, dashboards, run book policies, run book actions, ticket templates, credentials, proxy XML transformations, themes, and/or IT service policies.

---

# Chapter

# 2

## Installing a PowerPack

---



### Overview

This chapter describes how to install a PowerPack in your SL1 system. There are two general steps to install a PowerPack:

- **Importing** a PowerPack loads the PowerPack file into SL1 and allows you to see information about the PowerPack and how the contents of the PowerPack will be installed.
- **Installing** a PowerPack writes the contents of the PowerPack to your SL1 system.

These steps can be performed to install new PowerPacks (a PowerPack that has not previously been installed in the SL1) and to update PowerPacks that are already installed in your SL1 system.

Use the following menu options to navigate the SL1 user interface:

- To view a pop-out list of menu options, click the menu icon (.
- To view a page containing all of the menu options, click the Advanced menu icon (.

This chapter includes the following topics:

<i>How SL1 Updates Default PowerPacks</i> .....	8
<i>Importing and Installing a PowerPack</i> .....	11
<i>Importing a PowerPack</i> .....	11
<i>Installing a Single PowerPack</i> .....	12
<i>Installing Multiple PowerPacks</i> .....	15
<i>Checking the Status of Installed Content</i> .....	17
<i>Viewing the List of PowerPacks</i> .....	19
<i>Filtering the List of PowerPacks</i> .....	20


<a href="#">Viewing Documentation for a PowerPack .....</a>	<a href="#">22</a>
<a href="#">Viewing a Document from the .em7pp File .....</a>	<a href="#">23</a>
<a href="#">Downloading a Document .....</a>	<a href="#">23</a>
<a href="#">System Settings that Affect PowerPacks .....</a>	<a href="#">24</a>

**NOTE:** If ScienceLogic includes a new PowerPack in the standard software package, the PowerPack will be automatically installed the next time you apply an update to your SL1 system. The release notes for every release indicate which PowerPacks will be automatically installed.

---


## How SL1 Updates Default PowerPacks

ScienceLogic includes multiple PowerPacks in the default installation of SL1. When you apply an update to your system, new versions of the default PowerPacks will be automatically imported in to your system. If a PowerPack is included in an update and is not currently installed on your system, SL1 will automatically install the PowerPack. If a PowerPack is included in an update and is currently installed on your system, SL1 will automatically import (but not install) the PowerPack.

If PowerPacks have been imported into your system but have not been installed, the **Update** column appears in the **PowerPack Manager** page (System > Manage > PowerPacks). For each PowerPack that has been imported to your system but has not been installed, the lightning bolt icon () appears in the **Update** field on the **PowerPack Manager** page.

**NOTE:** If a PowerPack updates one or more device classes, device categories, or Dynamic Applications, SL1 will not overwrite the alignment between device dashboards and any updated device classes, device categories, or Dynamic Applications.

To install the new version of a single PowerPack:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. In the **PowerPack Manager** page, click the lightning bolt icon () for the PowerPack you want to install.



PowerPack™ Name	Version	Update	Publisher	Area	Events	Classes	Reports	Widgets	Dashbds	Actions	Creds	Tckt Tel	DashSL1	Dev Tel	ID	Edited By	Last Edited
1. Microsoft PowerPack Test Cred: 1.7	No	ScienceLogic, Inc.	--	--	--	--	--	--	--	--	21	--	--	--	177	em7admin	2019-07-26 15:16:28
2. SNMP Dynamic Application Ref: 1.0	No	ScienceLogic, Inc.	5	--	--	--	--	--	--	--	--	--	--	--	179	em7admin	2019-07-26 15:56:25
3. Cisco AppDynamics	100	No	ScienceLogic, Inc.	12	12	30	--	--	3	1	2	--	--	--	155	em7admin	2019-07-25 11:19:27
4. EM7 Default Dynamic Applicator: 7.7.0	No	ScienceLogic, Inc.	3	2	--	--	--	--	--	--	--	--	--	--	94	em7admin	2019-07-25 11:17:58
5. Microsoft Base Pack	106	No	ScienceLogic, Inc.	10	35	36	--	--	--	1	1	--	--	--	110	em7admin	2019-07-25 11:18:25
6. Microsoft Active Directory Serve	100	No	ScienceLogic, Inc.	11	2	--	--	--	--	--	--	--	--	--	86	em7admin	2019-07-25 11:17:41
7. Microsoft Azure	108	Yes	ScienceLogic, Inc.	72	48	233	--	--	--	8	5	--	--	--	101	em7admin	2019-07-25 11:18:12
8. Microsoft Azure Classic	3.5	No	ScienceLogic, Inc.	42	12	48	--	--	--	--	1	--	--	--	35	em7admin	2019-07-25 11:17:08
9. Microsoft DHCP Server	1.0	No	ScienceLogic, Inc.	7	--	--	--	--	--	--	--	--	--	--	51	em7admin	2019-07-25 11:17:33
10. Microsoft DNS Server	100	No	ScienceLogic, Inc.	12	--	--	--	--	--	--	--	--	--	--	67	em7admin	2019-07-25 11:17:42
11. Microsoft Exchange Server	100	No	ScienceLogic, Inc.	16	58	--	--	--	--	--	--	--	--	--	31	em7admin	2019-07-25 11:17:03
12. Microsoft Exchange Server 2011: 1.2	No	ScienceLogic, Inc.	20	114	--	--	--	--	--	--	--	--	--	--	64	em7admin	2019-07-25 11:17:38
13. Microsoft Hyper-V Server	100	No	ScienceLogic, Inc.	18	5	--	--	--	--	--	--	--	--	--	124	em7admin	2019-07-25 11:18:39
14. Microsoft IIS Server	101	No	ScienceLogic, Inc.	5	14	--	--	--	--	--	--	--	--	--	33	em7admin	2019-07-25 11:17:07
15. Microsoft Lync Server 2010	1.0	No	ScienceLogic, Inc.	24	13	--	--	--	--	--	1	--	--	--	79	em7admin	2019-07-25 11:17:51
16. Microsoft Lync Server 2013	1.0	No	ScienceLogic, Inc.	22	13	--	--	--	--	--	--	--	--	--	140	em7admin	2019-07-25 11:18:53
17. Microsoft SharePoint Server	1.0	No	ScienceLogic, Inc.	3	4	--	--	--	--	--	--	--	--	--	95	em7admin	2019-07-25 11:17:59
18. Microsoft SQL Server	100	No	ScienceLogic, Inc.	8	8	--	--	--	--	--	--	--	--	--	133	em7admin	2019-07-25 11:18:47
19. Microsoft SQL Server Enhanced	101	No	ScienceLogic, Inc.	21	43	3	--	--	--	--	1	--	--	--	102	em7admin	2019-07-25 11:18:15

- The **PowerPack Installer** modal page will display the contents of the PowerPack. The **PowerPack Installer** modal page will indicate how SL1 will update each item in the PowerPack. If the actions that SL1 will perform are acceptable, click the **[Install]** button.

Dynamic Application	Version	GUID	Action
1. Microsoft Azure Account Discovery	1.2	B72F3E759273C25B97F71ED0ED8C1F8	update
2. Microsoft Azure Active Directory Tenant Configuration	1.2	7EBB1C1FC34632BEAE48A8B1C40B672	update
3. Microsoft Azure Active Directory Tenant Discovery	1.3	1E854E85AC1734486E598711DD3C6E8E	update
4. Microsoft Azure App Configuration	1	63F77E1DF73CB6168FBF5DB5A666BCE	update
5. Microsoft Azure App Discovery	1	5FC0D316D8DEE82AFEC8A959C268BE	update
6. Microsoft Azure App Performance	1	609BC00230FADDC354766A881E5D1CB	update
7. Microsoft Azure App Service Discovery	1	38CA2B1D329454EAD31744AD1406AFB	update
8. Microsoft Azure App Service Plan Discovery	1	EC0941939C01C3C1E74ED3C2104551C	update

Installation Key: sD/0jhrdKhOfhRUZ6oC1Fwr/GbItvqccZjSIVqGJFYw1dJTlxGhLqVo4TJBA186UqX5IZATEcZOeK6SaaTN8=

**Install**

- If you have made any local changes to the Dynamic Applications or Event Policies in the PowerPack and that content will be overwritten with this update, SL1 will display the following message before updating the PowerPack:

WARNING: Local PowerPack changes detected. Proceeding with installation will overwrite these changes.


Click the **[OK]** button to overwrite the local changes. Click the **[Cancel]** button to quit the update.

- If you completed the update, , updated information about the PowerPack will appear in the **PowerPack Manager** page. All the items in the PowerPack will be automatically installed in your SL1 system.

**NOTE:** The *Enable Selective PowerPack Field Protection* field in the **Behavior Settings** page affects how updates behave. If the *Enable Selective PowerPack Field Protection* checkbox is selected, certain fields in Event Policies, Dynamic Applications, and Device Classes will **not** be updated.

To install the updates for multiple PowerPacks:

- Go to the **PowerPack Manager** page (System > Manage > PowerPacks).



- In the **PowerPack Manager** page, select the checkbox for each PowerPack you want to install.
- In the **Select Action** drop-down field (in the lower right), choose *Update PowerPack(s)*.

- SL1 will display the following message before updating the PowerPack(s):

Update the selected PowerPacks?

NOTE: Any customizations to items contained in updated PowerPacks will be overwritten by the version contained within the more recently imported PowerPack file.

Click the **[OK]** button to continue the installation. Click the **[Cancel]** button to quit the update.

- Click the **[Go]** button. If you completed the update, updated information about the PowerPack will appear in the **PowerPack Manager** page. All the items in the PowerPack will be automatically installed in your SL1 system.

**NOTE:** You can install multiple PowerPacks with the **Select Action** drop-down list only if each selected PowerPack includes an embedded Installation Key. PowerPacks that do not include embedded Installation Keys will fail to install.

**NOTE:** The **Enable Selective PowerPack Field Protection** field in the **Behavior Settings** page affects how updates behave. If the **Enable Selective PowerPack Field Protection** checkbox is selected, certain fields in Event Policies, Dynamic Applications, and Device Classes will **not** be updated.

---

## Importing and Installing a PowerPack

Before installing a PowerPack, you must first import it. After a PowerPack has been imported, you can immediately install it or install it at a later time.

**NOTE:** The following sections describe how to import and install PowerPacks using the user interface. In addition to the user interface, PowerPacks can also be imported or installed via the ScienceLogic API. PowerPacks imported or installed via the user interface will appear in the ScienceLogic API and vice versa. For information about importing or installing PowerPacks via the ScienceLogic API, see the manual *Using the ScienceLogic API*.


### Importing a PowerPack

You can import a PowerPack from the **PowerPack Manager** page. To import a PowerPack to be installed at a later time:

1. Download the PowerPack from the [ScienceLogic customer portal](#).
2. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).

**NOTE:** To install a PowerPack, you might have to enter the license key for the PowerPack. You can get this license key from the PowerPack's author or the PowerPack administrator for your system. You cannot install a PowerPack that requires a license key without the license key.

2. In the **PowerPack Manager** page, click the **[Actions]** button. Click *Import PowerPack*.
3. The **Import PowerPack** dialog box appears.



- Use the **[Browse]** button to navigate to the PowerPack file.
  - **If the PowerPack includes an embedded license key**, do not enter a value in the **License** field.
  - **If the PowerPack does not include an embedded license key**, enter the license key in the **License** field.
4. When the **PowerPack Installer** modal page appears, you can do one of the following:
- Immediately install the PowerPack.
  - Exit the page without installing the PowerPack. If you do so, SL1 will store the PowerPack for later installation.

**NOTE:** If you exit the **PowerPack Installer** modal page without installing the imported PowerPack, the imported PowerPack will not appear in the **PowerPack Manager** page. However, the imported PowerPack will appear in the **Imported PowerPacks** modal page. This page appears when you click the **[Actions]** menu and choose **Install PowerPack**.

**CAUTION:** If you have modified one or more content items in a PowerPack that you are updating and want to preserve your changes, you must remove those content items from the PowerPack in your system before installing the new version of the PowerPack. If the **Package Content** pane indicates that SL1 will *update* a content item that you have edited, any changes you have made will be overwritten when you install the PowerPack. If you do not want your changes to be overwritten, click the **[Close / Esc]** button, remove the content item from the PowerPack, then follow the steps listed in the [Installing a PowerPack](#) section to install the PowerPack. For instructions on how to remove a content item from a PowerPack, see the [Editing a PowerPack](#) section.

## Installing a Single PowerPack

To install a new or updated PowerPack that is not included in the default installation of SL1, you must first [import the PowerPack](#). You can then immediately install the PowerPack or install it at a later time.

To install a PowerPack that has previously been imported to your SL1 system, perform the following steps:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. If you have not already done so, [import the PowerPack](#).


3. In the **PowerPack Manager** page, click the **[Actions]** menu and click *Install PowerPack*.
4. The **Imported PowerPacks** modal page appears, displaying a list of PowerPacks that have already been imported. The list displays:

PowerPack Name	Flag	Version	Revision	GUID	Last Edited	Imported	
1. .SNMP Dynamic Application Refac	--	1.0	79	A36CCC03630179CFC7D54D52AAD497	2019-07-26 15:56:25	2019-07-26 15:56:16	
2. Microsoft: Windows Server Event L	--	0.5	335	1B6EAF550440C5B403110FE2C863FED	2019-07-26 15:16:53	2019-07-26 15:16:46	
3. .Microsoft PowerPack Test Creds	--	1.7	48	2E0F1F571A480DD0DB4FD69759FFB4C	2019-07-26 15:16:28	2019-07-26 15:16:23	
4. ScienceLogic: ICDA Hardcoded Te	--	1	178	7517D0D28F3AC101741C46A3283DB41	2019-07-30 08:29:31	2019-07-26 08:44:15	
5. ICDA Sample Apps	--	0.1	20	6B3C3E3871EEF8204FC16E75177D4F4	2019-07-30 08:27:46	2019-07-26 08:42:30	
6. Sample DCM+R Pack	--	1	17	FF52DAAD8B5CE9F708E1E67DA4AE54	2019-07-30 06:30:08	2019-07-26 06:40:40	
7. 2-level DCM app test	--	1.1	17	14B918E33092A8459C14BE3A80871B2	2019-07-30 08:28:38	2019-07-26 06:39:34	
8. Test Disable Collection Obj	--	1	95	C4D17C58625A7A45FD87A31BACAECE	2019-07-26 05:04:57	2019-07-26 05:04:41	
9. Unicode Test PowerPack	--	1	39	80732E286B1ED262FB068E8CBA1669E	2019-07-26 05:03:45	2019-07-26 05:03:30	
10. JMX Base Pack *BETA*	--	101	1840	DDA6DB3C806F97B7DA9B3E55E5553B	2019-07-25 15:18:08	2019-07-25 15:17:55	
11. a simple DCM app	--	3	40	088ADE6257C876669AF2A261DD6FF80	2019-07-25 14:15:22	2019-07-25 14:15:20	
12. Silo Test: DCM Scale	--	1.7	138	3E39A7CE2BD4070F869EB263D103759	2019-07-25 14:15:00	2019-07-25 14:14:56	
13. Silo Test: DCM Scale	--	1.5	112	3E39A7CE2BD4070F869EB263D103759	2019-07-25 14:15:00	2019-07-25 14:14:39	
14. Brocade Base Pack	--	7.3.6	112	E596054B240F9B4AEC479DFA0CB583C	2019-07-25 11:19:26	--	
15. Xerox Base Pack	--	1	135	2A4FB346C4E3048DEC20DB4FC43AEF	2019-07-25 11:16:47	--	

- **PowerPack Name.** Name of the PowerPack.
- **Flag.** Indicates if the PowerPack is a beta release.
- **Version.** Version of the PowerPack. This number is user-defined and manually incremented by the PowerPack author.
- **Revision.** The revision number for the PowerPack.
- **GUID.** Unique identifier for the PowerPack. This number is unique across all ScienceLogic appliances.
- **Last Edited.** Date and time the PowerPack was last imported or updated.
- **Imported.** Date and time the PowerPack was imported.
- **Lightning-bolt icon** (). Click this icon to install a single PowerPack.
- **Checkbox** (). Click the checkbox and use the **Select Action** menu to install multiple PowerPacks simultaneously.

5. In the **Imported PowerPack** modal page, click the lightning-bolt icon () for the PowerPack that you want to install.

6. After selecting a PowerPack, the **Install PowerPack** modal page appears. The page displays:



- **PowerPack Name.** Name of the PowerPack.
- **Version.** Version number for the PowerPack. You can enter any combination of characters in this field. You must manually update this field to change the version number.
- **Package Information.** Displays information about the PowerPack, including:
  - *GUID.* Unique identifier for the PowerPack. This number is unique across all SL1 appliances.
  - *Revision.* The revision number for the PowerPack.
  - *Exported From.* If possible, displays the name and build ID of the version where the PowerPack was exported.
  - *Created.* Date and time the PowerPack was created.
  - *Updated.* Date and time the PowerPack was last edited.
  - *Compiled.* Date and time the PowerPack was last built.
- **Package Content.** This pane displays a list of content items contained in the PowerPack and the action that SL1 will perform for each content item when the PowerPack is installed.
  - *Content Item Name.* Name of the content item.
  - *Version.* Version number of the content item.
  - *GUID.* Unique identifier for the content item. This number is unique across all SL1 appliances in your system.

- *Action*. When you install a PowerPack, SL1 will perform one of the following actions for each content item included in the PowerPack:
  - *Install*. The content item is not currently installed on your SL1 system. When you install the PowerPack, SL1 will add the content item to your system.
  - *Update*. The PowerPack you are installing is currently installed in your SL1 system, and the content item is currently installed on your SL1 system and still included in the PowerPack you are installing. When you install the PowerPack, SL1 will replace the currently installed version of the content item with the new version of the content item. SL1 will preserve the relationship the content item has to other entities in your system. For example, if a Dynamic Application is updated during the installation of a PowerPack, the Dynamic Application will remain aligned to devices with the same credential alignments and device-specific threshold settings.
  - *Ignore*. The content item is currently installed on your SL1 system, but is not currently associated with the PowerPack you are installing in your SL1 system. This typically occurs when a user has removed the content item from the PowerPack in your SL1 system. When you install the PowerPack, SL1 will not modify the currently installed version of the content item nor add the new version of the content item to your SL1 system.
- **Installation Key**. The Installation Key for the PowerPack.
  - If the actions that SL1 will perform are acceptable, click the **[Install]** button to install the PowerPack.
  - The PowerPack will now appear in the **PowerPack Manager** page. All the items in the PowerPack will be automatically installed in your SL1 system.


7. If the actions that SL1 will perform are acceptable, click the **[Install]** button to install the PowerPack.
8. The PowerPack will now appear in the **PowerPack Manager** page. All the items in the PowerPack will be automatically installed in your SL1 system.

## Installing Multiple PowerPacks

To install multiple PowerPacks that have previously been imported to your SL1 system, perform the following steps:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. If you have not already done so, [import the PowerPack](#).
3. In the **PowerPack Manager** page, click the **[Actions]** menu and click *Install PowerPack*.

- The **Imported PowerPacks** modal page appears, displaying a list of PowerPacks that have already been imported. The list displays:





- **PowerPack Name**. Name of the PowerPack.
- **Flag**. Indicates if the PowerPack is a beta release.
- **Version**. Version of the PowerPack. This number is user-defined and manually incremented by the PowerPack author.
- **Revision**. The revision number for the PowerPack.
- **GUID**. Unique identifier for the PowerPack. This number is unique across all ScienceLogic appliances.
- **Last Edited**. Date and time the PowerPack was last imported or updated.
- **Imported**. Date and time the PowerPack was imported.
- **Lightning-bolt icon** (⚡). Click this icon to install a single PowerPack.
- **Checkbox** (). Click the checkbox and use the **Select Action** menu to install multiple PowerPacks simultaneously

- In the **Imported PowerPacks** modal page, click the checkbox for each PowerPack that you want to install. To select all checkboxes for all PowerPacks, click the checkbox () at the top of the page.
- In the **Select Action** drop-down list, click *Install PowerPacks*.
- Click the **[Go]** button.



8. The **PowerPack Installation** modal page appears and displays the status of the installation.




- To view details about each installed PowerPack or to enter an **Installation Key**, click the lightning-bolt icon (  ). The **Install PowerPack** modal page appears. You can exit this page without performing any actions, and the PowerPacks are still automatically installed on your system. For a description of the **Install PowerPack** modal page, see the section on [Installing a Single PowerPack](#).
- If the installation is successful, the selected PowerPacks are installed on your system.
- Each PowerPack will now appear in the **PowerPack Manager** page. All the items in each PowerPack will be automatically installed in your SL1 system.

## Checking the Status of Installed Content

To check on the status of the installed content after one or more PowerPacks are installed:

- To check the status of any installed Dynamic Applications, look for the Dynamic Applications in the **Dynamic Applications Manager** page (System > Manage > Applications).
- To check the status of any installed event policies, look for the event policies in the **Event Policy Manager** page (Registry > Events > Event Manager).
- To check the status of any installed device categories, look for device categories in the **Device Category Editor** page (System > Customize > Device Categories).
- To view any installed device classes, look for the device classes in the **Device Class Editor** page (System > Customize > Device Classes).

- To check the status of any installed device templates, look for the device template in the **Configuration Templates** page (Registry > Devices > Templates).
- To check the status of any installed device groups, look for the device groups in the **Device Groups** page (Registry > Devices > Device Groups).
- To view any installed custom reports, look for the report in the **Run Quick Report** page (Reports > Create Report > Quick Report), in the Run Quick Report drop-down list.
- To check the status of any installed custom dashboard widgets, look for the widgets in the **Dashboard Widgets** page (System > Customize > Dashboard Widgets).
- To check the status of any installed device dashboards, look for device dashboards in the **Device Dashboards** page (System > Customize > Device Dashboards).
- To check the status of any installed SL1 dashboards, look for dashboards in the **Dashboards** page (  ).
- To check the status of any installed custom run book policies, look for run book policies in the **Automation Policy Manager** page (Registry > Run Book > Automation).
- To check the status of any installed custom run book actions, look for run book actions in the **Action Policy Manager** page (Registry > Run Book > Actions).
- To check the status of any installed custom run book action types, look for run book action types in the **Action Type Manager** page (Registry > Run Book > Action Types).
- To view any installed custom ticket templates, look for ticket templates in the **Ticket Templates** page (Registry > Ticketing > Templates).
- To check the status of any installed credentials, look for credentials in the **Credential Management** page (System > Manage > Credentials).
- To check the status of any installed credential tests, look for credential tests in the **Credential Test Management** page (System > Customize > Credential Tests).
- To check the status of any installed Proxy XSL Transformation, look for Proxy XSL Transformation in the **Proxy XSL Transformations** page (Registry > Web Proxies > Proxy XSL Transformations).
- To view any installed UI Themes, look for Themes in the **Theme Management** page (System > Customize > Themes).
- To check the status of any installed IT service policies, look for IT service policies in the **IT Service Manager** page (Registry > IT Services > IT Service Manager).
- To check the status of any installed collection labels, look for collection labels in the **Collection Labels** page (System > Manage > Collection Labels).

**NOTE:** If there are any credentials that had specific organization alignments in the installed PowerPack, you will need to go to the **Credential Management** page (System > Manage > Credentials) to align the credentials to their appropriate organizations. To learn more about aligning credentials to an organization, see the *Discovery and Credentials* manual.

**NOTE:** SL1 will automatically disable the **Organization** field in all Device Templates in the installed PowerPack. To learn more about Device Templates, see the **Device Groups and Device Templates** manual.

**CAUTION:** When you delete a PowerPack, SL1 automatically deletes the associated content and all data associated with it from the SL1 system. For example, if a PowerPack includes a Dynamic Application, when you delete the PowerPack, the Dynamic Application is removed from SL1. If you go to the **Dynamic Applications Manager** page (System > Manage > Applications), that Dynamic Application will not appear. In addition, all data collected from all devices with that Dynamic Application will also be deleted. If you must delete a PowerPack but want to keep the installed content, you should first remove the content from the PowerPack. This is described in the section **Removing Content from a PowerPack**. To remove content from a PowerPack, you must either have administrator/owner privileges for the PowerPack, or you must be the creator of the PowerPack. For details on privileges associated with PowerPacks, see the chapter on **Creating a PowerPack**.

## Viewing the List of PowerPacks

The **PowerPack Manager** page (System > Manage > PowerPacks) displays the list of existing PowerPacks. The page includes all PowerPacks that you have imported, installed, or created via the user interface or the ScienceLogic API.

For each PowerPack, the **PowerPack Manager** page displays the following:

PowerPack™ Name	Version	Update	Publisher	Apps	Events	Classes	Reports	Widgets	Dashboards	Actions	Credits	Tckt Tol	DashSL1	Dev Tol	ID	Edited By	Last Edited
1. a simple DCM app	3	No	ScienceLogic, Inc.	4	1	1									168	em7admin	2019-07-25 18:15:22
2. Microsoft PowerPack Test Credit	1.7	No	ScienceLogic, Inc.								21				177	em7admin	2019-07-26 19:16:28
3. SNMP Dynamic Application Ref	1.0	No	ScienceLogic, Inc.	5										11	179	em7admin	2019-07-26 19:58:25
4. 2-level DCM app test	1.1	No	ScienceLogic, Inc.	4	1	2									188	em7admin	2019-07-31 13:21:32
5. 3Com Base Pack	1	No	ScienceLogic, Inc.			298									30	em7admin	2019-07-25 15:17:02
6. Alcatel-Lucent Base Pack	1	No	ScienceLogic, Inc.			33									130	em7admin	2019-07-25 15:18:45
7. Alteon Base Pack	1.3	No	ScienceLogic, Inc.	3	5	6									114	em7admin	2019-07-25 15:18:27
8. Amazon Web Services	113	No	ScienceLogic, Inc.	211	222	149	13		13	5	3				41	em7admin	2019-07-25 15:17:23
9. APC Base Pack	7.3.6	No	ScienceLogic, Inc.	9	27	30									48	em7admin	2019-07-25 15:17:32
10. Application Management Pack	1	No	ScienceLogic, Inc.		24										5	em7admin	2019-07-25 15:16:39
11. Arista Networks: Base	1.0	No	ScienceLogic, Inc.			85									120	em7admin	2019-07-25 15:18:35
12. Aruba Base Pack	1.1	No	ScienceLogic, Inc.	3											146	em7admin	2019-07-25 15:18:58
13. AskEM7 Query Widgets	7.2.3	No	ScienceLogic, Inc.					3							34	em7admin	2019-07-25 15:17:07
14. Attachmate Base Pack	1.1	No	ScienceLogic, Inc.			13									56	em7admin	2019-07-25 15:17:35
15. Avaya Base Pack	7.3.5	No	ScienceLogic, Inc.			43									92	em7admin	2019-07-25 15:17:58
16. Avocent ACS Pack	7.3.6	No	ScienceLogic, Inc.	4											147	em7admin	2019-07-25 15:18:58
17. Avocent Base Pack	1.1	No	ScienceLogic, Inc.	3		6									54	em7admin	2019-07-25 15:17:35
18. Blue Coat Base Pack	1.2	No	ScienceLogic, Inc.	1	2	10									165	em7admin	2019-07-25 15:19:31
19. BlueCat Base Pack	1.1	No	ScienceLogic, Inc.	2											29	em7admin	2019-07-25 15:17:01

- **PowerPack Name.** Name of the PowerPack.
- **Version.** Version of the PowerPack. This number is defined and manually incremented by the author of the PowerPack.
- **Update.** Indicates whether an updated version of the PowerPack has been loaded onto the system by a patch. Possible values are Yes or No. This column is displayed only if at least one updated PowerPack has been loaded onto the system and has not yet been installed.
- **Publisher.** User-defined value that specifies the author of a PowerPack. For example, PowerPacks from ScienceLogic will include the value "ScienceLogic" in this field.
- **Apps.** Number of Dynamic Applications in the PowerPack.
- **Events.** Number of event policies in the PowerPack.
- **Classes.** Number of device classes in the PowerPack.
- **Reports.** Number of custom reports in the PowerPack.
- **Widgets.** Number of dashboard widgets in the PowerPack.
- **Dashbds.** Number of dashboards in the PowerPack.
- **Actions.** Number of run book actions in the PowerPack.
- **Creds.** Number of credentials in the PowerPack.
- **Tckt Tpl.** Number of ticket templates in the PowerPack.
- **DashSL1.** Number of SL1 dashboards in the PowerPack.
- **Dev Tpl.** Number of device templates in the PowerPack.
- **ID.** Numeric ID for the PowerPack, generated by SL1.
- **Edited By.** User who created or last edited the PowerPack.
- **Last Edited.** Date and time the PowerPack was created or last edited.

---

## Filtering the List of PowerPacks

The **PowerPack Manager** page includes 17 filters (the column headings in the page). You can filter the list of PowerPacks by one or multiple of these parameters. Only PowerPacks that meet all the filter criteria will be displayed in the **PowerPack Manager** page.

You can filter by one or more of the following parameters. The list of PowerPacks is dynamically updated as you select each filter.

- For each filter except **Last Edited** and **Update**, you must enter text to match against. SL1 will search for PowerPacks that match the text, including partial matches. Text matches are not case-sensitive. You can use the following special characters in each filter:
  - , Specifies an "or" operation. For example:
 

"dell, micro" would match all values that contain the string "dell" OR the string "micro".
  - ! Specifies a "not" operation. For example:
 

"!dell" would match all values that do not contain the string "dell".

You can use the following filters in the **PowerPack Manager** page:

PowerPack™ Name	Version	Update	Publisher	Apps	Events	Classes	Reports	Widgets	Dashboards	Actions	Credits	Ticks	DashSL1	Dev.Tel	ID	Edited By	Last Edited
1. a simple DCM app	3	No	ScienceLogic, Inc.	4		1									169	em7admin	2019-07-25 18:15:22
2. Microsoft PowerPack Test Creds	1.7	No	ScienceLogic, Inc.								21				177	em7admin	2019-07-26 19:16:28
3. SNMP Dynamic Application Refactor CA-34 1.0		No	ScienceLogic, Inc.	5											179	em7admin	2019-07-26 19:56:25
4. 2-level DCM app test	1.1	No	ScienceLogic, Inc.	4	1		2								188	em7admin	2019-07-31 13:21:32
5. 3Com Base Pack	1	No	ScienceLogic, Inc.				298								30	em7admin	2019-07-25 15:17:02
6. Alcatel-Lucent Base Pack	1	No	ScienceLogic, Inc.				33								130	em7admin	2019-07-25 15:18:45
7. Alteon Base Pack	1.3	No	ScienceLogic, Inc.	3	5	6									114	em7admin	2019-07-25 15:18:27
8. Amazon Web Services	113	No	ScienceLogic, Inc.	211	222	149	13		13	5	3				41	em7admin	2019-07-25 15:17:23
9. APC Base Pack	7.3.6	No	ScienceLogic, Inc.	9	27	30									48	em7admin	2019-07-25 15:17:32
10. Application Management Pack	1	No	ScienceLogic, Inc.		24										5	em7admin	2019-07-25 15:16:39
11. Arista Networks Base	1.0	No	ScienceLogic, Inc.				65								120	em7admin	2019-07-25 15:18:35
12. Aruba Base Pack	1.1	No	ScienceLogic, Inc.	3											146	em7admin	2019-07-25 15:18:58
13. AskEM7 Query Widgets	7.2.3	No	ScienceLogic, Inc.						3						34	em7admin	2019-07-25 15:17:07
14. Attachmate Base Pack	1.1	No	ScienceLogic, Inc.				13								56	em7admin	2019-07-25 15:17:35
15. Avaya Base Pack	7.3.6	No	ScienceLogic, Inc.				43								92	em7admin	2019-07-25 15:17:58
16. Avocent ACS Base Pack	7.3.6	No	ScienceLogic, Inc.	4											147	em7admin	2019-07-25 15:18:58
17. Avocent Base Pack	1.1	No	ScienceLogic, Inc.	3			6								54	em7admin	2019-07-25 15:17:35
18. Blue Coat Base Pack	1.2	No	ScienceLogic, Inc.	1	2	10									165	em7admin	2019-07-25 15:19:31
19. BlueCat Base Pack	1.1	No	ScienceLogic, Inc.	2											29	em7admin	2019-07-25 15:17:01
20. Brocade Base Pack	7.3.6	No	ScienceLogic, Inc.	5	12	5									154	em7admin	2019-07-25 15:19:26

- **PowerPack Name.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching name.
- **Version.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching version number.
- **Update.** Only those PowerPacks that match all the previously selected fields and have the specified update status will be displayed. The choices are:
  - All. Display all PowerPacks that match the other filters.
  - Yes. Display only PowerPacks for which an updated version has been loaded on to the SL1 system and has not yet been installed.
  - No. Display only PowerPacks for which an updated version has not been loaded on to the SL1 system.
- **Publisher.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching publisher.

- **Apps.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching number of Dynamic Applications.
- **Events.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching number of event policies.
- **Classes.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching number of device classes.
- **Reports.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching number of reports.
- **Widgets.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching number of dashboard widgets.
- **Dashbds.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching number of dashboards.
- **Actions.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching number of Run Book Actions.
- **Creds.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching number of credentials.
- **Tckt Tpl.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching number of ticket templates.
- **DashSL1.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching number of SL1 dashboards.
- **Dev Tpls.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching number of device templates.
- **ID.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching ID.
- **Edited By.** You can enter text to match, including special characters, and the **PowerPack Manager** page will display only PowerPacks that have a matching username.
- **Last Edited.** Only those PowerPacks that match all the previously selected fields and have the specified "last edited" date will be displayed. The choices are:
  - *All.* Display all PowerPacks that match the other filters.
  - *Last Minute.* Display only PowerPacks that have been modified within the last minute.
  - *Last Hour.* Display only PowerPacks that have been modified within the last hour.
  - *Last Day.* Display only PowerPacks that have been modified within the last day.
  - *Last Week.* Display only PowerPacks that have been modified within the last week.
  - *Last Month.* Display only PowerPacks that have been modified within the last month.
  - *Last Year.* Display only PowerPacks that have been modified within the last year.

---

## Viewing Documentation for a PowerPack

The **PowerPack Documentation Files** page allows you to view and download a document in a PowerPack.

## Viewing a Document from the .em7pp File

If a PowerPack includes a document with a **Visibility** of *Public*, you can view that document before you import or install the PowerPack.


To view a document before you import or install a PowerPack:


1. Make sure the PowerPack file (ending in .em7pp) is available from your local computer.
2. Use an "unzip" utility to open the PowerPack file.
3. In the Documents directory, you can view all documents with a **Visibility** of *Public*.


## Downloading a Document

If you are the author of a PowerPack or if you have installed a PowerPack and have access to the **PowerPack Documentation Files** page, you can download all documents included in the PowerPack, regardless of the **Visibility** assigned to each document.

To download documents that are included in a PowerPack:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. Find the PowerPack that contains the documents you want to download. Click its wrench icon ()
3. In the PowerPack NavBar, go to **Manage PowerPack** and click **Documentation**. The **PowerPack Documentation Files** page appears.




- In the **PowerPack Documentation Files** page, find the document you want to download. Click its green floppy-disk icon (  ).
- You will be prompted to navigate to the path where you want to store the file.

## System Settings that Affect PowerPacks

The following setting in the **Behavior Settings** page affects the behavior of the SL1 system when you update or install PowerPacks.

To define or edit the setting that affects PowerPacks:

- Go to the **Behavior Settings** page (System > Settings > Behavior).



The screenshot shows the 'Behavior Settings' page with various configuration options. A red box highlights the 'Enable Selective PowerPack Field Protection' checkbox, which is currently unchecked. Other settings include 'Interface URL' (http://em7.mydomain.com), 'Password Expiration' (disabled), 'SNMP Poll Timeout' (1000), and 'Event Console Ticket Life Ring Button Behavior' (Create / View EM7 Ticket).

- In the **Behavior Settings** page, edit the following:

- **Enable Selective PowerPack Field Protection**. This field is disabled by default. If you select this field, when you update a PowerPack, the **following fields will not be updated**:
  - Event Policy > Operational State
  - Event Policy > Event Severity
  - Event Policy > Event Message
  - Event Policy > Occurrence Count



- Event Policy > Occurrence Time
- Event Policy > Expiry Delay
- Event Policy > Detection Weight
- Event Policy > External Event ID
- Event Policy > External Category
- Event Policy > Use multi-match
- Event Policy > Use message-match
- Event Policy > Topology Suppression
- Dynamic Application > Properties > Operational State
- Dynamic Application > Properties > Poll Frequency
- Dynamic Application > Properties > Disable Data Rollup
- Dynamic Application > Collection > Custom Attribute
- Dynamic Application > Collection > Asset / Formlink
- Dynamic Application > Collection > Change Alerting
- Dynamic Application > Collection > Hide Object
- Dynamic Application > Presentation > Active State
- Dynamic Application > Threshold > Override Threshold Value
- Dynamic Application > Threshold > Numeric Range: High
- Dynamic Application > Threshold > Numeric Range: Low
- Dynamic Application > Threshold > Threshold Value
- Device Class > Device Dashboard

3. Click the **[Save]** button to save your changes.

---

# Chapter

# 3



## Creating a PowerPack

---

### Overview

This chapter will describe how to create a PowerPack, add content to a PowerPack, how to add intellectual property protection to content in a PowerPack, generate a license key for a PowerPack, and how to export a PowerPack.

Use the following menu options to navigate the SL1 user interface:

- To view a pop-out list of menu options, click the menu icon ().
- To view a page containing all of the menu options, click the Advanced menu icon ().

This chapter includes the following topics:

<b>Caveats</b> .....	<b>27</b>
<b>Creating a PowerPack</b> .....	<b>28</b>
<b>Creating a Container for a PowerPack</b> .....	<b>28</b>
<b>Adding Content to a PowerPack</b> .....	<b>30</b>
<b>Adding Documentation to a PowerPack</b> .....	<b>35</b>
<i>Adding a Documentation File to a PowerPack</i> .....	35
<i>Changing Visibility</i> .....	35
<i>Deleting a Document</i> .....	36
<b>Including Details on a PowerPack's Features, Benefits, and Technical Information</b> .....	<b>37</b>
<i>Features/Benefits</i> .....	37
<i>Technical Notes</i> .....	38
<b>Adding Intellectual Property Protection to Content in a PowerPack</b> .....	<b>39</b>

<b>Determining the PowerPack's Execution Environments</b> .....	<b>40</b>
<b>Building the PowerPack and Generating a License Key</b> .....	<b>41</b>
Building a PowerPack .....	41
Generating an Embedded License Key During the Initial Build .....	42
Generating an Unembedded License During the Initial Build .....	46
<b>Export Rules, Import Rules, and Substitutions</b> .....	<b>50</b>
Event Policies .....	50
Dynamic Applications .....	50
Dashboards .....	50
Run Book Actions .....	51
Run Book Policies .....	52
Credentials .....	53
Credential Tests .....	53
Ticket Templates .....	53
Device Templates .....	54
Device Groups .....	54
IT Service Policies .....	54
<b>Exporting a PowerPack</b> .....	<b>55</b>
<b>Generating an Embedded License Key After the Initial Build</b> .....	<b>57</b>
<b>Generating an Unembedded License Key After the Initial Build</b> .....	<b>58</b>

---

## Caveats

If you have content (Dynamic Applications, event policies, device classes, device templates, custom reports, custom dashboard widgets, dashboards, custom run book policies, custom run book actions, custom ticket templates, credentials, proxy XSL transformations, themes, device categories, device dashboards, collection labels, or IT services) that you must install on another SL1 system, you can create a PowerPack for that content. However, you must be aware of the following caveats:

- Content can be included in only a single PowerPack. For example, if you include the Dynamic Application "Cisco: Summary Statistics" in the PowerPack "networking\_powerpack", you cannot include that Dynamic Application in another PowerPack.
- When you delete a PowerPack, SL1 automatically deletes the associated content from the SL1 system and all data associated with it. For example, if a PowerPack includes a Dynamic Application, when you delete the PowerPack, the Dynamic Application is removed from SL1. If you go to the **Dynamic Applications Manager** page (System > Manage > Applications), that Dynamic Application will not appear. In addition, all data collected from all devices with that Dynamic Application will also be deleted.

- If you must delete a PowerPack but want to keep the installed content, you should first remove the content from the PowerPack. This is described in the section [Removing Content from a PowerPack](#). To remove content from a PowerPack, you must either have administrator/owner privileges for the PowerPack or you must be the creator of the PowerPack. For details on privileges associated with PowerPacks, see the [section on privileges](#).
- If you want to include content in a second PowerPack, you must first remove the content from the first PowerPack. This is described in the section [Removing Content from a PowerPack](#). To remove content from a PowerPack, you must either have administrator/owner privileges for the PowerPack or you must be the creator of the PowerPack. For details on privileges associated with PowerPacks, see the [section on privileges](#).
- If you include organization-specific credentials in a PowerPack, the organization alignment for those credentials is not preserved by that organization when the PowerPack is installed in another SL1 system. The credentials in a PowerPack will not be organization-specific in another SL1 system.
- If a PowerPack specifies that a minimum version of SL1 is required for installation, you will receive an error message if you are running an earlier version of SL1 and attempt to install the PowerPack.

---

## Creating a PowerPack

To create a PowerPack, you must perform the following steps:

- In the **PowerPack Properties** page, create a container for the PowerPack.
- In the **Embedded/Available** page, add content to the PowerPack.
- Optionally, add documentation to the PowerPack.
- In the **Compiled PowerPacks / Generate Installation Key** page, build the PowerPack, grant privileges, and generate a license key.

These steps are described in the following sections.

**NOTE:** The following sections describe how to create PowerPacks using the user interface. In addition to the user interface, PowerPacks can also be created via the ScienceLogic API. PowerPacks created via the user interface will appear in the ScienceLogic API and vice versa. For information about creating PowerPacks via the ScienceLogic API, see the manual *Using the ScienceLogic API*.

---

## Creating a Container for a PowerPack

To create a PowerPack, you must first define the basic properties and create the container. To do this:

1. Log in to SL1.
2. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).

- In the **PowerPack Manager** page, click the **[Actions]** button. Click *Create New PowerPack*. The **PowerPack Properties** page appears.

- In the **PowerPack Properties** page, supply values in each field.

- **Name**. Name of the PowerPack.
- **Version**. Version number for the PowerPack. You can enter any combination of characters in this field. You must manually update this field to change the version number.
- **Publisher**. User-defined value that specifies the author of a PowerPack. For example, PowerPacks from ScienceLogic will include the value "ScienceLogic" in this field.

**NOTE:** The **Publisher** field can be edited only on the system where the PowerPack was created and only by accounts with the appropriate Access Keys.

- **License Key**. The license key for the PowerPack. This key identifies the PowerPack and the author to SL1 and is updated each time you make a change to the PowerPack. The License Key confers owner privileges and allows you to import, edit properties and content, build, generate an install key, and export the PowerPack.

**NOTE:** Best practice is to safeguard the License Key for use only by the PowerPack creator and to generate Install Keys for other users of the PowerPack.

- **Creation**. Read-only field. SL1 automatically supplies the date and time the PowerPack was created.
- **Modification**. Read-only field. SL1 automatically supplies the date and time the PowerPack was last modified.
- **Revision**. Read-only field. SL1 automatically supplies the number of revisions to the PowerPack.

**NOTE:** When you save the values in the **PowerPack Properties** page, SL1 assigns the revision number "1" (one) to the PowerPack. When you add content and build the PowerPack (and optionally define privileges), SL1 assigns the revision number "2" (two) to the PowerPack. A PowerPack that contains content will have a revision number of "2" (two) or greater.


- **ID**. Read-only field. SL1 automatically supplies a numeric ID for the PowerPack. This numeric ID uniquely identifies the PowerPack on the current system.
- **Description**. Enter a detailed description of the PowerPack and its content.
- **Vendor(s) Supported**. Specify the vendor associated with the content in the PowerPack. For example, if a PowerPack includes the Dynamic Applications that monitor VMware devices, you could enter "VMware" in this field."
- **Model(s) Supported**. Specify the hardware or software model associated with the content in the PowerPack. For example, if a PowerPack includes Dynamic Applications that monitor Cisco Catalyst switches, you could specify "Catalyst 2950 and Catalyst 2960" in this field.
- **Version(s) Supported**. Specify the version of the hardware or software associated with the content in the PowerPack. For example, if a PowerPack includes Dynamic Applications that monitor Cisco CUCM, you could specify "Version 7 and Version 8" in this field.
- **Minimum EM7 Version**. Specify the earliest version of SL1 required by the PowerPack. If users try to install the PowerPack on earlier versions of SL1, an error message will appear.
  - You can enter any combination of numbers and periods. For example, you could enter "7.6.0".
  - If you leave this field blank, users can install the PowerPack on all versions of SL1.
- **Release Notes and Change Log**. Include any detailed release notes or record of changes to the PowerPack. The editor allows you to format the text and include links and images in the text. You can also use a document template to apply a standard format to the text.

5. Click the **[Save]** button to save the PowerPack and any changes you have made.

---

## Adding Content to a PowerPack

After you have saved the values in the **PowerPack Properties** page you can add content from the menu on the left. From this menu, you can start to add content to the PowerPack. To add content to the PowerPack, perform the following steps:

1. If you do not already have the PowerPack open, go to the **PowerPack Manager** page (System > Manage > PowerPacks). Find the PowerPack you want to add content to. Click its wrench icon ().

- From the **PowerPack Properties** page, select the type of content you want to add in the Navbar on the left side of the page.

- In the Navbar panel on the left side of the page, you can select from the following options:

**NOTE:** The entries under the **Contents** link are dependent upon your Access Hooks. An entry appears only if you have been granted an Access Key that contains the Access Hook that allows you to view the content-type in SL1. For example, the **Dynamic Applications** entry will appear under the **Contents** link only if you have permission to view the list of Dynamic Applications in the **Dynamic Applications Manager** page (System > Manage > Applications) in SL1.

- Dynamic Applications.** Displays the **Embedded/Available** page, where you can view a list of Dynamic Applications that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- Event Policies.** Displays the **Embedded/Available** page, where you can view a list of event policies that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).

**NOTE:** Event policies associated with Dynamic Application alerts do not appear in the **Available** pane, and cannot be explicitly added to a PowerPack. When a Dynamic Application is added to a PowerPack, any event policies associated with the Dynamic Application are automatically added to the PowerPack. Automatically added event policies will appear in the **Embedded** pane when Event Policies is selected in the NavBar.

**NOTE:** If an event policy is included in a PowerPack and has the **Use Modifier** checkbox selected, when the event policy is installed on another SL1 system, the event policy will have the **Use Modifier** checkbox selected.

- **Device Categories.** Displays the **Embedded/Available** page, where you can view a list of device categories that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **Device Classes.** Displays the **Embedded/Available** page, where you can view a list of device classes that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **Device Templates.** Displays the **Embedded/Available** page, where you can view a list of device templates that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **Device Groups.** Displays the **Embedded/Available** page, where you can view a list of dynamic device groups that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **Reports.** Displays the **Embedded/Available** page, where you can view a list of reports that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **Dashboard Widgets.** Displays the **Embedded/Available** page, where you can view a list of dashboard-widgets that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **Dashboards.** Displays the **Embedded/Available** page, where you can view a list of dashboards and device dashboards that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **Dashboards SL1.** Displays the **Embedded/Available** page, where you can view a list of SL1 dashboards that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **Run Book Policies.** Displays the **Embedded/Available** page, where you can view a list of Run Book Automation policies that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).

**NOTE:** If you include a Run Book Automation policy that executes one or more Run Book Action policies, you must also include those Run Book Action policies with the PowerPack.



- **Run Book Actions.** Displays the **Embedded/Available** page, where you can view a list of available run book actions that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **Run Book Action Types.** Displays the **Embedded/Available** page, where you can view a list of available run book action types that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **Ticket Templates.** Displays the **Embedded/Available** page, where you can view a list of Ticket Templates that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **Credentials.** Displays the **Embedded/Available** page, where you can view a list of Credentials that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **Credential Tests.** Displays the **Embedded/Available** page, where you can view a list of credential tests that can be removed from or added to a PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **Proxy XSL Transformations.** Displays the **Embedded/Available** page, where you can view a list of Proxy XSL Transformations that can be removed from and added to a PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **UI Themes.** Displays the **Embedded/Available** page, where you can view a list of UI Themes that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **IT Services.** Displays the **Embedded/Available** page, where you can view a list of IT Service policies that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **Log File Monitoring Policies.** Displays the **Embedded/Available** page, where you can view a list of log file monitoring policies that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣).
- **AP Content Objects.** Displays the **Embedded/Available** page, where you can view a list of AP content objects that can be removed from and added to the PowerPack. To add, click the lightning bolt icon (⚡). To remove, click the bomb icon (💣). AP Content Objects are features, modules, and updates for the ScienceLogic new user-interface.

**NOTE:** A Dynamic Application, event policy, device category, device class, device template, device group, custom report, dashboard widget, dashboard, run book policy, run book action, run book action type, ticket template, credential, credential test, proxy XSL transformation, theme, IT service, log file monitoring policy, or AP content object can be included in only one PowerPack. For example, a Dynamic Application cannot be included in three different PowerPacks. If you want to include content in a second PowerPack, you must remove it from its original PowerPack.

4. The display in the **Embedded/Available** modal page depends on your selection from the NavBar pane:

The screenshot shows the 'Editing PowerPack™ Amazon Web Services' interface. On the left is a navigation pane with categories like 'Manage PowerPack™', 'Properties', 'Build / Export', 'Features / Benefits', 'Technical Notes', 'Documentation', 'Contents', 'Dynamic Applications', 'Event Policies', 'Device Categories', 'Device Classes', 'Device Templates', 'Device Groups', 'Reports', 'Dashboard Widgets', 'Dashboards', 'Dashboards SL1', 'Run Book Policies', 'Run Book Actions', 'Run Book Action Types', 'Ticket Templates', 'Credentials', 'Credential Tests', 'Proxy XSL Transformations', 'UI Themes', 'IT Services', 'Log File Monitoring Policies', and 'AP Content Objects'. The main area is split into two panes. The top pane, 'Embedded Dynamic Applications [211]', contains a table with columns: Dynamic Application Name, IPP, Poll Rate, Type, Version, Collects, Alerts, Events, Thresh., ID, Edited By, and Last Edit. It lists 10 items, all with 'disabled' IPP and various configurations. The bottom pane, 'Available Dynamic Applications [1]', contains a single item: 'test blank item (IT Service)' with a 1 min poll rate and version 1.1. A lightning bolt icon is visible next to this item.

Dynamic Application Name	IPP	Poll Rate	Type	Version	Collects	Alerts	Events	Thresh.	ID	Edited By	Last Edit
1. AWS Account Discovery	disabled	5 min	Snippet Configuration	1.1	7	--	--	--	540	em7admin	2019-07-25 11:17:24
2. AWS API Gateway Service Con	disabled	5 min	Snippet Configuration	1.1	15	--	--	--	682	em7admin	2019-07-25 11:17:27
3. AWS API Gateway Service Dis	disabled	15 min	Snippet Configuration	1.1	5	--	--	--	674	em7admin	2019-07-25 11:17:26
4. AWS API Gateway Service Hea	disabled	60 min	Snippet Journal	1.2	2	--	--	--	681	em7admin	2019-07-25 11:17:27
5. AWS API Instance Configuratio	disabled	60 min	Bulk Snippet Configura	1.2	9	--	--	--	679	em7admin	2019-07-25 11:17:26
6. AWS API Instance Discovery	disabled	15 min	Snippet Configuration	1.1	5	--	--	--	675	em7admin	2019-07-25 11:17:26
7. AWS API Instance Performanc	disabled	5 min	Bulk Snippet Performa	1.1	7	10	10	15	680	em7admin	2019-07-25 11:17:26
8. AWS API Stage Instance Confi	disabled	60 min	Bulk Snippet Configura	1.2	21	--	--	--	677	em7admin	2019-07-25 11:17:26
9. AWS API Stage Instance Disco	disabled	15 min	Snippet Configuration	1.1	5	--	--	--	676	em7admin	2019-07-25 11:17:26
10. AWS API Stage Instance Perfo	disabled	5 min	Bulk Snippet Performa	1.1	7	10	10	15	678	em7admin	2019-07-25 11:17:26


Dynamic Application Name	Poll Rate	Type	Version	Collects	Alerts	Events	Thresh.	ID	Edited By	Last Edit
1. test blank item (IT Service)	1 min	--	1.1	1	--	--	--	1946	em7admin	2019-07-30 10:42:19

- **To add content**, go to the **Available** pane at the bottom of the page. Find the content you want to include in the PowerPack. Click the lightning bolt icon (⚡) for that content. The content will be moved to the top pane.

**NOTE:** The **Available** pane contains only content that is not included in any other PowerPack. If a Dynamic Application, event policy, device category, device class, device template, device group, custom report, dashboard widget, dashboard, run book policy, run book action, run book action type, ticket template, credential, credential test, proxy XSL transformation, theme, IT service, log file monitoring policy, or AP content object is included in another PowerPack, it will not appear in the **Available** pane.

**NOTE:** If you include a Dynamic Application that has aligned event policies (i.e., one or more events that are triggered with an alert from the Dynamic Application), SL1 will automatically include the corresponding event policies in the PowerPack. **Note that you cannot manually add an event with the source of "dynamic";** SL1 automatically includes these events when you add the aligned Dynamic Applications to the PowerPack.

**NOTE:** If you want to include an event that is aligned with an "auto-clear" event, SL1 requires that you include both events in the PowerPack. SL1 will not allow you to add such an event without also adding its aligned "auto-clear" event.

- **To remove content**, go to the **Embedded** pane at the top of the page. Find the content you want to remove from the PowerPack. Click the bomb icon () for that content. The content will be removed from the PowerPack and will now appear in the bottom pane.

---

## Adding Documentation to a PowerPack

The **PowerPack Documentation Files** page allows you to include a document in a PowerPack, download a document from a PowerPack, and delete a document from a PowerPack.


### Adding a Documentation File to a PowerPack


To add a documentation file to a PowerPack:

1. In the left pane, go to **Manage PowerPack** and click **Documentation**.
2. In the **PowerPack Documentation Files** page, click the **[Upload]** button.
3. In the **Document Import** modal page, navigate to the document you want to add to the PowerPack. Click the **[Import]** button to add the document to the PowerPack.
4. The document appears in the top pane of the **PowerPack Documentation Files** page.
5. The document will be saved with the PowerPack and its contents.

### Changing Visibility

After you have added a documentation file to a PowerPack, you can set its **Visibility**.

To change the Visibility, click on the lock icon () in the **Visibility** column. You can toggle between *Private* and *Public*.




- **Private.** Document can be viewed and accessed only from the **PowerPack Documentation Files** page. This means that users other than the author of the PowerPack must install the PowerPack to view the document.
- **Public.** Document is included in the export file for the PowerPack and can be accessed by opening the PowerPack file with a "zip" utility. Users do not need to install the PowerPack to view the document.


## Deleting a Document


If you are the author of a PowerPack or if you have installed a PowerPack and have access to the **PowerPack Documentation Files** page, you can delete one or more documents from the PowerPack, regardless of the **Visibility** assigned to each document.

To delete a document from a PowerPack:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).

2. Find the PowerPack that contains the document(s) you want to delete. Click its wrench icon ()



3. In the PowerPack, go to the NavBar, go to **Manage PowerPack** and click **Documentation**.
4. In the **PowerPack Documentation Files** page, find the document you want to delete. Click its bomb icon ()
5. The document will be deleted from the PowerPack.

---

## Including Details on a PowerPack's Features, Benefits, and Technical Information


You can optionally add additional information about a PowerPack's content in the **Features/Benefits** page and the **Technical Notes** page.

### Features/Benefits

The **Features/Benefits** page allows you to add details on the features and benefits of the PowerPack content.

The editor allows you to format the text and include links and images in the text.

You can also use a document template to apply a standard format to the text.




## Technical Notes

The **Technical Notes** page allows you to add technical information about the PowerPack and its content.

The editor allows you to format the text and include links and images in the text.

You can also use a document template to apply a standard format to the text.




---


## Adding Intellectual Property Protection to Content in a PowerPack


After adding content to a PowerPack, you can add **Intellectual Property Protection** to included Dynamic Applications and event policies. Intellectual Properties Protection, or IPP, prevents other users from editing or viewing information on Dynamic Applications on any SL1 system except the original system where the Dynamic Application was created.











- **When you enable Intellectual Property Protection for a Dynamic Application**, users are prevented from viewing and editing advanced implementation details about the Dynamic Application on any SL1 system, except the original system where the Dynamic Application was created. After installation on another SL1 system (other than the author system), users cannot disable the Intellectual Property Protection feature and can view and edit only the **[Properties]**, **[Policies]**, and **[Subscribers]** tab of the Dynamic Application (within the PowerPack or in the **Dynamic Applications Manager** page). Even if the PowerPack is installed with the License Key or with an Install Key that grants Administrator/Owner privileges, users will not be able to access all tabs for the Dynamic Application. When Intellectual Property Protection is enabled, the following tabs will not be displayed for the Dynamic Application:
  - **[Collections]**
  - **[Presentation]**
  - **[Thresholds]**
  - **[Snippets]** (for Dynamic Applications of type "snippet")
  - **[Requests]** (for Dynamic Applications of type "SOAP", "XSLT", and "WMI")
  - **[Alerts]**
- **When you add Intellectual Property Protection to an event policy**, users are prevented from viewing and editing advanced implementation details about the event policy on any SL1 system, except the original system where the event policy was created. After installation on another SL1 system (other than the author system), users cannot disable the Intellectual Property Protection feature and can edit only the **[Policy]** and **[Suppressions]** tab of the event policy application (within the PowerPack or in the **Event Policy Manager** page). Even if the PowerPack is installed with the License Key or with an Install Key that grants Administrator/Owner privileges, users will not be able to access all of the tabs for the event policy. When Intellectual Property Protection is enabled, the following tab and information will not be displayed for the event policy:
  - **[Advanced]**
  - The **[Save As]** button will not appear on any tab.

**To add Intellectual Property Protection to a Dynamic Application or an event policy:**











1. If you do not already have the PowerPack open, go to the **PowerPack Manager** page (System > Manage > PowerPacks). Find the PowerPack you want to add content to. Click its wrench icon ()

- From the **PowerPack Properties** page, select from the applicable options in the navigation panel to the left.
- Select the entry for the content to which you want to add Intellectual Property Protection:
  - Manage Dynamic Applications.** Displays the **Embedded/Available** page for Dynamic Applications, where you can view a list of Dynamic Applications that are already in the PowerPack and a list of Dynamic Applications that can be added to the PowerPack.
  - Manage Event Policies.** Displays the **Embedded/Available** page for event policies, where you can view a list of event policies that are already in the PowerPack and a list of event policies that can be added to the PowerPack.
- To view the **Embedded/Available** page for a type of content, go to the **Embedded** pane at the top of the page, find the content you want to protect, and click on the lock icon (  ). If the IPP column contains the value "enabled", the Dynamic Application or event policy is protected:



Editing PowerPack™ Cisco: Base Pack												
Embedded Dynamic Applications [13]												
Dynamic Application Name	IPP	Poll Rate	Type	Version	Collects	Alerts	Events	Thresh.	ID	Edited By	Last Edit	
1. Cisco: BGP Peer	enabled	5 min.	Snippet Performance	1.6	11	--	--	--	839	em7admin	2018-04-04 22:00:19	
2. Cisco: BGP Peer	disabled	5 min.	Snippet Configuration	1.1	13	2	2	--	840	em7admin	2018-04-04 22:00:19	
3. Cisco: CPU	disabled	5 min.	Snippet Performance	2.2	3	2	2	1	831	em7admin	2018-04-04 22:00:16	
4. Cisco: Environm	disabled	30 min.	SNMP Configuration	1.4	10	9	9	--	832	em7admin	2018-04-04 22:00:17	
5. Cisco: Fibre Chs	disabled	60 min.	Snippet Configuration	1	18	--	--	--	841	em7admin	2018-04-04 22:00:19	
6. Cisco: Fibre Chs	disabled	5 min.	SNMP Performance	1	57	--	--	--	842	em7admin	2018-04-04 22:00:19	
7. Cisco: FRU Con	disabled	5 min.	Snippet Configuration	1.4	23	6	6	--	836	em7admin	2018-04-04 22:00:18	
8. Cisco: Interface	disabled	15 min.	SNMP Performance	1	8	--	--	--	838	em7admin	2018-04-04 22:00:19	
9. Cisco: Old Interf	disabled	15 min.	SNMP Performance	1	12	--	--	--	837	em7admin	2018-04-04 22:00:18	
10. Cisco: Physical I	disabled	5 min.	Snippet Performance	2.2	10	4	4	1	830	em7admin	2018-04-04 22:00:16	

Available Dynamic Applications [11]												
Dynamic Application Name	Poll Rate	Type	Version	Collects	Alerts	Events	Thresh.	ID	Edited By	Last Edit		
1. SAC Scheduler Test (IT Servic	15 min.	--	1.1	1	--	--	--	1495	em7admin	2018-04-13 01:06:58		
2. SAC Scheduler Test (IT Servic	15 min.	--	1.1	1	--	--	--	1519	em7admin	2018-04-18 20:48:36		
3. SAC Scheduler Test (IT Servic	15 min.	--	1.1	1	--	--	--	1518	em7admin	2018-04-18 00:39:40		
4. SAC Scheduler Test (IT Servic	15 min.	--	1.1	1	--	--	--	1516	em7admin	2018-04-17 23:01:17		
5. SAC Scheduler Test (IT Servic	15 min.	--	1.1	1	--	--	--	1515	em7admin	2018-04-17 22:14:53		
6. SAC Scheduler Test (IT Servic	15 min.	--	1.1	1	--	--	--	1514	em7admin	2018-04-17 21:52:47		
7. SAC Scheduler Test (IT Servic	15 min.	--	1.1	1	--	--	--	1513	em7admin	2018-04-17 21:35:54		
8. SAC Scheduler Test (IT Servic	15 min.	--	1.1	1	--	--	--	1497	em7admin	2018-04-13 17:10:26		
9. SAC_Sanity_ITSM_Test (IT Se	1 min.	--	1.1	6	1	1	--	1546	em7admin	2018-04-20 23:15:41		
10. SAC_Streaming_Rollups ITS	1 min.	--	1.1	1	--	--	--	1560	em7admin	2018-04-22 22:56:55		

## Determining the PowerPack's Execution Environments

When you build a PowerPack, it includes the execution environments that are aligned with the PowerPack's Dynamic Applications, Credential Tests, and Run Book Actions that execute snippets.

An **execution environment** is an on-demand Python environment that includes the supporting modules, code, scripts, directories, and files (packaged in one or more ScienceLogic Libraries) needed to run a snippet. An execution environment includes its own installation directories, doesn't share libraries with other environments, and allows granular control of dependencies and versions.

To determine which execution environments are included in a PowerPack:



1. Go to the **Dynamic Applications Manager** page (System > Manage > Applications).
2. In the **PowerPack** filter-while-you-type field, type the name of the PowerPack. This filters the list so only the Dynamic Applications from the specified PowerPack appear.
3. The Environment column displays the execution environment aligned with each Dynamic Application included in the PowerPack.

---

## Building the PowerPack and Generating a License Key

After you have added content to a PowerPack you must build the PowerPack (to generate a single file that contains all the associated content), select the permissions to associate with a license key for the PowerPack, and generate a license key for the PowerPack.

A license key allows a user to install a PowerPack on a SL1 system. A license key used to install a PowerPack also determines the actions that can be performed on the PowerPack and its contents. You can embed a license key in the PowerPack, so the user will not need to enter a license key upon importing the PowerPack. If you do not embed a license key, you will need to provide a license key to the user that must be entered when they import the PowerPack.

You are not limited to one license key per PowerPack. You can generate multiple license keys for a single PowerPack. You are not required to rebuild a PowerPack each time you generate a new license key.

- For example, during initial build of a PowerPack, you could generate and embed a license key with "Install & Use Only" privileges. You could then export the PowerPack and distribute the PowerPack to a customer. When the customer imports and installs the PowerPack, the customer does not have to enter a license key and will be given "Install & Use Only" privileges.
- For the same PowerPack, you could generate an administrator-level license key that you copy and paste in a file. You could then distribute the same PowerPack file you distribute to customers to a system administrator in your organization. The system administrator can then use the administrator-level license key from the text file instead of the embedded license key.


Note that the last generated license key is the one that will be displayed in the **Compiled PowerPacks / Generate Installation Key** modal page, either in the **Embedded License Key** column in the top pane or in the **Generated Install Key** field in the bottom pane.

## Building a PowerPack

To build a PowerPack:

1. If you have not already, go to the **PowerPack Manager** page (System > Manage > PowerPacks) and either create a PowerPack or edit an existing PowerPack.


- Expand the Manage PowerPack entry in the left NavBar and click **Build/Export**.



- If this is a new PowerPack or if you have made a change to the PowerPack, you will see a link telling you to *Create a new build*.
- To build the PowerPack, click on the link.

## Generating an Embedded License Key During the Initial Build

- During the initial build, after you select the *Create a new build* link in the **Compiled PowerPacks / Generate Installation Key** modal page, the **Configure Export File** modal page appears.



2. The **Configure Export File** modal page allows you to embed a license key within the PowerPack. When you embed the license key in the PowerPack, the user who imports and installs the PowerPack does not have to enter a license key.
  - If you want to embed a license key in the PowerPack, enter a value in each field.
  - If you do not want to embed a license key in the PowerPack, exit the **Configure Export File** page. You must manually generate a license key in the bottom pane of the **Compiled PowerPacks / Generate Installation Key** modal page.
  
3. To embed a license key, enter the following in the **Configure Export File** modal page:
  - **Embedded license key.** Displays a drop-down list of options that allow you to select whether to want to embed the license key in the PowerPack, and if so, how you would like the embedded key to function. Choices are:
    - *None.* The license key will not be embedded in the PowerPack. You must manually generate the license key and then copy and paste the license key in a text file. The user who imports and installs the PowerPack must enter the license key during installation.
    - *Install & Use Only.* The license key will be embedded. Users will be allowed to install this PowerPack on another SL1 system (other than the author system). In the **PowerPack Properties** page for the PowerPack, users will be allowed to edit only the name and version number of the PowerPack. Users will not be allowed to edit any of the installed content, either from within the PowerPack or in SL1.
    - *Administrative (including export & license).* The license key will be embedded. After installation on another SL1 system (other than the author system), users will be allowed to edit each of the installed items from this PowerPack. Users can edit the content from within the PowerPack and in SL1. Users will also be allowed to edit the properties of the PowerPack, delete content from the PowerPack, export the PowerPack, and generate a license key for the PowerPack.
    - *Manage Content Items of Selected Types.* The license key will be embedded. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed content type, from the associated page in the user interface. In the **PowerPack Properties** page for the PowerPack, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
  - **Available Types/Selected Types.** The entries in these fields become active if you clicked *Manage Content Items of Selected Types* in the **Embedded license key** field.
    - **To select a content option**, in the *Available Types* field, highlight the option and click the right arrow button. The option will now appear in the **Selected Types** pane and will be included in the license key. Repeat these steps for each content type you want to include in the license key.
    - **To remove a content option**, in the *Selected Types* field, highlight the option and click the left arrow button. The option will now appear in the **Available Types** pane and will not be included in the license key. Repeat these steps for each content type you want to removed from the license key.

The content types are:

- *Dynamic Applications*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed Dynamic Applications from the **Dynamic Applications Manager** page (System > Manage > Applications). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Event Policies*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed event policies from the **Event Policy Manager** page (Registry > Events > Event Manager). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

**NOTE:** If the PowerPack contains one or more Dynamic Applications or event policies that use Intellectual Property Protection, users will not be able to edit the Dynamic Applications or event policies when they are installed on another server, even if the PowerPack includes Administrator/Owner privileges.

- *Device Categories*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed device categories from the **Device Category Editor** page (System > Customize > Device Categories). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Device Classes*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed device classes from the **Device Class Editor** page (System > Customize > Device Classes). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Device Templates*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed device templates from the **Configuration Templates** page (Registry > Devices > Templates). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Reports*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed report from the **[Reports]** tab. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Dashboard Widgets*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed widget from the **Dashboard Widgets** page (System > Customize > Dashboard Widgets). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Dashboards*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed dashboards from the **Dashboards tab** page. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

- *Run Book Policies*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed Run Book policies from the **Automation Policy Manager** page (Registry > Run Book > Automation). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Run Book Actions*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed Run Book actions from the **Action Policy Manager** page (Registry > Run Book > Actions). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Run Book Action Types*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed Run Book Action Types from the **Action Type Manager** page (Registry > Run Book > Action Types). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Ticket Templates*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed ticket templates from the **Ticket Templates** page (Registry > Ticketing > Templates). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Credentials*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed credentials from the **Credential Management** page (System > Manage > Credentials). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

**NOTE:** If you include organization-specific credentials in a PowerPack, the credentials cannot be preserved by that organization when the PowerPack is installed on another environment. The credentials in a PowerPack are the responsibility of the customer, and cannot be guaranteed to be organization-specific in another SL1 system.

- *Credential Tests*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed credential tests from the **Credential Test Management** page (System > Customize > Credential Tests). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Proxy XSL Transformations*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed transformations from the **Proxy XSL Transformations** page (Registry > Web Proxies > Proxy XSL Transformations). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *UI Themes*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed themes from the **Theme Management** page (System > Customize > Themes). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

- *IT Services*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed IT Service policies from the **IT Service Manager** page (Registry > IT Services > IT Service Manager). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
  - *Log File Monitoring Policies*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed log file monitoring policies from the **Log File Monitoring Policies** page (System > Manage > Log File Monitoring Policies). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
4. Click the **[Build]** button, and then click the **[Save]** button to save the embedded license. Notice that the *Embedded License* field in the top pane of the **Compiled PowerPacks / Generate Installation Key** page now matches the newly generated license.

## Generating an Unembedded License During the Initial Build

If you did not embed a license key during the initial build of a PowerPack, you must generate a separate license key to install the PowerPack on other SL1 systems. After selecting *None* in the **Configure Export File** modal page, perform the following steps to generate an unembedded license key:

1. In the bottom pane of the **Compiled PowerPacks / Generate Installation Key** page, select the values in the following fields:

The screenshot shows the 'Compiled PowerPacks' section with a table of builds. Below the table, the 'Generate Installation/License Key' section is active. The 'License key type' dropdown is highlighted with a red box and set to 'Install & Use Only'. A dropdown menu is open, showing 'Administrative (including export & license)' selected. Below it, a list of 'Available Types' includes Dynamic Applications, Device Classes, Reports, Ticket Templates, Credentials, and Credential Tests. A 'Generate Key' button is visible at the bottom.

PowerPack Export File	Embedded License	MD5 Checksum	Version	Revision	ID	Compiled
1. Cisco%3A_Base_Pack_Version-204	Admin	7238058da0ac8b2fbc4315584c32eb9	204	3393	125	2017-03-15 05:47:59

- **License key type.** Defines how the generated license key will function. Choices are:
  - *Install & Use Only.* After installation on another SL1 system (other than the author system), users will be allowed to edit only the name and version number of the PowerPack in the **PowerPack Properties** page. Users will not be allowed to edit any of the installed content, either from within the PowerPack or in SL1.
  - *Administrative (including export & license).* After installation on another SL1 system (other than the author system), users will be allowed to edit each of the installed items from this PowerPack. Users can edit the content from within the PowerPack and in SL1. Users will also be allowed to edit the properties of the PowerPack, delete content from the PowerPack, export the PowerPack, and generate a license key for the PowerPack.
  - *Manage Content Items of Selected Types.* After installation on another SL1 system (other than the author system), users will be allowed to edit the installed content type, from the associated page in the SL1 interface. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- **Available Types/Selected Types.** The entries in these fields become active if you selected *Manage Content Items of Selected Types* in the **License key type** field.
  - **To select a content option,** in the **Available Types** field, highlight the option and click the right arrow button. The option will now appear in the **Selected Types** pane and will be included in the license key. Repeat these steps for each content type you want to include in the license key.
  - **To remove a content option,** in the **Selected Types** field, highlight the option and click the left arrow button. The option will now appear in the **Available Types** pane and will not be included in the license key. Repeat these steps for each content type you want to remove from the license key.

The content types are:

- *Dynamic Applications.* After installation on another SL1 system (other than the author system), users will be allowed to edit the installed Dynamic Applications from the **Dynamic Applications Manager** page (System > Manage > Applications). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Event Policies.* After installation on another SL1 system (other than the author system), users will be allowed to edit the installed event policies from the **Event Policy Manager** page (Registry > Events > Event Manager). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

**NOTE:** If the PowerPack contains one or more Dynamic Applications or event policies that use Intellectual Property Protection, users will not be able to edit the Dynamic Applications or event policies when they are installed on another server, even if the PowerPack includes Administrator/Owner privileges.

- *Device Categories.* After installation on another SL1 system (other than the author system), users will be allowed to edit the installed device categories from the **Device Category Editor** page (System > Customize > Device Categories). In the **PowerPack Properties** page, users will be

allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

- *Device Classes*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed device classes from the **Device Class Editor** page (System > Customize > Device Classes). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Device Templates*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed device templates from the **Configuration Templates** page (Registry > Devices > Templates). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Reports*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed report from the **[Reports]** tab. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Dashboard Widgets*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed widget from the **Dashboard Widgets** page (System > Customize > Dashboard Widgets). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Dashboards*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed dashboards from the **Dashboards tab** page. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Run Book Policies*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed Run Book policies from the **Automation Policy Manager** page (Registry > Run Book > Automation). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Run Book Actions*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed Run Book actions from the **Action Policy Manager** page (Registry > Run Book > Actions). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Run Book Action Types*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed Run Book Action Types from the **Action Type Manager** page (Registry > Run Book > Action Types). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Ticket Templates*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed ticket templates from the **Ticket Templates** page (Registry > Ticketing > Templates). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.



- *Credentials*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed credentials from the **Credential Management** page (System > Manage > Credentials). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

**NOTE:** If you include organization-specific credentials in a PowerPack, the credentials cannot be preserved by that organization when the PowerPack is installed on another environment. The credentials in a PowerPack are the responsibility of the customer, and cannot be guaranteed to be organization-specific in another SL1 system.

- *Credential Tests*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed credential tests from the **Credential Test Management** page (System > Customize > Credential Tests). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Proxy XSL Transformations*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed transformations from the **Proxy XSL Transformations** page (Registry > Web Proxies > Proxy XSL Transformations). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *UI Themes*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed themes from the **Theme Management** page (System > Customize > Themes). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *IT Services*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed IT Service policies from the **IT Service Manager** page (Registry > IT Services > IT Service Manager). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
- *Log File Monitoring Policies*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed log file monitoring policies from the **Log File Monitoring Policies** page (System > Manage > Log File Monitoring Policies). In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.

2. Click the **Generate Key** button.
3. When the new license key appears in the *Generated Install Key* field, copy the license key and paste it into a text file.

---

## Export Rules, Import Rules, and Substitutions

Some of the content items that can be included in a PowerPack are dependent on, or reference, other entities in SL1. The following sections describes how SL1 handles each dependency or reference during export and import. When you build a PowerPack, for each item you include in the PowerPack, you must ensure that you have also included any referenced or dependent items. SL1 will display an error message and will not build the PowerPack if dependent items are not included.

### Event Policies

If you include an *event policy* that is aligned with an *auto-clear* event, SL1 requires that you include both events in the PowerPack. SL1 will not allow you to add an event that can be auto-cleared without also adding its aligned *auto-clear* event.

### Dynamic Applications

Dynamic Applications have the following dependencies:

- If you include a Dynamic Application that has the **Caching** field set to Consume cached results, you must also include the Dynamic Application that creates the cache. The Dynamic Application that creates the cache has the **Caching** field set to Cache results.
- If you include a Dynamic Application that has the **Component Mapping** field selected, you must also include the aligned Device Class of type Component.
- If you include a Dynamic Application that contains a *Presentation* formula or an *Alert* formula, you must ensure that the referenced Collection Objects are included in the same Dynamic Application.
- If you include a Dynamic Application that uses Collection Labels, SL1 will automatically export those Collection Labels with the PowerPack. However, those Collection Labels will not appear in the **Embedded/Available** page for the PowerPack and can still be included in other PowerPacks. Collection Labels cannot be explicitly added to or removed from a PowerPack.
- If you include a Dynamic Application that is aligned with an execution environment, SL1 will automatically export that execution environment and its associated ScienceLogic Libraries with the PowerPack.

### Dashboards

If you include a Dashboard in a PowerPack but do not include one or more of the widgets that appear on the dashboard in the PowerPack:

- For the widgets that are not included in the PowerPack, SL1 will automatically export those widgets with the PowerPack. However, those widgets will not appear in the **Embedded/Available** page for the PowerPack and can still be included in other PowerPacks.
- When the PowerPack is installed on a SL1 system, SL1 will install the widgets that were not included in the PowerPack only if those widgets are not already installed. If SL1 discovers one or more of the widgets in the PowerPack already exists on the SL1 system and those widgets were not installed by the current PowerPack, **SL1 will not overwrite the existing widgets.**

- If a widget is installed on a SL1 system by a PowerPack that does not explicitly include that widget and the PowerPack that does include that widget is installed at a later date, the widget definition that exists on the system will be associated with its PowerPack and will be updated by that PowerPack.

## Run Book Actions

**NOTE:** You cannot include Run Book of type "Create a New Ticket" in a PowerPack.

When a Run Book Action Policy is included in a PowerPack, some system-specific values will be automatically substituted by SL1.

- For action policies of type **Send an Email Notification**:
  - **Organization**. This field will contain the default value "System".
  - **Available Emails**. This list will be automatically updated with email addresses from the system where the PowerPack is installed.
  - **Assigned Emails**. By default, this list will be empty.
- For action policies of type **Send an SNMP Trap**:
  - **Organization**. This field will contain the default value "System".
  - **Trap Host**. By default, this field will be empty.
  - **Trap Credential**. By default, no value will be selected in this field.
- For action policies of type **Send an SNMP Set**:
  - **Organization**. This field will contain the default value "System".
  - **SNMP Host**. By default, this field will be empty.
  - **SNMP Credential**. By default, no value will be selected in this field.
- For action policies of type **Run a Snippet**:
  - **Organization**. This field will contain the default value "System".
  - **Snippet Credential**. By default, no value will be selected in this field.
- For action policies of type **Execute an SQL Query**:
  - **Organization**. This field will contain the default value "System".
  - **Database Credential**. By default, no value will be selected in this field.

Additionally, if you include a Run Book Action policy of type **Run a Snippet** that is aligned with an execution environment, SL1 will automatically export that execution environment and its associated ScienceLogic Libraries with the PowerPack.

## Run Book Policies

When a Run Book Automation Policy is included in a PowerPack, the following system-specific values will be automatically substituted by the platform:

- **Organization**. This field will contain the default value "System".
- **Aligned Devices**. Specific devices will be removed from this field. The policy will match all devices.

If you include an IT service policy that includes a metric that uses a Dynamic Application in a PowerPack, SL1 will automatically include the Dynamic Application in the PowerPack. When the PowerPack is installed on a ScienceLogic system, SL1 will install the Dynamic Application (with their aligned PowerPack GUIDs). However, if SL1 discovers one or more of the Dynamic Applications in the PowerPack already exists on the system, **SL1 will not overwrite the existing widgets**.

If you include a Run Book Automation policy that executes one or more Run Book Action policies, you must also include those Run Book Action policies in the PowerPack.

If you include a Run Book Automation policy that includes an Automation Schedule, SL1 will automatically include the required Automation Schedule in the PowerPack.

## Credentials

If you include credentials in a PowerPack, you must make sure that the credentials are portable and can be used on both the author's system and the system where the PowerPack will be installed.

To make credentials more portable:

- You can use **%D** in place of a specific IP address.
- You can use **%N** in place of a specific host name.

Credentials can be aligned with an organization. When you align a credential with an organization, only users who are members of that organization can view the name of the credential in SL1. Only users who are members of that organization can assign that credential in SL1. For details, see the guide for the **Credential Management** page.

- **When creating or editing a PowerPack**, the **Available** pane will display a list of credentials that are not yet included in any other PowerPack and further filters the list by including only those credentials that you have access to. Your organization membership(s) might affect the list of credentials you can see in the **Available** pane. For details, see the guide for the **Credential Management** page.
- **When creating or editing a PowerPack**, if you remove a credential from the PowerPack using the bomb icon, and you are not a member of the organization aligned with that credential, the credential will not appear in the **Available** pane.
- **When viewing the list of included credentials** in the PowerPack in the **Embedded** pane, all users who can access the PowerPack, regardless of their organization, can view the list of credentials. If a credential is aligned with one or more organization, the **Organization** column in the **Embedded** pane displays *limited*. If the credential is aligned with all organization, the **Organization** column in the **Embedded** pane displays *all orgs*.
- **When a user imports and installs a PowerPack** on a system other than the author system:
  - credentials aligned with **all orgs** are still aligned with all organizations on the new system.
  - credentials aligned with one or more organizations on the author system are aligned with **no organizations** on the new system. An administrator or user who is a member of all organizations must edit the installed credential and align it with one or more organizations. Until the credential is aligned with one, multiple, or all organizations, it is not visible to other users in SL1.

## Credential Tests

If you include a Credential Test that is aligned with an execution environment, SL1 will automatically export that execution environment and its associated ScienceLogic Libraries with the PowerPack.

## Ticket Templates

When a Ticket Template is included in a PowerPack, some system-specific values will be automatically substituted by SL1.

For each ticket template in a PowerPack, SL1 will automatically substitute the following values:

- **Organization**. This field will contain the default value "System".
- **Ticket Queue**. By default, no value will be selected in this field.
- **Assigned User**. By default, no value will be selected in this field.
- **Category**. By default, no value will be selected in this field.

## Device Templates

If you include a Device Template that contains one or more Dynamic Applications or Log File Monitoring Policies, you must also include those Dynamic Applications and Log File Monitoring Policies with the PowerPack.

When a device template is included in a PowerPack, SL1 automatically makes some changes to the device template to make it more portable:

- **Device Organization**. This field will not contain a value and will be deactivated.

## Device Groups

When a device group is included in a PowerPack, SL1 automatically makes some changes to the device group to make it more portable:

- **Active Selectors**. *Custom Attributes* have special behavior in PowerPacks.
  - If you included a Base Custom Attribute in this pane, the Base Custom Attribute will be exported with the PowerPack and will appear on the new system when imported.
  - If you included an Extended Custom Attribute in this pane, the Extended Custom Attribute will be exported with the PowerPack.
    - If the target system does not already include the Extended Custom Attribute, the Extended Custom Attribute will not appear in the **Active Selectors** pane.
    - If the target system does include the Extended Custom Attribute, the Extended Custom Attribute will appear in the **Active Selectors** pane.

## IT Service Policies

When an IT service policy is included in a PowerPack, the following properties of the IT service policy are included:

- The settings defined in the **[Properties]** sub-tab in the **IT Service Editor**. However, the following system-specific values are substituted when the PowerPack is installed:
  - The **IT Service Owner** field is set to the user that installed the PowerPack.
  - The values that were selected in the **Permission Keys** field are removed.
- The dynamic device rules defined in the **[Model]** sub-tab in the **IT Service Editor**. Statically aligned devices, device groups, and service dependencies are not included.
- The device subsets defined in the **[Model]** sub-tab in the **IT Service Editor**. However, only dynamic device rules are included in those subsets. Statically aligned devices are not included.
- All settings defined in the **[Metrics]**, **[Collection]**, and **[Alerting]** sub-tabs in the **IT Service Editor**.

When a PowerPack that includes an IT service policy is installed on a SL1 system, the following items are also installed by the PowerPack:

- All event policies associated with the IT service policy.
- All interface tags that are specified in a metric in the IT service policy.


If you include an IT service policy that includes a metric that uses a Dynamic Application in a PowerPack but do not include the Dynamic Application in the PowerPack:

- For the Dynamic Applications that are not included in the PowerPack, SL1 will automatically export those Dynamic Applications with the PowerPack. However, those Dynamic Applications will not appear in the **Embedded/Available** page for the PowerPack and can still be included in other PowerPacks.
- When the PowerPack is installed on a SL1 system, SL1 will install the Dynamic Applications that were not included in the PowerPack only if those Dynamic Applications are not already installed. If SL1 discovers one or more of the Dynamic Applications in the PowerPack already exists on the SL1 system and those Dynamic Applications were not installed by the current PowerPack, **SL1 will not overwrite the existing Dynamic Applications.**
- If a Dynamic Application is installed on a SL1 system by a PowerPack that does not explicitly include that Dynamic Application and the PowerPack that does include that Dynamic Application is installed at a later date, the Dynamic Application definition that exists on the system will be associated with its PowerPack and will be updated by that PowerPack.

---

## Exporting a PowerPack

If you want users to be able to install a PowerPack on another SL1 system, you must export the PowerPack to a file. To do this:


1. If the **Editing PowerPack** page is not open, go to the **PowerPack Manager** page (System > Manage > PowerPacks). Find the PowerPack you want to export and click its green disk icon () .
2. If the PowerPack is already open, click **Build and Export** from the Navbar to the left.

3. In the **Compiled PowerPacks / Generate Installation Key** page, go to the **Compiled PowerPacks** pane at the top of the page.

The screenshot shows the 'Compiled PowerPacks' section of the 'Amazon Web Services' PowerPack editor. It features a table with the following data:

	PowerPack Export File	Embedded License	MDC Checksum	Version	Revision	ID	Compiled
1.	Amazon_Web_Services_Version-108	Admin	950c3634943674d430b541f0c7ca36e	108	9931	336	2018-02-13 20:35:04
2.	Amazon_Web_Services_Version-103	Admin	f9fca573922cb6786c9515f1da10994	103	7737	36	2017-03-29 23:22:43

Below the table is the 'Generate Installation/License Key for Amazon\_Web\_Services\_Version-108, revision 9931' section. It includes a 'License key type' dropdown set to 'Install & Use Only', two lists of 'Available Types' and 'Selected Types' (currently empty), and a 'Generate Key' button.


4. Find the revision of the PowerPack you want to export and click its green disk icon (  ).
5. When prompted, save the PowerPack to a local file.
6. You can now distribute the file for installation on other SL 1 systems.
7. If the exported PowerPack does not include an embedded license key, you must send the license key to each user who will install and import the PowerPack.



# Generating an Embedded License Key After the Initial Build



If you want to generate a new, embedded license key for the PowerPack after the initial build, perform the following:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).





The screenshot shows the PowerPack Manager interface with a table of 163 PowerPacks. The table has columns for ID, Name, Version, Revision, and Actions. The Actions column contains icons for Build, Export, and Wrench (License Key). The Wrench icon is highlighted for the 'NTI Base Pack' (ID 126).

ID	Name	Version	Revision	Actions
126	NTI Base Pack	1.2	2	Build, Export, Wrench
127	Polycom Endpoint	7.5.4	150	Build, Export, Wrench
128	Polycom Infrastructure	7.5.2	39	Build, Export, Wrench
129	Printer Base Pack	1.3	28	Build, Export, Wrench
130	Rackspace Base Pack	1.3	5	Build, Export, Wrench
131	Redback Base Pack	1.1	1	Build, Export, Wrench
132	RIM BlackBerry Base Pack	1.1	2	Build, Export, Wrench
133	Powered Base Pack	1.1	2	Build, Export, Wrench
134	ScienceLogic CMT Base Pack	1.1	28	Build, Export, Wrench
135	ScienceLogic Subscription Audit Pack	2.5	2	Build, Export, Wrench
136	ScienceLogic Support Pack	7.3.8	15	Build, Export, Wrench
137	Sensitronics Base Pack	1.1	2	Build, Export, Wrench
138	Service Level Management	7.5.1	1	Build, Export, Wrench
139	Service Proxy MiddelPowerpack	1.4	1	Build, Export, Wrench
140	SLPSD Onboarding	0.2.3	24	Build, Export, Wrench
141	SL_PS Cisco 3rd Party Device Support	1.4	26	Build, Export, Wrench
142	SNMP Research Base Pack	1	7	Build, Export, Wrench
143	SoftLayer Cloud	0.5	30	Build, Export, Wrench
144	Supplemental Device Class Pack	7.5.3	727	Build, Export, Wrench
145	System Lifetime	1.0	2	Build, Export, Wrench
146	SystemEdge Base Pack	7.3.8	5	Build, Export, Wrench
147	Tandberg Endpoint Base Pack	7.5.4	16	Build, Export, Wrench
148	Tandberg Infrastructure	7.5	24	Build, Export, Wrench
149	Telnet Client Generator	1	1	Build, Export, Wrench
150	Tipping Point Base Pack	1.2	26	Build, Export, Wrench
151	Tomcat	1.2	2	Build, Export, Wrench
152	UCSD-SNMP Base Pack	7.3.6	2	Build, Export, Wrench
153	Video Performance App Pack	7.5.2	5	Build, Export, Wrench
154	Video Reports	7.5.2	19	Build, Export, Wrench
155	VMware Dashboards	7.3.3	1	Build, Export, Wrench
156	VMware vCloud	7.3.6	22	Build, Export, Wrench
157	VMware vSphere Base Pack	7.5.5	17	Build, Export, Wrench
158	VMware vSphere Reports	7.5.2	1	Build, Export, Wrench
159	WiFi	7.3.4	1	Build, Export, Wrench
160	Windows Restart Automatic Services	7.3.2	1	Build, Export, Wrench
161	XenServer Base Pack	7.5.2	17	Build, Export, Wrench
162	Xerox Base Pack	1	105	Build, Export, Wrench
163	Xirus Base Pack	7.3.5	4	Build, Export, Wrench

2. Find the PowerPack for which you want to generate a license key. Click its Build/Export icon (  ).
3. The **Compiled PowerPacks / Generate Installation Key** modal page appears.
4. In the **Compiled PowerPacks** pane, find the Version and Revision of the PowerPack for which you want to generate a new, embedded license key. Click its wrench icon (  ).


- In the **Configure Export File** page, define the embedded license key. For details on each field, see the section [Generating an Embedded License Key During the Initial Build](#).





- Click the **[Save]** button to save the embedded license. Notice that the **Embedded License** field in the top pane of the **Compiled PowerPacks / Generate Installation Key** page now matches the newly generated license.
- After saving the license key, you can export the PowerPack. To do this, go to the **Compiled PowerPacks / Generate Installation Key** modal page. In the **Compiled PowerPacks** pane, find the Version and Revision of the PowerPack you want to export.
- Click the "download this build" icon (  ). The PowerPack will be exported to your local computer. You can then distribute the PowerPack to users.
- When users import and install the PowerPack, they do not need to enter a license key.

## Generating an Unembedded License Key After the Initial Build

If you want to generate a new license key, not embedded, for the PowerPack after the initial build, perform the following:

- Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
- Find the PowerPack for which you want to generate a license key. Click its Build/Export icon (  ).
- The **Compiled PowerPacks / Generate Installation Key** modal page appears.

4. In the **Compiled PowerPacks** pane, find the Version and Revision of the PowerPack for which you want to generate a new license key. Click its **Generate License Key** icon ()
5. The selected Version and Revision of the PowerPack is loaded into the **Generate Installation/License Key** pane.
6. In the **Generate Installation/License Key** pane, define the privileges for the new license key and generate the new license key. For details on each field, see the section [Generating an Unembedded License During the Initial Build](#).
7. Copy the license key and paste it into a text file.
8. After saving the license key, you can export the PowerPack. To do this, go to the **Compiled PowerPacks / Generate Installation Key** modal page. In the **Compiled PowerPacks** pane, find the Version and Revision of the PowerPack you want to export.
9. Click the "download this build" icon () . The PowerPack will be exported to your local computer. You can then distribute the PowerPack to users.
10. You must send the license key to each user who will install and import the PowerPack.

---

# Chapter

# 4



## Editing a PowerPack

---

### Overview

This chapter describes how to edit a PowerPack, assign a new license key to a PowerPack that has already been installed, how to delete a PowerPack, and how to remove content from a PowerPack.

Use the following menu options to navigate the SL1 user interface:

- To view a pop-out list of menu options, click the menu icon ()
- To view a page containing all of the menu options, click the Advanced menu icon ()

This chapter includes the following topics:

<i>Caveats</i> .....	61
<i>Privileges for Editing a PowerPack</i> .....	61
<i>Editing a PowerPack</i> .....	68
<i>Editing Dynamic Applications in a PowerPack</i> .....	70
<i>Generating a New License Key for the PowerPack</i> .....	70
<i>Assigning a New License Key to an Already-Installed PowerPack</i> .....	71
<i>Deleting One or More PowerPacks</i> .....	72
<i>Removing Content from a PowerPack</i> .....	73

---

## Caveats

- Content can be included in only a single PowerPack. For example, if you include the Dynamic Application "Cisco: Summary Statistics" in the PowerPack "networking\_powerpack", you cannot include that Dynamic Application in another PowerPack. If you want to include content in a second PowerPack, you must first remove the content from the first PowerPack. This is described in the section [Removing Content from a PowerPack](#).
- When you delete a PowerPack, SL1 automatically deletes the associated content from the SL1 system and all data associated with it. For example, if a PowerPack includes a Dynamic Application, when you delete the PowerPack, the Dynamic Application is removed from SL1. If you go to the **Dynamic Applications Manager** page (System > Manage > Applications), that Dynamic Application will not appear. In addition, all data collected from all devices with that Dynamic Application will also be deleted.
- If you must delete a PowerPack but want to keep the installed content, you should first remove the content from the PowerPack. This is described in the section [Removing Content from a PowerPack](#). To remove content from a PowerPack, you must either have administrator/owner privileges for the PowerPack or you must be the creator of the PowerPack. For details on privileges associated with PowerPacks, see the [section on privileges](#) in this chapter.
- If you want to include content in a second PowerPack, you must first remove the content from the first PowerPack. This is described in the section [Removing Content from a PowerPack](#). To remove content from a PowerPack, you must either have administrator/owner privileges for the PowerPack or you must be the creator of the PowerPack. For details on privileges associated with PowerPack, see the [section on privileges](#) in this chapter.
- The privileges associated with a PowerPack's license key control the actions that users can perform after they install a PowerPack.
- Authors of PowerPacks are allowed to perform all editing actions on the PowerPack and its content. On the SL1 system where the PowerPack was created, only authors can edit the **Publisher** field for a PowerPack.
- If content in PowerPacks uses Intellectual Property Protection, you will not be able to edit the content on any system other than the system where the content was authored. This is true regardless of the license key associated with the PowerPack.
- If you include organization-specific credentials in a PowerPack, the credentials cannot be preserved by that organization when the PowerPack is installed on another environment. The credentials in a PowerPack are the responsibility of the customer, and cannot be guaranteed to be organization-specific in another SL1 system.

---

## Privileges for Editing a PowerPack

On the system where the PowerPack is created, privileges are controlled by user-type (user or administrator) and access keys. Additionally, on the author system, the license key for a PowerPack endows author privileges.

On the system where the PowerPack is installed, privileges are controlled by the license key, and/or Intellectual Property Protection. When creating a PowerPack or a revision of a PowerPack, the author can assign privileges and capture those privileges in a license key. **The following table describes privileges on the system where the PowerPack is installed.**

**NOTE:** If the PowerPack contains one or more Dynamic Applications or event policies that use Intellectual Property Protection, users will not be able to edit the Dynamic Applications or event policies when they are installed on another system, even if the PowerPack includes Administrator/Owner privileges.

Privilege	Actions
License Key from <b>PowerPack Properties</b> page	<p>Provides author-level privileges for the author of the PowerPack on the author system. Authors can edit the content from within the PowerPack and in SL1. Authors are also allowed to edit the properties of the PowerPack, including the <b>Publisher</b> field, delete content from the PowerPack, export the PowerPack, and generate a license key for the PowerPack.</p> <p>For users of the PowerPack, the License Key is a field on the <a href="#">Properties</a> page that displays the license key currently associated with the PowerPack.</p>
License Key - Install and Use Only	<p>Users will be allowed to install this PowerPack on another system (other than the author system). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. Users will not be allowed to edit any of the installed content, either from within the PowerPack manager or in their respective management pages.</p>
Administrative (Including Export & License)	<p>After installation on a system (other than the author system), users will be allowed to edit each of the installed items from this PowerPack. Users can edit the content from within the PowerPack and in SL1. Users will also be allowed to edit the properties of the PowerPack (but cannot edit the <b>Publisher</b> field), delete content from the PowerPack, export the PowerPack, and generate a license key for the PowerPack.</p>

Privilege	Actions
License Key - Dynamic Applications	After installation on a system (other than the author system), users will be allowed to edit the installed Dynamic Applications from the <b>Dynamic Applications Manager</b> page (System > Manage > Applications). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Event Policies	After installation on a system (other than the author system), users will be allowed to edit the installed event policies from <b>Event Policy Manager</b> page (Registry > Events > Event Manager). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access any other pages for the PowerPack.
License Key - Device Categories	After installation on a system (other than the author system), users will be allowed to edit the installed device categories from the <b>Device Category Editor</b> page (System > Customize > Device Categories). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Device Classes	After installation on a system (other than the author system), users will be allowed to edit the installed device classes from the <b>Device Class Editor</b> page (System > Customize > Device Classes). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Device Templates	After installation on a system (other than the author system), users will be allowed to edit the installed device classes from <b>Configuration Templates</b> page (Registry > Devices > Templates). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.

Privilege	Actions
License Key - Reports	After installation on a system (other than the author system), users will be allowed to edit the installed report from the <b>[Reports]</b> tab. In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Dashboard Widgets	After installation on a system (other than the author system), users will be allowed to edit the installed dashboard-widget from the <b>Dashboard Widgets</b> page (System > Customize > Dashboard Widgets). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Dashboards	After installation on a system (other than the author system), users will be allowed to edit the installed dashboards from the <b>Dashboards tab</b> page. In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Run Book Policies	After installation on a system (other than the author system), users will be allowed to edit the installed run book policies from the <b>Automation Policy Manager</b> page (Registry > Run Book > Automation). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Run Book Actions	After installation on a system (other than the author system), users will be allowed to edit the installed run book actions from the <b>Action Policy Manager</b> page (Registry > Run Book > Actions). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.



Privilege	Actions
License Key - Ticket Templates	After installation on a system (other than the author system), users will be allowed to edit the installed ticket templates from the <b>Ticket Templates</b> page (Registry > Ticketing > Templates). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Credentials	After installation on a system (other than the author system), users will be allowed to edit the installed credentials from the <b>Credential Management</b> page (System > Manage > Credentials). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack. If the credential is organization-restricted on the author system, these restrictions won't apply on the target system.
License Key - Credential Tests	After installation on a system (other than the author system), users will be allowed to edit the installed credential tests from the <b>Credential Test Management</b> page (System > Customize > Credential Tests). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Proxy XSL Transformations	After installation on a system (other than the author system), users will be allowed to edit the installed Proxy XSL Transformations from the <b>Proxy XSL Transformations</b> page (Registry > Web Proxies > Proxy XSL Transformations). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.

Privilege	Actions
License Key - UI Themes	After installation on a system (other than the author system), users will be allowed to edit the installed themes from the <b>Theme Management</b> page (System > Customize > Themes). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - IT Services	After installation on a system (other than the author system), users will be allowed to edit the installed IT service policies from the <b>IT Service Manager</b> page (Registry > IT Services > IT Service Manager). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.
License Key - Log File Monitoring Policies	After installation on a system (other than the author system), users will be allowed to edit the installed log file monitoring policies from the <b>Log File Monitoring Policies</b> page (System > Manage > Log File Monitoring Policies). In the <b>PowerPack Properties</b> page, users will be allowed to edit only the name and version number of the PowerPack. With only this privilege, users cannot access or edit any other pages for the PowerPack.

Privilege	Actions
Intellectual Property Protection - Dynamic Applications	<p>Adding Intellectual Property Protection to a Dynamic Application prevents users from viewing information required only for editing purposes, and from editing the Dynamic Application on any system except the system where the Dynamic Application was created.</p> <p>After installation on a system (other than the author system), users cannot disable the Intellectual Property Protection feature and can view only the <b>[Properties]</b> and <b>[Subscribers]</b> tab of the Dynamic Application (within the PowerPack or in the <b>Dynamic Applications Manager</b> page). Even if the PowerPack is installed with a license key that grants Administrator/Owner privileges, users won't be able to access all tabs for the Dynamic Application. When Intellectual Property Protections is enabled, the tabs below will not be displayed for the Dynamic Application:</p> <ul style="list-style-type: none"> <li>○ Collections</li> <li>○ Presentation</li> <li>○ Thresholds</li> <li>○ Snippets (for Dynamic Applications of type "snippe")</li> <li>○ Requests (for Dynamic Applications of type "SOAP" and "XSLT")</li> <li>○ Alerts</li> </ul>
Intellectual Property Protection - Event Policies	<p>Adding Intellectual Property Protection to an event policy prevents users from viewing information required only for editing purposes, and from editing the event policy on any system except the system where the event policy was created.</p> <p>After installation on a system (other than the author system), users cannot disable the Intellectual Property Protection feature and can view only the <b>[Policy]</b> and <b>[Suppressions]</b> tab of the event policy application (within the PowerPack or in the <b>Event Policy Manager</b> page). Even if the PowerPack is installed with a license key that grants Administrator/Owner privileges, users won't be able to access all tabs for the event policy. When Intellectual Property Protections is enabled, the tab below will not be displayed for the event policy:</p> <ul style="list-style-type: none"> <li>○ Advanced</li> </ul>

---

## Editing a PowerPack

If you have administrator rights for a PowerPack, you can edit an existing PowerPack.

If you have installed a PowerPack on a system other than the author system, your [editing privileges](#) are determined by the license key and/or intellectual property protection associated with the PowerPack.

To edit a PowerPack:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).

PowerPack™ Name	Version	Publisher	Apps	Events	Classes	Reports	Widgets	Actions	Credits	Test	XSLT	Dev	Test	ID	Edited By	Last Edited
1. 3Com Base Pack	1	ScienceLogic, Inc.	--	--	298	--	--	--	--	1	--	--	--	1	em7admin	2015-05-14 11:24:52
2. ADIC Base Pack	1.2	ScienceLogic, Inc.	22	24	3	--	--	--	--	--	--	--	--	2	em7admin	2015-05-14 11:24:53
3. Alcatel-Lucent Base Pack	1	ScienceLogic, Inc.	--	--	33	--	--	--	--	--	--	--	--	4	em7admin	2015-05-14 11:24:54
4. Alteon Base Pack	1.3	ScienceLogic, Inc.	23	25	6	--	--	--	--	--	--	--	--	5	em7admin	2015-05-14 11:24:54
5. Amazon Web Services	7.7.0	ScienceLogic, Inc.	144	71	84	3	--	20	--	1	--	--	--	6	em7admin	2015-10-14 14:47:57
6. APC Base Pack	7.3.0	ScienceLogic, Inc.	9	27	30	--	--	--	--	--	--	--	--	3	em7admin	2015-05-14 11:24:53
7. Arista Networks Base Pack	1.0	ScienceLogic, Inc.	--	--	65	--	--	--	--	--	--	--	--	153	em7admin	2015-09-04 11:37:45
8. Aruba Base Pack	1.1	ScienceLogic, Inc.	3	--	--	--	--	--	--	--	--	--	--	7	em7admin	2015-05-14 11:24:59
9. Ascend Communication Base Pack	1	ScienceLogic, Inc.	--	--	19	--	--	--	--	--	--	--	--	8	em7admin	2015-05-14 11:24:59
10. AsEM7 Query Widgets	7.2.3	ScienceLogic, Inc.	--	--	--	3	--	--	--	--	--	--	--	9	em7admin	2015-05-14 11:24:59
11. Atachmate Base Pack	1.1	ScienceLogic, Inc.	--	--	13	--	--	--	--	--	--	--	--	10	em7admin	2015-05-14 11:24:59
12. Avaya Base Pack	7.3.5	ScienceLogic, Inc.	--	--	43	--	--	--	--	--	--	--	--	11	em7admin	2015-05-14 11:25:00
13. Avicent ACS Base Pack	7.3.8	ScienceLogic, Inc.	4	--	--	--	--	--	--	--	--	--	--	12	em7admin	2015-05-14 11:25:00
14. Avocent Base Pack	1.1	ScienceLogic, Inc.	3	--	6	--	--	--	--	--	--	--	--	13	em7admin	2015-05-14 11:25:00
15. BL Test	1	BL	--	--	--	--	--	--	--	--	--	--	--	156	em7admin	2015-10-29 10:56:11
16. Blue Coat Base Pack	1.2	ScienceLogic, Inc.	1	2	10	--	--	--	--	--	--	--	--	15	em7admin	2015-05-14 11:25:02
17. BlueCat Base Pack	1.1	ScienceLogic, Inc.	2	--	--	--	--	--	--	--	--	--	--	14	em7admin	2015-05-14 11:25:00
18. Brocade Base Pack	7.3.0	ScienceLogic, Inc.	5	12	5	--	--	--	--	--	--	--	--	16	em7admin	2015-05-14 11:25:04
19. Cabletron Systems Base Pack	1	ScienceLogic, Inc.	--	--	15	--	--	--	--	--	--	--	--	17	em7admin	2015-05-14 11:25:05
20. Cisco CM Power-Pack	7.5.1	ScienceLogic, Inc.	36	67	9	1	3	--	--	1	--	--	--	19	em7admin	2015-05-14 11:25:10
21. Cisco IPSLA	7.3.0	ScienceLogic, Inc.	10	81	--	--	--	--	--	1	--	--	--	20	em7admin	2015-05-14 11:25:13
22. Cisco Nexus	7.6.1	ScienceLogic, Inc.	83	34	53	--	--	1	--	2	--	--	--	21	em7admin	2015-10-06 10:42:39
23. Cisco Unity Pack	1.2	ScienceLogic, Inc.	2	6	--	--	--	--	--	--	--	--	--	22	em7admin	2015-05-14 11:25:19
24. Cisco VPN Pack	1.1	ScienceLogic, Inc.	2	--	--	--	--	--	--	--	--	--	--	23	em7admin	2015-05-14 11:25:19
25. Cisco: ACI	0.5	ScienceLogic, Inc.	42	7	20	--	--	8	2	3	--	--	--	142	em7admin	2015-11-24 14:03:02
26. Cisco: ACI Dashboards	0.5	ScienceLogic, Inc.	--	--	--	--	--	8	--	--	--	--	--	151	em7admin	2015-07-31 17:22:49
27. Cisco: Base Pack	7.6.1	ScienceLogic, Inc.	11	26	1403	--	--	--	--	2	--	--	--	18	em7admin	2015-10-06 10:42:33
28. Cisco: Contact Center Enterprise	0.5	ScienceLogic, Inc.	14	33	19	--	--	--	--	--	--	--	--	162	em7admin	2015-12-14 13:50:50
29. Cisco: CUCM Cisco Unified Communications Manager	1.0	ScienceLogic, Inc.	112	133	52	--	--	23	--	1	--	--	--	148	em7admin	2015-08-28 14:28:51
30. Cisco: CUCM Dashboards	1.0	ScienceLogic, Inc.	--	--	--	--	--	28	--	--	--	--	--	150	em7admin	2015-08-03 13:38:00
31. Cisco: TelePresence: Endpoints	7.7.0	ScienceLogic, Inc.	10	85	47	--	--	--	--	--	--	--	--	24	em7admin	2015-10-28 13:26:18
32. Cisco: TelePresence: Infrastructure	7.3.4	ScienceLogic, Inc.	20	23	15	--	--	--	--	--	--	--	--	25	em7admin	2015-05-14 11:25:27
33. Cisco: TelePresence: Traps	7.3.8	ScienceLogic, Inc.	--	--	37	--	--	--	--	--	--	--	--	26	em7admin	2015-05-14 11:25:28
34. Cisco: UCS	7.5.5	ScienceLogic, Inc.	44	257	19	--	--	--	--	1	--	--	--	27	em7admin	2015-06-02 18:30:52
35. Citrix Base Pack	7.3.0	ScienceLogic, Inc.	12	18	--	--	--	--	--	--	--	--	--	28	em7admin	2015-05-14 11:25:30

2. In the **PowerPack Manager** page, find the PowerPack you want to edit. Click its wrench icon ().
3. You can edit one or more fields in the **PowerPack Properties** page. For details on the Navbar for a PowerPack and their fields, see the section on [Creating a PowerPack](#).

**NOTE:** If you edit a content item in the PowerPack (either from the **Embedded** pane in the **Embedded/Available** page or from a page in the user interface) **after** the PowerPack is installed or the last time the PowerPack was compiled (whichever is late), that content item will be highlighted in red and will have an updated date in the **Last Edited** column in the **Embedded/Available** page.

4. If you edited the PowerPack, you must rebuild the PowerPack and generate a new license key. For details, see the section [Building the PowerPack and Generating a License Key](#).
5. When you have finished building the PowerPack and generating the license key, you can export the updated PowerPack. For details, see the [Exporting a PowerPack](#) section.

**NOTE:** Any edits applied to the PowerPack before you create a new build will be highlighted in red in the **PowerPack** pages.

## Editing Dynamic Applications in a PowerPack

You cannot use a PowerPack to globally delete an existing collection object. When you install a PowerPack on multiple systems, and you log in to one of those systems and delete a collection object from a Dynamic Application in that PowerPack, you must then log in to each system and manually delete that collection object from each system. Saving the edited PowerPack and re-installing it will not perform a deletion. This is a behavior built into the PowerPack to protect your data.

For example:

- Suppose you have a PowerPack named **PowerPack\_test**.
- Suppose **PowerPack\_test** includes a Dynamic Application named **DynApp\_test**.
- Suppose you install **PowerPack\_test** on two systems, **EM7\_sys1** and **EM7\_sys2**.
- Suppose you:
  - Log in to **EM7\_sys1**.
  - Edit **PowerPack\_test**.
  - In **PowerPack\_test**, edit **DynApp\_test**.
  - In **DynApp\_test**, delete a collection object called **my\_object**.
  - Save **PowerPack\_test** with a new version number.
  - Export the new version of **PowerPack\_test**.
- Suppose you log in to **EM7\_sys2** and install the new version of **PowerPack\_test**.
- The updated PowerPack will not delete the existing collection object from **EM7\_sys2**.
- After installing **PowerPack\_test**, go to the Dynamic Applications Manager page (System > Manage > Applications). Open the Dynamic Application **DynApp\_test**. Notice that the Dynamic Application still contains the collection object **my\_object**.
- To remove the collection object, you must manually edit the Dynamic Application and delete the collection object. You cannot use an updated PowerPack to delete the collection object.

---



## Generating a New License Key for the PowerPack


To learn how to generate a new license key for a PowerPack, see the sections on generating embedded and un-embedded license keys after the initial build in the section [Creating a PowerPack](#).

# Assigning a New License Key to an Already-Installed PowerPack

Suppose you want to change the privileges associated with an already-installed PowerPack, but you don't want to force the end-user to re-install the PowerPack. To do this, you can generate a new, un-embedded license key for the already-installed revision of the PowerPack.

The user of the PowerPack can then paste the new license key into the *License Key* field in the **PowerPack Properties** page for the PowerPack. To assign a new license key to an already-installed PowerPack:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).
2. Find the PowerPack you want to assign a new license key to. Click its wrench icon () .
3. In the **PowerPack Properties** page, click *Build / Export*.
4. In the **Compiled PowerPacks / Generate Installation Key** page, each revision of the PowerPack is displayed. To select the PowerPacks revision for which you want to generate an installation key, click its pencil and paper icon () .



5. In the **License Key type** field, you can now select if you want to embed the license key in the PowerPack, and if so, how you would like the embedded key to function. Choices are:
  - *Install & Use Only*. After installation on another SL1 system (other than the author system), users will be allowed to edit only the name and version number of the PowerPack in the **PowerPack Properties** page. Users will not be allowed to edit any of the installed content, either from within the PowerPack or in SL1 .

- *Administrative (including export & license)*. After installation on another SL1 system (other than the author system), users will be allowed to edit each of the installed items from this PowerPack. Users can edit the content from within the PowerPack and in SL1. Users will also be allowed to edit the properties of the PowerPack, delete content from the PowerPack, export the PowerPack, and generate a license key for the PowerPack.
  - *Manage Content Items of Selected Types*. After installation on another SL1 system (other than the author system), users will be allowed to edit the installed content type, from the associated page in the user interface. In the **PowerPack Properties** page, users will be allowed to edit only the name and version number of the PowerPack. Users cannot access or edit any other pages for the PowerPack.
6. Click the **Generate Key** button. When the new license key appears in the *Generated Install Key* field, copy the license key and paste it into a text file.

---

## Deleting One or More PowerPacks


If you have the appropriate Access Keys, you can delete one or more PowerPacks from the **PowerPack Manager** page.

**CAUTION:** When you delete a PowerPack, SL1 automatically deletes the associated content from the SL1 system and all data associated with it. For example, if a PowerPack includes a Dynamic Application, when you delete the PowerPack, the Dynamic Application is removed from SL1. If you go to the **Dynamic Applications Manager** page (System > Manage > Applications), that Dynamic Application will not appear. In addition, all data collected from all devices with that Dynamic Application will also be deleted. If you must delete a PowerPack but want to keep the installed content, you should first remove the content from the PowerPack. This is described in the section [Removing Content from a PowerPack](#). To remove content from a PowerPack, you must either have administrator/owner privileges for the PowerPack or you must be the creator of the PowerPack. For details on privileges associated with PowerPacks, see the section on [Creating a PowerPack](#).



To delete a PowerPack:

1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).



2. Find the PowerPack you want to delete. Click its checkbox .
3. Click the checkbox for each PowerPack you want to delete.
4. In the **Select Action** drop-down field (in the lower right), choose *Delete PowerPack(s)*.
5. Click the **[Go]** button.
6. In the pop-up window that appears, click the **[OK]** button.
7. The selected PowerPacks will be deleted from SL1.

## Removing Content from a PowerPack

If you have the license key with author's privileges for a PowerPack or if you have owner/administrator privileges with your license key, you can remove content from a PowerPack. There are two situations where you might want to remove content from a PowerPack.

- If you must delete a PowerPack but want to keep the installed content, you should first remove the content from the PowerPack.
- Each piece of content in SL1 (Dynamic Application, event policy, device class, custom report, custom dashboard-widget, run book policy, run book action, ticket template, credential, Proxy XSL Transformations, UI themes, and/or IT services) can be included in **only one** PowerPack. If you want to include content in a second PowerPack, you must first remove the content from the first PowerPack.
- You cannot use a PowerPack to delete existing collection objects from a Dynamic Application. For details, section on [Editing a Dynamic Application in a PowerPack](#).

To remove content from a PowerPack:


1. Go to the **PowerPack Manager** page (System > Manage > PowerPacks).

PowerPack™ Manager | PowerPacks™ Found [163]

PowerPack™ Name	Version	Publisher	Apps	Events	Classes	Reports	Widgets	Actions	Creds	Test Tr	SSL	Dev Tr	ID	Edited By	Last Edited	
1. 3Com Base Pack	1	ScienceLogic, Inc.	--	--	2298	--	--	--	21	--	--	--	1	em7admin	2015-05-14 11:24:52	
2. ADIC Base Pack	1.2	ScienceLogic, Inc.	22	24	23	--	--	--	--	--	--	--	2	em7admin	2015-05-14 11:24:53	
3. Alcatel-Lucent Base Pack	1	ScienceLogic, Inc.	--	--	233	--	--	--	--	--	--	--	4	em7admin	2015-05-14 11:24:54	
4. Alteon Base Pack	1.3	ScienceLogic, Inc.	23	25	26	--	--	--	--	--	--	--	5	em7admin	2015-05-14 11:24:54	
5. Amazon Web Services	7.7.0	ScienceLogic, Inc.	2144	271	294	23	--	220	--	21	--	--	6	em7admin	2015-10-14 14:47:57	
6. APC Base Pack	7.3.0	ScienceLogic, Inc.	219	227	230	--	--	--	--	--	--	--	3	em7admin	2015-05-14 11:24:53	
7. Arista Networks Base Pack	1.0	ScienceLogic, Inc.	--	--	265	--	--	--	--	--	--	--	153	em7admin	2015-09-04 11:37:45	
8. Aruba Base Pack	1.1	ScienceLogic, Inc.	23	--	--	--	--	--	--	--	--	--	7	em7admin	2015-05-14 11:24:59	
9. Ascend Communication Base Pack	1	ScienceLogic, Inc.	--	--	219	--	--	--	--	--	--	--	8	em7admin	2015-05-14 11:24:59	
10. AsEM7 Query Widgets	7.2.3	ScienceLogic, Inc.	--	--	--	23	--	--	--	--	--	--	9	em7admin	2015-05-14 11:24:59	
11. Asimble Base Pack	1.1	ScienceLogic, Inc.	--	--	213	--	--	--	--	--	--	--	10	em7admin	2015-05-14 11:24:59	
12. Aysa Base Pack	7.3.5	ScienceLogic, Inc.	--	--	243	--	--	--	--	--	--	--	11	em7admin	2015-05-14 11:25:00	
13. Avocent ACS Pack	7.3.6	ScienceLogic, Inc.	24	--	--	--	--	--	--	--	--	--	12	em7admin	2015-05-14 11:25:00	
14. Avocent Base Pack	1.1	ScienceLogic, Inc.	23	--	26	--	--	--	--	--	--	--	13	em7admin	2015-05-14 11:25:00	
15. BL Test	1	BL	--	--	--	--	--	--	--	--	--	--	156	em7admin	2015-10-29 10:56:11	
16. Blue Coat Base Pack	1.2	ScienceLogic, Inc.	21	22	210	--	--	--	--	--	--	--	15	em7admin	2015-05-14 11:25:02	
17. BlueCat Base Pack	1.1	ScienceLogic, Inc.	22	--	--	--	--	--	--	--	--	--	14	em7admin	2015-05-14 11:25:00	
18. Brocade Base Pack	7.3.6	ScienceLogic, Inc.	25	22	25	--	--	--	--	--	--	--	16	em7admin	2015-05-14 11:25:04	
19. Cabletron Systems Base Pack	1	ScienceLogic, Inc.	--	--	215	--	--	--	--	--	--	--	17	em7admin	2015-05-14 11:25:05	
20. Cisco CM Power-Pack	7.5.1	ScienceLogic, Inc.	26	27	29	21	23	--	21	--	--	--	19	em7admin	2015-05-14 11:25:10	
21. Cisco IPSLA	7.3.6	ScienceLogic, Inc.	210	251	--	--	--	--	21	--	--	--	20	em7admin	2015-05-14 11:25:13	
22. Cisco Nexus	7.6.1	ScienceLogic, Inc.	263	234	253	--	--	21	--	22	--	--	21	em7admin	2015-10-05 10:42:39	
23. Cisco Unity Pack	1.2	ScienceLogic, Inc.	22	26	--	--	--	--	--	--	--	--	22	em7admin	2015-05-14 11:25:19	
24. Cisco VPN Pack	1.1	ScienceLogic, Inc.	22	--	--	--	--	--	--	--	--	--	23	em7admin	2015-05-14 11:25:19	
25. Cisco ACI	0.5	ScienceLogic, Inc.	242	27	220	--	--	28	22	23	--	21	142	em7admin	2015-11-24 14:03:02	
26. Cisco ACI Dashboards	0.5	ScienceLogic, Inc.	--	--	--	--	--	28	--	--	--	--	151	em7admin	2015-07-31 17:22:49	
27. Cisco Base Pack	16.1	ScienceLogic, Inc.	211	225	21403	--	--	22	--	--	--	--	18	em7admin	2015-10-05 10:42:33	
28. Cisco Contact Center Enterprise	0.5	ScienceLogic, Inc.	254	233	219	--	--	--	--	--	--	--	182	em7admin	2015-12-14 13:50:50	
29. Cisco CUCM Cisco Unified Communications Manager	1.0	ScienceLogic, Inc.	212	231	252	--	--	223	--	21	--	--	21	149	em7admin	2015-08-28 14:28:51
30. Cisco CUCM Dashboards	1.0	ScienceLogic, Inc.	--	--	--	--	--	228	--	--	--	--	150	em7admin	2015-08-03 13:38:00	
31. Cisco TelePresence Endpoints	7.7.0	ScienceLogic, Inc.	210	285	247	--	--	--	--	--	--	--	24	em7admin	2015-10-28 13:28:18	
32. Cisco TelePresence Infrastructure	7.3.4	ScienceLogic, Inc.	220	223	215	--	--	--	--	--	--	--	25	em7admin	2015-05-14 11:25:27	
33. Cisco TelePresence Traps	7.3.0	ScienceLogic, Inc.	--	2371	--	--	--	--	--	--	--	--	26	em7admin	2015-05-14 11:25:28	
34. Cisco UCS	7.5.5	ScienceLogic, Inc.	244	257	29	--	--	--	21	--	--	27	em7admin	2015-06-02 18:30:52		
35. Citrix Base Pack	7.3.6	ScienceLogic, Inc.	212	218	--	--	--	--	--	--	--	--	28	em7admin	2015-05-14 11:25:30	

[Select Action] Go

Logic, Inc. All rights reserved.

2. Find the PowerPack you want to edit. Click its wrench icon ().

- In the **PowerPack Properties** page, in the Navbar on the left side, select the option for the content you want to remove.

The screenshot shows the 'Editing PowerPack™ Amazon Web Services' interface. On the left, a navigation menu is visible with 'Contents' selected. The main content area is titled 'Properties' and contains the following information:

- Name:** Amazon Web Services
- Version:** 113
- Publisher:** ScienceLogic, Inc.
- License Key:** TQYD+HMnSVaVQIMpTgahn/HZ5sMSzCQezfHwVzBJF9
- Creation:** em7admin [2013-04-15 21:01:15]
- Modification:** em7admin [2019-07-25 15:17:23]
- Revision:** 15765
- ID:** 41
- Description:** This PowerPack supports monitoring of Amazon Web Service account activities.
- Vendor(s) Supported:** Amazon Web Services, Inc.
- Model(s) Supported:** Amazon Web Services
- Version(s) Supported:** N/A
- Minimum EM7 Version:** 8.10.0

Below the properties is a 'Release Notes and Change Log' section for **Version 113:**

- Added new dynamic application AWS VPC NAT Gateway Instance Discovery.
- Added new dynamic application AWS VPC NAT Gateway Instance Configuration.
- Added new dynamic application AWS VPC NAT Gateway Instance Performance.
- Added new dynamic application AWS WAF Global Service Discovery.


A 'Save' button is located at the bottom of the release notes section.

**NOTE:** The entries under the **Contents** link are dependent upon your Access Hooks. An entry appears only if you have been granted an Access Key that contains the Access Hook that allows you to view the content-type in SL1. For example, the **Dynamic Applications** entry will appear under the **Contents** link only if you have permission to view the list of Dynamic Applications in the **Dynamic Applications Manager** page (System > Manage > Applications) in SL1.

- **Dynamic Applications.** Select this option to remove one or more Dynamic Applications from the PowerPack.
- **Event Policies.** Select this option to remove one or more event policies from the PowerPack.
- **Device Categories.** Select this option to remove one or more device categories from the PowerPack.
- **Device Classes.** Select this option to remove one or more device classes from the PowerPack.
- **Device Templates.** Select this option to remove one or more device templates from the PowerPack.
- **Reports.** Select this option to remove one or more custom reports from the PowerPack.
- **Dashboard Widgets.** Select this option to remove one or more custom dashboard-widgets from the PowerPack.
- **Dashboards.** Select this option to remove one or more dashboards or device dashboards from the PowerPack.
- **Run Book Policies.** Select this option to remove one or more custom run book policies from the PowerPack.

- **Run Book Actions.** Select this option to remove one or more custom run book actions from the PowerPack.
- **Run Book Action Types.** Select this option to remove one or more run book action types from the PowerPack.
- **Ticket Templates.** Select this option to remove one or more custom ticket templates from the PowerPack.
- **Credentials.** Select this option to remove one or more credentials from the PowerPack. If you delete an Embedded credential that is aligned to an organization you are not a member of, that credential will no longer be available to you.
- **Credential Tests.** Select this option to remove one or more credential tests from the PowerPack.
- **Proxy XSL Transformations.** Select this option to remove one or more Proxy XSL Transformations from the PowerPack.
- **UI Themes.** Select this option to remove one or more UI themes from the PowerPack.
- **IT Services.** Select this option to remove one or more IT Services from the PowerPack.
- **Log File Monitoring Policies.** Select this option to remove one or more log file monitoring policies from the PowerPack.
- **AP Content Objects.** Select this option to remove one or more AP content objects from the PowerPack.

4. In the **Embedded/Available** page for the content, go to the **Embedded** pane at the top of the page.



5. Find the content you want to remove from the PowerPack. Click the bomb icon (🧨) for that content. The content will be removed from the PowerPack and will now appear in the bottom pane.

© 2003 - 2019, ScienceLogic, Inc.

All rights reserved.

#### LIMITATION OF LIABILITY AND GENERAL DISCLAIMER

ALL INFORMATION AVAILABLE IN THIS GUIDE IS PROVIDED "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED. SCIENCELOGIC™ AND ITS SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT.

Although ScienceLogic™ has attempted to provide accurate information on this Site, information on this Site may contain inadvertent technical inaccuracies or typographical errors, and ScienceLogic™ assumes no responsibility for the accuracy of the information. Information may be changed or updated without notice. ScienceLogic™ may also make improvements and / or changes in the products or services described in this Site at any time without notice.

#### Copyrights and Trademarks

ScienceLogic, the ScienceLogic logo, and EM7 are trademarks of ScienceLogic, Inc. in the United States, other countries, or both.

Below is a list of trademarks and service marks that should be credited to ScienceLogic, Inc. The ® and ™ symbols reflect the trademark registration status in the U.S. Patent and Trademark Office and may not be appropriate for materials to be distributed outside the United States.

- ScienceLogic™
- EM7™ and em7™
- Simplify IT™
- Dynamic Application™
- Relational Infrastructure Management™

The absence of a product or service name, slogan or logo from this list does not constitute a waiver of ScienceLogic's trademark or other intellectual property rights concerning that name, slogan, or logo.

Please note that laws concerning use of trademarks or product names vary by country. Always consult a local attorney for additional guidance.

#### Other

If any provision of this agreement shall be unlawful, void, or for any reason unenforceable, then that provision shall be deemed severable from this agreement and shall not affect the validity and enforceability of any remaining provisions. This is the entire agreement between the parties relating to the matters contained herein.

In the U.S. and other jurisdictions, trademark owners have a duty to police the use of their marks. Therefore, if you become aware of any improper use of ScienceLogic Trademarks, including infringement or counterfeiting by third parties, report them to Science Logic's legal department immediately. Report as much detail as possible about the misuse, including the name of the party, contact information, and copies or photographs of the potential misuse to: [legal@sciencelogic.com](mailto:legal@sciencelogic.com)



800-SCI-LOGIC (1-800-724-5644)

International: +1-703-354-1010