



---

# ServiceNow Incident Synchronization PowerPack

Version 3.0.0

---

# Table of Contents

<b>Introduction to the ServiceNow Incident Synchronization PowerPack</b> .....	<b>7</b>
Architecture Overview for ServiceNow Synchronization PowerPacks .....	9
SL1 and ServiceNow Terminology .....	10
Dependency Map for ServiceNow Synchronization PowerPacks .....	10
Prerequisites for ServiceNow Synchronization PowerPacks .....	11
Contents of the Synchronization PowerPack .....	12
PowerFlow Applications .....	12
PowerFlow Application (Internal) .....	12
<b>Installing and Configuring the Incident Synchronization PowerPack</b> .....	<b>13</b>
Downloading, Importing, and Installing the ServiceNow Incident Synchronization PowerPack .....	14
Downloading the Synchronization PowerPack .....	14
Importing the Synchronization PowerPack .....	14
Installing the Synchronization PowerPack .....	15
Allowing Cross-Scoped Access in ServiceNow .....	16
Installing the ScienceLogic SL1: CMDB & Incident Automation Application in ServiceNow .....	18
Installing the ServiceNow Base Pack PowerPack in SL1 .....	19
Validating Network Communications .....	20
Checking DNS .....	20
Checking HTTPS and JSON .....	21
HTTP Codes .....	21
Creating a ServiceNow Group .....	22
Creating a ServiceNow User .....	24
<b>Configuring Integrations for the Incident Synchronization PowerPack</b> .....	<b>26</b>
Event Data Flow Between PowerFlow and ServiceNow .....	28
Event Data Flow: PowerFlow to ServiceNow .....	28
Event Data Flow: SL1 to PowerFlow .....	30
Overview of the Run Book Automation for Incident Sync .....	31
Configuring Incident Sync .....	33
Creating and Aligning a Configuration Object .....	33
Creating a Configuration Object .....	34
Aligning a Configuration Object .....	36
Creating a ServiceNow Credential in SL1 .....	38
Enabling the Run Book Automation Policies .....	40
Enabling and Customizing the Run Book Action Policy .....	42
Customizing the Snippet Code in the Input Parameters Pane .....	43
Customizing Logging in the Run Book Action .....	46
Sending Custom Data to ServiceNow Using the Passthrough Option .....	46
Passing Custom Data to ServiceNow .....	47
Snippet Code Example .....	49
Configuring the "ServiceNow: Click to Create Incident" Automation Policy .....	50
Viewing Incidents and Events .....	52
Incident Topology Suppression .....	54
Hyperlinking Events .....	59
ServiceNow Hyperlinking .....	60
Viewing the Incident Import Table in ServiceNow .....	60
ServiceNow, ScienceLogic Event, and Incident Priority Matrix .....	62
Adding Additional Fields to the Transform Map .....	63
<b>Troubleshooting the Incident Synchronization PowerPack</b> .....	<b>69</b>
Initial Troubleshooting Steps .....	70
SL1 PowerFlow .....	70

ServiceNow .....	70
Resources for Troubleshooting .....	70
Useful PowerFlow Ports .....	70
Helpful Docker Commands .....	71
Viewing Container Versions and Status .....	71
Restarting a Service .....	71
Stopping all PowerFlow Services .....	71
Restarting Docker .....	71
Viewing Logs for a Specific Service .....	72
Clearing RabbitMQ Volume .....	72
Viewing the Process Status of All Services .....	73
Deploying Services from a Defined Docker Compose File .....	73
Dynamically Scaling for More Workers .....	73
Completely Removing Services from Running .....	73
Diagnosis Tools .....	73
Retrieving Additional Debug Information (Debug Mode) .....	74
Frequently Asked Questions .....	75
Why are Incidents not getting created in ServiceNow? .....	75
What if my Incident does not have a CI? .....	76
What if the PowerFlow user interface is unresponsive and Incidents are not being generated in ServiceNow? .....	77
Why are Incident numbers not populated in SL1 on Incident creation in ServiceNow? .....	77
Why am I not getting any Incidents after disabling the firewall? .....	77
<b>Checklists for Deployment .....</b>	<b>78</b>
CMDB-Only ServiceNow Integration with Single SL1, no Domain Separation in ServiceNow .....	79
Sync Devices from SL1 to ServiceNow .....	79
Discover Devices from ServiceNow in SL1 .....	80
Sync Business Services from SL1 to ServiceNow .....	80
Sync File Systems from SL1 to ServiceNow .....	80
Sync Network Interfaces from SL1 to ServiceNow .....	80
Sync Installed Software from SL1 to ServiceNow .....	81
Sync Maintenance Schedules from ServiceNow to SL1 .....	81
Sync Advanced Topology from SL1 to ServiceNow .....	81
CMDB-Only ServiceNow Integration with Single SL1 and Domain-Separated ServiceNow .....	82
Sync Devices from SL1 to ServiceNow .....	82
Discover Devices from ServiceNow in SL1 .....	83
Sync Business Services from SL1 to ServiceNow .....	83
Sync File Systems from SL1 to ServiceNow .....	84
Sync Network Interfaces from SL1 to ServiceNow .....	84
Sync Installed Software from SL1 to ServiceNow .....	84
Sync Maintenance Schedules from ServiceNow to SL1 .....	84
Sync Advanced Topology from SL1 to ServiceNow .....	85
CMDB-Only ServiceNow Integration with Multiple SL1 Systems, no Domain-Separated ServiceNow .....	86
Sync Devices from SL1 to ServiceNow .....	87
Discover Devices from ServiceNow in SL1 .....	87
Sync Business Services from SL1 to ServiceNow .....	88
Sync File Systems from SL1 to ServiceNow .....	88
Sync Network Interfaces from SL1 to ServiceNow .....	88
Sync Installed Software from SL1 to ServiceNow .....	89
Sync Maintenance Schedules from ServiceNow to SL1 .....	89
Sync Advanced Topology from SL1 to ServiceNow .....	89
Incident-Only ServiceNow Integration with Single SL1, no Domain Separation in ServiceNow .....	90

<b>Certified Application Objects</b> .....	<b>91</b>
Roles .....	92
Tables .....	93
Table Columns (cmdb_ci) .....	93
Table Columns (core_company) .....	94
Table Columns (cmdb_group) .....	94
Script Includes .....	94
Event Registry .....	94
Scripted Actions .....	95
Data Lookup Definitions .....	95
System Properties .....	95
Catalog Item .....	96
Catalog UI Policies .....	96
Variable Sets .....	96
Catalog Client Scripts .....	97
Workflows .....	97
Scripted REST Resources .....	98
Transform Maps .....	100
Transform Scripts .....	100
<b>ServiceNow API Endpoints</b> .....	<b>101</b>
Business Services .....	103
HTTP Method .....	103
Pagination .....	103
Resource Path .....	103
Default Resource Path .....	103
Example (Request URL) .....	103
Example (Response) .....	104
Change Requests .....	105
HTTP Method .....	105
Resource Path .....	105
Default Resource Path .....	105
Fixed Internal Query .....	106
Example .....	106
Example (Response) .....	106
Classification version 1 .....	107
HTTP Method .....	107
Pagination .....	107
Resource Path .....	107
Default Resource Path .....	107
Fixed Internal Query .....	108
Example .....	108
Example (Response) .....	108
Classification version 2 .....	110
HTTP Method .....	110
Pagination .....	110
Resource Path .....	110
Default Resource Path .....	110
Fixed Internal Query .....	111
Example .....	111
Example (Response) .....	111
CMDB Group .....	113
HTTP Method .....	113

Pagination .....	113
Resource Path .....	113
Default Resource Path .....	113
Example (Request URL) .....	113
Example (Body) .....	113
Example (Response) .....	114
Companies .....	115
HTTP Method .....	115
Pagination .....	115
Resource Path .....	115
Default Resource Path .....	115
Fixed Internal Query .....	116
Example .....	116
Example (Response) .....	116
Device Identification Engine .....	118
HTTP Method .....	118
Pagination .....	118
Resource Path .....	118
Default Resource Path .....	118
Example (Request URL) .....	118
Example (Body) .....	118
Example Business Service (Body) .....	119
Example (Response) .....	120
Discovery Dependents .....	121
HTTP Method .....	121
Pagination .....	121
Resource Path .....	121
Default Resource Path .....	121
Fixed Internal Query .....	122
Example .....	122
Example (Response) .....	122
File Systems .....	123
HTTP Method .....	123
Pagination .....	123
Resource Path .....	123
Default Resource Path .....	123
Fixed Internal Query .....	124
Example .....	124
Example (Response) .....	124
Import Set .....	125
HTTP Method .....	125
Resource Path .....	125
Default Resource Path .....	125
Example (Request URL) .....	125
Example (Body) .....	125
Incidents .....	127
HTTP Method .....	127
Pagination .....	127
Resource Path .....	127
Default Resource Path .....	127
Fixed Internal Query .....	128
Example .....	128

Example (Response) .....	128
Installed Software .....	130
HTTP Method .....	130
Pagination .....	130
Resource Path .....	130
Default Resource Path .....	130
Fixed Internal Query .....	131
Example (Request URL) .....	131
Manufacturer .....	133
HTTP Method .....	133
Pagination .....	133
Resource Path .....	133
Default Resource Path .....	133
Example (Request URL) .....	133
Example (Body) .....	133
Example (Response) .....	134
Model .....	135
HTTP Method .....	135
Resource Path .....	135
Default Resource Path .....	135
Example (Request URL) .....	135
Example (Body) .....	135
Example (Response) .....	136
Network Adapters .....	137
HTTP Method .....	137
Pagination .....	137
Resource Path .....	137
Default Resource Path .....	137
Fixed Internal Query .....	138
Example (Request URL) .....	138
Example (Response) .....	138
Service Requests .....	139
HTTP Method .....	139
Pagination .....	139
Resource Path .....	139
Default Resource Path .....	139
Fixed Internal Query .....	140
Example .....	140
Example (Response) .....	140

---

# Chapter

# 1

## Introduction to the ServiceNow Incident Synchronization PowerPack

---

### Overview

This chapter describes the *ServiceNow Incident Synchronization PowerPack*, which is the ScienceLogic integration with the ServiceNow Incident Management Module.

This Synchronization PowerPack automatically logs, de-duplicates, correlates, updates, and appends ServiceNow Incidents, reducing the amount of time to resolve critical service issues. This Synchronization PowerPack covers the entire Incident life cycle, providing a bi-directional integration between SL1 events and ServiceNow Incidents, while providing a granular view into both the event and the associated Incident.

**WARNING:** You should not use the *ServiceNow Incident Synchronization PowerPack* and the *ServiceNow Events Synchronization PowerPack* on the same PowerFlow system.

**NOTE:** After the 2.1.0 release of the Integration Service platform, the *Integration Service* was rebranded as *SL1 PowerFlow*, which is available in SL1 Standard solutions. Also, the *Automation Builder* was rebranded as *SL1 PowerFlow builder*, which is available in SL1 Premium solutions.

**NOTE:** The label "SyncPack" is used in place of "Synchronization PowerPack" in the PowerFlow user interface.


This chapter covers the following topics:

<a href="#">Architecture Overview for ServiceNow Synchronization PowerPacks</a> .....	9
<a href="#">SL1 and ServiceNow Terminology</a> .....	10


<i>Dependency Map for ServiceNow Synchronization PowerPacks</i> .....	10
<i>Prerequisites for ServiceNow Synchronization PowerPacks</i> .....	11
<i>Contents of the Synchronization PowerPack</i> .....	12

# Architecture Overview for ServiceNow Synchronization PowerPacks

The following diagram details the various elements that are contained in SL1 and the PowerFlow system, and how PowerFlow sits between the core SL1 platform and an external data platform:



The following diagram provides an example of the high-level architecture of a PowerFlow system with High Availability, Disaster Recovery, and a proxy configured:



---

## SL1 and ServiceNow Terminology


The following table lists the different names for the shared elements in SL1 and ServiceNow:

SL1	ServiceNow
Device	CI (Configuration Item)
Discovery Session	Service Catalog Request
Event	Incident
Alert	Event
Organization	Company or Domain
Schedule	Maintenance Schedule
Topology	Dependency

---

## Dependency Map for ServiceNow Synchronization PowerPacks

The following graphic describes which Synchronization PowerPacks depend on other Synchronization PowerPacks:



**TIP:** For more information about the Standard *Base Steps* Synchronization PowerPack, see the *SL1 PowerFlow Platform* manual.

# Prerequisites for ServiceNow Synchronization PowerPacks

This section describes the prerequisites for the ServiceNow Synchronization PowerPacks. For more information about the specific software versions required by a ServiceNow Synchronization PowerPack, see the release notes for that Synchronization PowerPack.

To install any of the ScienceLogic ServiceNow Synchronization PowerPacks, you must have administrator access to both SL1 and ServiceNow. Specifically, you will need:

- ScienceLogic administrator access to the Administration Portal
- ServiceNow administrator access

Additional information related to uploading, installing, and upgrading the ServiceNow Synchronization PowerPacks:

- If you want to upload and install multiple ServiceNow Synchronization PowerPacks at the same time, you should upload *all* of the Synchronization PowerPacks first, and then install them to address any dependencies between the Synchronization PowerPacks.
- If you are upgrading from version 1.8.4 of PowerFlow (formerly called the "Integration Service"), you can first move to version 2.5.0 of the ServiceNow Synchronization PowerPack, then upgrade to version 2.0 of the PowerFlow platform, and finally move to version 3.0.0 or later of the relevant ServiceNow Synchronization PowerPacks.
- If you made customizations to version 2.5.0 or earlier of the ServiceNow Synchronization PowerPack, you must make a copy of that Synchronization PowerPack and save it as a new Synchronization PowerPack to keep your customizations. For more information, see the **SL1 PowerFlow for Developers** manual.
- If you are starting out with version 2.0.0 of the PowerFlow platform, you should skip version 2.5.0 of the ServiceNow Synchronization PowerPack and instead install version 3.0.0 of the relevant ServiceNow Synchronization PowerPacks.
- There is no backwards compatibility after you upgrade a ServiceNow Synchronization PowerPack from version 2.5.0 to 3.0.0.

The following table lists the port access required by PowerFlow and this Synchronization PowerPack:

Source IP	PowerFlow Destination	PowerFlow Source Port	Destination Port	Requirement
PowerFlow	SL1 API	Any	TCP 443	SL1 API Access
PowerFlow	ServiceNow API	Any	TCP 443	ServiceNow API Access
SL1 Run Book Action	PowerFlow	Any	TCP 443	Send SL1 data to PowerFlow
PowerFlow	SL1 Database	Any	TCP 7706	SL1 Database Access

---

# Contents of the Synchronization PowerPack

This section lists the contents of the *ServiceNow Incident Synchronization PowerPack*.

## PowerFlow Applications

The following PowerFlow applications are included with the *ServiceNow Incident Synchronization PowerPack*:

- **Create or Update ServiceNow Incident from SL1 Event.** Reads SL1 events and creates or updates the corresponding ServiceNow Incident.
- **Sync Incident State from ServiceNow to SL1 Event.** Clears or updates SL1 events when the related ServiceNow Incident is updated.
- **Update ServiceNow Incident when SL1 Event is Acknowledged.** Updates the synced ServiceNow incident when the corresponding SL1 event is acknowledged.
- **Update ServiceNow Incident when SL1 Event is Cleared.** Updates the synced ServiceNow Incident when the corresponding SL1 event is cleared.

## PowerFlow Application (Internal)

To view the internal PowerFlow application, click the Filter icon () on the **Applications** page and select *Show Hidden Applications*. Internal applications are hidden by default. The following application is "internal" and should not be run directly. Instead, it is automatically run by applications from the previous list:

- **Bulk Update SL1 Events.** Bulk updates SL1 events with a given payload.

## Installing and Configuring the Incident Synchronization PowerPack

---

### Overview

This chapter describes the how to install and configure the *ServiceNow Incident Synchronization PowerPack* and the components used by the Synchronization PowerPack.

The following workflow covers how to install and configure this Synchronization PowerPack:

1. In PowerFlow, download, import, and install the *ServiceNow Incident Synchronization PowerPack*.
2. In ServiceNow, enable cross-scoped access and install the "ScienceLogic SL1 : CMDB & Incident Automation" application.
3. In SL1, install the *ServiceNow Base Pack PowerPack*.
4. Validate network communications.
5. In ServiceNow, create a ServiceNow group and user account.

These installation and configuration steps are covered in the following topics:

<a href="#">Downloading, Importing, and Installing the ServiceNow Incident Synchronization PowerPack</a>	14
<a href="#">Allowing Cross-Scoped Access in ServiceNow</a>	16
<a href="#">Installing the ScienceLogic SL1: CMDB &amp; Incident Automation Application in ServiceNow</a>	18
<a href="#">Installing the ServiceNow Base Pack PowerPack in SL1</a>	19
<a href="#">Validating Network Communications</a>	20
<a href="#">Creating a ServiceNow Group</a>	22
<a href="#">Creating a ServiceNow User</a>	24

---

# Downloading, Importing, and Installing the ServiceNow Incident Synchronization PowerPack

A Synchronization PowerPack file has the **.whl** file extension type. You can download the Synchronization PowerPack file from the ScienceLogic Support site.

**WARNING:** If you are *upgrading* to this version of the Synchronization PowerPack from a previous version, make a note of any settings you made on the **Configuration** pane of the various PowerFlow applications in this Synchronization PowerPack, as these settings are *not* retained when you upgrade.

## Downloading the Synchronization PowerPack

A Synchronization PowerPack file has the **.whl** file extension type. You can download the Synchronization PowerPack file from the ScienceLogic Support site.

To locate and download the Synchronization PowerPack:

1. Go to the ScienceLogic Support site at <https://support.sciencelogic.com/s/>.
2. Click the **Product Downloads** tab, select *PowerPacks*, and then click the "Synchronization" link. The **Synchronization PowerPack Downloads** page appears.
3. Click the name of the Synchronization PowerPack you want to install. The **PowerPack** page appears.
4. In the **Files** list, locate the Synchronization PowerPack **.whl** file, click the down arrow button, and select *Download*.

**NOTE:** Synchronization PowerPacks do not require a specific license. After you download a Synchronization PowerPack, you can import it to your PowerFlow system using the PowerFlow user interface.

**NOTE:** If you are installing or upgrading to the latest version of this Synchronization PowerPack in an offline deployment, see "Installing or Upgrading in an Offline Environment" in the release notes for this Synchronization PowerPack to ensure you install any external dependencies.

## Importing the Synchronization PowerPack

To import a Synchronization PowerPack in the PowerFlow user interface:

1. On the **SyncPacks** page of the PowerFlow user interface, click **[Import SyncPack]**. The **Import SyncPack** page appears.
2. Click **[Browse]** and select the **.whl** file for the Synchronization PowerPack you want to install.

**TIP:** You can also drag and drop a **.whl** file to the **SyncPacks** page.

3. Click **[Import]**. PowerFlow registers and uploads the Synchronization PowerPack. The Synchronization PowerPack is added to the **SyncPacks** page.

**NOTE:** You cannot edit the content package in a Synchronization PowerPack published by ScienceLogic. You must make a copy of a ScienceLogic Synchronization PowerPack and save your changes to the new Synchronization PowerPack to prevent overwriting any information in the original Synchronization PowerPack when upgrading.

## Installing the Synchronization PowerPack

**NOTE:** You must import and install the *ServiceNow Base Synchronization PowerPack* before uploading and installing any of the other ServiceNow Synchronization PowerPacks.

To install a Synchronization PowerPack in the PowerFlow user interface:

1. On the **SyncPacks** page of the PowerFlow user interface, click the **[Actions]** button (  ) for the Synchronization PowerPack you want to install and select *Activate & Install*. The **Activate & Install SyncPack** modal appears.

**TIP:** By default, the **SyncPacks** page displays only activated and installed PowerPacks. If you do not see the PowerPack that you want to install, click the Filter icon (  ) on the **SyncPacks** page and select *Show All SyncPacks* to see a list of the uninstalled PowerPacks.

2. Click **[Yes]** to confirm the activation and installation. When the Synchronization PowerPack is activated, the **SyncPacks** page displays a green check mark icon (  ) for that Synchronization PowerPack. If the activation or installation failed, then a red exclamation mark icon (  ) appears.

**TIP:** While the Synchronization PowerPack is installing, you cannot click any of the options that appear when you click the **[Actions]** button (  ).

3. For more information about the activation and installation process, click the check mark icon (  ) or the exclamation mark icon (  ) in the **Activated** column for that Synchronization PowerPack. For a successful installation, the "Activate & Install SyncPack" application appears, and you can view the Step Log for the steps. For a failed installation, the **Error Logs** window appears.

---

## Allowing Cross-Scoped Access in ServiceNow

When using custom tables that are extended from the **cmdb\_ci** table, you must configure cross-scope access for any custom tables created outside of the base ServiceNow deployment.

The following examples contain errors that might occur when cross-scope access is required.

Example of an API response:

```
{"results":[{"error":  
{"message":"com.glide.script.fencing.access.ScopeAccessNotGrantedException: read  
access to ui_test_hardware not granted","detail":""},"status":"failure"}]}
```

Example of navigating to a URL directly from a web browser when cross-scope access is required:




In this example, the table requires that you grant access to the ScienceLogic Scope to allow the API call to run correctly. In the above example, the target table is **u\_test\_hardware**.

**NOTE:** A ServiceNow account with System Administrator is required.

To grant access to the ScienceLogic Scope in ServiceNow:


1. Log in to your ServiceNow instance.
2. Click the **Settings** icon (⚙️) and select the **Developer** tab. The **Developer System Settings** window appears:



3. From the **Application** drop-down list, select *ScienceLogic ServiceNow Integration*.
4. Close the **Developer System Settings** window and navigate to the **Cross scope privileges** page (System Applications > Application Cross-Scope Access).

**NOTE:** Make sure you are in the ScienceLogic ServiceNow Application scope and track these updates in an update set.

5. Click the **[New]** button to create a new record on the **Cross scope privileges** page:



6. Verify that the **Source Scope** and **Application** fields are set to *ScienceLogic ServiceNow Integration*. If they are not, repeats steps 2-3.
7. Complete the following fields:
  - **Target Scope**. Specify the scope of the target table, such as *Global*.
  - **Operation**. Select *Read*.
  - **Target Name**. Specify the name of the target table.
  - **Status**. Select *Allowed*.
  - **Target Type**. Select *Table*.
8. Click the **[Submit]** button.

For more information, see [https://docs.servicenow.com/bundle/madrid-application-development/page/build/applications/reference/c\\_CrossScopePrivilegeRecord.html](https://docs.servicenow.com/bundle/madrid-application-development/page/build/applications/reference/c_CrossScopePrivilegeRecord.html).

---

## Installing the ScienceLogic SL1: CMDB & Incident Automation Application in ServiceNow

The *ServiceNow Incident Synchronization PowerPack* uses the "ScienceLogic SL1: CMDB & Incident Automation Application" to sync incident status update from ServiceNow back to SL1.

You must install the "ScienceLogic SL1: CMDB & Incident Automation" application on your ServiceNow instance to enable this Synchronization PowerPack. The "ScienceLogic SL1: CMDB & Incident Automation" application is also known as the "Certified Application" or the "Scoped Application".

**NOTE:** You must have a ServiceNow HI Service Account to request this application and download it onto your ServiceNow instance.

**WARNING:** PowerFlow instances running version 2.0.0 or later of the ServiceNow applications are not backwards-compatible with the previous ServiceNow update sets or with SyncServer. After you install the "ScienceLogic SL1: CMDB & Incident Automation" application on your ServiceNow instance, you need to upgrade your ServiceNow applications to version 2.0.0 or later on all PowerFlow instances. The "ScienceLogic SL1: CMDB & Incident Automation" application is also not backwards-compatible with SyncServer. This change cannot be reverted.

You must first request the "ScienceLogic SL1: CMDB & Incident Automation" application from the ServiceNow Store, and then you can install it.

To request and install the Certified Application:

1. Go to the ServiceNow Store at <https://store.servicenow.com> and search for "ScienceLogic SL1".
2. Select the "ScienceLogic SL1: CMDB & Incident Automation" application. The detail page for the application appears.
3. Click the **[Get]** button and log in with your HI credentials.
4. After the request is approved, log in to ServiceNow as an administrator and navigate to **Application Manager** (System Applications > Applications or My Company Applications).
5. Click **[Downloads]** in the menu header or search for "ScienceLogic".
6. Click the version drop-down for the "ScienceLogic ServiceNow Integration" application listing to make sure you are using the correct version of the application that is compatible with your version of this Synchronization PowerPack.
7. Click the **[Install]** button for the "ScienceLogic ServiceNow Integration" application. The installation is complete when the button changes to **[Installed]**.
8. In the filter navigator, search for "ScienceLogic" and locate the application in the left-hand navigation menu to verify that the application was installed.

---

## Installing the ServiceNow Base Pack PowerPack in SL1

The *ServiceNow Base Pack PowerPack* monitors the ServiceNow Incident and CMDB tables, and it returns information about Incident types, priorities, and states, displaying the information in an easy-to-consume dashboard. The PowerPack also returns information about the CI records that are actively being synced between SL1 and ServiceNow with PowerFlow, including basic CI metadata as well as an overall count.

Also, this PowerPack is a critical component of the Incident Sync Integration with ServiceNow, using Run Book Automations to integrate with the ServiceNow Incident Management module.

**TIP:** By default, installing a new version of a PowerPack overwrites all content in that PowerPack that has already been installed on the target system. You can use the **Enable Selective PowerPack Field Protection** setting in the **Behavior Settings** page (System > Settings > Behavior) to prevent new PowerPacks from overwriting local changes for some commonly customized fields. For more information, see the **System Administration** manual.

To install the *ServiceNow Base Pack* PowerPack:

1. Download the latest version of the PowerPack from the Customer Portal to a local computer.
2. In SL1, log in and go to the **PowerPack Manager** page (System > Manage > PowerPacks).
3. Click **[Actions]** and select *Import PowerPack*.
4. Click **[Browse]** and navigate to the *ServiceNow Base Pack* PowerPack file from step 1.
5. Select the PowerPack file and click **[Import]**. The **PowerPack Installer** modal page displays a list of the PowerPack contents.

6. Click **[Install]**. After the installation is complete, the *ServiceNow Base Pack PowerPack* appears on the **PowerPack Manager** page.

---

## Validating Network Communications

All communication between SL1 and ServiceNow is done through TCP port 443. To allow communication between SL1 and ServiceNow, the SL1 Database Server, Data Collector, or All-In-One Appliance must have external access to the ServiceNow instance. No inbound TCP ports are required to be open to the SL1 server. Outbound communication may use NAT or be direct.

**NOTE:** All firewall session-limiting policies must be disabled. If firewall session-limiting policies are enabled, HTTPS requests might be dropped by the firewall, resulting in data loss. Check with your security or firewall administrator to make sure there are no session limiting policies on TCP port 443 for your SL1 servers.

## Checking DNS

Because ServiceNow is a cloud-based service, DNS must be configured on all SL1 servers that communicate with your ServiceNow instance.

**NOTE:** ServiceNow instances are generally named as: ***your-instance.service-now.com***, where ***your-instance*** is the name of your ServiceNow server. The examples below use ***mycompany.service-now.com***. Your instance name will be unique to your subscription.

To validate that your SL1 server has proper DNS name resolution configured, test network connectivity and name resolution using the `nmap` command, which is available from the command line of any SL1 server:

```
nmap -sT -p 443 mycompany.service-now.com
```

If the test was successful, you will see a message similar to the following:

```
Starting Nmap 5.51 ( http://nmap.org ) at 2013-11-12 20:22 UTC
Nmap scan report for mycompany.service-now.com (199.91.136.100)
Host is up (0.067s latency).
PORT STATE SERVICE
443/tcp open  https
```

If domain name resolution fails, you will see a message similar to:

```
Failed to resolve given hostname/IP: mycompany.service-now.com.
```

## Checking HTTPS and JSON

You can administer a simple test to determine if the ServiceNow JSON Plug-in web service is configured and operating using the Basic Authentication method on your ServiceNow instance. To do so, run the following command from the ScienceLogic Central Database or All-In-One Appliance:

**NOTE:** In the example below, replace the `admin:admin` username and password key/value pair with your ServiceNow administrator username and password and `mycompany.service-now.com` with your ServiceNow instance name.

```
curl --location -vu admin:admin -H "Accept: application/json" -H "Content-Type: application/json" 'https://mycompany.service-now.com/api/now/table/incident'
```

If not successful, the following message appears:

```
HTTP/1.1 401 Unauthorized
```

If successful, a JSON encoded string starting with the "result" variable appears:

```
{"result":[{"upon_approval":"","location":"1083361cc611227501b682158cabf646"},...
```

## HTTP Codes

HTTP codes are necessary for identifying specific problems. The following table lists typical HTTP codes that might occur when testing the ServiceNow JSON Web Service.

Code	Definition
401	Unauthorized. Check that the username and password are correct and properly formatted.
403	Forbidden. ServiceNow understood the request, but either the URL is incorrect, or the user account does not have permission to see the requested object.
404	The ServiceNow server has not found anything matching the requested URL. Check to make sure there is data in the target table.
200	Success.
201	Success. Data is posted.


**TIP:** For more information about the ServiceNow JSON Web Service and the Table API, see [http://wiki.servicenow.com/index.php?title=Table\\_API](http://wiki.servicenow.com/index.php?title=Table_API). If you continue to have problems, please contact either ScienceLogic or ServiceNow customer support.

# Creating a ServiceNow Group

For best practice and security, create a dedicated ServiceNow account that has restricted access to only the groups, access control lists (ACLs), and roles needed for ScienceLogic incident management.


To create a ServiceNow Account for ScienceLogic Incident management:

1. In ServiceNow, search in the filter navigator for "groups".
2. On the **Groups** page (System Security > Groups), click **[New]**. A **New record** page appears.
3. In the **New record** page, type the group name and any additional information. **Name** is the only required field:




The screenshot shows the 'New record' form for a Group in ServiceNow. The form has a header with a back arrow, a hamburger menu, the text 'Group New record', and icons for edit, list, and a 'Submit' button. The main form area contains several input fields: 'Name' with the value 'Scienelogic Service Accounts', 'Group email' (empty), 'Manager' with the value 'System Administrator', and 'Parent' (empty). There is also a 'Description' text area. A 'Submit' button is located at the bottom left of the form.

4. Right-click the gray header and click Save to save the record.



The screenshot shows the same 'New record' form as above, but with a context menu open over the header area. The menu options are: Save, Configure, Export, Create Favorite, Copy URL, Copy sys\_id, and Reload form. The 'Save' option is highlighted.

5. At the bottom of the Group form, select the **[Roles]** tab and click **[Edit:]**



The screenshot shows the 'Roles' tab for the Group 'Scienelogic Service Accounts'. The page has a header with 'Roles', 'Edit...', 'Go to', 'Created', and a search bar. Below the header, there is a filter icon and a table with columns for 'Created', 'Role', 'Granted by', and 'Inherits'. The table is currently empty, displaying 'No records to display'.

6. Search for `x_sclo_scilogic.Admin` and move it to the **Roles List** column using the arrow buttons:

The screenshot shows a role assignment interface with two main panes: 'Collection' and 'Roles List'. The 'Collection' pane contains a search bar and a list of roles. The 'Roles List' pane contains the roles assigned to the group. The role 'x\_sclo\_scilogic.Admin' is highlighted in red in the 'Roles List' pane.

Collection	Roles List
action_designer	x_sclo_scilogic.Admin
activity_admin	
activity_creator	
admin	
agent_admin	
announcement_admin	
api_analytics_read	
app_service_admin	
app_service_user	
approval_admin	
approver_user	
assessment_admin	
asset	
assignment_rule_admin	
atf_test_admin	
atf_test_designer	

7. Click **[Save]**. Your ServiceNow Group now has an assigned Role:

The screenshot shows the 'IS4 - Service Accounts' group configuration page. The 'Roles' tab is selected, and a table lists the assigned roles. The role 'x\_sclo\_scilogic.Admin' is highlighted with a red box.

Created	Role	Granted by	Inherits
2019-01-15 12:09:31	x_sclo_scilogic.Admin	(empty)	true

8. Next, create a ServiceNow user to use with this Group. See the following procedure for the details.

## Creating a ServiceNow User

**NOTE:** The ServiceNow user you create in this procedure will *not* be able to log into the ServiceNow user interface with the username and password you give this user. However, you will use the username and password in the relevant configuration objects in the PowerFlow user interface to run applications. For more information about configuration objects, see [Creating and Aligning a Configuration Object](#).

To create a ServiceNow Account for ScienceLogic Incident management:

1. In ServiceNow, search in the filter navigator for "users".
2. On the **Users** page (System Security > Users), click **[New]**. A **New record** page appears.
3. Complete the following fields:
  - **User ID**. Type a user ID. Required.
  - **First Name**. Type the user's first name.
  - **Last Name**. Type the user's last name.
  - **Password**. Type a password. Required.
  - **Active**. Select this checkbox. Required.
  - **Web Service Access Only**. Select this checkbox. Required.
  - **Time Zone**. Select *GMT*. Required.
  - **Date Format**. Select *System (yyyy-MM-dd)*.
4. Right-click the gray header and click **Save** to save the user.
5. Select the **[Groups]** tab at the bottom of the record and click the **[Edit]** button:



6. Find the group you created previously and move the group to the right-hand column using the arrow buttons:

Collection

Groups List

Service Account

sciencelogic

--None--

Sciencelogic Service Accounts

>

<

Cancel Save

Name Sciencelogic Service Accounts

7. Click **[Save]**. After the user has been added to the group, you can see their Roles and Groups at bottom of the record:

Roles (18) Groups (1) Delegates Subscriptions Manage Subscriptions

Roles Edit... Go to Role Search

1 to 18 of 18

**NOTE:** As a best practice, you should use a non-administrator ServiceNow user for the PowerFlow configuration object.

## Configuring Integrations for the Incident Synchronization PowerPack

---

### Overview

This chapter describes the how to configure and run the various PowerFlow applications and SL1 Run Book Automations contained in the *ServiceNow Incident Synchronization PowerPack*.

A **PowerFlow application** is a JSON object that includes all the information required for executing an integration on the PowerFlow platform. In this Synchronization PowerPack, the applications are aligned with an **SL1 Run Book Automation** that you can configure to ensure that whenever SL1 detects a new, acknowledged, or cleared Event, a corresponding Incident is created or updated in ServiceNow.

This chapter covers the following topics:


<i>Event Data Flow Between PowerFlow and ServiceNow</i> .....	28
<i>Overview of the Run Book Automation for Incident Sync</i> .....	31
<i>Configuring Incident Sync</i> .....	33
<i>Creating and Aligning a Configuration Object</i> .....	33
<i>Creating a ServiceNow Credential in SL1</i> .....	38
<i>Enabling the Run Book Automation Policies</i> .....	40
<i>Enabling and Customizing the Run Book Action Policy</i> .....	42
<i>Sending Custom Data to ServiceNow Using the Passthrough Option</i> .....	46
<i>Configuring the "ServiceNow: Click to Create Incident" Automation Policy</i> .....	50
<i>Viewing Incidents and Events</i> .....	52
<i>Incident Topology Suppression</i> .....	54
<i>Hyperlinking Events</i> .....	59

<i>Viewing the Incident Import Table in ServiceNow</i> .....	60
<i>ServiceNow, ScienceLogic Event, and Incident Priority Matrix</i> .....	62
<i>Adding Additional Fields to the Transform Map</i> .....	63

# Event Data Flow Between PowerFlow and ServiceNow

## Event Data Flow: PowerFlow to ServiceNow

The following chart and steps illustrate the event data flow from PowerFlow to a ServiceNow instance:



1. Workers are subscribed to the PowerFlow (IS) task queue.
2. When a new event to be synced is placed in the PowerFlow task queue, it is assigned and pushed to a worker.
3. The worker processes and transforms the necessary SL1 event data into a ServiceNow incident and POSTs the incident to the ServiceNow endpoint.
  - If the resulting status code matches the expected status code for the request, the original message is acknowledged and removed from the queue.
  - If the worker crashes while processing the event, the queue senses the unexpected disconnect, and the same event message is re-delivered to a new worker.


**NOTE:** The above results are performed through the "late acknowledgment" of tasks. With this setting enabled, a PowerFlow worker will not remove a message from the queue until the message has been fully processed by the worker. This setting can be enabled or disabled with the environment variable "task\_acks\_late".

4. If ServiceNow responds with an unexpected status code when POSTing the incident, the message will be placed back in the queue with specified re-try parameters.

**NOTE:** You can configure re-try parameters on a per-task basis. You may want to manually alter your re-try parameters for tasks depending on the action the task is taking. The configuration of retries includes the maximum number of times a task is retried after consistently failing, and the delay length between retries.

# Event Data Flow: SL1 to PowerFlow

The following chart and steps illustrate the event data flow from SL1 to PowerFlow:




1. Through a Run Book Automation, SL1 identifies an event that should be synced to ServiceNow.
2. A Run Book Action executes a POST action to the PowerFlow API to let PowerFlow know that a PowerFlow application should be run to sync the event.
  - If the Run Book Action is successful and the POST responds with a 200, then the event data is stored in the PowerFlow queue for syncing.
  - If the POST does not respond with a 200, then the Run Book Action inserts the missed event into a table in the SL1 database so that it can be retrieved later.
3. In parallel, a scheduled PowerFlow event continuously checks the SL1 database for any missed events. If any missed events are found, they will be pulled from the database and inserted into the IPowerFlow (IS) queue.

**NOTE:** The PowerFlow queue is persistently saved to disk, so if the service stops, any events that existed in the queue before to the failure will still exist in the queue after the service is running again.

4. Missed events are not removed from the SL1 database until after they are inserted into the queue.

# Overview of the Run Book Automation for Incident Sync

You can configure a Run Book Automation to ensure that whenever SL1 detects a new, acknowledged, or cleared event, a corresponding incident is created or updated in ServiceNow:



The "ServiceNow: Add/Update/Clear Incident" Run Book Action policy is responsible for sending the SL1 payload to PowerFlow. PowerFlow then sends that payload to ServiceNow and creates, updates, acknowledges, or clears an incident, as needed.

SL1 features three Run Book Automation policies that facilitate this process:

- ServiceNow: Add/Update Incident
- ServiceNow: Event Acknowledged
- ServiceNow: Event Cleared

**NOTE:** A fourth Run Book Automation policy, "ServiceNow: Click to Create Incident" lets you manually create an incident in ServiceNow by clicking the life-preserver icon (🛟) in SL1. For more information, see [Configuring the "ServiceNow: Click to Create Incident" Automation Policy](#).

**NOTE:** The "Sync Incident State from ServiceNow to SL1 Event" application does not have an associated Run Book Action that triggers Incident Sync. You must schedule this application to run every minute, or to a time suitable for your requirements. You can use a cron job to trigger this schedule, or you can use the PowerFlow user interface to schedule the application. For more information about scheduling, see .

Each Run Book Automation policy calls a single action in SL1. Ensure that the application in PowerFlow points to the relevant SL1 system and ServiceNow instance. The action then calls an application on PowerFlow that determines the workflow to execute.

Events in SL1 frequently occur and resolve due to fluctuations in the network and other changing conditions. However, the Run Book Automation policies above use a de-duplication algorithm to ensure that only a single open ServiceNow incident exists per device. As a result, if a device already has an existing ServiceNow incident, the following updates are made to the ServiceNow incident record:

- The "Work Notes" activity log in the incident record is updated with information about the secondary event(s).
- If a secondary event is of a higher severity than the event that originally created the ServiceNow incident, then the **Impact**, **Urgency**, and **Priority** fields are updated automatically in the ServiceNow incident record. If the secondary event is of a lesser severity, those fields are not updated.
- If an event is cleared in SL1 and then later reoccurs before the incident has been "Closed" in ServiceNow, then the subsequent events appear in the original ServiceNow incident record for that device. If an incident record has been "Closed," then ServiceNow will create a new incident record when a cleared event reoccurs in SL1.
- By default, if an event is acknowledged in SL1, the ServiceNow incident record will be updated with the work notes and the acknowledging user. Clearing an SL1 event will move the ServiceNow incident record state to "Resolved". If all SL1 events associated with a ServiceNow incident record are clear, the ServiceNow incident record will, by default, move to a "Resolved" state.

**NOTE:** You can edit the Run Book Action Snippet code to adjust the behavior for changing states when an SL1 event is acknowledged or cleared.

---

## Configuring Incident Sync

This workflow covers how to set up the Run Book Automation to run Incident Sync:

1. [Create a configuration object in the PowerFlow user interface](#)
2. [Align the new configuration file with the following PowerFlow applications:](#)
  - o "Create or Update ServiceNow Incident from SL1 Event"
  - o "Sync Incident State from ServiceNow to SL1 Event"
  - o "Update ServiceNow Incident when SL1 Event is Acknowledged"
  - o "Update ServiceNow Incident when SL1 Event is Cleared"
3. [Create a ServiceNow credential in SL1](#)
4. [Enable the following Run Book Automation Policies:](#)
  - o "ServiceNow: Add/Update Incident"
  - o "ServiceNow: Event Acknowledged"
  - o "ServiceNow: Event Cleared"
3. [Enable and customize the "ServiceNow: Add/Update/Clear Incident" Run Book Action Policy](#)
4. Optionally, [send custom data to ServiceNow using the Passthrough Option](#)
5. Optionally, [enable and configure the "ServiceNow: Click to Create Incident" Policy](#)

---

## Creating and Aligning a Configuration Object

A **configuration object** supplies the login credentials and other required information needed to execute the steps for an application in PowerFlow. The **Configurations** page (⚙️) of the PowerFlow user interface lists all available configuration objects for that system.

You can create as many configuration objects as you need. An integration can only use one configuration object at a time, but you can use (or "align") the same configuration object with multiple applications.

To use this Synchronization PowerPack, you will need to use an existing configuration object in the PowerFlow user interface or create a new configuration object. Next, you need to align that configuration object to the relevant applications that are triggered by the Run Book Actions in SL1.


**TIP:** Depending on your SL1 and ServiceNow environments, you might be able to use the same configuration object with other ServiceNow Synchronization PowerPacks.

# Creating a Configuration Object

For this Synchronization PowerPack, you can make a copy of the "ServiceNow SyncPack" configuration object, which is the sample configuration file that was installed with the *ServiceNow Base Synchronization PowerPack*.

To create a configuration object based on the "ServiceNow SyncPack" configuration object:

1. In the PowerFlow user interface, go to the **Configurations** page (⚙️).
2. Click the **[Actions]** button (⋮) for the "ServiceNow SyncPack" configuration object and select *Edit*. The **Configuration** pane appears:



3. Click **[Copy as]**. The **Create Configuration** pane appears:

Name	Value	Encrypted	
sl1_host	em7.sciencelogic.com	<input type="checkbox"/>	×
sl1_password	SVh9nTCUEffef1edepEIJW8NrgF	<input checked="" type="checkbox"/>	×
sl1_user	em7admin	<input type="checkbox"/>	×
sl1_db_host	\${config.sl1_host}	<input type="checkbox"/>	×
sl1_db_user	root	<input type="checkbox"/>	×
sl1_db_password	IDPx5lwLIX5HOQzsg6niL4FpSgc	<input checked="" type="checkbox"/>	×
snow_host	sciencelogic.service-now.com	<input type="checkbox"/>	×

4. Complete the following fields:
  - **Friendly Name**. Name of the configuration object that will display on the **Configurations** page.
  - **Description**. A brief description of the configuration object.
  - **Author**. User or organization that created the configuration object.
  - **Version**. Version of the configuration object.
5. Click **[Toggle JSON Editor]** to show the JSON code.
6. In the **Configuration Data** field, be sure to include the required block of code to ensure that the applications aligned to this configuration object do not fail:

```
{
  "encrypted": false,
  "name": "s11_db_host",
  "value": "${config.s11_host}"
}
```

For example:

```
{
  "encrypted": false,
  "name": "s11_db_host",
  "value": "10.2.11.42"
}
```

**NOTE:** If you are using SL1 with an External Database (SL1 Extended architecture or a cloud-based architecture), update the "value" of that block of code to be the host of your database. This field accepts IP addresses. For example: "value": "db.sciencelogic.com". If you are *not* using the SL1 Extended architecture or a cloud-based architecture, you do not need to make any changes to the block of code other than pasting the code into the configuration object.

7. In the **Configuration Data** field, update the default variable definitions to match your PowerFlow configuration.

**TIP:** The "ServiceNow SyncPack" configuration object contains all of the required variables. Simply update the variables from that object to match your SL1 and ServiceNow settings.

**NOTE:** The **region** value is a user-defined variable that identifies your SL1 instance within ServiceNow.

8. To create a configuration variable, define the following keys:
  - **encrypted**. Specifies whether the value will appear in plain text or encrypted in this JSON file. If you set this to "true", when the value is uploaded, PowerFlow encrypts the value of the variable. The plain text value cannot be retrieved again by an end user. The encryption key is unique to each PowerFlow system. The value is followed by a comma.
  - **name**. Specifies the name of the configuration file, without the JSON suffix. This value appears in the user interface. The value is surrounded by double-quotes and followed by a comma.
  - **value**. Specifies the value to assign to the variable. The value is surrounded by double-quotes and followed by a comma.
9. Click **[Save]**. You can now align this configuration object with one or more applications.

## Aligning a Configuration Object

To run Incident Sync, you must "align" the configuration object to run with the following PowerFlow applications:

- "Create or Update ServiceNow Incident from SL1 Event"
- "Update ServiceNow Incident when SL1 Event is Acknowledged"
- "Update ServiceNow Incident when SL1 Event is Cleared"
- "Sync Incident State from ServiceNow to SL1 Event"

**NOTE:** The "Sync Incident State from ServiceNow to SL1 Event" application is the *only* application for Incident Sync that can be run manually or scheduled. The other three applications should only be triggered by Run Book Automations.

To align the configuration object with the relevant applications:

1. On the **Integrations** page of the PowerFlow user interface, open an "incident" application and click **[Configure]** (⚙️). The **Configurations** pane for that application appears:

**Create or Update ServiceNow Incident from SL1 Event** [Cancel] [Save]

Align configuration and save

Configuration  
scoped-app-conf

snow\_hostname: ven01056.service-no [lock] snow\_user: is4User1 [lock] snow\_password: [lock] sl1\_hostname: 10.2.11.41 [lock]  
\${config.snow host} \${config.snow user} \${config.sl1 host}

sl1\_user: em7admin [lock] sl1\_password: [lock]  
\${config.sl1 user}

eventDetails

1
---

expects type: json

region: QARegion10 [lock] snow\_state: 2  
\${config.region}

passthrough

1
---

expects type: json

correlation\_type: 5

discard assignmentGroup retry\_max: 0

2. From the **Configurations** drop-down, select the configuration object you want to use.
3. Click **[Save]** to align that configuration with the application.
4. Wait until you see the "App & Config modifications saved" pop-up message before proceeding.
5. Repeat this process for every application you want to use.

**NOTE:** The values for **eventDetails** and the other parameters that appear in the **Configuration** pane with a padlock icon (🔒) are populated either by the configuration object you aligned with the application or by the Run Book Action. Do not modify these values. If you encounter an error, make sure your Run Book Action is configured properly.

# Creating a ServiceNow Credential in SL1

To configure SL1 to communicate with ServiceNow, you must first create a SOAP/XML credential. This credential allows the Run Book Automation scripts and the Dynamic Applications in the *ServiceNow Base Pack PowerPack* to connect with your ServiceNow instance. These Run Book Automations are responsible for sending the SL1 event data to PowerFlow, which ultimately sends the data to a ServiceNow Incident.

The **ServiceNow RBA - Example** credential from the *ServiceNow Base Pack PowerPack* is an example SOAP/XML credential that you can configure for your own use.

To configure the **ServiceNow RBA - Example** credential:

1. In SL1, go to the **Credential Management** page (System > Manage > Credentials).
2. Locate the **ServiceNow RBA - Example** credential and click its wrench icon (🔧). The **Edit SOAP/XML Credential** page appears:

The screenshot shows the 'Credential Editor [85]' window with the following details:

- Basic Settings:**
  - Profile Name: ServiceNow RBA - Example
  - Content Encoding: [text/xml]
  - Method: [POST]
  - HTTP Version: [HTTP/1.1]
  - URL: https://INTEGRATIONSERVICEHOSTNAME
  - HTTP Auth User: USERNAME
  - HTTP Auth Password: \*\*\*\*\*
  - Timeout (seconds): 5
- Soap Options:**
  - Embedded Password [%P]:
  - Embed Value [%1]:
  - Embed Value [%2]:
  - Embed Value [%3]:
  - Embed Value [%4]:
- Proxy Settings:**
  - Hostname/IP:
  - Port: 0
  - User:
- CURL Options:**
  - CAINFO
  - CAPATH
  - CLOSEPOLICY
  - CONNECTTIMEOUT
  - COOKIE
  - COOKIEFILE
  - COOKIEJAR
  - COOKIELIST
  - CRLF
  - CUSTOMREQUEST
  - DNSCACHETIMEOUT

3. Complete the following fields:
  - **Profile Name.** Type a new name for the ServiceNow credential.
  - **Content Encoding.** Make sure *text/xml* is selected.
  - **Method.** Make sure *POST* is selected.
  - **HTTP Version.** Select *HTTP/1.1*.
  - **URL.** Type the URL for your PowerFlow instance.
  - **HTTP Auth User.** Type the username of your PowerFlow instance.

- **HTTP Auth Password.** Type the password of your PowerFlow instance.
- **Timeout.** Type "5".

4. Click **[Save As]**.
5. When the confirmation message appears, click **[OK]**.
6. On the **Credential Management** page (System > Manage > Credentials), make a note of the value in the **ID** column for the credential you just created:

Profile Name	Organization	RQ Use	RW Use	DA Use	Type	Credential User	Host	Port	Timeout (ms)	ID	Last Edited	Edited By
servicenow.rba	[all orgs]	--	--	--	SOAP/XML Host USERNAME	INTEGRATIONSERVICEHOSTNAME		443	5000	107	2019-07-15 11:10:54	em7admin

You will use this value with the "sl1\_credential\_id" parameter when you *enable and customize the snippet code of the "ServiceNow: Add/Update/Clear Incident" Run Book Action*:

**Policy Editor | Editing Action [455]**

Action Name: ServiceNow: Add/Update/Clear Incident  
 Action State: [Disabled]

Description: Adds and Updates Incidents in ServiceNow.

Organization: [System]      Action Type: ServiceNow: Create, Update, Clear Incident or Event (1.1)

Execution Environment: [-- Default: ServiceNow Base Pack]      Action Run Context: [Database]

Input Parameters:

```
{
  "sl1_credential_id": "107",
  "debug": false,
  "configuration": "",
  "queue": "",
  "discard_if_no_ci": false,
  "is_app_name_new": "incident_sync_update_create",
  "is_app_name_ack": "event_acknowledged",
  "is_app_name_clear": "event_cleared",
  "servicenow_state_new": "1",
  "servicenow_state_ack": "",
  "servicenow_state_clear": "6",
  "correlation_type": "5",
  "assignment_group_new": "",
  "assignment_group_ack": ""
}
```

Buttons: Save, Save As

---

## Enabling the Run Book Automation Policies

Before you can run the "ServiceNow: Add/Update/Clear Incident" Run Book Action, you must enable the three related Run Book Automation policies in SL1 :

- ServiceNow: Add/Update
- ServiceNow: Event Acknowledged
- ServiceNow: Event Cleared

**NOTE:** Version 104 of the ServiceNow Base Pack PowerPack separated these Run Book Action policies by Event and Incident, such as "ServiceNow: [Events] - Add/Update" and "ServiceNow: [Incident] - Add/Update". This update lets you choose the Run Book Actions based on whether you are using the *ServiceNow Events Synchronization PowerPack* or the *ServiceNow Incident Synchronization PowerPack*.

To enable the three ServiceNow Run Book Automation policies:

1. In SL1, go to the **Automation Policy Manager** page (Registry > Run Book > Automation).
2. Locate the "ServiceNow: Add/Update" automation policy and click its wrench icon (🔧). The **Automation Policy Editor** page appears:

The screenshot shows the 'Automation Policy Editor' interface for editing the 'ServiceNow: Add/Update Incident' policy. The interface is divided into several sections:

- Policy Configuration:** Includes fields for Policy Name, Policy Type (Active Events), Policy State (Enabled), Policy Priority (High), and Organization (System). The Policy State and Policy Priority fields are highlighted with red boxes.
- Criteria Logic:** A sequence of logic operators: [Severity >=], [Notice,], [and no time has elapsed], [since the first occurrence,], [and event is NOT cleared], and [and all times are valid].
- Match Logic:** [Text search]
- Match Syntax:** (Empty field)
- Repeat Time:** [Only once]
- Align With:** [Devices]
- Include events for entities other than devices (organizations, assets, etc.):** (Unchecked checkbox)
- Trigger on Child Rollup:** (Checked checkbox)
- Available Devices:** A list of devices including 'System' and several ScienceLogic EM7 All-In-One devices.
- Aligned Devices:** (All devices)
- Available Events:** A list of critical events such as 'AKCP: AC Voltage sensor detects no current' and 'AKCP: DC Voltage sensor High Critical'.
- Aligned Events:** (All events)
- Available Actions:** A list of actions including 'SNMP Trap [1]: EM7 Event Trap' and 'Snippet [5]: AWS: Disable Instance By Tag'. The 'Available Actions' section is highlighted with a red box.
- Aligned Actions:** 1. ServiceNow: Create, Update, Clear Incident [100]: Sr

At the bottom of the editor, there are 'Save' and 'Save As' buttons.

3. Update the following fields:

- **Policy State.** Select *Enabled*.
- **Policy Priority.** Select *High* to ensure that this PowerFlow automation policy is added to the top of the queue.
- **Available Actions.** If it is not already selected, select the corresponding ServiceNow Run Book Action policy.

**TIP:** By default, the "ServiceNow: [Incidents] Add/Update" automation policy will create ServiceNow Incidents for **all** devices. You can limit the devices affected by making changes to the **Organization, Severity, Match Logic, Aligned Devices,** and/or **Aligned Events** fields.

**WARNING:** ScienceLogic highly recommends that you do not make changes to the **Policy Type, Repeat Time, or Align With** fields or the *And event is NOT acknowledged* setting.

4. Click **[Save]**.

5. Repeat steps 2-4 for the "ServiceNow: Event Acknowledged" and "ServiceNow: Event Cleared" Run Book Automation policies.

---

## Enabling and Customizing the Run Book Action Policy


The "ServiceNow: Add/Update/Clear Event" and the "ServiceNow: Add/Update/Clear Incident" Run Book Action policies contain several default values in the snippet code for the policy that you can customize to use with the *ServiceNow Events Synchronization PowerPack* or the *ServiceNow Incident Synchronization PowerPack*.

You can edit these values in the **Input Parameters** pane of the **Action Policy Editor** page for this policy.

For example, the **Correlation Type** is a value that you can use to correlate an SL1 event with a ServiceNow incident. For the Correlation Type, which is also called the "Correlation ID", you can choose a number of different ways in which an incident can be created. The default setting is "correlation\_type": "5", which means that this Run Book Action correlates all events by device ID and event policy ID, and if the event matches and the state is active, the Action updates the existing incident. The Action creates a new incident if the event does *not* match by device ID and event policy ID. As a result, the Correlation Type helps determine which events get rolled up under an incident. All Run Book Action scripts should use the same Correlation Type value, otherwise correlation will fail.

To enable and customize the Run Book Automation policies:

1. In SL1, go to the **Action Policy Manager** page (Registry > Run Book > Actions).
2. Locate the **ServiceNow: Add/Update/Clear Incident (or Event)** policy and click its wrench icon (🔧). The **Action Policy Editor** page appears:



3. For the **Action State** field select *Enabled*.
4. In the **Input Parameters** pane, edit the snippet code as necessary, using the information in the **Customizing the Snippet Code in the Input Parameters Pane** section, below. When you are finished, click **[Save]**.

## Customizing the Snippet Code in the Input Parameters Pane

SL1 Run Book Action snippets are written in Python. In the event of a syntax error, the policies will no longer run. As a result, you must ensure that all edits adhere to Python standards. True and False options are case-sensitive and must not contain quotes.

**NOTE:** Previous SyncServer users had three separate Run Book Action scripts for add/update, acknowledge, and clear. These have been rolled into a single Run Book Action in this Synchronization PowerPack, but there are still three Automation policies.

You can customize the following values in the "ServiceNow: Add/Update/Clear Incident (or Event)" Run Book Action snippet code:

- **sl1\_credential\_id**. Specifies the ID of the credential object. You can find this value in the **ID** column of the **Credentials** page (System > Manage > Credentials of SL1).
- **debug**. A true/false value that determines if the action is logged in SL1 and if the application is run in Debug Mode on PowerFlow. Troubleshooting logs are written to **/data/tmp/servicenow\_rba.log**.
- **configuration**. Specifies the ID of the configuration object used on PowerFlow. The configuration ID is all lower-case, with spaces in the configuration object "friendly" name replaced by underscores. For example: "configuration": "servicenow\_syncpack\_configs"

**NOTE:** To find the configuration ID with the API, make a GET request on this endpoint:  
[https://<powerflow\\_hostname>/api/v1/configurations](https://<powerflow_hostname>/api/v1/configurations).

- **queue**. Specifies the worker queue on which the application runs. Leave this as default.
- **discard\_if\_no\_ci**. Specifies whether PowerFlow should create incidents or events in ServiceNow for devices that do not have a matching CI record. The default is *false*. Your options include:
  - *true*. If a device is not mapped to a CI, PowerFlow will *not* create an incident or event in ServiceNow, and SL1 is not updated. The following log message appears: "No CI found".
  - *false*. If a device is not mapped to a CI, PowerFlow *will* create an incident or event in ServiceNow and update SL1.

**NOTE:** The following parameters are specific to the "ServiceNow: Add/Update/Clear Incident" Run Book Action.

- **servicenow\_state\_new**:
  - 1. Incident state is "New". This is the default value.
  - 2. Incident state is "In Progress".
  - 3. Incident state is "On Hold".
  - 6. Incident state is "Resolved".
  - 7. Incident state is "Closed".
  - 8. Incident state is "Canceled".

- **servicenow\_state\_ack:**

- 1. Incident state is "New". There is no default value.
- 2. Incident state is "In Progress".
- 3. Incident state is "On Hold".
- 6. Incident state is "Resolved".
- 7. Incident state is "Closed".
- 8. Incident state is "Canceled".

- **servicenow\_state\_clear:**

- 1. Incident state is "New".
- 2. Incident state is "In Progress".
- 3. Incident state is "On Hold".
- 6. Incident state is "Resolved". This is the default value.
- 7. Incident state is "Closed".
- 8. Incident state is "Canceled".

- **correlation\_type.** Correlates an SL1 event with a ServiceNow incident. For this value, which is also called the "Correlation ID", you can choose a number of different ways in which an incident can be created. The default setting is "correlation\_type": "5", which means that this Run Book Action correlates all events by device ID and event policy ID, and if the event matches and the state is active, the Action updates the existing incident. The Action creates a *new* incident if the event does *not* match by device ID and event policy ID. As a result, the Correlation Type helps determine which events get rolled up under an incident. All Run Book Action scripts should use the same Correlation Type value, otherwise correlation will fail.

The possible Correlation Type values include the following:

- 1. Correlate all duplicate incidents by SL1 ID only.
- 2. Correlate all duplicate incidents by event policy ID only.
- 3. Correlate all duplicate incidents by device ID only.
- 4. Correlate all duplicate incidents by Interface ID only. This correlation requires that the SL1 event has an interface aligned. If there is no interface aligned to the event, the returned Interface ID will be 0.
- 5. Correlate all duplicate incidents by device ID and event policy ID. This is the default Correlation Type value.
- 6. Correlate all duplicate incidents by device ID, event policy ID, and event sub entity ID.
- 7. Correlate all duplicate incidents by device ID, event policy ID, region, and event ID. Please note that using this correlation type will result in all events triggering new incidents.
- 8. Correlate all events to the root device ID of the component device into one incident. Please note that using this correlation type might lead to undesirable behavior, as not all events generated on a child device indicate a problem on the root device. As a result, ScienceLogic recommends that you only use this correlation type against specific event policies.

- You can assign the assignment group to one of the new, acknowledged, or cleared incidents that are mapped. To disable this feature, ensure that no values are set. After an incident is created, the assignment group value will not be changed by the Run Book Action. To assign an assignment group, set the variable value to the **sys\_id** of the ServiceNow Assignment Group. In the following example, the assignment group is assigned to incidents that are *cleared*:

```
"assignment_group_new": "",  
"assignment_group_ack": "",  
"assignment_group_clear": "sys_id"
```

## Customizing Logging in the Run Book Action

You can customize the following logging-related items in the "ServiceNow: Add/Update/Clear Incident" Run Book Action snippet code:

- `logfile = /data/tmp/ServiceNow_add_update_clear_incident.log`
  - Location for logging output.
  - Will be created if it does not exist.
  - Will be appended with each Run Book job.
  - Is case-sensitive.
- `do_debug_logging = True`
  - True is on, False is off.
  - Is case-sensitive.
  - For troubleshooting, these can be enabled or changed.
  - Writes logs to **/data/tmp/servicenow\_rba.log**.

---

## Sending Custom Data to ServiceNow Using the Passthrough Option

You can use the "ServiceNow: [Incident] Add/Update" Run Book Automation and the "ServiceNow: Add/Update/Clear Incident" Run Book Action to "pass through" custom data about incidents to ServiceNow. For example, you might want to use the passthrough functionality to overwrite the impact and urgency of a ServiceNow Incident, which is the only way to change the priority of the Incident.

**NOTE:** You can also use the "ServiceNow: [Events] Add/Update" Run Book Automation and the "ServiceNow: Add/Update/Clear Event" Run Book Action to "pass through" custom data about events to ServiceNow. The steps in the following procedure use the Incident Automation and Incident Action as an example.

To pass custom data to ServiceNow:

- Create a new Run Book Action that pulls the relevant data and adds it to a dictionary called EM7\_RESULT.
- Add the new Run Book Action to the "ServiceNow: Add/Update Incident" Run Book Automation Policy, ahead of the "ServiceNow: Add/Update/Clear Incident" Run Book Action so that the new Action runs first, and then is consumed by the ServiceNow Action.

The following procedure describes how to configure the passthrough functionality.

## Passing Custom Data to ServiceNow

To pass custom data to ServiceNow:

1. In SL1, go to the **Action Policy Manager** page (Registry > Run Book > Actions) and click **[Create]** to create a new Run Book Action policy:

The screenshot shows the 'Policy Editor | Creating New Action' interface. It features a 'Reset' button in the top right corner. The form contains the following fields and values:

- Action Name:** Example Passthrough EM7\_RESULT
- Action State:** [Enabled]
- Description:** Passthrough data using EM7\_RESULT dictionary
- Organization:** [System]
- Action Type:** Run a Snippet
- Snippet Credential:** (None)
- Action Run Context:** Database
- Execution Environment:** [-- Default Environment]
- Snippet Code:** EM7\_RESULT = {"work\_notes": "This is a new note"}

A 'Save' button is located at the bottom center of the form.

2. Complete the following fields:
  - **Action Name.** Type a unique name for the Action.
  - **Action State.** Select *Enabled*.
  - **Action Type.** Select *Run a Snippet*.
  - **Execution Environment.** Select *ServiceNow Base Pack*.
  - Complete the other fields as needed.


3. In the **Snippet Code** pane, add the snippet code you want to include for the EM7\_RESULT dictionary. For example, the following snippet code lets you override the ServiceNow Incident work notes with a hardcoded note:

```
EM7_RESULT = {"work_notes": "This is a new note"}
```

Additional notes about the structure of the EM7\_RESULT dictionary:

- EM7\_RESULT = is required for the dictionary, and the formatting of the keys should match the example above.
  - All keys defined in the EM7\_RESULT dictionary need to map to field IDs on the **ScienceLogic Events** table in ServiceNow.
  - You can hard-code the values in the EM7\_RESULT dictionary, or you can use variables and functions, like the "Snippet Code Example", below.
  - As a best practice, avoid sending null passthrough values to ServiceNow. If you must send 'null' or 'NULL' values to ServiceNow, pass through that value as an empty string, such as "location": "". Also, only pass through values that you need. For example, instead of sending {"location": "", "work\_notes": "stuff"}, simply send {"work\_notes": "stuff"}.
  - A long snippet might delay the ticket being created
4. Click **[Save]**.
  5. Go to the **Automation Policy Manager** page (Registry > Run Book > Automation) and open the "ServiceNow: Add/Update Incident" Run Book Automation Policy.

- In the **Available Actions** section, add the new Run Book Action *before* the "ServiceNow: Create, Update, Clear Incident" Run Book Action:



**NOTE:** The output of this new Run Book Action will be consumed by the "ServiceNow: Create, Update, Clear Incident" Run Book Action, ensuring that the EM7\_RESULT dictionary is passed through to ServiceNow. The "ServiceNow: Create, Update, Clear Incident" Run Book Action automatically populates the passthrough values with any values from EM7\_LAST\_RESULT. The passthrough overwrites any other previously defined fields, such as assignment group.

- You can add additional Run Book Actions to the Run Book Automation Policy for any additional workflows that you might want to run. The Automation Policy execute these Actions in a sequential, top-down order. However, the "ServiceNow: Create, Update, Clear Incident" Run Book Action only consumes the EM7\_RESULT dictionary from the Run Book Action directly above it.

## Snippet Code Example

The following snippet code example shows how to pull additional information and make it available for passthrough. All of the additional information that is going to be sent is contained in a dictionary variable called EM7\_RESULT. You can pass through multiple items through in a single Run Book Action by adding additional keys to the EM7\_RESULT dictionary.

This example lets you assign assignment groups to an Incident based on certain criteria, such as event policy IDs:

```
from future.utils import iteritems

def invert_mappings(mappings):
    """
    Invert received one-to-many mappings and converts it into a one-to-one
    mapping.

    Args:
        mappings (dict): Dictionary of mapped values

    Returns:
        dict: inverted dictionary.

    """
    inverted_mappings = dict()
    for key, values in iteritems(mappings):
        for sub_value in values:
            invert_mappings[sub_value] = key
    return inverted_mappings

# Example of assignment group to list of event policy ids mapping.
assignment_groups_to_event_policies = {
    "sys_id_1": [1, 2, 3, 4, 5],
    "sys_id_2": [6, 7, 8, 9, 10],
}
# which sys_id to use if the current event_policy_id isn't mapped
default_sys_id = "sys_id_3"

# invert the mappings
event_policy_to_assignment_group = invert_mappings(assignment_groups_to_event_
policies)

# Send assignment group sys_id to IS RBA
EM7_RESULT = {
    "assignment_group": event_policy_to_assignment_group.get(
        EM7_VALUES["%3"], default_sys_id
    )
}
```

---


## Configuring the "ServiceNow: Click to Create Incident" Automation Policy

The "ServiceNow: Click to Create" Run Book Automation policy lets you manually create an incident in ServiceNow by clicking the life-preserver icon (🛟) in SL1. This policy is available in the *ServiceNow Base Pack PowerPack*.

**NOTE:** Version 104 of the ServiceNow Base Pack PowerPack separated this Run Book Automation policies by Event and Incident: "ServiceNow: [Event] Click to Create" and "ServiceNow: [Incident] Click to Create".

To configure the "ServiceNow: Click to Create" policy:

1. In SL1, go to the Behavior Settings page (System > Settings > Behavior) and set the **Event Console Ticket Life Ring Button Behavior** option to *Create/View External Ticket*.
2. Click **[Save]** to save your changes.
3. Go to the **Automation Policy Manager** page (Registry > Run Book > Automation).
4. Locate the **ServiceNow: Click to Create Incident** policy and click its wrench icon (🔧). The **Automation Policy Editor** page appears:




5. Update the following fields:

- **Policy State.** Select *Enabled*.
- **Repeat Time.** Specify the frequency at which SL1 should execute the automation policy while the conditions are still met. The choices range from "every 30 seconds until satisfied" to "every 2 hours until satisfied", or "only once". By default, the policy only runs once.
- **Available Actions.** If it is not already selected, select the corresponding ServiceNow Run Book Action policy to add it to the **Aligned Actions** field.

6. Click [Save].

## Viewing Incidents and Events

To view SL1-created incidents in ServiceNow, go to the **Incidents** page (Incident > Open) in ServiceNow:



	Number	Caller	Short description	Category	Correlation ID	Priority	State	Assignment group	Assigned to
	INC0019677		Itava-demo3.sciencetologic.local: GeneralHostWarningEvent: Issue Detected On It-	Monitoring	EM7+EVENT+107	3 - Moderate	Awaiting Evidence		
	INC0019676		TCPREPLAY: Device Failed Availability Check: Component Device 209 Is Not Availab-	Monitoring	EM7+EVENT+209	2 - High	New		
	INC0019675		TCPREPLAY: Device Failed Availability Check: Component Device 208 Is Not Availab-	Monitoring	EM7+EVENT+208	2 - High	Awaiting Evidence		
	INC0019674		PlixerSIOLOB: Device Failed Availability Check: Component Device 206 Is Not Ava-	Monitoring	EM7+EVENT+206	2 - High	Awaiting Evidence		
	INC0019673		JPLDemoTest: Device Failed Availability Check: Component Device 205 Is Not Avail	Monitoring	EM7+EVENT+205	2 - High	Awaiting Evidence		
	INC0019672		Lab-ven01.acme.com: Filesystem Unavailable: /var/mnt/mount/ta707c5-3008-558	Monitoring	EM7+EVENT+88	3 - Moderate	Awaiting Evidence		
	INC0019671		CLCM10-01.qa.sciencetologic.local: Device Failed Availability Check: LDAP - SNMP	Monitoring	EM7+EVENT+204	2 - High	Awaiting Evidence		
	INC0019670		Svcnodemo_db: Physical Memory Has Exceeded Threshold: (80%) Currently (81%)	Monitoring	EM7+EVENT+164	3 - Moderate	Awaiting Evidence		
	INC0019669		Svcnodemo_c01: Physical Memory Has Exceeded Threshold: (80%) Currently (85%)	Monitoring	EM7+EVENT+163	3 - Moderate	Awaiting Evidence		
	INC0019668		NTNX-155M65260085-C-CVM: Nutanix: CVM Exceeded High Memory Threshold: 100%	Monitoring	EM7+EVENT+191	3 - Moderate	New		
	INC0019667		Dc2hntxcls01: Nutanix Cluster Alert [Warning]: Wall Clock Time Has Drifted By	Monitoring	EM7+EVENT+166	3 - Moderate	Awaiting Evidence		
	INC0019666		NTNX-155M65260085-A-CVM: Nutanix: CVM Exceeded High Memory Threshold: 100%	Monitoring	EM7+EVENT+187	3 - Moderate	New		
	INC0019665		NTNX-155M65260085-B-CVM: Nutanix: CVM Exceeded High Memory Threshold: 100%	Monitoring	EM7+EVENT+179	3 - Moderate	New		
	INC0019664		CS-020X230X.acme.com: Device Failed Availability Check: UDP - SNMP	Monitoring	EM7+EVENT+37	2 - High	Awaiting Evidence		
	INC0019663		Generic-printer-Xerox1310-2: Device Failed Availability Check: UDP - SNMP	Monitoring	EM7+EVENT+66	2 - High	Awaiting Evidence		

All SL1 incidents use the event message from the SL1 **Events** page as the incident description in ServiceNow. The SL1 **Events** page also links to the Incident record if you click the life-preserver icon (🔗) under the **External Ticket** column. Note that you might need to enable the **External Ticket** column by modifying the Console preferences.

SL1 and ServiceNow use slightly different methods for designating the severity or priority of an event or incident. A custom data lookup table handles the conversion by translating the SL1 event severity into ServiceNow **Impact**, **Urgency**, and **Priority** fields. This severity data lookup table for automatically deploys with the "ScienceLogic SL1: CMDB & Incident Automation Application", also called the Scoped or Certified Application:

Severity	Impact	Urgency
1	1	2
2	2	2
3	2	3
4	3	3

If a second event for the same incident occurs, that event will update the **Impact** and **Urgency** values, based on the severity lookup table.

When the SL1 Run Book Automation creates a ServiceNow incident, the action taken depends on the **Correlation Type** you specified in the "ServiceNow Add/Update/Clear Incident" Run Book Action. If one or more events are aligned to the same incident, those events will show up in the **[Events]** tabs at the bottom of the Incident record in ServiceNow. All event-specific information for an incident is listed on this page:

Incident = INC0013377	Action policy	Active	Automation policy	Correlation	Device	Event count	Event created	Event ID	Event policy	Hyperlink
ServiceNow: Add/Update /Clear Incident	false	ServiceNow: Add/Update Incident	fsundemo89+DEV+2197+EVENT+1705	(empty)	1	2019-09-19 09:23:16	●	Poller: Network Latency Exceeded Threshold	<a href="http://em7.mydomain.com/em7/index.em?nwec-event&amp;g_type=aid&amp;g_arg=117652264g_sev=1&amp;g_sort=0&amp;g_oper=0">http://em7.mydomain.com/em7/index.em?nwec-event&amp;g_type=aid&amp;g_arg=117652264g_sev=1&amp;g_sort=0&amp;g_oper=0</a>	
ServiceNow: Add/Update /Clear Incident	false	ServiceNow: Add/Update Incident	fsundemo89+DEV+2197+EVENT+1705	(empty)	1	2019-09-19 08:28:17	●	Poller: Network Latency Exceeded Threshold	<a href="http://em7.mydomain.com/em7/index.em?nwec-event&amp;g_type=aid&amp;g_arg=117655784g_sev=1&amp;g_sort=0&amp;g_oper=0">http://em7.mydomain.com/em7/index.em?nwec-event&amp;g_type=aid&amp;g_arg=117655784g_sev=1&amp;g_sort=0&amp;g_oper=0</a>	
ServiceNow: Add/Update /Clear Incident	false	ServiceNow: Add/Update Incident	fsundemo89+DEV+2197+EVENT+1705	(empty)	1	2019-09-19 08:18:16	●	Poller: Network Latency Exceeded Threshold	<a href="http://em7.mydomain.com/em7/index.em?nwec-event&amp;g_type=aid&amp;g_arg=117654964g_sev=1&amp;g_sort=0&amp;g_oper=0">http://em7.mydomain.com/em7/index.em?nwec-event&amp;g_type=aid&amp;g_arg=117654964g_sev=1&amp;g_sort=0&amp;g_oper=0</a>	
ServiceNow: Add/Update /Clear Incident	false	ServiceNow: Add/Update Incident	fsundemo89+DEV+2197+EVENT+1705	(empty)	1	2019-09-19 07:33:17	●	Poller: Network Latency Exceeded Threshold	<a href="http://em7.mydomain.com/em7/index.em?nwec-event&amp;g_type=aid&amp;g_arg=117652064g_sev=1&amp;g_sort=0&amp;g_oper=0">http://em7.mydomain.com/em7/index.em?nwec-event&amp;g_type=aid&amp;g_arg=117652064g_sev=1&amp;g_sort=0&amp;g_oper=0</a>	
ServiceNow: Add/Update /Clear Incident	false	ServiceNow: Add/Update Incident	fsundemo89+DEV+2197+EVENT+1705	(empty)	1	2019-09-19 07:13:16	●	Poller: Network Latency Exceeded Threshold	<a href="http://em7.mydomain.com/em7/index.em?nwec-event&amp;g_type=aid&amp;g_arg=117650564g_sev=1&amp;g_sort=0&amp;g_oper=0">http://em7.mydomain.com/em7/index.em?nwec-event&amp;g_type=aid&amp;g_arg=117650564g_sev=1&amp;g_sort=0&amp;g_oper=0</a>	
ServiceNow: Add/Update /Clear Incident	false	ServiceNow: Add/Update Incident	fsundemo89+DEV+2197+EVENT+1705	(empty)	1	2019-09-19 07:03:18	●	Poller: Network Latency Exceeded Threshold	<a href="http://em7.mydomain.com/em7/index.em?nwec-event&amp;g_type=aid&amp;g_arg=117649864g_sev=1&amp;g_sort=0&amp;g_oper=0">http://em7.mydomain.com/em7/index.em?nwec-event&amp;g_type=aid&amp;g_arg=117649864g_sev=1&amp;g_sort=0&amp;g_oper=0</a>	

**TIP:** If the **[Events]** tab does not display at the bottom of the Incident record, you can add it by opening the Incident record, clicking the Additional actions icon (☰), and selecting **Configure > Related Lists**. Add **Event > Incident** to the **Selected** column and click **[Save]**.

For more information about ServiceNow incident management, see [https://docs.servicenow.com/bundle/newyork-it-service-management/page/product/incident-management/concept/c\\_IncidentManagement.html](https://docs.servicenow.com/bundle/newyork-it-service-management/page/product/incident-management/concept/c_IncidentManagement.html).


# Incident Topology Suppression

**Incident topology suppression** is used when ServiceNow incidents that have been synced with SL1 devices occur on devices that have a parent/child relationship. If you choose to enable incident topology suppression in SL1, child events synced with ServiceNow incidents do not appear in the SL1 **Event Console** as separate events. Instead, the child events are nested under the parent event.

**NOTE:** The steps in this process use the Classic user interface for SL1.

To enable incident topology suppression:


1. In SL1, navigate to the **Event Policy Manager** page (Registry > Events > Event Manager) and click the **[Create]** button. The **Event Policy Editor** modal appears:



2. On the **[Policy]** tab, update the following fields:

- **Event Source:** Select *API*.
- **Operational State:** Select *Enabled*.
- **Event Severity:** Select *Critical* as the severity of the event.
- **Policy Name.** Type the name of the event. Can be any combination of alphanumeric characters, up to 48 characters in length
- **Event Message.** Type the message that will appear when this event occurs.


3. Click the **[Advanced]** tab.



4. On the **[Advanced]** tab, update the following fields:


- **Detection Weight.** Select *20 - Last*. If two event definitions are very similar, the weight field specifies the order in which SL1 should match messages against the similar event definitions. The event definition with the lowest weight will be matched first. This field is most useful for events that use expression matching. Options range from 0 (first) - 20 (last).
- **Match Logic.** Select *Regex Match*. Specifies whether SL1 should process the First Match String field and Second Match String as regular expressions or as simple text matches. Because you selected *Regex Match*, you cannot define a "match all" expression by leaving the First Match String and Second Match String fields empty.
- **Use Message-match.** Select this option. If SL1 has generated an event and then a second log message or alert matches the same event policy for the same entity, SL1 will not generate a second event, but will increase the count value for the original event. This behavior will occur only if the log messages or alerts contain the same message.
- **First Regular Expression.** Type "CRITICAL" as the string used to correlate the event with a log message.
- **Topology Suppression.** Select *Both*. If this event occurs on a parent device, it behaves as a suppressing event. If this event occurs on a child device, it behaves as a suppressible event.

5. Click **[Save]** and close the **Event Policy Editor** modal.
6. Next, go to the **Device Groups** page (Registry > Device Groups) and click the **[Create]** button. A **Device Group Editor** page appears:



7. Complete the following fields, and leave the default settings for the remaining fields:
  - **Template Name.** Specify the name of the new device group.
  - **Force Child Visibility.** Select "No".
  - **Visibility.** Select *Config Policies/Bulk Edit* to let you configure all the devices in the new device group using a device template.

- Click the **[Save]** button and then click the **[Add]** button in the **Dynamic Rules** pane to add dynamic rules to the new device group. The Device Group Rule Editor modal page appears:




- In the **Active Selectors** pane, select *Device Name*.
- Optionally, in the **Selector Definitions** pane, type an asterisk (\*) in the **Device Name** field. Using the \* includes all devices by Device Name. In the **Matched Devices** pane, a list of all devices appears.
- Click **[OK]** to close the modal page.
- On the **Device Group Editor** modal page, click **[Save]** and close the page.

13. Next, create a Device Group Template that will disable Event Masking for all devices in the new Device Group. Click the building blocks icon (🧱) for the new device group. A **Device Template Editor** page appears:

The screenshot displays the 'Device Template Editor' interface. At the top, there is a navigation bar with the title 'Device Template Editor | Applying Template to Devices | Click [Save] to commit changes | Config Template Settings (Click field labels to enable/dis)'. Below this, there are fields for 'Template' (set to 'New / One-off Template'), 'Save When Applied & Confirmed' (checkbox), and 'Template Name'. A tabbed interface shows 'Config' as the active tab, with other tabs including 'Interface', 'CV Policies', 'Port Policies', 'Svc Policies', 'Proc Policies', 'Dyn Apps', and 'Logs'. The main content area is divided into several sections: 'Access & Monitoring', 'Device Preferences', 'Device Retention & Basic Thresholds', and 'Interface Inventory Settings'. In the 'Access & Monitoring' section, the 'Event Mask' dropdown menu is highlighted with a red box and is set to 'Disabled'. Other settings in this section include 'Device Organization' (Acme Inc), 'SNMP Read' (Cisco SNMPv2 - Example), 'SNMP Write' (None), 'Availability Protocol' (TCP), 'Avail Port' (ICMP), 'Latency Protocol' (TCP), 'Latency Port' (ICMP), 'Avail+Latency Alert' (Disabled), 'Collection' (Enabled), 'Collector Grp' (CUG), 'Coll. Type' (Standard), and 'Critical Ping' (Disabled). The 'Device Preferences' section includes options like 'Auto-Clear Events', 'Scan All IPs', 'Accept All Logs', 'Dynamic Discovery', 'Daily Port Scans', 'Preserve Hostname', 'Auto-Update', 'Disable Asset Update', and 'Bypass Interface Inventory'. The 'Device Retention & Basic Thresholds' section features sliders for 'System Latency' (100 ms), 'Daily Rollup Bandwidth Data' (730 days), 'Hourly Rollup Bandwidth Data' (120 days), 'Raw Performance Data' (7 days), 'Daily Rollup Performance Data' (730 days), 'Availability Packet Size' (56 bytes), and 'Availability Ping Count' (1 pings). The 'Interface Inventory Settings' section at the bottom includes 'Interface Inventory' (60000) and 'Maximum Allowed' (10000) with an 'Apply' button.

14. Because all of the fields are disabled (grayed-out) by default, click the **Event Mask** field name to enable the field. Use the default setting of *Disabled*.
15. Click **[Apply]** and click **[Confirm]** on the **Device Template Editor** page.
16. Next, turn off the *Trigger on Child Rollup* option on the "ServiceNow: Add/Update Incident" Run Book Automation. Go to the **Automation Policy Manager** page (Registry > Run Book > Automation) and click the wrench icon (🔧) for the "ServiceNow: Add/Update Incident" Run Book Automation. The **Automation Policy Editor** page appears:



17. Make sure the *Trigger on Child Rollup* option is not selected and click **[Save]**. Close the **Automation Policy Editor** page.

## Hyperlinking Events

Both ServiceNow and SL1 provide mechanisms for hyperlinking to multiple active events and incidents. This section describes those processes.

## ServiceNow Hyperlinking

Each incident in ServiceNow will have one or more events aligned with it through the Related List of events, which you can view in the **[Events]** tab at the bottom of the Incident record.

By default the **Hyperlink** field appears on the custom event table provided with the Certified application (`x_sclo_scilogic_event`). Each event shown in the **[Events]** tab at the bottom of the Incident record will have its own URL associated. The following image shows the Event record for an event aligned with an Incident:

Event 315

Incident: INC0010020

Region: region6341

Event ID: 315

Event policy: Dynamic App Snippet Exception

Automation policy: ServiceNow: Click to Create Incident

Action policy: ServiceNow: Add/Update/Clear Inciden

Message: em7-ao-47: App: 90, Snippet: 110 reported a collection problem (Explanation: SNMP error returned: Timeout. Location: Using walkbulk to query .1.3.6.1.2.1.25.2.3.1.2)

Device: em7-ao-47

Organization: System

Severity: Minor

Event created: 2019-10-30 13:00:19

Last detected: 2019-10-30 13:00:19

Event count: 1

Hyperlink: [http://em7.mydomain.com/em7/index.em7?exec=events&q\\_type=aid&q\\_arg=315&q\\_sev=1&q\\_sort=0&q\\_oper=0](http://em7.mydomain.com/em7/index.em7?exec=events&q_type=aid&q_arg=315&q_sev=1&q_sort=0&q_oper=0)

**TIP:** If the **[Events]** tab does not display at the bottom of the Incident record, you can add it by opening the Incident record, clicking the Additional actions icon (☰), and selecting *Configure > Related Lists*. Add *Event->Incident* to the **Selected** column and click **[Save]**.

## Viewing the Incident Import Table in ServiceNow

Each time SL1 creates or changes an incident in ServiceNow, data is inserted into a temporary import table on the ServiceNow system. This table displays all inbound data from SL1 and is a useful tool to determine what data is being sent and imported. The incident import table is created automatically when you install the ScienceLogic Certified (Scoped) Application.

To view the data and the status of the import process, go to the **Import Incidents** page (ScienceLogic > Event > Events) in ServiceNow:

Event ID	Created	Correlation ID	Incident	CMDB CI	Updated	Target record	State	Incident state	Created by	Import set run
1175595	2019-09-19 09:33:21	fuadem089-DEV-2196-EVENT+1705	INC0013315	(empty)	2019-09-19 09:33:21	Event_1175595	Updated	Resolved	fun	(empty)
1175595	2019-09-19 09:33:21	fuadem089-DEV-2196-EVENT+1705	INC0013315	(empty)	2019-09-19 09:33:21	Incident_INC0013315	Updated	Resolved	fun	(empty)
1175595	2019-09-19 09:28:27	fuadem089-DEV-2196-EVENT+1705	INC0013315	(empty)	2019-09-19 09:28:27	Event_1175595	Inserted	In Progress	fun	(empty)
1175595	2019-09-19 09:28:27	fuadem089-DEV-2196-EVENT+1705	INC0013315	(empty)	2019-09-19 09:28:27	Incident_INC0013315	Updated	In Progress	fun	(empty)
1175592	2019-09-19 09:28:26	fuadem089-DEV-2197-EVENT+1705	INC0013317	(empty)	2019-09-19 09:28:26	Incident_INC0013317	Updated	Resolved	fun	(empty)
1175592	2019-09-19 09:28:26	fuadem089-DEV-2197-EVENT+1705	INC0013317	(empty)	2019-09-19 09:28:26	Event_1175592	Updated	Resolved	fun	(empty)
1175592	2019-09-19 09:23:22	fuadem089-DEV-2197-EVENT+1705	INC0013317	(empty)	2019-09-19 09:23:22	Incident_INC0013317	Updated	In Progress	fun	(empty)
1175592	2019-09-19 09:23:22	fuadem089-DEV-2197-EVENT+1705	INC0013317	(empty)	2019-09-19 09:23:22	Event_1175592	Inserted	In Progress	fun	(empty)
1175577	2019-09-19 09:03:34	fuadem089-DEV-2196-EVENT+1705	INC0013315	(empty)	2019-09-19 09:03:34	Event_1175577	Updated	Resolved	fun	(empty)
1175577	2019-09-19 09:03:34	fuadem089-DEV-2196-EVENT+1705	INC0013315	(empty)	2019-09-19 09:03:34	Incident_INC0013315	Updated	Resolved	fun	(empty)
1175577	2019-09-19 08:58:30	fuadem089-DEV-2196-EVENT+1705	INC0013315	(empty)	2019-09-19 08:58:30	Incident_INC0013315	Updated	In Progress	fun	(empty)
1175577	2019-09-19 08:58:30	fuadem089-DEV-2196-EVENT+1705	INC0013315	(empty)	2019-09-19 08:58:30	Event_1175577	Inserted	In Progress	fun	(empty)
1175579	2019-09-19 08:53:35	fuadem089-DEV-2196-EVENT+1705	INC0013315	(empty)	2019-09-19 08:53:35	Incident_INC0013315	Updated	Resolved	fun	(empty)
1175579	2019-09-19 08:53:35	fuadem089-DEV-2196-EVENT+1705	INC0013315	(empty)	2019-09-19 08:53:35	Event_1175579	Updated	Resolved	fun	(empty)
1175579	2019-09-19 08:48:31	fuadem089-DEV-2196-EVENT+1705	INC0013315	(empty)	2019-09-19 08:48:31	Incident_INC0013315	Updated	In Progress	fun	(empty)
1175579	2019-09-19 08:48:31	fuadem089-DEV-2196-EVENT+1705	INC0013315	(empty)	2019-09-19 08:48:31	Event_1175579	Inserted	In Progress	fun	(empty)
1175556	2019-09-19 08:38:32	fuadem089-DEV-2196-EVENT+1705	INC0013315	(empty)	2019-09-19 08:38:32	Incident_INC0013315	Updated	Resolved	fun	(empty)

You can view a complete audit of all import data and transforms by going to the **Transform Histories** page (System Import Sets > Advanced > Transform History):

Started	State	Completed	Run time	Set	Import set table	Total	Inserts	Updates	Ignored	Skipped	Errors	Transform Map
2016-09-04 04:00:50	Complete	2016-09-04 04:00:50	0 Seconds	ISET0013291	ScienceLogic File System [u_sciencelogic_file_system]	1	0	0	1	0	0	ScienceLogic File System T-Map
2016-09-01 12:00:27	Complete	2016-09-01 12:00:27	0 Seconds	ISET0013275	ScienceLogic Network Interfaces [u_sciencelogic_adapters]	1	0	0	1	0	0	ScienceLogic Adapter T-Map
2016-09-02 14:00:12	Complete	2016-09-02 14:00:12	0 Seconds	ISET0013278	ScienceLogic Hardware Models [u_sciencelogic_hardware_models]	1	0	0	1	0	0	ScienceLogic Hardware Model T-Map
2016-09-01 16:00:44	Complete	2016-09-01 16:00:44	0 Seconds	ISET0013276	ScienceLogic File System [u_sciencelogic_file_system]	1	0	0	1	0	0	ScienceLogic File System T-Map
2016-08-31 18:01:16	Complete	2016-08-31 18:01:16	0 Seconds	ISET0013271	ScienceLogic File System [u_sciencelogic_file_system]	1	0	0	1	0	0	ScienceLogic File System T-Map
2016-09-02 03:00:28	Complete	2016-09-02 03:00:28	0 Seconds	ISET0013280	ScienceLogic File System [u_sciencelogic_file_system]	1	0	0	1	0	0	ScienceLogic File System T-Map
2016-09-01 20:01:03	Complete	2016-09-01 20:01:03	0 Seconds	ISET0013276	ScienceLogic File System [u_sciencelogic_file_system]	1	0	0	1	0	0	ScienceLogic File System T-Map
2016-09-03 02:01:22	Complete	2016-09-03 02:01:22	0 Seconds	ISET0013286	ScienceLogic File System [u_sciencelogic_file_system]	1	0	0	1	0	0	ScienceLogic File System T-Map
2016-09-01 12:00:59	Complete	2016-09-01 12:00:59	0 Seconds	ISET0013275	ScienceLogic Network Interfaces [u_sciencelogic_adapters]	1	0	0	1	0	0	ScienceLogic Adapter T-Map
2016-09-03 12:00:12	Complete	2016-09-03 12:00:12	0 Seconds	ISET0013283	ScienceLogic Hardware Models [u_sciencelogic_hardware_models]	1	0	0	1	0	0	ScienceLogic Hardware Model T-Map
2016-09-04 22:00:33	Complete	2016-09-04 22:00:33	0 Seconds	ISET0013290	ScienceLogic Network Interfaces [u_sciencelogic_adapters]	1	0	0	1	0	0	ScienceLogic Adapter T-Map
2016-09-01 16:01:17	Complete	2016-09-01 16:01:17	0 Seconds	ISET0013276	ScienceLogic File System [u_sciencelogic_file_system]	1	0	0	1	0	0	ScienceLogic File System T-Map

# ServiceNow, ScienceLogic Event, and Incident Priority Matrix

By default, when SL1 triggers an event, it is sent to ServiceNow through PowerFlow. The following mappings are currently in place for mapping an SL1 Event to a ServiceNow Incident (ScienceLogic > Event > Severity Lookup Rules):

Severity	Impact	Urgency
1	1	2
2	2	2
3	2	3
4	3	3

**NOTE:** This severity lookup table handles all Severity conversions.

A **transformation script** that translates the SL1 event severity into the ServiceNow **Impact**, **Urgency**, and **Priority** fields automatically deploys with the ScienceLogic Certified (Scoped) Application.

By default, the **Priority** field is read-only and must be set by selecting the **Impact** and **Urgency** values.

Priority is calculated according to the following data lookup rules:

Impact	Urgency	Priority
1 - High	1 - High	1 - Critical
1 - High	2 - Medium	2 - High
1 - High	3 - Low	3 - Moderate
2 - Medium	1 - High	2 - High
2 - Medium	2 - Medium	3 - Moderate
2 - Medium	3 - Low	4 - Low
3 - Low	1 - High	3 - Moderate
3 - Low	2 - Medium	4 - Low
3 - Low	3 - Low	5 - Planning

# Adding Additional Fields to the Transform Map


If you require additional mandatory fields to be filled out to resolve an incident, you can add those fields to the **transform map** in ServiceNow.

For example, if you require four mandatory fields in the ServiceNow Incident—**Assignment Group**, **IT Service**, **Service Component**, and **Description**—to be filled out before that incident can be resolved in SL1, you would perform the following steps.

The screenshot displays the 'Main Details' section of a ServiceNow Incident form. The form is organized into two columns of fields. The left column includes fields for Caller (Science Logic), Behalf of user, Company (Motorpoint Limited), Location, IT service, Service component, Symptom, Configuration item, and Short description. The right column includes fields for Contact type (web), Impact (Some Users), Urgency (3 - Low), Priority (4 - Low), Major incident state, Owing group, Assignment group, and Assigned to. A 'Related Search Results' section is located below the main fields. Four fields are highlighted with red rectangular boxes: 'IT service', 'Service component', 'Assignment group', and 'Description'. The 'Description' field is located in the 'Related Search Results' section.

To add an assignment group:

1. Navigate to **User Administration > Groups** and select the assignment group you want to add. The Group record appears.
2. Right-click the gray task bar at the top and select **Copy sys\_id**.



3. In SL1, open to the "ServiceNow: Add/Update/Clear Incident" Run Book Action (Registry > Run Book > Actions).
4. Edit the **Input Parameters** of the Run Book Action to add the **sys\_id** to the relevant parameter or parameters to assign the assignment group to one of the new, acknowledged, or cleared incidents that are mapped. After an incident is created, the assignment group value will not be changed by the Run Book Action.

In the following example, the assignment group is assigned to incidents that are *cleared*:

```
"assignment_group_new": "",  
"assignment_group_ack": "",  
"assignment_group_clear": "sys_id"
```


The **IT Service**, **Service Component**, and **Description** fields in our example must be filled in before an Incident can be closed. To do this, changes must be made in the transform maps that are provided in the form of update sets from ScienceLogic.

**TIP:** For more information about mapping new fields and other mappings options, see [https://docs.servicenow.com/bundle/newyork-platform-administration/page/script/server-scripting/concept/c\\_MappingOptions.html](https://docs.servicenow.com/bundle/newyork-platform-administration/page/script/server-scripting/concept/c_MappingOptions.html).

To add the **Description** field:

1. In ServiceNow, search for "transform map" in the filter navigator. Click **Transform Maps**.
2. In the list of transform maps, search for "ScienceLogic" in the field above the **Name** column.

- Open the "ScienceLogic Incident" map:



- The **Field Maps** table at the bottom of the page allows you to edit or create mappings from the ScienceLogic Incident Import table to the ServiceNow Incident table. Click **[New]** to create a new field mapping.
- The **Source table** field should contain the ScienceLogic Incident Import and the **Target table** should include the ServiceNow Incident table:



- To create a new mapping to copy the contents of the **Short description** field to the **Description** field, select **Short description** from the **Source field** drop-down menu.
- In the **Target field** drop-down menu, select **Description**.
- Click **Update** to save your changes.

The **IT Service** and **Service Component** fields in our example are set in the Transform Script in the "ScienceLogic Event" transform map. To set the fields:

- In ServiceNow, make sure you have the **sys\_id** value for the target fields. If a field contains a magnifying glass, it will require a **sys\_id**. If a field has a drop-down, type in the field you wish to apply from the drop-down. In the case of our example, the **sys\_id** values of the two fields are required.
- In your ServiceNow instance, navigate to the **Transform Maps** table and select "ScienceLogic Event".

3. In the ScienceLogic Event transform map page, click the **[Transform Script]** tab and open the "onAfter" script.


The screenshot displays the configuration interface for a ScienceLogic Event transform map. The main configuration area includes fields for Source table, Target table, Application, Created date, Order, and Run script. Below this, there are options for Active status, Run business rules, Enforce mandatory fields, and Copy empty fields. A 'Related Links' section provides links for Auto Map Matching Fields, Transform, and Index Coalesce Fields.

The 'Transform Scripts' tab is selected, showing a table with the following data:

When	Script	Order	Active
onAfter	(function runTransformScript(source, map...	100	true
onBefore	(function runTransformScript(source, map...	100	true

4. Add the following under the "//Update target record when the Event was cleared from Sciencelogic" text:

```
sl_INT.(target field) = '[sys_id of the source field]'; //(IT service field)
sl_INT.(target field) = '[sys_id of the source field]'; //(Service component)
```



The screenshot shows a script editor interface. At the top, the 'When' dropdown is set to 'onAfter', the 'Application' is 'ScienceLogic', and the 'Order' is '100'. The script content is as follows:

```
1 (function runTransformScript(source, map, log, target /*undefined onStart*/ ) {
2
3     event_state_management();
4
5     function event_state_management(){
6         //Check ScienceLogic Events to see, if the Incident can be closed.
7         var sl_events = new GlideRecord('u_silo_events');
8         sl_events.addEncodedQuery('u_active=true^u_silo_task=' + source.u_task);
9         sl_events.query();
10        if(sl_events.getRowCount() == 0){
11            var sl_INT = new GlideRecord('incident');
12            sl_INT.get(target.u_silo_task);
13            if(source.u_incident_state == 6 && sl_INT.close_code.nil()){
14                //Update target record when the Event was cleared from ScienceLogic.
15                sl_INT.close_code='Closed/Resolved by Caller';
16                sl_INT.close_notes=source.u_work_notes;
17                sl_INT.state= 6;
18            }else if(source.u_incident_state ==6 && !sl_INT.close_code.nil()){
19                //Update target record when Event was cleared From ServiceNow.
20                sl_INT.close_notes= sl_INT.close_notes + " (" + source.u_work_notes + ")";
21            }
22            sl_INT.update();
23        }
24        return;
25    }
26
27 })(source, map, log, target);
```

- To find the target field, make a temporary mapping to see what the target field is. This mapping can be deleted once you know the target field.

	Source field	Target field
<input type="checkbox"/>	<a href="#">u_short_description</a>	shprt_description
<input type="checkbox"/>	<a href="#">u_contact_type</a>	contact_type
<input type="checkbox"/>	<a href="#">u_active</a>	active
<input type="checkbox"/>	<a href="#">u_short_description</a>	description
<input type="checkbox"/>	<a href="#">u_assignment_group</a>	assignment_group
<input type="checkbox"/>	<a href="#">u_correlation_id</a>	correlation_id
<input type="checkbox"/>	<a href="#">sys_updated_by</a>	caller_id
<input type="checkbox"/>	<a href="#">u_urgency</a>	urgency
<input type="checkbox"/>	<a href="#">u_cmdb_ci</a>	cmdb_ci
<input type="checkbox"/>	<a href="#">u_work_notes</a>	work_notes
<input checked="" type="checkbox"/>	<a href="#">u_impact</a>	<b>u_service_component</b>
<input type="checkbox"/>	<a href="#">u_impact</a>	impact
<input type="checkbox"/>	[Script]	company
<input type="checkbox"/>	[Script]	location

- Click **[Update]** to save your changes. The selected fields will be added into an Incident on closure.

---

# Chapter

# 4

## Troubleshooting the Incident Synchronization PowerPack

---

### Overview

This chapter contains troubleshooting resources, procedures, and the answers to frequently asked questions to use with the *ServiceNow Incident Synchronization PowerPack*.

This chapter covers the following topics:

<i>Initial Troubleshooting Steps</i> .....	70
<i>Resources for Troubleshooting</i> .....	70
<i>Frequently Asked Questions</i> .....	75

---

## Initial Troubleshooting Steps

PowerFlow acts as a middle server between data platforms. For this reason, the first steps should always be to ensure that there are no issues with the data platforms with which PowerFlow is talking. There might be additional configurations or actions enabled on ServiceNow or SL1 that result in unexpected behavior. For detailed information about how to perform the steps below, see [Resources for Troubleshooting](#).

### SL1 PowerFlow

1. Run `docker service ls` on the PowerFlow server.
2. Note the Docker container version, and verify that the Docker services are running.
3. If a certain service is failing, make a note the service name and version.
4. If a certain service is failing, run `docker service ps <service_name>` to see the historical state of the service and make a note of this information. For example: `docker service ps iservices_contentapi`.
5. Make a note of any logs impacting the service by running `docker service logs <service_name>`. For example: `docker service logs iservices_couchbase`.

### ServiceNow

1. Make a note of the ServiceNow version and Synchronization PowerPack version, if applicable.
2. Make a note of whether the user is running an update set or a version of the Certified/Scoped application, if relevant.
3. Make a note of the ServiceNow application that is failing on PowerFlow.
4. Make a note of what step is failing in the application, try running the application in debug mode, and capture any traceback or error messages that occur in the step log.

---

## Resources for Troubleshooting

This section contains port information for PowerFlow and troubleshooting commands for Docker, Couchbase, and the PowerFlow API.

### Useful PowerFlow Ports

- **http://<IP of PowerFlow>:8081**. Provides access to Docker Visualizer, a visualizer for Docker Swarm.
- **https://<IP of PowerFlow>:8091**. Provides access to Couchbase, a NoSQL database for storage and data retrieval.
- **https://<IP of PowerFlow>:15672**. Provides access to the RabbitMQ Dashboard, which you can use to monitor the service that distributes tasks to be executed by PowerFlow workers.
- **https://<IP of PowerFlow>/flower**. Provides access to Flower, a tool for monitoring and administrating Celery clusters.

**NOTE:** For version 2.0.0 and later of PowerFlow, port 5556 must be open for both PowerFlow and the client.

## Helpful Docker Commands

PowerFlow is a set of services that are containerized using Docker. For more information about Docker, see the [Docker tutorial](#).

Use the following Docker commands for troubleshooting and diagnosing issues with PowerFlow:

### Viewing Container Versions and Status

To view the PowerFlow version, SSH to your PowerFlow instance and run the following command:

```
docker service ls
```

In the results, you can see the container ID, name, mode, status (see the *replicas* column), and version (see the *image* column) for all the services that make up PowerFlow:

```
[root@fsunislab ~]# docker service ls
ID                NAME                MODE                REPLICAS            IMAGE                PORTS
ommihu35v30i     iservices_gui       replicated          1/1                 repository.auto.sciencelogic.local:5000/is-gui:1.7.0    *:80->80/tcp, *:443->443/tcp
40vs9it1wvh3     iservices_redis     replicated          1/1                 redis:4.0.2
j1m6h1jvumif     iservices_flowerv   replicated          1/1                 repository.auto.sciencelogic.local:5000/is-worker:1.7.0  *:5555->5555/tcp
hh3p2l3lrsf      iservices_scheduler replicated          1/1                 repository.auto.sciencelogic.local:5000/is-worker:1.7.0
htimlcv96kxh     iservices_contentapi replicated          1/1                 repository.auto.sciencelogic.local:5000/is-api:1.7.0    *:5000->5000/tcp
eyin9qgsudmi     iservices_rabbitmq  replicated          1/1                 rabbitmq:3
klul9h8jfsf6     iservices_visual    replicated          2/1                 dockersamples/visualizer:latest                       *:8081->8080/tcp
vcy38w8buauw     iservices_couchbase replicated          1/1                 repository.auto.sciencelogic.local:5000/is-couchbase:1.7.0 *:8091->8091/tcp, *:8092->8092/tcp
p->8093/tcp, *:8094->8094/tcp, *:11210->11210/tcp
libxatxot7uf     iservices_steprunner replicated          5/5                 repository.auto.sciencelogic.local:5000/is-worker:1.7.0
```

### Restarting a Service

Run the following command to restart a single service:

```
docker service update --force <service_name>
```

### Stopping all PowerFlow Services

Run the following command to stop all PowerFlow services:

```
docker stack rm iservices
```

### Restarting Docker

Run the following command to restart Docker:

```
systemctl restart docker
```

**NOTE:** Restarting Docker does not clear the queue.

## Viewing Logs for a Specific Service

You can use the Docker command line to view the logs of any current running service in the PowerFlow cluster. To view the logs of any service, run the following command:

```
docker service logs -f iservices_<service_name>
```

Some common examples include the following:

```
docker service logs -f iservices_couchbase
```

```
docker service logs -f iservices_steprunner
```

```
docker service logs -f iservices_contentapi
```

**NOTE:** Application logs are stored on the central database as well as on all of the Docker hosts in a clustered environment. These logs are stored at `/var/log/iservices` for both single-node or clustered environments. However, the logs on each Docker host only relate to the services running on that host. For this reason, using the Docker service logs is the best way to get logs from all hosts at once.

## Clearing RabbitMQ Volume

RabbitMQ is a service that distributes tasks to be executed by PowerFlow workers. This section covers how to handle potential issues with RabbitMQ.

The following error message might appear if you try to run a PowerFlow application via the API:

```
Internal error occurred: Traceback (most recent call last):\n File \"/content_
api.py", line 199, in kickoff_application\n task_status = ... line 623, in _on_
close\n (class_id, method_id), ConnectionError)\nInternalError: Connection.open: (541)
INTERNAL_ERROR - access to vhost '/' refused for user 'guest': vhost '/' is down
```

First, verify that your services are up. If there is an issue with your RabbitMQ volume, you can clear the volume with the following commands:

```
docker service rm iservices_rabbitmq
docker volume rm iservices_rabbitdb
```

If you get a message stating that the volume is in use, run the following command:

```
docker rm <id of container using volume>
```

Re-deploy PowerFlow by running the following command:

```
docker stack deploy -c /opt/iservices/scripts/docker-compose.yml iservices
```

**NOTE:** Restarting Docker does not clear the queue, because the queue is persistent. However, clearing the queue with the commands above might result in data loss due to the tasks being removed from the queue.

## Viewing the Process Status of All Services

Run the following command:

```
docker ps
```

## Deploying Services from a Defined Docker Compose File

Run the following command:

```
docker stack deploy -c <compose-file> iservices
```

## Dynamically Scaling for More Workers

Run the following command:

```
docker service scale iservices_steprunner=10
```

## Completely Removing Services from Running

Run the following command:

```
docker stack rm iservices
```

## Diagnosis Tools

Multiple diagnosis tools exist to assist in troubleshooting issues with the PowerFlow platform:

- **Docker PowerPack.** This PowerPack monitors your Linux-based PowerFlow server with SSH (the PowerFlow ISO is built on top of an Oracle Linux Operating System). This PowerPack provides key performance indicators about how your PowerFlow server is performing. For more information on the Docker PowerPack and other PowerPacks that you can use to monitor PowerFlow, see the "Using SL1 to Monitor SL1 PowerFlow" chapter in the *SL1 PowerFlow Platform* manual.
- **Flower.** This web interface tool can be found at the /flower endpoint. It provides a dashboard displaying the number of tasks in various states as well as an overview of the state of each worker. This tool shows the current number of active, processed, failed, succeeded, and retried tasks on the PowerFlow platform. This tool also shows detailed information about each of the tasks that have been executed on the platform. This data includes the UUID, the state, the arguments that were passed to it, as well as the worker and the time of execution. Flower also provides a performance chart that shows the number of tasks running on each individual worker.
- **Debug Mode.** All applications can be run in "debug" mode via the PowerFlow API. Running applications in debug mode may slow down the platform, but they will result in much more detailed logging information that is helpful for troubleshooting issues. For more information on running applications in Debug Mode, see [Retrieving Additional Debug Information](#).
- **Application Logs.** All applications generate a log file specific to that application. These log files can be found at /var/log/iservices and each log file will match the ID of the application. These log files combine all the log messages of all previous runs of an application up to a certain point. These log files roll over and will get auto-cleared after a certain point.

- **Step Logs.** Step logs display the log output for a specific step in the application. These step logs can be accessed via the PowerFlow user interface by clicking on a step in an application and bringing up the **Step Log** tab. These step logs display just the log output for the latest run of that step.
- **Service Logs.** Each Docker service has its own log. These can be accessed via SSH by running the following command:

```
docker service logs -f <service_name>
```

## Retrieving Additional Debug Information (Debug Mode)

The logs in PowerFlow use the following **loglevel** settings, from most verbose to least verbose:

- **10.** Debug Mode.
- **20.** Informational.
- **30.** Warning. This is the default settings if you do not specify a loglevel.
- **40.** Error.

**WARNING:** If you run applications with "loglevel": 10, those applications will take longer to run because of increased I/O requirements. Enabling debug logging using the following process is the only recommended method. ScienceLogic does not recommend setting "loglevel": 10 for the whole stack with the docker-compose file.

To run an application in Debug Mode, POST the following to the API endpoint:

```
https://<PowerFlow>/api/v1/applications/run
```

Request body:

```
{
  "name": "<application_name>",
  "params": {
    "loglevel": 10
  }
}
```

After running the application in Debug Mode, go back to the PowerFlow user interface and review the step logs to see detailed debug output for each step in the application. When run in Debug Mode, the step log output shows additional debug statements such as "Saved data for next step", which displays the data being sent from one step to the next.

This information is especially helpful when trying to understand why an application or step failed:

The screenshot displays the 'NVD To Events' interface. At the top, there are buttons for 'Reports', 'Edit', 'Configure', and 'Run Now'. Below this is a workflow diagram with the following steps: 'GetDataXML' (green box), 'GetInstalledSoftware' (red box), 'ParseXML', 'FormatSoftware', 'CompareSoftware', and 'TriggerEvents'. A 'Run failure' indicator is shown below the diagram. The 'Logs' section contains a table with the following data:

Step	Step Name	Timestamp	Level	Message
6	MySqlSelect	15 Oct, 2016 11:00:21, 626	INFO	Loaded parameter value: root, type <type 'str'> for parameter: username
7	MySqlSelect	15 Oct, 2016 11:00:21, 629	INFO	Loaded parameter value: em7admin, type <type 'str'> for parameter: password
8	MySqlSelect	15 Oct, 2016 11:00:21, 630	INFO	Loaded parameter value: SELECT did.title FROM master_dev.device_packages, type <type 'str'> for parameter: select_query
9	MySqlSelect	15 Oct, 2016 11:00:21, 633	INFO	Loaded parameter value: *, type <type 'str'> for parameter: fields
10	MySqlSelect	15 Oct, 2016 11:00:21, 633	INFO	Loaded parameter value: 7706, type <type 'int'> for parameter: port
11	BaseStep	15 Oct, 2016 11:00:21, 733	ERROR	Error when connecting to DB Host: 'http://192.168.32.188'. Username: 'root', database: 'master_dev' - (2003, 'Can't connect to MySQL server on 'http://192.168.32.188' (Errno -2) Name or service not known)'

You can also run an application in debug using curl via SSH:

1. SSH to the PowerFlow instance.
2. Run the following command:

```
curl -v -k -u isadmin:em7admin -X POST "https://<your_hostname>/api/v1/applications/run" -H 'Content-Type: application/json' -H 'cache-control: no-cache' -d '{"name": "interface_sync_sciencelogic_to_servicenow", "params": {"loglevel": 10}}'
```


## Frequently Asked Questions

This section contains a set of frequently asked questions (FAQs) and the answers to address those situations.

### Why are Incidents not getting created in ServiceNow?

1. In SL1, go to the **[Events Console]** (Classic user interface) or the **Events** page (SL1 user interface) and locate the event that was created.
  - In the SL1 user interface, click the **[Actions]** button ( **•••** ) for that event and select *View Automation Actions*.
  - In the Classic user interface, click the **View Notification Log** mailbox icon (  ) for that event.

The **Event Actions Log** window appears:



2. On the **Event Actions Log** window, verify that the Run Book Action was triggered, and that the Run Book Action successfully posted to PowerFlow.
3. In the "Add/Update Incident action" pane, locate the PowerFlow run ID, which is the first six or seven characters of the "isapp" integration ID associated with that run of the integration. For example: `isapp-a7805e58`.
4. In the PowerFlow user interface, go to the **Applications** page and open the "Create or Update ServiceNow Incident from SL1 Event" application.
5. Click the **[Timeline]** button  to locate the run that contains the PowerFlow run ID associated with that run of the integration (from step 3, above).
6. Click **[View Run]** for that run on the **Timeline** and review the logs in the **Step Log** panel to see where the application failed.

## What if my Incident does not have a CI?

For an incident with an active event:

1. In SL1, go to the **[Events Console]** (classic user interface) or the **Events** page (new user interface) and locate the event that was created.
  - In the SL1 user interface, click the **[Actions]** button ( **\*\*\*** ) for that event and select *View Automation Actions*.

- In the Classic user interface, click the **View Notification Log** mailbox icon () for that event.

The **Event Actions Log** window appears

2. On the **Event Actions Log** window, locate the PowerFlow run ID, which is the first six or seven characters of the "isapp" integration ID associated with that run of the integration. For example: *isapp-a7805e58*.
3. In the PowerFlow user interface, go to the **Applications** page and open the application that used that run.
4. Review the Step Log and confirm that the device class was mapped in the "Sync Devices from SL1 to ServiceNow" application.
5. Confirm that the "Sync Devices from SL1 to ServiceNow" application is running at least every 24 hours, and that the "Sync Devices from SL1 to ServiceNow" application has run within 24 hours of that event sync run.

## What if the PowerFlow user interface is unresponsive and Incidents are not being generated in ServiceNow?

If the PowerFlow user interface is unresponsive, and Incidents are not being generated in ServiceNow, this might mean that during the deployment process, a change to the firewall rules for monitoring broke the ingress network for Docker.

To address this issue, run the following command to restart Docker every time you make a firewall or network configuration change:

```
systemctl restart docker
```

## Why are Incident numbers not populated in SL1 on Incident creation in ServiceNow?

If an incident exists in ServiceNow, but incident data is not getting back to SL1, and the "Sync ServiceNow Incident State to SL1 Event" application fails on the "Get Incident" step (with a 404 error) and eventually times out, the issue might be because the ServiceNow API is overloaded.

## Why am I not getting any Incidents after disabling the firewall?

If you disabled the firewall to enable SNMP monitoring on PowerFlow, but were not able to connect, you should add the additional rule you need.

---

# Appendix

# A

## Checklists for Deployment

---

### Overview

This appendix describes the checklists for deploying PowerFlow and the ServiceNow Synchronization PowerPacks, based on your environment and configuration.

This appendix includes the following topics:

<i>CMDB-Only ServiceNow Integration with Single SL1, no Domain Separation in ServiceNow</i> .....	79
<i>CMDB-Only ServiceNow Integration with Single SL1 and Domain-Separated ServiceNow</i> .....	82
<i>CMDB-Only ServiceNow Integration with Multiple SL1 Systems, no Domain-Separated ServiceNow</i> .	86
<i>Incident-Only ServiceNow Integration with Single SL1, no Domain Separation in ServiceNow</i> .....	90

---

# CMDB-Only ServiceNow Integration with Single SL1, no Domain Separation in ServiceNow

1. Deploy the PowerFlow ISO:
  - IP address, Netmask, Gateway, DNS, Hostname provided
  - Root password provided (this is the root user for the OS)
  - Start Docker services after installation:

```
    /opt/iservices/scripts/pull_start_iservices.sh
```
  - Validate that iservices are running:

```
    docker service ls
```
2. Activate the Configuration Management For Scoped Apps (CMDB) Plugin.
3. Install the ScienceLogic Certified Application and create a ServiceNow group and user account:
  - Username
  - Password
  - Web Service Access Only
  - GMT Time Zone
  - x\_sclo\_scilogic.Admin role assigned
4. Install the ServiceNow Synchronization PowerPacks on PowerFlow.
5. Create the PowerFlow configuration object using the "ServiceNow SyncPack" configuration object as a template.

## Sync Devices from SL1 to ServiceNow

1. Align the configuration object to the following applications:
  - Cache ServiceNow CIs and SL1 Device Classes
  - Sync Devices from SL1 to ServiceNow
2. Run "Cache ServiceNow CIs and SL1 Device Classes" to retrieve all device class information from SL1 and ServiceNow. This will populate the device class mapping in the following step. This integration should be run at least every 23 hours.
3. Configure class and attribute mappings in "Sync Devices from SL1 to ServiceNow".
4. Run "Generate Required CI Relations for ServiceNow" to see if you are missing any service rules or class mappings and create any required maps, containment rules, and hosting rules.
5. Run "Sync Devices from SL1 to ServiceNow" either manually or on a schedule. This integration should be run at least every 23 hours. See documentation for more information.

## Discover Devices from ServiceNow in SL1

1. Align the configuration object to the following applications:
  - Sync Discovery Requirements
  - Sync Discovery Session Requests from ServiceNow to SL1
  - Sync Discovery Session Status from SL1 to ServiceNow
2. Set additional configuration variables for each of the integrations applications above in the respective **Configuration** pane.
3. Run "Sync Discovery Requirements" to sync all discovery-dependent information from SL1 to ServiceNow.
4. Make sure that the Discovery request RITM is successfully created and approved in ServiceNow using the provided Service Catalogs.
5. Run "Sync Discovery Session Requests from ServiceNow to SL1" either manually or on a schedule to create and execute the discovery session in SL1.
6. After the discovery session has completed in SL1, run "Sync Discovery Session Status from SL1 to ServiceNow" either manually or on a schedule to update the status of the RITM in ServiceNow.

**NOTE:** The following applications only sync CIs that are aligned with the devices that are already synced with ServiceNow. Before syncing any of the CIs below, you must first sync devices between SL1 and ServiceNow.

## Sync Business Services from SL1 to ServiceNow

1. Align the configuration object to the following application:
  - Sync Business Services from SL1 to ServiceNow
2. Configure the service classification mappings in "Sync Business Services from SL1 to ServiceNow". These are defined in the **Configuration** pane.
3. Run "Sync Business Services from SL1 to ServiceNow" either manually or on a schedule.

## Sync File Systems from SL1 to ServiceNow

1. Align the configuration object to the following application:
  - Sync File Systems from SL1 to ServiceNow
2. The parent CI must be synced in order to see these related CIs.
3. Run "Sync File Systems from SL1 to ServiceNow" either manually or on a schedule.

## Sync Network Interfaces from SL1 to ServiceNow

1. Align the configuration object to the following application:

- Sync Network Interfaces from SL1 to ServiceNow
2. Determine additional filters for syncing network interfaces using the **adapter\_sync** variable defined in the **Configuration** pane.
  3. The parent CI must be synced in order to see these related CIs.
  4. Run "Sync Network Interfaces from SL1 to ServiceNow" either manually or on a schedule. This application should be run at least every 23 hours if you would like to sync interface-level relationships with "Sync Advanced Topology from SL1 to ServiceNow".

## Sync Installed Software from SL1 to ServiceNow

1. Align the configuration object to the following application:
  - Sync Software Packages from SL1 to ServiceNow
  - Sync Installed Software from SL1 to ServiceNow
2. The parent CI must be synced in order to see these related CIs.
3. First, run "Sync Software Packages from SL1 to ServiceNow". Verify that the integration has run successfully.
4. Run "Sync Installed Software from SL1 to ServiceNow" either manually or on a schedule.

## Sync Maintenance Schedules from ServiceNow to SL1

1. Align the configuration object to the following application:
  - Sync Maintenance Schedules from ServiceNow to SL1
2. The parent CI must be synced in order to see these related CIs. The affected CI must have **SL1 Monitored** set to *True*.
3. If needed, configure the **Request** and **Task state** IDs in the **Configuration** pane. This is needed if the customer has custom IDs for certain change request or change task states.
4. Run "Sync Maintenance Schedules from ServiceNow to SL1" either manually or on a schedule.

## Sync Advanced Topology from SL1 to ServiceNow

1. Align the configuration object to the following application:
  - Sync Advanced Topology from SL1 to ServiceNow
2. The parent CI must be synced in order to see these related CIs. Syncing Interface-level relationships (Layer 2, LLDP, and CDP) will require that "Sync Network Interfaces from SL1 to ServiceNow" is set to run at least every 23 hours.
3. Run "Sync Advanced Topology from SL1 to ServiceNow" either manually or on a schedule.

---

# CMDB-Only ServiceNow Integration with Single SL1 and Domain-Separated ServiceNow

1. Deploy the PowerFlow ISO:
  - IP address, Netmask, Gateway, DNS, Hostname provided
  - Root password provided (this is the root user for the OS)
  - Start Docker services after installation:

```
/opt/iservices/scripts/pull_start_iservices.sh
```
  - Validate that iservices are running:

```
docker service ls
```
2. Activate the Configuration Management For Scoped Apps (CMDB) Plugin.
3. Install the ScienceLogic Certified Application and create a ServiceNow group and user account:
  - Username
  - Password
  - Web Service Access Only
  - GMT Time Zone
  - x\_sclo\_scilogic.Admin role assigned
4. Install the ServiceNow Synchronization PowerPacks on PowerFlow.
5. Create the PowerFlow configuration object using the "ServiceNow SyncPack" configuration object as a template.

## Sync Devices from SL1 to ServiceNow

1. Align the configuration object to following applications:
  - Sync Organizations from SL1 to ServiceNow Companies
  - Cache ServiceNow CIs and SL1 Device Classes
  - Sync Devices from SL1 to ServiceNow
2. In "Sync Organizations from SL1 to ServiceNow Companies" **Configuration** pane, set the **Source\_of\_Truth** to *ServiceNow* and set the **Domain\_Separation** flag to *True*.
3. Run "Sync Organizations from SL1 to ServiceNow Companies".
4. Run "Cache ServiceNow CIs and SL1 Device Classes" to retrieve all device class information from SL1 and ServiceNow. This will populate the device class mapping in the following step. This application should be run at least every 23 hours.

5. Configure class and attribute mappings in "Sync Devices from SL1 to ServiceNow". Set **Domain\_Separation** to *True*.
6. Run "Generate Required CI Relations for ServiceNow" to see if you are missing any service rules or class mappings, and then create any required maps, containment rules, and hosting rules.
7. Run "Sync Devices from SL1 to ServiceNow" either manually or on a schedule. This application should be run at least every 23 hours.

## Discover Devices from ServiceNow in SL1

1. Align Configuration Object to following applications:
  - Sync Discovery Requirements
  - Sync Discovery Session Requests from ServiceNow to SL1
  - Sync Discovery Session Status from SL1 to ServiceNow
2. In "Sync Discovery Requirements" **Configuration** pane, set the **Source\_of\_Truth** to *ServiceNow*. Set **Domain\_Separation** to *True*.
3. Run "Sync Discovery Requirements" to sync all discovery-dependent information from SL1 to ServiceNow and back to SL1.
4. Set additional configuration variables for each of the other applications above in the respective **Configuration** pane.
5. Discovery request RITM is successfully created and approved in ServiceNow using the provided Service Catalogs.
6. Run "Sync Discovery Session Requests from ServiceNow to SL1" either manually or on a schedule to create and execute the discovery session in SL1.
7. After the discovery session completes in SL1, run "Sync Discovery Session Status from SL1 to ServiceNow" either manually or on a schedule to update the status of the RITM in ServiceNow.

**NOTE:** Domain separation requires that "Sync Organizations from SL1 to ServiceNow Companies" is configured with **Domain\_Separation** enabled and **Source\_of\_Truth** set to *ServiceNow*. In a domain-separated ServiceNow environment, this application must be properly configured and run successfully before syncing any additional CI items. SL1 organizations that are linked to a ServiceNow company will have the **crm\_id** populated with the ServiceNow Company **sys\_id**.

**NOTE:** The following integrations only sync CIs that are aligned with the devices that are already synced with ServiceNow. Before syncing any of the CIs below, you must first sync devices between SL1 and ServiceNow.

## Sync Business Services from SL1 to ServiceNow

1. Align the configuration object to the following application:

- Sync Business Services from SL1 to ServiceNow
2. Configure the service classification mappings in "Sync Business Services from SL1 to ServiceNow". These are defined in the **Configuration** pane.
  3. Ensure that **Domain\_Separation** is set to *True* in the **Configuration** pane.
  4. Run "Sync Business Services from SL1 to ServiceNow" either manually or on a schedule.

## Sync File Systems from SL1 to ServiceNow

1. Align the configuration object to the following application:
  - Sync File Systems from SL1 to ServiceNow
2. Ensure that **Domain\_Separation** is set to *True* in the **Configuration** pane.
3. The parent CI must be synced in order to see these related CIs.
4. Run "Sync File Systems from SL1 to ServiceNow" either manually or on a schedule.

## Sync Network Interfaces from SL1 to ServiceNow

1. Align the configuration object to the following application:
  - Sync Network Interfaces from SL1 to ServiceNow
2. Determine additional filters for syncing network interfaces using the **adapter\_sync** variable defined in the **Configuration** pane.
3. Ensure that **Domain\_Separation** is set to *True* in the **Configuration** pane.
4. The parent CI must be synced in order to see these related CIs.
5. Run "Sync Network Interfaces from SL1 to ServiceNow" either manually or on a schedule. This application should be run at least every 23 hours if you would like to sync interface-level relationships with "Sync Advanced Topology from SL1 to ServiceNow".

## Sync Installed Software from SL1 to ServiceNow

1. Align the configuration object to the following application:
  - Sync Software Packages from SL1 to ServiceNow
  - Sync Installed Software from SL1 to ServiceNow
2. The parent CI must be synced in order to see these related CIs.
3. First, run "Sync Software Packages from SL1 to ServiceNow". Verify that the integration has run successfully.
4. Run "Sync Installed Software from SL1 to ServiceNow" either manually or on a schedule.

## Sync Maintenance Schedules from ServiceNow to SL1

1. Align the configuration object to the following application:

- Sync Maintenance Schedules from ServiceNow to SL1
2. The parent CI must be synced in order to see these related CIs. The affected CI must have **SL1 Monitored** set to *True*.
  3. If needed, configure the **Request** and **Task state** IDs in the **Configuration** pane. This is needed if the customer has custom IDs for certain change request or change task states.
  4. Run "Sync Maintenance Schedules from ServiceNow to SL1" either manually or on a schedule.

## Sync Advanced Topology from SL1 to ServiceNow

1. Align the configuration object to the following application:
  - Sync Advanced Topology from SL1 to ServiceNow
2. Ensure that **Domain\_Separation** is set to *True* in the **Configuration** pane.
3. The parent CI must be synced in order to see these related CIs. Syncing Interface-level relationships (Layer 2, LLDP, and CDP) will require that "Sync Network Interfaces from SL1 to ServiceNow" is set to run at least every 23 hours.
4. Run "Sync Advanced Topology from SL1 to ServiceNow" either manually or on a schedule.

---

## CMDB-Only ServiceNow Integration with Multiple SL1 Systems, no Domain-Separated ServiceNow

**NOTE:** Depending on the size of your SL1 stacks and the number of SL1 stacks you have, you may need to consider a “multi-tenant” configured IS. This is a more advanced deployment model. Please contact a ScienceLogic representative for more information.

1. Deploy the PowerFlow ISO:

- IP address, Netmask, Gateway, DNS, Hostname provided
- Root password provided (this is the root user for the OS)
- Start Docker services after installation:

```
/opt/iservices/scripts/pull_start_iservices.sh
```

- Validate that iservices are running:

```
docker service ls
```

2. Activate the Configuration Management For Scoped Apps (CMDB) Plugin.

3. Install the ScienceLogic Certified Application and create a ServiceNow group and user account:


- Username
- Password
- Web Service Access Only
- GMT Time Zone
- x\_sclo\_scilogic.Admin role assigned

4. Install the ServiceNow Synchronization PowerPacks on PowerFlow.

5. Create the PowerFlow configuration object using the "ServiceNow SyncPack" configuration object as a template.

**NOTE:** The key difference between integrating a single SL1 stack on PowerFlow and integrating multiple SL1 stacks on PowerFlow is how you run the application. Running the application with multiple SL1 stacks involves creating an individual configuration object for each SL1 stack. Then, create an individual schedule for each configuration object. Each schedule should use a configuration object that is specific to a single SL1 stack.

When creating the schedule, populate the custom parameters with the configuration object ID. For example:



## Sync Devices from SL1 to ServiceNow

1. Create a schedule for each SL1 stack for the following Applications following the note above:
  - Cache ServiceNow CIs and SL1 Device Classes
  - Sync Devices from SL1 to ServiceNow
2. Wait for the "Cache ServiceNow CIs and SL1 Device Classes" to retrieve all device class information from SL1 and ServiceNow. This will populate the device class mapping in the following step. This integration should be run at least every 23 hours.
3. Configure class and attribute mappings in "Sync Devices from SL1 to ServiceNow". If each SL1 stack has different class and attribute mapping requirements, you will need to specify the mappings in each schedule's custom parameters for this application.
4. Run "Generate Required CI Relations for ServiceNow" to see if you are missing any service rules or class mappings and create any required maps, containment rules, and hosting rules. By default, these will pull from the mappings set in "Sync Devices from SL1 to ServiceNow". If you have defined different mappings for each SL1 stack, you will need to also specify these mappings in each schedule's custom parameters for this application.
5. Run "Sync Devices from SL1 to ServiceNow" with a schedule where each schedule uses the configuration object for a SL1 stack. This application should be run at least every 23 hours.

## Discover Devices from ServiceNow in SL1

1. Create a schedule for each SL1 stack for the following applications:
  - Sync Discovery Requirements
  - Sync Discovery Session Requests from ServiceNow to SL1

- Sync Discovery Session Status from SL1 to ServiceNow
2. If any additional configuration variables are needed, these will need to be set in the custom parameters section for each schedule
  3. Run "Sync Discovery Requirements" on a schedule to sync all discovery-dependent information from SL1 to ServiceNow.
  4. Verify that the discovery request RITM is successfully created and approved in ServiceNow using the provided Service Catalogs.
  5. Run "Sync Discovery Session Requests from ServiceNow to SL1" on a schedule where each schedule uses the configuration object for a SL1 stack to create and execute the discovery session in SL1.
  6. Once the discovery session has completed in SL1, run "Sync Discovery Session Status from SL1 to ServiceNow" via schedule where each schedule uses the configuration object for a SL1 stack to update the status of the RITM in ServiceNow.

The following applications only sync CIs that are aligned with the devices that are already synced with ServiceNow. Before syncing any of the CIs below, you must first sync devices between SL1 and ServiceNow.

## Sync Business Services from SL1 to ServiceNow

1. Create a schedule for each SL1 stack for the following application:
  - Sync Business Services from SL1 to ServiceNow
2. Configure service classification mappings in "Sync Business Services from SL1 to ServiceNow" application. These are defined in the **Configuration** pane.
3. Run "Sync Business Services from SL1 to ServiceNow" on a schedule where each schedule uses the configuration object for a SL1 stack.

## Sync File Systems from SL1 to ServiceNow

1. Create a schedule for each SL1 stack for the following application:
  - Sync File Systems from SL1 to ServiceNow
2. The parent CI must be synced in order to see these related CIs.
3. Run "Sync File Systems from SL1 to ServiceNow" on a schedule where each schedule uses the configuration object for a SL1 stack.

## Sync Network Interfaces from SL1 to ServiceNow

1. Create a schedule for each SL1 stack for the following application:
  - Sync Network Interfaces from SL1 to ServiceNow

2. Determine additional filters for syncing network interfaces using the **adapter\_sync** variable defined in the **Configuration** pane.
3. The parent CI must be synced in order to see these related CIs.
4. Run "Sync Network Interfaces from SL1 to ServiceNow" on a schedule where each schedule uses the configuration object for a SL1 stack. This application should be run at least every 23 hours if you would like to sync interface-level relationships with "Sync Advanced Topology from SL1 to ServiceNow".

## Sync Installed Software from SL1 to ServiceNow

1. Create a schedule for each SL1 stack for the following application:
  - Sync Software Packages from SL1 to ServiceNow
  - Sync Installed Software from SL1 to ServiceNow
2. The parent CI must be synced in order to see these related CIs.
3. "Sync Software Packages from SL1 to ServiceNow" must run on a schedule before "Sync Installed Software from SL1 to ServiceNow". Verify that the software packages have been synced before continuing.
4. After the software packages have been synced, run "Sync Installed Software from SL1 to ServiceNow" on a schedule where each schedule uses the configuration object for a SL1 stack.

## Sync Maintenance Schedules from ServiceNow to SL1

1. Create a schedule for each SL1 stack for the following application:
  - Sync Maintenance Schedules from ServiceNow to SL1
2. The parent CI must be synced in order to see these related CIs. The affected CI must have the **SL1 Monitored** field set to *True*.
3. If needed, configure the **Request** and **Task state** IDs in the **Configuration** pane. This is needed if the customer has custom IDs for certain change request or change task states.
4. Run "Sync Maintenance Schedules from ServiceNow to SL1" on a schedule where each schedule uses the configuration object for a SL1 stack.

## Sync Advanced Topology from SL1 to ServiceNow

1. Create a schedule for each SL1 stack for the following application:
  - Sync Advanced Topology from SL1 to ServiceNow
2. The parent CI must be synced in order to see these related CIs. Syncing Interface-level relationships (Layer 2, LLDP, and CDP) will require that you set "Sync Network Interfaces from SL1 to ServiceNow" to run at least every 23 hours.
3. Run "Sync Advanced Topology from SL1 to ServiceNow" on a schedule where each schedule uses the configuration object for a SL1 stack.

---

# Incident-Only ServiceNow Integration with Single SL1, no Domain Separation in ServiceNow

1. Deploy the PowerFlow ISO:
  - IP address, Netmask, Gateway, DNS, Hostname provided
  - Root password provided (this is the root user for the OS)
  - Start Docker services after installation:

```
    /opt/iservices/scripts/pull_start_iservices.sh
```
  - Validate that iservices are running:

```
    docker service ls
```
2. Install the ScienceLogic Certified Application and create a ServiceNow group and user account:
  - Username
  - Password
  - Web Service Access Only
  - GMT Time Zone
3. Install the ServiceNow Synchronization PowerPacks on PowerFlow.
4. Create the PowerFlow configuration object using the "ServiceNow SyncPack" configuration object as a template:
  - Align the configuration object to the following applications:
    - Create or Update ServiceNow Incident from SL1 Event
    - Update ServiceNow Incident when SL1 Event is Acknowledged
    - Update ServiceNow Incident when SL1 Event is Cleared
    - Sync Incident State from ServiceNow to SL1 Event
  - Only the following Integration should be run manually or scheduled:
    - Sync Incident State from ServiceNow to SL1 Event
5. Install the ServiceNow Base PowerPack and configure SL1 :
  - Use the "ServiceNow RBA – Example" credential as a template to create a new credential that points to the PowerFlow instance.
  - Align the newly-created credential to the "ServiceNow – Add/Update/Clear Incident" Run Book Action.
  - Ensure that all Run Book Actions and Run Book Policies are enabled.

---

# Appendix

# B

## Certified Application Objects

---

### Overview

This appendix describes the tables, endpoints, and roles that were created in ServiceNow as part of the "ScienceLogic SL1 : CMDB & Incident Automation" application. This application is also known as the "Certified Application" or the "Scoped Application".

This appendix includes the following topics:

<i>Roles</i> .....	92
<i>Tables</i> .....	93
<i>Table Columns (cmdb_ci)</i> .....	93
<i>Table Columns (core_company)</i> .....	94
<i>Table Columns (cmdb_group)</i> .....	94
<i>Script Includes</i> .....	94
<i>Event Registry</i> .....	94
<i>Scripted Actions</i> .....	95
<i>Data Lookup Definitions</i> .....	95
<i>System Properties</i> .....	95
<i>Catalog Item</i> .....	96
<i>Catalog UI Policies</i> .....	96
<i>Variable Sets</i> .....	96
<i>Catalog Client Scripts</i> .....	97
<i>Workflows</i> .....	97
<i>Scripted REST Resources</i> .....	98

Transform Maps .....	100
Transform Scripts .....	100

## Roles

Two Roles were added with the ScienceLogic update set, Admin (x\_sclo\_scilogic.Admin) and User (x\_sclo\_scilogic.User). Both give access to SL1.

Role	Inherited Roles	Other Inherited Roles	Role Definition
x_sclo_scilogic.Admin			Role for ScienceLogic Service Accounts.
	itil		Can perform standard actions for an ITIL help desk technician. This is the default "Technician" role. Can open, update, close incidents, problems, changes, config management items. By default, only users with the itil role can have tasks assigned to them
		Dependency_view	A special role to be applied both on the \$ngbsm UI page and on the BSMPProcessor. This role is required to access the dependency views module. By default, ITIL includes this role to avoid regressions.
		cmdb_query_builder	Can access the CMDB Query Builder application to create, run, and save queries on the CMDB.
		template_editor	
		view_changer	Can switch active views.
		app_service_user	Can view and retrieve information using API from application service maps (cmdb_ci_service_discovered).
		certification	Can work on Certification tasks.
	import_transformer		Can manage Import Set Transform Maps and run transforms.
x_sclo_scilogic.User			General user account that allows read-only access to SL1.

## Tables

Name	Label	Extends	Comments
x_sclo_scilogic_event	Event	(empty)	Event information
x_sclo_scilogic_event_severity	Event Severity Look Rules	Data Lookup Matcher Rules	Look up table for event Severity
x_sclo_scilogic_incident	Import Incident	Import Set Row	Import / staging events before transform to Event and Incident
x_sclo_scilogic_import_installed_software	Import Installed Software	Import Set Row	Import / staging events before transform to Software Instance
x_sclo_scilogic_org_ven_mfg	Import ORG VEN MFG	Import Set Row	Import / staging events before transform to core_company
x_sclo_scilogic_import_discovery_dependent	Import Discovery Dependent	Import Set Row	Import / staging events before transform to Discovery Dependent table
x_sclo_scilogic_discovery_dependent	Discovery Dependent	(empty)	Discovery Dependent Information
x_sclo_scilogic_catalog_item_templates	Catalog item Templates	(empty)	Templates use to fill out catalog items
x_sclo_scilogic_import_service_request	Import Service Request	Import Set Row	Import / staging events before transform to Service Requests

## Table Columns (cmdb\_ci)

Name	Label	Type	Comments
x_sclo_scilogic_id	SL1 ID	Integer	Unique ID
x_sclo_scilogic_region	SL1 Region	String	Unique String of SL1 Platform
x_sclo_scilogic_url	SL1 URL	URL	URL to SL1 Platform
x_sclo_scilogic_monitored	SL1 Monitored	True/False	Device currently synced with SL1 Platform

---

## Table Columns (core\_company)

Name	Label	Type	Comments
x_sclo_scilogic_id	SL1 ID	String	Unique ID
x_sclo_scilogic_region	SL1 Region	String	Unique String of SL1 Platform
x_sclo_scilogic_monitored	SL1 Monitored	True/False	Organization currently synced with SL1 Platform

---

## Table Columns (cmdb\_group)

Name	Label	Type	Comments
x_sclo_scilogic_id	SL1 ID	String	Unique ID
x_sclo_scilogic_region	SL1 Region	String	Unique String of SL1 Platform

---

## Script Includes

Name	API Name	Comments
CatalogUtils	x_sclo_scilogic.catalogUtils	Catalog Script include scripts
ChangeUtils	x_sclo_scilogic.changeUtils	Change Script include scripts
DeviceUtils	x_sclo_scilogic.DeviceUtils	Device Script include scripts
EventUtils	x_sclo_scilogic.EventUtils	Event Script include scripts
GeneralUtils	x_sclo_scilogic.GeneralUtils	General Script include scripts

---

## Event Registry

Suffix	Event name	Table	Comments
device_monitoring	x_sclo_scilogic.device_monitoring	Configuration Item [cmdb_ci]	Event for Device Monitoring
Remove_monitoring	x_sclo_scilogic.remove_monitoring	Configuration Item [cmdb_ci]	Event for Remove Monitoring

## Scripted Actions

Name	Event name	Comments
Device Monitoring Catalog item	x_sclo_scilogic.device_monitoring	Action used to submit Catalog item via Event.
Device Removal Catalog item	x_sclo_scilogic.remove_monitoring	Action used to submit Catalog item via Event.

## Data Lookup Definitions

Name	Source Table	Matcher Table	Comments
Event Severity	Import Incident [x_sclo_scilogic_incident]	Event Severity Lookup Rules [x_sclo_scilogic_event_severity]	Lookup for ScienceLogic Severity to Impact and Urgency

## System Properties

Suffix	Name	Comments
CatalogItemDiscovery	x_sclo_scilogic.CatalogItemDiscovery	Unique value (sys_id)
CatalogItemRemove	x_sclo_scilogic.CatalogItemRemove	Unique value (sys_id)
closeCode	x_sclo_scilogic.closeCode	Value to use for Close Code for Incident Transform
Contact type	x_sclo_scilogic.Contact Type	Value to use for Contact type for Incident Transform
deviceLogging	x_sclo_scilogic.deviceLogging	Turn on Logging
deviceLoggingParam	x_sclo_scilogic.deviceLoggingParm	Add additional parameters beyond the default errors
discoverySource	x_sclo_scilogic.discoverySource	Discovery Source to be used by PowerFlow
notResolved	x_sclo_scilogic.notResolved	Value of Reopened Incident
stateNew	x_sclo_scilogic.stateNew	Value of New Incident
StateResolved	x_sclo_scilogic.stateResolved	Value of Resolved Incident

---

## Catalog Item

Name	Comments
Device Discovery	Role for ScienceLogic Service Accounts.
Monitoring Removal	General user account that allows read only access to ScienceLogic Application.

---

## Catalog UI Policies

Catalog item	Short description	Comments
Device Discovery	Catalog Template	Updates form based on Select template
Device Discovery	Create Virtual Device	Updates form based on Request type
Device Discovery	Create Virtual Device (Retired)	
Device Discovery	Device Discovery	Updates form based on Request type
Device Discovery	Device Discovery (Retired)	
Monitoring Removal	Hide Overview variables not required	Hide variables not required for the Monitoring Removal request
Device Discovery	Port Scan	Hide scan ports that are not default
Device Discovery	Port Scan (Retired)	
Device Discovery	Region	Updates form based on Organization
Device Discovery	Region (Retired)	
Monitoring Removal	Region via Organization	Updates form based on Organization
Device Discovery	Save as Template	Updates form based on Save as template

---

## Variable Sets

Title	Internal name	Comments
Create_virtual_device	create_virtual_device	
Discovery Overview	discovery_overview	

Title	Internal name	Comments
Discovery Sesion - Basic Settings	discovery_sesion_basic_settings	
Discovery Session - Detection and Scanning	discovery_session_detection_and_scanning	
Discovery Session - IP & Credentials	discovery_session_ip_credentials	
Monitoring Removal	monitoring_removal	
Service Catalog item Template	service_catalog_item_template	

---

## Catalog Client Scripts

Name	Catalog item	Type	Comments
Hide Request Type Options	Monitoring Removal	onLoad	Shared variable hide options that don't apply
Hide Request Type Options	Device Discovery	onLoad	Shared variable hide options that don't apply
Region	Monitoring Removal	onChange	Update Region field based on Company Region
Region	Monitoring Removal	onChange	Update Region field based on Company Region

---

## Workflows

Name	Table	Comments
SL1 Monitoring Removal	Requested Item [sc_req_item]	Workflow for Removal of devices from SL1 process
SL1 Discovery Session	Requested Item [sc_req_item]	Workflow for Discovery session process

## Scripted REST Resources

Name		Comments	
Business Services	/api/x_sclo_scilogic/v1/sciencelogic/business_service	GET	This GET api will pull all ScienceLogic monitored Configuration items specific to Business Services class from the CMDB. It will be ordered via the sys_id field to ensure the same order every time.
CMDB Group	/api/x_sclo_scilogic/v1/sciencelogic/cmdb_group	POST	Use this API to create cmdb_groups & add a CI to them.
Change Requests	/api/x_sclo_scilogic/v1/sciencelogic/change_requests	GET	This GET api will pull Active Change Requests or Change Tasks based on the record_type supplied that have ScienceLogic monitored CI attached. It will be ordered via the sys_id field to ensure the same order every time.
Classification	/api/x_sclo_scilogic/v1/sciencelogic/classification	GET	This GET api will pull all required CMDB information to build JSON payloads.
Companies	/api/x_sclo_scilogic/v1/sciencelogic/companies	GET	This GET api will pull all Active Companies that are ScienceLogic monitored. It will be ordered via the sys_id field to ensure the same order every time.
Configuration Items	/api/x_sclo_scilogic/v1/sciencelogic/configuration_Items	GET	This GET api will pull all ScienceLogic monitored Configuration items from the CMDB. It will be ordered via the sys_id field to ensure the same order every time.
Device IdentificationEngine	/api/x_sclo_scilogic/v1/sciencelogic/IdentificationEngine	POST	Use this API to create or update configuration items within the CMDB via ScienceLogic.

Name		Comments	
File Systems	/api/x_sclo_scilogic/v1/sciencelogic/file_systems	GET	This GET api will pull all ScienceLogic monitored Configuration items specific to File systems class from the CMDB. It will be ordered via the sys_id field to ensure the same order every time.
Import Set	/api/x_sclo_scilogic/v1/sciencelogic/import_set	POST	This POST API will post to the target import set table and create a record for each cmdb_ci.
Incidents	/api/x_sclo_scilogic/v1/sciencelogic/incidents	GET	This GET api will pull all incidents. It will be ordered via the sys_id field to ensure the same order every time.
Installed Software	/api/x_sclo_scilogic/v1/sciencelogic/installed_software	GET	This GET api will pull all Servicenow Software packages and installed instances from the CMDB. It will be ordered via the sys_id field to ensure the same order every time.
Manufacture	/api/x_sclo_scilogic/v1/sciencelogic/manufactures	POST	This POST API will pull all Manufactures.
Model	/api/x_sclo_scilogic/v1/sciencelogic/models	POST	This POST API will pull all Model.
Network Adapters	/api/x_sclo_scilogic/v1/sciencelogic/network_adapters	GET	This GET api will pull all ScienceLogic monitored Configuration items specific to Network Adapter class from the CMDB. It will be ordered via the sys_id field to ensure the same order every time.
Service Request	/api/x_sclo_scilogic/v1/sciencelogic/service_request	GET	This GET api will pull all ServiceRequest items from the CMDB associated with Device Discovery Catalog item. It will be ordered via the sys_id field to ensure the same order every time.
Classification	/api/x_sclo_scilogic/v2/sciencelogic/classification	GET	This GET api will pull all required CMDB information to build JSON payloads.

## Transform Maps

Name	Source Table	Target Table	Comments
ScienceLogic Discovery Dependent	Import Discovery Dependent	Discovery Dependent	Import / staging table for Catalog Dependents
ScienceLogic Event	Import Incident	Event	Import / staging table for Events.
ScienceLogic Incident	Import Incident	Incident [incident]	Import / staging table for Incident
ScienceLogic Organization	Import ORG VEN MFG []	Company [core_company]	Import / staging table for Organization
ScienceLogic Service Request	Import Service Request []	Request Item [sc_req_item]	Import / staging table for Request item

## Transform Scripts

Name	Transform Map	Order	Comments
onBefore	ScienceLogic Event	100	Check Action
onAfter	ScienceLogic Event	100	Check Action; Get Resolved Validation script include
onBefore	ScienceLogic Incident	100	Check Action, event workflow script include
onAfter	ScienceLogic Incident	100	Check Action, Affected CI script include

---

# Appendix

# C

## ServiceNow API Endpoints

---

### Overview

This appendix describes the customized ServiceNow API Endpoints that were created for the ServiceNow Synchronization PowerPacks. These scripted endpoints reduce the amount of REST calls that PowerFlow makes to ServiceNow.

Please note that for pagination, the following Query parameters are not required: `sysparm_offset` and `sysparm_limit`. The default settings are:

- `sysparm_offset=0`
- `sysparm_limit` = ServiceNow defines the default upper limits for data export. It will check the following properties at *System Properties > Import Export*: `glide.json.export.limit`, `glide.ui.export.limit`, and then `glide.ui.export.war.threshold`.

For example, if you have 200 total records and you want to pull the records in 100-record chunks, then the first pull would be `sysparm_offset=0 & sysparm_limit=100` and the second pull would be `sysparm_offset=100 & sysparm_limit=100`. For more information, see the ServiceNow documentation for [Export Limits](#).

This appendix includes the following topics:

<a href="#">Business Services</a> .....	103
<a href="#">Change Requests</a> .....	105
<a href="#">Classification version 1</a> .....	107
<a href="#">Classification version 2</a> .....	110
<a href="#">CMDB Group</a> .....	113
<a href="#">Companies</a> .....	115
<a href="#">Device Identification Engine</a> .....	118

<i>Discovery Dependents</i> .....	121
<i>File Systems</i> .....	123
<i>Import Set</i> .....	125
<i>Incidents</i> .....	127
<i>Installed Software</i> .....	130
<i>Manufacturer</i> .....	133
<i>Model</i> .....	135
<i>Network Adapters</i> .....	137
<i>Service Requests</i> .....	139

---

# Business Services

## HTTP Method

GET

## Pagination

Enabled

## Resource Path

`/api/x_sclo_scilogic/v1/sciencelogic/business_service`

## Default Resource Path

`/api/x_sclo_scilogic/sciencelogic/business_service`

This operation pulls all the fields from just the Business Service (**cmdb\_ci\_service**) table. The return is ordered by **sys\_id**, so the results display in the same order every time. The results are filtered by the **SL1 monitored** and **SL1 ID** field on the ServiceNow side. This operation requires the region to be supplied by the requester, and it will only return region-supplied configuration items.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

Parameters	
Key	Value
region (required)	ScienceLogic
sysparm_offset	0
sysparm_limit	glide.json.export.limit, glide.ui.export.limit, glide.ui.export.war.threshold

## Example (Request URL)

`https://<your Instance>.service-now.com/api/x_sclo_scilogic/v1/ sciencelogic/business_service`

## Example (Response)

```
{
  "results": [
    {
      "operational_status": "1",
      "sys_updated_on": "2019-02-06 19:32:34",
      "discovery_source": "Other Automated",
      "first_discovered": "2019-02-06 19:31:19",
      "sys_updated_by": "admin",
      "sys_created_on": "2019-02-06 19:31:19",
      "sys_domain": "global",
      "used_for": "Production",
      "sys_created_by": "is4user1",
      "sys_domain_path": "/",
      "install_status": "1",
      "name": "One Service to rule them",
      "subcategory": "Service",
      "busines_criticality": "1 - most critical",
      "last_discovered": "2019-02-06 19:31:19",
      "sys_class_name": "cmdb_ci_service",
      "sys_id": "52da95dcdb6323009f7dd7a0cf961918",
      "sys_class_path": "/!/#C",
      "comments": "Postman",
      "sys_mod_count": "1",
      "x_sclo_scilogic_id": "1570",
      "model_id": "e8aaeb3f3763100044e0bfc8bcbe5d20",
      "cost_cc": "USD",
      "x_sclo_scilogic_monitored": "true",
      "category": "Business Service",
      "service_classification": "Technical Service",
      "x_sclo_scilogic_region": "ScienceLogic"
    }
  ],
  "sysparm_offset": 0,
  "sysparm_limit": 100,
  "return_count": 1,
  "total_count": 1
}
```

---

# Change Requests

## HTTP Method

GET

## Resource Path

```
/api/x_sclo_scilogic/v1/sciencelogic/change_requests?record_type=change_request&state=1&region=ScienceLogic
```

## Default Resource Path

```
/api/x_sclo_scilogic/v1/sciencelogic/change_requests?record_type=change_request&state=1&region=ScienceLogic
```

This scripted API was built for pulling Change Requests or Change Tasks and formatting a JSON object response with the required information to create a maintenance schedule in SL1. The GET queries the **task\_ci** table to find configuration items that are monitored by SL1 and are the correct record type. The GET operation returns all records with their configuration items in formatted JSON strings that include planned start and end time.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

Parameters	
Key	Value
record_type (required)	change_request
state	-5
region (required)	ScienceLogic
sysparm_offset	0
sysparm_limit	glide.json.export.limit, glide.ui.export.limit, glide.ui.export.war.threshold

HTTP Status
-------------

Code	Value
200	OK
400	Query parameter \region\ is not defined and is required.

## Fixed Internal Query

### State:

```
`task.sys_class_name=' + recordType + `task.state=' + state + `^ci_item.x_sclo_scilogic_monitored=true^ci_item.x_sclo_scilogic_region=' + region
```

### Non-State:

```
`task.active=true^task.sys_class_name=' + recordType + `ci_item.x_sclo_scilogic_monitored=true^ci_item.x_sclo_scilogic_region=' + region
```

## Example

[https://<your Instance>.service-now.com/api/x\\_sclo\\_scilogic/v1/sciencelogic/change\\_requests?record\\_type=change\\_request&state=-5&region=ScienceLogic](https://<your Instance>.service-now.com/api/x_sclo_scilogic/v1/sciencelogic/change_requests?record_type=change_request&state=-5&region=ScienceLogic)

## Example (Response)

```
{
  "results": [
    {
      "sys_id": "48ebaba0db962f00dc44f00fbf961961",
      "number": "CHG0030001",
      "state_value": "-5",
      "state": "New",
      "short_description": "Test Change",
      "planned_start_date": "2019-01-01 06:00:01",
      "planned_end_date": "2019-01-01 18:00:01",
      "device": [
        {
          "sys_id": "d83dac0adb4dab00dc44f00fbf961919",
          "name": "Postman Test Server 11",
          "id": "11",
          "region": "ScienceLogic"
        }
      ]
    }
  ]
}
```

---

# Classification version 1

**NOTE:** This API Endpoint has been deprecated. The last version of the "ScienceLogic SL1 : CMDB & Incident Automation" application" (also called the Certified or Scoped application), that used this endpoint was version 1.0.18.

## HTTP Method

GET

## Pagination

Enabled

## Resource Path

`/api/x_sclo_scilogic/v1/sciencelogic/classification`

## Default Resource Path

`/api/x_sclo_scilogic/sciencelogic/classification`

To support the identification and reconciliation framework, SL1 requires a large amount of information to know how to correctly fill out the JSON formatted string defined by the Identification Engine documentation. This operation uses the **getTableExtension()** function to find all the tables extended from the **cmdb\_ci** table and then goes through each table one by one. This operation collects information about each class, such as which fields are required to identify and if it considers another class to help find uniqueness. This operation then finds all the associated metadata. Finally, the operation pulls a list of all field names from the table. By default the **criterion\_attributes** and **attributes** are not included and require "action=attributes" as a parameter in the API call to be passed.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

Parameters	
Key	Value
action	attributes

Attributes require x\_sclo\_scilogic.Admin be added to **sys\_dictionary.\*** (read) ACL to allow the API to access field names on each class table.

## Fixed Internal Query

### Example

```
https://<your Instance>.service-now.com/api/x_sclo_scilogic/sciencelogic/
classification
```

### Example (Response)

```
{
  "results": [
    {
      "class_label": "Storage Area Network",
      "class_table": "cmdb_ci_san",
      "criterion_attributes": [
        ""
      ],
      "independent": "false",
      "containment_rule": [

      ],
      "hosting_rule": [

      ],
      "reference_rule": [

      ],
      "attributes": [
        "asset",
        "asset_tag",
        "assigned",
        "assigned_to",
        "assignment_group",
        "attributes",
        "can_print",
        "category",
        "change_control",
        "checked_in",
        "checked_out",
        "comments",
        "company",
        "correlation_id",
        "cost",
        "cost_cc",
        "cost_center",
        "delivery_date",
        "department",
        "discovery_source",
        "dns_domain",
        "due",
        "due_in",
        "fault_count",
```

```

    "first_discovered",
    "fqdn",
    "gl_account",
    "install_date",
    "install_status",
    "invoice_number",
    "ip_address",
    "justification",
    "last_discovered",
    "lease_id",
    "location",
    "mac_address",
    "maintenance_schedule",
    "managed_by",
    "manufacturer",
    "model_id",
    "model_number",
    "monitor",
    "name",
    "operational_status",
    "order_date",
    "owned_by",
    "po_number",
    "purchase_date",
    "san_id",
    "schedule",
    "serial_number",
    "short_description",
    "skip_sync",
    "start_date",
    "subcategory",
    "supported_by",
    "support_group",
    "sys_class_name",
    "sys_class_path",
    "sys_created_by",
    "sys_created_on",
    "sys_domain",
    "sys_domain_path",
    "sys_id",
    "sys_mod_count",
    "sys_updated_by",
    "sys_updated_on",
    "unverified",
    "vendor",
    "warranty_expiration",
    "x_sclo_scilogic_id",
    "x_sclo_scilogic_monitored",
    "x_sclo_scilogic_region",
    "x_sclo_scilogic_url"
  ]
}
]
}

```

---

# Classification version 2

## HTTP Method

GET

## Pagination

Enabled

## Resource Path

`/api/x_sclo_scilogic/v2/sciencelogic/classification`

## Default Resource Path

`/api/x_sclo_scilogic/sciencelogic/classification`

To support the identification and reconciliation framework, SL1 requires a large amount of information to know how to correctly fill out the JSON formatted string defined by the Identification Engine documentation. This operation uses the **getTableExtension()** function to find all the tables extended from the **cmdb\_ci** table and then goes through each table one by one. This operation collects information about each class, such as which fields are required to identify and if it considers another class to help find uniqueness. This operation then finds all the associated metadata. Finally, the operation pulls a list of all field names from the table. By default the **criterion\_attributes** and **attributes** are not included and require "action=attributes" as a parameter in the API call to be passed.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

Parameters	
Key	Value
action	attributes
sysparm_offset	0
sysparm_limit	glide.json.export.limit, glide.ui.export.limit, glide.ui.export.war.threshold

Attributes require x\_sclo\_scilogic.Admin be added to **sys\_dictionary.\*** (read) ACL to allow the API to access field names on each class table.

## Fixed Internal Query

### Example

```
https://<your Instance>.service-now.com/api/x_sclo_scilogic/v2/sciencelogic/
classification
```

### Example (Response)

```
{
  "results": [
    {
      "class_label": "Storage Area Network",
      "class_table": "cmdb_ci_san",
      "criterion_attributes": [
        ""
      ],
      "independent": "false",
      "containment_rule": [
      ],
      "hosting_rule": [
      ],
      "reference_rule": [
      ],
      "attributes": [
        "asset",
        "asset_tag",
        "assigned",
        "assigned_to",
        "assignment_group",
        "attributes",
        "can_print",
        "category",
        "change_control",
        "checked_in",
        "checked_out",
        "comments",
        "company",
        "correlation_id",
        "cost",
        "cost_cc",
        "cost_center",
        "delivery_date",
        "department",
        "discovery_source",
        "dns_domain",
        "due",
        "due_in",
        "fault_count",
        "first_discovered",
        "fqdn",
        "gl_account",
```

```

    "install_date",
    "install_status",
    "invoice_number",
    "ip_address",
    "justification",
    "last_discovered",
    "lease_id",
    "location",
    "mac_address",
    "maintenance_schedule",
    "managed_by",
    "manufacturer",
    "model_id",
    "model_number",
    "monitor",
    "name",
    "operational_status",
    "order_date",
    "owned_by",
    "po_number",
    "purchase_date",
    "san_id",
    "schedule",
    "serial_number",
    "short_description",
    "skip_sync",
    "start_date",
    "subcategory",
    "supported_by",
    "support_group",
    "sys_class_name",
    "sys_class_path",
    "sys_created_by",
    "sys_created_on",
    "sys_domain",
    "sys_domain_path",
    "sys_id",
    "sys_mod_count",
    "sys_updated_by",
    "sys_updated_on",
    "unverified",
    "vendor",
    "warranty_expiration",
    "x_sclo_scilogic_id",
    "x_sclo_scilogic_monitored",
    "x_sclo_scilogic_region",
    "x_sclo_scilogic_url"
  ]
}
]
}

```

---

# CMDB Group

## HTTP Method

POST

## Pagination

Enabled

## Resource Path

```
/api/x_sclo_scilogic/v1/sciencelogic/cmdb_group
```

## Default Resource Path

```
/api/x_sclo_scilogic/sciencelogic/cmdb_group
```

This operation handles the intake of groups of devices from SL1 and converts the device groups to CMDB groups. This operation uses a standard formatted JSON string, and it checks for a **sys\_id** of the group first by searching for a matching group. This process creates a group if a group is not supplied or found, and then it passes the JSON object to the ServiceNow CMDBGroupAPI, which sets the manual CI list of the group.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

## Example (Request URL)

```
https://<your Instance>.service-now.com/api/x_sclo_scilogic/v1/sciencelogic/cmdb_group
```

## Example (Body)

```
[
  {
    "items": [
      {
        "name": "test",
        "description": "",
        "group": "",
        "manualCIList": "d83dac0adb4dab00dc44f00fbf961919,2e6b7046db8dab00dc44f00fbf961929,7fb39667dba12380dc44f00fbf961901,77b39667dba12380dc44f00fbf961917,7bb39667dba12380dc44f00fbf96191c",
        "region": "Cisco",
        "id": "1"
      }
    ]
  }
]
```

```
    ]
  }
]
```

## Example (Response)

```
{
  "result": [
    {
      "idList": [
      ],
      "partialCIListDueToACLFlag": false,
      "nextBatchStart": 0,
      "result": true
    },
    {
      "idList": [
      ],
      "partialCIListDueToACLFlag": false,
      "nextBatchStart": 0,
      "result": true
    }
  ]
}
```

---

# Companies

## HTTP Method

GET

## Pagination

Enabled

## Resource Path

`/api/x_sclo_scilogic/v1/sciencelogic/companies`

## Default Resource Path

`/api/x_sclo_scilogic/sciencelogic/companies`

This operation supports Domain Separation enabled or not enabled. This operation pulls all the fields for from the company table that are not NULL values. The return is ordered by **sys\_id**, so the results display in the same order every time. The results are filtered by the **SL1 Monitored** and **region** values. The region must be supplied by the requester, and it will only return region-specific companies.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

Parameters	
Key	Value
region (required)	ScienceLogic
domainSep	false
sysparm_offset	0
sysparm_limit	glide.json.export.limit, glide.ui.export.limit, glide.ui.export.war.threshold

HTTP Status
-------------

Code	Value
200	OK
400	Query parameter \region\ is not defined and is required.

## Fixed Internal Query

### Domain:

```
'x_sclo_scilogic_region=' + region + '^x_sclo_scilogic_monitored=true^sys_
domain!=global'
```

### Non-Domain:

```
'^x_sclo_scilogic_monitored=true^x_sclo_scilogic_idISNOTEMPTY^x_sclo_scilogic_region'
+ region
```

## Example

```
https://<your instance>.service-now.com/api/x_sclo_scilogic/v1/sciencelogic/
companies?region=ScienceLogic&sysparm_offset=0&sysparm_limit=100
```

## Example (Response)

```
{
  "results": [
    {
      "country": "USA",
      "notes": "What's on your digital horizon?",
      "city": "San Jose",
      "sys_updated_on": "2018-11-30 16:03:45",
      "sys_class_name": "core_company",
      "sys_id": "1ac84f95dbce2700dc44f00fbf9619c8",
      "sys_updated_by": "is4user1",
      "market_cap": "0",
      "street": "170 West Tasman Dr.",
      "sys_created_on": "2018-11-27 16:32:33",
      "state": "CA",
      "sys_created_by": "admin",
      "zip": "95134",
      "profits": "0",
      "revenue_per_year": "0",
      "sys_mod_count": "4",
      "x_sclo_scilogic_id": "1",
      "x_sclo_scilogic_monitored": "true",
      "phone": "18005532447",
      "name": "Cisco Systems, Inc.",
      "x_sclo_scilogic_region": "Cisco"
    }
  ],
  "sysparm_offset": 0,
  "sysparm_limit": 1,
  "return_count": 1,
  "total_count": 1
}
```



---

# Device Identification Engine

## HTTP Method

POST

## Pagination

Enabled

## Resource Path

```
/api/x_sclo_scilogic/v1/sciencelogic/IdentificationEngine
```

## Default Resource Path

```
/api/x_sclo_scilogic/sciencelogic/IdentificationEngine
```

This operation handles all creates and updates to the CMDB. This operation incorporates Identification Engine and uses the Identification and Reconciliation framework to properly import devices into the CMDB as a configurable discovery source. SL1 uses the classification GET to populate the JSON object.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

Parameters	
Key	Value
test	true

## Example (Request URL)

```
https://<your Instance>.service-now.com/api/x_sclo_scilogic/v1/sciencelogic/IdentificationEngine?test=true
```

## Example (Body)

```
[
  {
    "items": [
      {
        "className": "cmdb_ci_linux_server",
```

```

    "values": {
      "name": "Postman Test Server 1",
      "serial_number": "9876EFGH",
      "mac_address": "BF:D4:D6:6E:56:F1",
      "ip_address": "10.10.10.4",
      "ram": "16000",
      "x_sclo_scilogic_region": "ScienceLogic",
      "x_sclo_scilogic_id": "1"
    }
  }
],
{
  "items": [
    {
      "className": "cmdb_ci_linux_server",
      "values": {
        "name": "Postman Test Server 2",
        "serial_number": "HGFE6789",
        "mac_address": "87:54:3C:8C:2A:A3",
        "ip_address": "10.10.10.5",
        "ram": "16000",
        "x_sclo_scilogic_region": "ScienceLogic",
        "x_sclo_scilogic_id": "2"
      }
    }
  ]
}
]

```

## Example Business Service (Body)

```

[
  {
    "items": [
      {
        "className": "cmdb_ci_service",
        "values": {
          "name": "Integration Service",
          "busines_criticality": "1 - most critical",
          "used_for": "Production",
          "operational_status": "1",
          "service_classification": "Technical Service",
          "comments": "Postman",
          "x_sclo_scilogic_region": "ScienceLogic",
          "x_sclo_scilogic_id": "1570"
        }
      },
      {
        "className": "cmdb_ci_linux_server",
        "values": {
          "name": "Postman Test Server",
          "serial_number": "7MDvqrSNyd",
          "manufacturer": "ScienceLogic, Inc.",
          "model_id": "",
          "mac_address": "EE:D6:0B:79:32:C7",

```

```

"ip_address": "10.10.10.224",
"ram": "16000",
"x_sclo_scilogic_region": "ScienceLogic",
"x_sclo_scilogic_id": "10"
}
}
],
"relations": [
{
"type": "Depends on::Used by",
"parent": 0,
"child": 1
}
]
}
]

```

## Example (Response)

```

{
  "result": [
    {
      "items": [
        {
          "className": "cmdb_ci_linux_server",
          "operation": "NO_CHANGE",
          "sysId": "7fb39667dba12380dc44f00fbf961936",
          "identifierEntrySysId": "fb27f69cc3000200d8d4bea192d3ae67",
          "identificationAttempts": [
            {
              "identifierName": "Hardware Rule",
              "attemptResult": "SKIPPED",
              "attributes": [
                "serial_number",
                "serial_number_type"
              ],
              "searchOnTable": "cmdb_serial_number"
            },
            {
              "identifierName": "Hardware Rule",
              "attemptResult": "MATCHED",
              "attributes": [
                "serial_number"
              ],
              "searchOnTable": "cmdb_ci_hardware"
            }
          ]
        }
      ]
    }
  ],
  "relations": [
  ]
}
]
}

```

---

# Discovery Dependents

## HTTP Method

GET

## Pagination

Enabled

## Resource Path

`/api/x_sclo_scilogic/v1/sciencelogic/discovery_dependent`

## Default Resource Path

`/api/x_sclo_scilogic/sciencelogic/discovery_dependent`

This operation pulls all Discovery-dependent records that are tied to the **region** value, which is used for the catalog request process. Based on the request type, this operation returns a formatted JSON object. This operation pulls all the required information for both SL1 processes: Discovery Session and Create Virtual Device. Both requests require different information and are formatted accordingly.

The basic catalog item Device Discovery is set up as information collection to support the process within SL1. The Service Catalog has been simplified to its most basic form. The Service Catalog moves the request into the correct state to be picked up by the GET Request and then waits for its return before completing the workflow.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

Parameters	
Key	Value
region (required)	ScienceLogic
sysparm_offset	0
sysparm_limit	glide.json.export.limit, glide.ui.export.limit, glide.ui.export.war.threshold

HTTP Status	
Code	Value
200	OK
400	Query parameter \'region\' is not defined and is required.

## Fixed Internal Query

Region Specific: 'region=' + region

## Example

[https://<your instance>.service-now.com/api/x\\_sclo\\_scilogic/v1/sciencelogic/discovery\\_dependent?region=del\\_test&sysparm\\_offset=0&sysparm\\_limit=100](https://<your instance>.service-now.com/api/x_sclo_scilogic/v1/sciencelogic/discovery_dependent?region=del_test&sysparm_offset=0&sysparm_limit=100)

## Example (Response)

```
{
  "results": [
    {
      "sys_updated_on": "2019-08-28 18:03:50",
      "type": "credential",
      "type_label": "Credentials",
      "sys_id": "0491aae51b273f0045c8db1dcd4bcbc2",
      "hostname": "example.com",
      "sys_updated_by": "is4user1",
      "sys_created_on": "2019-08-28 18:03:50",
      "name": "AppDynamics Example",
      "id": "93",
      "category": "soapCredentials",
      "region": "del_test",
      "sys_created_by": "is4user1"
    }
  ],
  "sysparm_offset": 0,
  "sysparm_limit": 1,
  "return_count": 1,
  "total_count": 150
}
```

---

# File Systems

## HTTP Method

GET

## Pagination

Enabled

## Resource Path

`/api/x_sclo_scilogic/v1/sciencelogic/file_systems`

## Default Resource Path

`/api/x_sclo_scilogic/sciencelogic/file_systems`

This operation pulls all the fields from the File System table. The return is ordered by **sys\_id**, so the results display in the same order every time. The results are filtered by the **SL1 monitored** and **SL1 ID** field on the ServiceNow side. This operation requires the region to be supplied by the requester, it returns only region-supplied configuration items.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

Parameters	
Key	Value
region (required)	ScienceLogic
sysparm_offset	0
sysparm_limit	glide.json.export.limit, glide.ui.export.limit, glide.ui.export.war.threshold

HTTP Status	
Code	Value

200	OK
400	Query Parameter \region\ is not defined and is required.

## Fixed Internal Query

```
`x_sclo_scilogic_monitored=true^x_sclo_scilogic_idISNOTEMPTY^x_sclo_scilogic_region='
+ region
```

## Example

```
https://<your Instance>.service-now.com/api/x_sclo_scilogic/v1/sciencelogic/file_
systems?region=ScienceLogic&sysparm_offset=0&sysparm_limit=100
```

## Example (Response)

```
{
  "results": [
    {
      "operational_status": "1",
      "sys_updated_on": "2018-11-12 21:59:52",
      "media_type": "fixed",
      "sys_created_by": "admin",
      "sys_domain_path": "/",
      "sys_class_name": "cmdb_ci_file_system",
      "computer": "d83dac0adb4dab00dc44f00fbf961919",
      "x_sclo_scilogic_monitored": "true",
      "x_sclo_scilogic_region": "ScienceLogic",
      "sys_updated_by": "admin",
      "sys_created_on": "2018-11-12 21:59:06",
      "sys_domain": "global",
      "install_status": "1",
      "name": "/root",
      "subcategory": "File Share",
      "sys_id": "afd30ba0dbf5a380dc44f00fbf961951",
      "file_system": "ntfs",
      "sys_class_path": "!!!/K/!!",
      "mount_point": "/root",
      "sys_mod_count": "3",
      "x_sclo_scilogic_id": "31",
      "label": "/root",
      "cost_cc": "USD",
      "category": "Resource"
    }
  ],
  "sysparm_offset": 0,
  "sysparm_limit": 100,
  "return_count": 1,
  "total_count": 1
}
```

---

# Import Set

## HTTP Method

POST

## Resource Path

`/api/x_sclo_scilogic/v1/sciencelogic/import_set`

## Default Resource Path

`/api/x_sclo_scilogic/sciencelogic/import_set`

This operation handles the custom intake of import sets before it reaches the transform map staging table, such as `x_sclo_scilogic_import_installed_software`. This operations is currently only used for importing installed software (`x_sclo_scilogic_import_installed_software`).

Headers	
Key	Value
Accept	application/json
Content-Type	application/json

Parameters	
Key	Value
record_type (required)	x_sclo_scilogic_import_installed_software

## Example (Request URL)

`https://<your Instance>.service-now.com/api/x_sclo_scilogic/v1/sciencelogic/import_set`

## Example (Body)

```
[
  {
    "records": [
      {
        "name": "acl-2.2.51-12.e17",
        "software": "671bafd8dba13700dc44f00fbf961953",
        "cldb_ci": [
          "ff01a81edb1df300dc44f00fbf961947",
          "4011a81edb1df300dc44f00fbf961958",
          "f301a81edb1df300dc44f00fbf96193d",
          "7b01a81edb1df300dc44f00fbf961942",
        ]
      }
    ]
  }
]
```

```
        "c411a81edbfd300dc44f00fbf96195d",
        "7701a81edbfd300dc44f00fbf961922",
        "7b01681edbfd300dc44f00fbf9619e7",
        "fb01a81edbfd300dc44f00fbf961927"
    ],
    "active": true
}
]
]
```

---

# Incidents

## HTTP Method

GET

## Pagination

Enabled

## Resource Path

`/api/x_sclo_scilogic/v1/sciencelogic/incidents`

## Default Resource Path

`/api/x_sclo_scilogic/sciencelogic/incidents`

This operation pulls all records from the incident table that are created by a specific **user\_id** and its related events. The results are ordered by the **sys\_id** of the incident, so the results display in the same order every time. This operation is also based on the incident being in an active state. This operation returns a pre-set of data and does not return everything on the Incident and Event (x\_sclo\_scilogic\_event) tables.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

Parameters	
Key	Value
user_id (required)	is4user1
sysparm_offset	0
sysparm_limit	glide.json.export.limit, glide.ui.export.limit, glide.ui.export.war.threshold

HTTP Status	
Code	Value

200	OK
400	Query Parameter '\user_id\' is not defined and is required.

## Fixed Internal Query

```
'sys_created_by=' + user_id + 'active=true'
```

## Example

```
https://<your Instance>.service-now.com/api/x_sclo_
scilogic/v1/scienceologic/incidents?user_id=is4user1&sysparm_offset=0&sysparm_limit=100
```

## Example (Response)

```
{
  "results": [
    {
      "sys_id": "0141807bdbb16300dc44f00fbf9619fc",
      "number": "INC0010135",
      "state": "2",
      "state_label": "In Progress",
      "events": [
        {
          "event_id": "16908",
          "device": {
            "sys_id": {

          }
        }
      ],
      {
        "event_id": "16874",
        "device": {
          "sys_id": {

        }
      },
      {
        "event_id": "16865",
        "device": {
          "sys_id": {

        }
      }
    ]
  },
  "sysparm_offset": 0,
  "sysparm_limit": 1,
  "return_count": 1,
}
```

```
"total_count": 44  
}
```

---

# Installed Software

## HTTP Method

GET

## Pagination

Enabled

## Resource Path

`/api/x_sclo_scilogic/v1/sciencelogic/installed_software`

## Default Resource Path

`/api/x_sclo_scilogic/sciencelogic/installed_software`

This operation pulls all the fields from the software (cmdb\_ci\_spkg) table. The return is ordered by **sys\_id**, so the results display in the same order every time. The results are filtered by the **SL1 monitored** field on the ServiceNow side. This operation requires the **region** to filter the installed software on devices.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

Parameters	
Key	Value
region	ScienceLogic
sysparm_offset	0
sysparm_limit	glide.json.export.limit, glide.ui.export.limit, glide.ui.export.war.threshold

HTTP Status	
Code	Value
200	OK

400

Query parameter `\'region\'` is not defined and are required.

## Fixed Internal Query

```
'x_sclo_scilogic_monitored=true'
```

## Example (Request URL)

```
https://<your Instance>.service-now.com/api/x_sclo_scilogic/v1/sciencelogic/installed_software?sysparm_offset=0&sysparm_limit=100&region=ScienceLogic
```

```
Example (Response){
  "results": [
    {
      "operational_status": "1",
      "operational_status_label": "Operational",
      "sys_updated_on": "2019-05-01 06:00:09",
      "install_count": "2",
      "sys_updated_by": "system",
      "sys_created_on": "2019-03-29 19:42:58",
      "sys_domain": "global",
      "sys_created_by": "admin",
      "sys_domain_path": "/",
      "install_status": "1",
      "install_status_label": "Installed",
      "name": "Test_31",
      "subcategory": "Package",
      "sys_class_name": "cmdb_ci_spkg",
      "sys_class_name_label": "Software",
      "sys_id": "1e9608fcdb2cb740dc44f00fbf961949",
      "sys_class_path": "/!/#$",
      "key": "Test_31::_NULL",
      "license_available": "-2",
      "sys_mod_count": "1",
      "x_sclo_scilogic_id": "31",
      "model_id": "2c146728dbe8b740dc44f00fbf9619c6",
      "model_id_label": "Unknown",
      "cost_cc": "USD",
      "cost_cc_label": "USD",
      "x_sclo_scilogic_monitored": "true",
      "package_name": "Test_31",
      "category": "Software",
      "x_sclo_scilogic_region": "AutoGenerateClass",
      "installed_on": [
        {
          "sys_id": "5a271407dbfe6300dc44f00fbf96190f",
          "id": "10",
          "region": "ScienceLogic",
          "monitored": "true"
        },
        {
          "sys_id": "5a271407dbfe6300dc44f00fbf96190f",
```

```
"id": "10",  
"region": "ScienceLogic",  
"monitored": "true"  
}  
]  
},  
"sysparm_offset": 0,  
"sysparm_limit": 100,  
"return_count": 4,  
"total_count": 4  
}
```

---

# Manufacturer

## HTTP Method

POST

## Pagination

Enabled

## Resource Path

```
/api/x_sclo_scilogic/v1/sciencelogic/manufacture
```

## Default Resource Path

```
/api/x_sclo_scilogic/sciencelogic/manufactures
```

This operation does not populate any data into ServiceNow. Instead, this operation takes an array of manufacturer names and attempts to line them up with manufacturers already in ServiceNow. Then the operation returns the sys\_id of manufacturers it was able find based on matching name. If the Normalization Data Services Client is active on the target instance, this operation uses those tables to find a matching company record; otherwise the operation will match on whether name and manufacturer is true on the core\_company table.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

Parameters	
Key	Value
region (required)	ScienceLogic

## Example (Request URL)

```
https://<your Instance>.service-now.com/api/x_sclo_scilogic/v1/sciencelogic/manufacture
```

## Example (Body)

```
{  
  "manufactures": [  
    "Cisco Systems Inc",  
  ]  
}
```

```
"Cisco Systems, Incorporated",
"CiscoSystems",
"American Power Conversion Inc.",
"APC Corp",
"Apc",
"IBM",
"IBM CORP",
"International Business Machines",
"Juniper Systems",
"Juniper Networks,Inc",
"Juniper Solutions"

]
}
```

### Example (Response)

```
{
  "result": {
    "Cisco Systems Inc": "",
    "Cisco Systems, Incorporated": "",
    "CiscoSystems": "",
    "American Power Conversion Inc.": "",
    "APC Corp": "",
    "Apc": "",
    "IBM": "",
    "IBM CORP": "",
    "International Business Machines": "",
    "Juniper Systems": "",
    "Juniper Networks,Inc": "",
    "Juniper Solutions": ""
  }
}
```

---

# Model

## HTTP Method

POST

## Resource Path

```
/api/x_sclo_scilogic/v1/sciencelogic/model
```

## Default Resource Path

```
/api/x_sclo_scilogic/sciencelogic/models
```

This operation does not populate any data into ServiceNow. Instead, this operation takes an array of model names and attempts to line them up with models already in ServiceNow and returns the sys\_id of models it was able to find based on matching name.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

Parameters	
Key	Value
region (required)	ScienceLogic

## Example (Request URL)

```
https://<your Instance>.service-now.com/api/x_sclo_scilogic/v1/sciencelogic/models
```

## Example (Body)

```
{
  "models": [
    "4331 ISR",
    "7206VXR",
    "7609S",
    "AS5300",
    "ASR5000",
    "Catalyst 3560G-24TS",
    "Catalyst 4948",
    "Catalyst 6509-CatOS",
    "BIG-IP Viprion B4300",
  ]
}
```

```
"F5 BIG-IP DNS",  
"BIG-IP Wide IP Container",  
"BIG-IP Data Center Container"  
]  
}
```

## Example (Response)

```
{  
  "result": {  
    "4331 ISR": "",  
    "7206VXR": "",  
    "7609S": "",  
    "AS5300": "",  
    "ASR5000": "",  
    "Catalyst 3560G-24TS": "",  
    "Catalyst 4948": "",  
    "Catalyst 6509-CatOS": "",  
    "BIG-IP Viprion B4300": "",  
    "F5 BIG-IP DNS": "",  
    "BIG-IP Wide IP Container": "",  
    "BIG-IP Data Center Container": ""  
  }  
}
```

---

# Network Adapters

## HTTP Method

GET

## Pagination

Enabled

## Resource Path

`/api/x_sclo_scilogic/v1/sciencelogic/network_adapters`

## Default Resource Path

`/api/x_sclo_scilogic/sciencelogic/network_adapters`

This operation pulls all the fields from the network adapter table. The return is ordered by **sys\_id**, so the results display in the same order every time. The results are filtered by the **SL1 monitored** and **SL1 ID** field on the ServiceNow side. This operation requires the region to be supplied by the requester, and it only returns region-supplied configuration items.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

Parameters	
Key	Value
region (required)	ScienceLogic
sysparm_offset	0
sysparm_limit	glide.json.export.limit, glide.ui.export.limit, glide.ui.export.war.threshold

HTTP Status	
Code	Value

200	OK
400	Query Parameter '\region\' is not defined and is required.

## Fixed Internal Query

```
'x_sclo_scilogic_monitored=true^x_sclo_scilogic_idISNOTEMPTY^x_sclo_scilogic_region='
+ region
```

## Example (Request URL)

```
https://<your Instance>.service-now.com/api/x_sclo_scilogic/v1/sciencelogic/network_
adapters?region=ScienceLogic&sysparm_offset=0&sysparm_limit=100
```

## Example (Response)

```
{
  "results": [
    {
      "operational_status": "1",
      "sys_updated_on": "2018-11-12 21:29:23",
      "sys_updated_by": "admin",
      "sys_created_on": "2018-11-12 21:27:48",
      "sys_domain": "global",
      "sys_created_by": "admin",
      "cmdb_ci": "d83dac0adb4dab00dc44f00fbf961919",
      "sys_domain_path": "/",
      "install_status": "1",
      "name": "eth0",
      "subcategory": "Network",
      "sys_class_name": "cmdb_ci_network_adapter",
      "sys_id": "33ac36acdbb5a380dc44f00fbf961963",
      "netmask": "255.255.255.0",
      "sys_class_path": "/!?!8",
      "mac_address": "BF:D4:D6:6E:56:F1",
      "sys_mod_count": "3",
      "x_sclo_scilogic_id": "20",
      "ip_address": "10.10.10.4",
      "cost_cc": "USD",
      "x_sclo_scilogic_monitored": "true",
      "category": "Hardware",
      "x_sclo_scilogic_region": "ScienceLogic"
    }
  ],
  "sysparm_offset": 0,
  "sysparm_limit": 1,
  "return_count": 1,
  "total_count": 5
}
```

---

# Service Requests

## HTTP Method

GET

## Pagination

Enabled

## Resource Path

`/api/x_sclo_scilogic/v1/sciencelogic/service_request`

## Default Resource Path

`/api/x_sclo_scilogic/sciencelogic/service_request`

This operation pulls all service requests that are tied to specific catalog item. Based on the request type it returns a formatted JSON object. It pulls all the required information for an SL1 Discovery session and creating a virtual device in SL1. Both requests require different information and are formatted accordingly.

The basic catalog item Device Discovery is set up as information collection to support the process within SL1. The Service Catalog has been simplified to its most basic form. The workflow moves the request into the correct state to be picked up by the GET request and then waits for its return before completing the workflow.

Headers	
Key	Value
Content-Type	application/json
Accept	application/json

Parameters	
Key	Value
region (required)	ScienceLogic
state	2
sysparm_offset	0
sysparm_limit	glide.json.export.limit, glide.ui.export.limit, glide.ui.export.war.threshold

HTTP Status	
Code	Value
200	OK
400	Query Parameter \region\ is not defined and is required.

## Fixed Internal Query

### State:

```
`request_item.active=true^request_item.cat_item=' + catalog + `^sc_item_option.item_option_new.name=Region^sc_item_option.value=' + region
```

### Non-State:

```
`request_item.active=true^request_item.cat_item=' + catalog + `^sc_item_option.item_option_new.name=Region^sc_item_option.value=' + region + `^request_item.state=' + state
```

## Example

```
https://<your Instance>.service-now.com/api/x_sclo_scilogic/v1/sciencelogic/ service_request?region=Cisco
```

## Example (Response)

```
{
  "results": [
    {
      "number": "RITM0010018",
      "sysid": "00365de2db1a2340dc44f00fbf961941",
      "state": "2",
      "request_type": "Discover Device",
      "region": "Cisco",
      "log_all": "false",
      "ip_hostname_list": "167.132.14.15",
      "credentials": [
        {
          "Category": "Linux",
          "ID": "1"
        }
      ],
      "discover_non_snmp": "false",
      "model_devices": "true",
      "dhcp": "false",
      "device_model_cache_ttl_h": "2",
      "collection_server": "1",
      "organization": "1",
      "add_devices_to_device_groups": [
        "test"
      ],
      "device_template": "1",
      "initial_scan_level": "System Default (Recommended)",
    }
  ]
}
```

```

"scan_throttle": "System Default (Recommended)",
"scan_ports": "21,22,23,25,80",
"port_scan_all": "System Default (Recommended)",
"port_scan_timeout": "System Default (Recommended)",
"interface_inventory_timeout": "600000",
"maximum_allowed_interfaces": "10000",
"bypass_interface_inventory": "false"
},
{
  "number": "RITM0010016",
  "sysid": "194447e8db162f00dc44f00fbf96195b",
  "state": "2",
  "request_type": "Discover Device",
  "region": "Cisco",
  "log_all": "false",
  "ip_hostname_list": "192.168.1.1",
  "credentials": [
    {
      "Category": "Linux",
      "ID": "1"
    }
  ],
  "discover_non_snmp": "false",
  "model_devices": "false",
  "dhcp": "false",
  "device_model_cache_ttl_h": "2",
  "collection_server": "1",
  "organization": "1",
  "add_devices_to_device_groups": [

  ],
  "device_template": "1",
  "initial_scan_level": "System Default (Recommended)",
  "scan_throttle": "System Default (Recommended)",
  "scan_ports": "21,22,23,25,80",
  "port_scan_all": "System Default (Recommended)",
  "port_scan_timeout": "System Default (Recommended)",
  "interface_inventory_timeout": "600000",
  "maximum_allowed_interfaces": "10000",
  "bypass_interface_inventory": "false"
},
{
  "number": "RITM0010014",
  "sysid": "250dae2cdbd22f00dc44f00fbf961954",
  "state": "2",
  "request_type": "create_virtual_device",
  "region": "Cisco",
  "collection_server": "1",
  "virtual_device_class": "1"
}
]
}

```

© 2003 - 2020, ScienceLogic, Inc.

All rights reserved.

#### LIMITATION OF LIABILITY AND GENERAL DISCLAIMER

ALL INFORMATION AVAILABLE IN THIS GUIDE IS PROVIDED "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED. SCIENCELOGIC™ AND ITS SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT.

Although ScienceLogic™ has attempted to provide accurate information on this Site, information on this Site may contain inadvertent technical inaccuracies or typographical errors, and ScienceLogic™ assumes no responsibility for the accuracy of the information. Information may be changed or updated without notice. ScienceLogic™ may also make improvements and / or changes in the products or services described in this Site at any time without notice.

#### Copyrights and Trademarks

ScienceLogic, the ScienceLogic logo, and EM7 are trademarks of ScienceLogic, Inc. in the United States, other countries, or both.

Below is a list of trademarks and service marks that should be credited to ScienceLogic, Inc. The ® and ™ symbols reflect the trademark registration status in the U.S. Patent and Trademark Office and may not be appropriate for materials to be distributed outside the United States.

- ScienceLogic™
- EM7™ and em7™
- Simplify IT™
- Dynamic Application™
- Relational Infrastructure Management™

The absence of a product or service name, slogan or logo from this list does not constitute a waiver of ScienceLogic's trademark or other intellectual property rights concerning that name, slogan, or logo.

Please note that laws concerning use of trademarks or product names vary by country. Always consult a local attorney for additional guidance.

#### Other

If any provision of this agreement shall be unlawful, void, or for any reason unenforceable, then that provision shall be deemed severable from this agreement and shall not affect the validity and enforceability of any remaining provisions. This is the entire agreement between the parties relating to the matters contained herein.

In the U.S. and other jurisdictions, trademark owners have a duty to police the use of their marks. Therefore, if you become aware of any improper use of ScienceLogic Trademarks, including infringement or counterfeiting by third parties, report them to Science Logic's legal department immediately. Report as much detail as possible about the misuse, including the name of the party, contact information, and copies or photographs of the potential misuse to: [legal@sciencelogic.com](mailto:legal@sciencelogic.com)



800-SCI-LOGIC (1-800-724-5644)

International: +1-703-354-1010